

Hydraulic equipment for agricultural machinery —

Part 6: Specification for dimensions and location of agricultural tractor hydraulic return to sump porting

UDC 631.372:629.114.2 – 578.4

Confirmed February 2011

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Agricultural Machinery and Implements Standards Committee (AGE/-) to Technical Committee AGE/25, upon which the following bodies were represented:

- AFRC Institute of Engineering Research
- Agricultural Engineers Association
- British Fluid Power Association
- Local Authority Organizations
- National Farmers' Union

This British Standard, having been prepared under the direction of the Agricultural Machinery and Implements Standards Committee, was published under the authority of the Board of BSI and comes into effect on 31 August 1988

© BSI 10-1999

The following BSI references relate to the work on this standard:
Committee reference AGE/25
Draft for comment 87/70762 DC

ISBN 0 580 16656 2

Amendments issued since publication

Amd. No.	Date of issue	Comments

Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
1 Scope	1
2 Definitions	1
3 Dimensions	1
4 Performance	2
Figure 1 — Basic dimensions for port connection and stud coupling	1
Figure 2 — Dimensions of the zone of clearance around the port connection	3
Figure 3 — The location of the port connection on tractor	4
Table 1 — Basic dimensions for port connection and stud coupling	2
Publications referred to	Inside back cover