

BS 4A 116:2012

Incorporating Corrigendum No. 1



BSI Standards Publication

Steel pan head bolts (Unified threads), cadmium plated, for aircraft

bsi.

...making excellence a habit.
AVA Document Sharing Hub

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2012

Published by BSI Standards Limited 2012

ISBN 978 0 580 79467 4

ICS 49.030.20

The following BSI references relate to the work on this standard:

Committee reference ACE/12

Draft for comment 11/30252412 DC

Publication history

First published February 1954

Second edition February 1956

Third edition June 1962

Fourth (current) edition March 2012

Amendments issued since publication

Date	Text affected
30 June 2012	This corrigendum incorporates a number of typographical corrections including the capitalization of "Unified" and the correction of "indentifier" to "identifier" in Clause 8.

Contents

Foreword *ii*

1	Scope	1
2	Normative references	1
3	General requirements	2
4	Material and manufacture	2
5	Dimensions	2
6	Screw threads	3
7	Protective finish	3
8	Identification and marking	3
9	Inspection procedure	3

Annexes

Annex A (informative) Table for conversion of inches to approximate millimetre equivalents 10

Bibliography 11

List of figures

Figure 1 – Basic dimensions 3

Figure 2 – Bearing length, clamping length and overall length dimensions 5

List of tables

Table 1 – Dimensions 4

Table 2 – Bearing length L , clamping length M and overall length E 6

Table A.1 – Table for conversion of inches to approximate millimetre equivalents 10

Summary of pages

This document comprises a front cover, an inside front cover, pages i to ii, pages 1 to 12, an inside back cover and a back cover.

Foreword

Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 March 2012. It was prepared by Technical Committee ACE/12, *Aerospace fasteners and fastening systems*. A list of organizations represented on this committee can be obtained on request to its secretary.

Supersession

This British Standard supersedes BS 3A 116:1962, which is withdrawn.

Information about this document

This new edition of this British Standard incorporates technical changes only. It does not represent a full review or revision of the standard, which will be undertaken in due course.

CAUTION. BS A 116 bolts have cadmium as a plating material which has been restricted and/or banned for use in many countries owing to environmental and health concerns; they should not be used in new product designs. Local officials should be consulted about any concerns on using cadmium-plated parts.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is "shall".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

1 Scope

This British Standard specifies the materials, dimensions, finish and inspection requirements for steel pan head bolts with Unified threads, cadmium plated, for aircraft.

NOTE 1 The values in British units are to be regarded as the standard. Table A.1 provides a ready means of calculating the approximate millimetre equivalents of the inch dimensions. More accurate conversions should be based on the tables in BS 350.

NOTE 2 In place of the customary, but incorrect, use of the ton as a unit of force, the unit called a ton force (abbreviation tonf) is used in this British Standard. It is the force which, when acting on a body of mass one ton, gives an acceleration equal to that of standard gravity.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 4A 100:2003, *Specification for general requirements for bolts and free running nuts of tensile strength not exceeding 1 249 MPa*

BS EN 2133, *Cadmium plating of steels with specified tensile strength $\leq 1\,450$ MPa, copper, copper alloys and nickel alloys*

BS S 95, *Specification for 1½ per cent nickel-chromium-molybdenum steel (90/110 kgf/mm)*

BS S 102, *Specification for carbon-molybdenum steel (bar for the manufacture of forged bolts only)*

BS S 105, *Specification for carbon steel (bar for the manufacture of forged bolts only)*

BS S 114, *Manganese-Molybdenum Steel (55/65 tonf/sq in: limiting ruling section 2½ inches)*

BS S 116, *Specification for aircraft material. '40' Carbon Steel Bright Bars for Machining (55-65 tonf/sq in: limiting ruling section ¾ inch) (Primarily Intended for the Manufacture of Machined Bolts)*

BS S 117, *Specification for aircraft material. 1 per cent chromium steel (55/65 tonf/sq in: limiting ruling section 1⅛ inch)*

BS S 147, *Specification for 0.5% nickel-chromium-molybdenum steel bars for the manufacture of forged bolts and forged nuts*

BS S 148, *Specification for low nickel-chromium steel (bar for the manufacture of forged bolts only)*

BS S 149, *Specification for 1.75% nickel-chromium-molybdenum steel bars for the manufacture of forged bolts and forged nuts*

BS S 154, *Specification. 2½% nickel-chromium-molybdenum steel billets, bars, forgings and parts (880-1080 MPa: limiting ruling section 150 mm)*

BS S 158, *Specification for 1% chromium-molybdenum steel bars for the manufacture of forged bolts and forged nuts*

Def Stan 03-19, *Electro-deposition of cadmium*

3 General requirements

The bolts shall conform to the relevant requirements of BS 4A 100:2003 in respect of manufacture, screw threads, anti-corrosion treatment, identification and marking.

4 Material and manufacture

The bolts shall be manufactured by one of the following methods:

- a) Machined from bright drawn alloy steel bars that conform to one of the following:

- 1) BS S 95
- 2) BS S 114
- 3) BS S 116
- 4) BS S 117; or
- 5) BS S 154.

NOTE Material conforming to BS S 96 may be used until stocks are exhausted.

- b) Forged from alloy steel that conforms to one of the following:

- 1) BS S 102;
- 2) BS S 105;
- 3) BS S 147;
- 4) BS S 148;
- 5) BS S 149; or
- 6) BS S 158.

NOTE Material conforming to BS S 103 may be used until stocks are exhausted.

- c) In the finally head-treated condition, the mechanical properties of the material used for forged bolts shall be as follows:

0.1 per cent proof stress	not less than 43 tonf/in ² (664 MPa)
Tensile strength	not less than 55 tonf/in ² (850 MPa) not more than 65 tonf/in ² (1003 MPa)
Elongation on 5.65√ area	not less than 18%
Izod impact value	not less than 40 ft lbf (54 J)

5 Dimensions

All finished bolts, after the application of the protective finish, shall conform to the dimensions and tolerances given in Table 1, Table 2, Figure 1 and Figure 2.

The clamping length of the bolt shall conform to the dimensions and tolerances given in Table 2, and shall be such that, when a standard nut without countersink or ring gauge without countersink has been screwed on as far as possible by hand, its leading face is within the distance *M* from the underside of the bolt head. The runout of thread shall not exceed twice the pitch.

The nominal length of the bolt shall be the minimum bearing length, *L*, which is determined by the minimum clamping length, *M*, less two thread pitches.