

Methods of test for

Footwear and footwear materials —

Part 4: Other components —

Section 4.6 Shear strength of ribs stuck to insoles

NOTE It is recommended that this Section should be read in conjunction with the information in the General introduction to BS 5131, published separately.

UDC 685.31:620.1:685.312.124:676.017.42:539.415

Confirmed
January 2011

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 3 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
1 Scope	1
2 Principle	1
3 Supplementary information	1
4 Test pieces	1
5 Apparatus	2
6 Procedure	3
7 Expression of results	3
8 Test report	3
Figure 1 — Test piece layout for the determination both of the shear strength and the resistance to peeling of an attached rib insole	1
Figure 2 — Test piece layout for the determination both of the shear strength and the resistance to peeling of ribs stuck to insole material	2
Figure 3 — Diagram of a suitable apparatus with test piece (E) in position (see clause 5 for key to lettering)	2