

Methods of test for

Footwear and footwear materials —

Part 5: Testing of complete footwear —

Section 5.13 Measurement of the
strength of stitched seams in upper and
lining materials

NOTE It is recommended that this Section should be read in conjunction with the information in the General Introduction to BS 5131, published separately.

UDC 683.31:620.1:[685.312.14:685.312.33]:539.412.1

Confirmed
January 2011

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 5 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

This British Standard, having been prepared under the direction of the Clothing Standards Committee, was published under the authority of the Executive Board and comes into effect on 30 April 1980

© BSI 07-1999

The following BSI references relate to the work on this standard:
Committee reference CLT/7
Draft for comment 77/35456 DC

ISBN 0 580 11318 3

Amendments issued since publication

Amd. No.	Date of issue	Comments

Contents

	Page
1 Scope	1
2 References	1
3 Definitions	1
4 Principle	1
5 Test piece preparation	1
6 Apparatus	3
7 Conditioning	3
8 Procedure	3
9 Calculation and expression of results	4
10 Test report	4
Figure 5.13/1 — Lapped seam	2
Figure 5.13/2 — Closed seam	2
Figure 5.13/3 — Dimensions of made-up test seams	3
Figure 5.13/4 — Desirable dimensions of seam test piece cut from a shoe	4
Figure 5.13/5 — Test piece clamped in the tensile test machine	5