

Specification for

**Dimensions of cable  
terminations for multi-core  
extruded solid dielectric  
insulated distribution cables of  
rated voltages 600/1000 V  
and 1900/3300 V having copper  
or aluminium conductors**

ICS 29.060.20

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

**BSI**  
Documents

**AVA**

Document Sharing Hub

# Committees responsible for this British Standard

The preparation of this British Standard was entrusted by Technical Committee GEL/20, Electric cables, to Subcommittee GEL/20/7, Cable joints and terminations, upon which the following bodies were represented:

- Association of Consulting Engineers
- BEAMA Electrical Cable and Conductor Accessory Manufacturers' Association
- British Approvals Service for Cables
- British Cable Makers Confederation
- British Iron and Steel Producers' Association
- British Plastics Federation
- Department of Trade and Industry (Consumer Safety Unit, CA Division)
- Electricity Association
- London Transport

The following bodies were also represented in the drafting of the standard, through subcommittees and panels:

- ERA Technology Ltd.
- Electrical Contractors' Association
- Electrical Installation Equipment Manufacturers' Association (BEAMA Ltd.)
- Institution of Lighting Engineers
- London Underground Ltd.

This British Standard, having been prepared under the direction of the Electrotechnical Sector Board, was published under the authority of the Standards Board and comes into effect on 15 June 1997

© The British Standards Institution 2012  
Published by BSI Standards Limited 2012

First published June 1976  
Second edition February 1989  
Third edition June 1996

The following BSI references relate to the work on this standard:  
Committee reference GEL/20/7  
Drafts for comment  
96/211951 DC  
12/30249327 DC

ISBN 978 0 580 75934 5

## Amendments issued since publication

| Amd. No. | Date         | Comments     |
|----------|--------------|--------------|
| A1       | October 2012 | See foreword |
|          |              |              |
|          |              |              |
|          |              |              |

# Contents

|                                                                                                               | Page               |
|---------------------------------------------------------------------------------------------------------------|--------------------|
| Committees responsible                                                                                        | Inside front cover |
| Foreword                                                                                                      | ii                 |
| <b>Specification</b>                                                                                          |                    |
| <b>1</b> Scope                                                                                                | 1                  |
| <b>2</b> Definitions                                                                                          | 1                  |
| <b>3</b> Dimensions                                                                                           | 2                  |
| <b>Annexes</b>                                                                                                |                    |
| <b>A</b> Factors which affect cable accommodation                                                             | 4                  |
| <b>B</b> The relationship between equipment rating and cable terminations                                     | 4                  |
| <b>Tables</b>                                                                                                 |                    |
| <b>1</b> Dimensions of cable terminations for 600/1000 V cables with solid and stranded aluminium conductors  | 2                  |
| <b>2</b> Dimensions of cable terminations for 600/1000 V cables with stranded copper conductors               | 2                  |
| <b>3</b> Dimensions of cable terminations for 1900/3300 V cables with solid and stranded aluminium conductors | 3                  |
| <b>4</b> Dimensions of cable terminations for 1900/3300 V cables with stranded copper conductors              | 3                  |
| <b>Figure</b>                                                                                                 |                    |
| <b>1</b> Typical cable terminations                                                                           | 1                  |
| List of references                                                                                            | Inside back cover  |