

Methods for

Evaluating resistance to tracking and erosion of electrical insulating materials used under severe ambient conditions

UDC 621.315.611.001.4:620.193.7:621.317.333.6

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW



Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the General Electrotechnical Engineering Standards Committee (GEL/-) to Technical Committee GEL/16, upon which the following bodies were represented:

- Adhesive Tape Manufacturers' Association
- British Industrial Ceramic Manufacturers' Association
- British Paper and Board Industry Federation (PIF)
- British Plastics Federation
- British Telecommunications plc
- Department of Trade and Industry (National Measurement Accreditation Service)
- Electrical and Electronic Insulation Association (BEAMA Ltd)
- Electrical Installation Equipment Manufacturers' Association (BEAMA Ltd)
- Electricity Supply Industry in England and Wales
- Electronic Engineering Association
- ERA Technology Ltd
- Ministry of Defence
- Rotating Electrical Machines Association (BEAMA Ltd)
- Rubber and Plastics Research Association of Great Britain
- Telecommunication Engineering and Manufacturing Association (TEMA)
- Transmission and Distribution Association (BEAMA Ltd)

This British Standard, having been prepared under the direction of the General Electrotechnical Engineering Standards Committee, was published under the authority of the Board of BSI and comes into effect on 31 July 1986

© BSI 11-1999

First published June 1978
First revision July 1986

The following BSI references relate to the work on this standard:
Committee reference GEL/16
Draft for comment 85/28025 DC

ISBN 0 580 15268 5

Amendments issued since publication

Amd. No.	Date of issue	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
1 Scope and object	1
2 Definitions	1
3 Test specimens	1
4 Apparatus	1
5 Procedure	2
6 Test report	3
Figure 1 — Test specimen with holes for fixing electrodes	3
Figure 2a — Schematic circuit diagram	4
Figure 2b — Example: typical circuit for an overcurrent delay relay (F in Figure 2a)	4
Figure 3a — Assembly of the electrodes	5
Figure 3b — Test assembly, schematic	5
Figure 4 — Top electrode, stainless steel 0.5 mm thick	6
Figure 5 — Bottom electrode, stainless steel 0.5 mm thick	6
Figure 6 — Filter-paper (eight sheets requested for each top electrode)	6
Table I	1

National foreword

This revision of BS 5604, published under the direction of the General Electrotechnical Engineering Standards Committee, is identical with IEC 587:1984 “*Test methods for evaluating resistance to tracking and erosion of electrical insulating materials used under severe ambient conditions*”, published by the International Electrotechnical Commission (IEC). It supersedes BS 5604:1978 which is withdrawn.

Terminology and conventions. The text of the International Standard has been approved as suitable for publication as a British Standard without deviation. Some terminology and certain conventions are not identical with those used in British Standards; attention is drawn especially to the following.

In Figure 4 the comma has been used as a decimal marker. In British Standards it is current practice to use a full point on the baseline as the decimal marker.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 6 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.