

Rolling bearings — bearings with spherical outside surface and extended inner ring width —

Part 4: Specification for insert bearings and eccentric locking collars

UDC 621.822.74

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Machinery and Components Standards Policy Committee (MCE/-) to Technical Committee MCE/7, upon which the following bodies were represented:

- Ball and Roller Bearing Manufacturers' Association
- Ministry of Defence
- Society of British Aerospace Companies Ltd.

This British Standard, having been prepared under the direction of the Machinery and Components Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 15 August 1993

© BSI 10-1999

The following BSI references relate to the work on this standard:
Committee reference MCE/7
Draft for comment 90/74629 DC

ISBN 0 580 22494 5

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Symbols	1
5 Characteristics	2
Figure 1 — Bearing with eccentric locking collar — Wide overall width	3
Figure 2 — Bearing with concentric locking collar around the inner ring — Intermediate overall width	3
Figure 3 — Bearing with set screws in the inner ring — Intermediate overall width	4
Figure 4 — Bearing with eccentric locking collar — Narrow overall width	4
Figure 5 — Inner ring eccentric extension	4
Figure 6 — Eccentric locking collar	5
Table 1 — Insert bearings — Diameter series 2 — Wide overall width — Axially extending eccentric locking collar	6
Table 2 — Insert bearings — Diameter series 2 — Intermediate overall width — Locking device not axially extending	7
Table 3 — Insert bearings — Diameter series 2 — Narrow overall width — Axially extending eccentric locking collar	8
Table 4 — Insert bearings — Inner ring eccentric extension — Diameter series 2 — Wide and narrow overall width	9
Table 5 — Eccentric locking collar for insert bearings — Diameter series 2 — Wide and narrow overall width	10
Table 6 — Tolerances for bearings	11
Table 7 — Tolerances for eccentric locking collars	11
Table 8 — Radial internal clearance	12
List of references	Inside back cover

National foreword

This Part of BS 6010 has been prepared under the direction of the Machinery and Components Standards Policy Committee. It is identical with ISO 9628:1992 *Rolling bearings — Insert bearings and eccentric locking collars* published by the International Organization for Standardization (ISO).

BS 6010-4 is a technical revision of BS 6010-1:1980 and BS 6010-2:1980, both of which are superseded and withdrawn.

BS 6010 consists of the following Parts.

- *Part 3 Specification for dimensions of cast and pressed housings;*
- *Part 4 Specification for insert bearings and eccentric locking collars.*

Cross-references

International Standard	Corresponding British Standard
ISO 15:1981	BS 6267:1982 <i>Specification for rolling bearings: boundary dimensions for radial bearings</i> (Identical)
ISO 5593:1984	BS 6560:1984 <i>Glossary of terms for rolling bearings</i> (Identical)

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 12, an inside back cover and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

1 Scope

This International Standard specifies the characteristics, boundary dimensions, tolerances and radial internal clearances of insert bearings and eccentric locking collars.

NOTE 1 An insert bearing is defined as a radial rolling bearing with a spherical outside surface and an extended inner ring with a locking device (see ISO 5593). The locking device, for fixing the inner ring to the shaft, may be an eccentric locking collar or set screws either in a concentric collar around the inner ring or directly in the inner ring.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 15:1981, *Rolling bearings — Radial bearings — Boundary dimensions — General plan*.

ISO 5593:1984, *Rolling bearings — Vocabulary*.

3 Definitions

For the purposes of this International Standard, the definitions given in ISO 5593 apply.

4 Symbols

NOTE 2 The symbols (except those for tolerances) shown in the figures and given in the tables denote nominal dimensions unless otherwise specified.

A	width of inner ring eccentric surface
A_1	width of collar eccentric surface
ΔA_{1s}	deviation of a single collar eccentric surface width of eccentric locking collar
B	width of inner ring
B_1	overall inner ring width including eccentric locking collar
B_2	width of eccentric locking collar
ΔB_{2s}	deviation of a single collar width of eccentric locking collar
C	width of outer ring
C_a	distance from centre of outer ring to centre of lubrication zone
C_b	width of lubrication zone
d	bore diameter of bearing and eccentric locking collar

Δd_{mp}	deviation of mean bearing bore diameter in a single plane
V_{dp}	variation of bearing bore diameter in a single radial plane
Δd_s	deviation of single bore diameter of eccentric locking collar
d_1	outside diameter of eccentric locking collar
d_2	small bore diameter of eccentric surface (at theoretical sharp corner) of eccentric locking collar
Δd_{2s}	deviation of single small bore diameter of eccentric surface of eccentric locking collar
d_3	large diameter of inner ring eccentric surface (at theoretical sharp corner)
D	outside diameter of bearing
H	eccentricity
ΔH_s	eccentricity deviation in a single radial plane
r_1	chamfer dimension of inner ring eccentric surface
$r_{1s \min}$	smallest single chamfer dimension of inner ring eccentric surface
r_2	fillet radius of inner ring eccentric surface
$r_{2s \max}$	largest single fillet radius of inner ring eccentric surface
r_3	fillet radius of collar eccentric surface
$r_{3s \max}$	largest single fillet radius of collar eccentric surface
r_4	chamfer dimension of collar eccentric surface
$r_{4s \min}$	smallest single chamfer dimension of collar eccentric surface
S	distance from centre of raceway to inner ring face on side opposite the locking device
S_1	distance from centre of raceway to the face of inner ring or locking collar limiting the overall bearing width on the locking device side.

5 Characteristics

5.1 General

The bearings on one shaft are as a rule mounted in two or more separate housings, which are not always perfectly aligned. The outer ring has a spherical outside surface so that the bearing may be mounted in a housing with a matching spherical seating to provide correct initial alignment.

The bore surface may be plated to reduce corrosion during operation.

5.2 Bore diameter

To each bearing and eccentric locking collar size there is related one bore in millimetres and one or several bores in inches. The non-preferred inch bores, which are shown in parentheses in Table 1 to Table 3, should be avoided wherever possible.

Contrary to general rolling bearing practice, the bore tolerance is on the plus side of the nominal bore diameter, in order that the bearing and collar may be slipped over standard shafting.

5.3 Outside diameter

The outside diameter corresponds (with respect to the metric bore diameter) to the diameter series 2 of ISO 15.

5.4 Inner ring width and locking devices

The inner ring width does not conform to the requirements of ISO 15. It is determined by the requirements of space for sealing and locking devices and by the axial extension of the shaft support considered suitable for various applications.

Where the locking device extends axially beyond the inner ring, the width over the locking device, called the overall width, and the location with respect to the outer ring centreline of the side surface limiting the overall width, are important dimensions and are therefore specified in this International Standard.

Three series of overall widths, designated wide, intermediate and narrow, are given. Each of the Figure 1 to Figure 4 shows one example only of locking device design.

NOTE 3 The figures are drawn schematically and sealing devices are not shown.

5.5 Width of outer ring

For bearings with spherical outside surface, the width of the outer ring is not important provided the range of width is known so that assembly slots in the housing may be properly dimensioned. This International Standard therefore gives outer ring widths which range from a minimum that conforms to dimension series 02 in ISO 15 to a maximum that provides sufficient space for various seals and lubrication holes.

5.6 Relubrication

Depending on the application, these bearings are supplied with or without means for relubrication, for example one or several small radial holes drilled through the outer ring. The exact design or location of such means is not specified in this International Standard. It gives only the width and location of a zone which any relubrication means, provided on one or both sides of the outer ring, should intersect in such a way that lubricant will satisfactorily feed into the bearing from the housing bore groove covering the zone.