

Magnetic tape sound recording and reproducing systems —

Part 11: Guide to an address code for compact cassettes

UDC 681.846.7

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Electronic Equipment Standards Policy Committee (EEL/-) to Technical Committee EEL/22, upon which the following bodies were represented:

- British Broadcasting Corporation
- British Kinematograph, Sound and Television Society
- Council for Educational Technology for the United Kingdom
- Electronic Engineering Association
- Independent Broadcasting Authority
- Independent Television Authority
- Sound and Communication Industries Federation

The following bodies were also represented in the drafting of the standard, through subcommittees and panels:

- Association of Professional Recording Studios
- Audio Engineering Society
- British Tape Industry Association
- Royal Photographic Society

This British Standard, having been prepared under the direction of the Electronic Equipment Standards Policy Committee, was published under the authority of the Board of BSI and comes into effect on 29 September 1989

© BSI 12-1999

The following BSI references relate to the work on this standard:
Committee reference EEL/22
Draft for comment *BSI News*
July 1988

ISBN 0 580 17631 2

Amendments issued since publication

Amd. No.	Date of issue	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
1 Object	1
2 Features of address code system	1
3 Code	1
3.1 General description	1
3.2 The basic code	1
3.3 Electric signal properties/flux on tape	1
3.4 Positioning of code signal	1
Figure 1 — Example of a code signal	2
Figure 2a — Address code table	2
Figure 2b — Position of the pulses on the tape	3
Figure 3 — Tape flux according to Sub-clauses 3.3.3	3
Figure 4 — Tape flux according to Sub-clauses 3.3.3	4
Figure 5 — Magnetic situation of head during playback	4
Figure 6 — Recommended minimum interval to be respected between time-code and audio signal	5
Figure 7 — Audio attenuation to be applied under minimum interval conditions of Figure 6	5