

Specification for

Scales and sizes for plotting frequency characteristics and polar diagrams

UDC 621.3.085.4:621.3.018.4:621.3.012.12

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

Committees responsible for this British Standard

This British Standard was published under the direction of the Electronic Equipment Standards Committee EEL/-. Its preparation was entrusted to Technical Committee EEL/24 upon which the following bodies were represented:

- British Radio and Electronic Equipment Manufacturers' Association
- Department of Health and Social Security
- Department of Industry (National Physical Laboratory)
- Institution of Electronic and Radio Engineers
- Post Office
- Royal National Institute for the Deaf
- Society of Hearing Aid Audiologists Limited

This British Standard, having been prepared under the direction of the Electronic Equipment Standards Committee, was published under the authority of the Board of BSI and comes into effect on 29 July 1983

© BSI 12-1999

The following BSI references relate to the work on this standard:
Committee reference EEL/24
Draft for comment 82/32494 DC

ISBN 0 580 13381 8

Amendments issued since publication

Amd. No.	Date of issue	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
Introduction	1
1 Scope	1
2 Logarithmic frequency scales	1
3 Polar level diagrams	1
Appendix A Examples of the requirements specified in this standard	2
Figure A.1 — Example of ventilating noise spectrum with a scale proportion such that the length of the abscissa corresponding to a frequency ratio of 10 : 1 is equal to the length of the ordinate corresponding to 25 dB	3
Figure A.2 — Example of a microphone calibration curve showing sensitivity level S as a function of frequency f , with a scale proportion of 10 dB for a frequency ratio 10 : 1	4
Figure A.3 — Example of loudspeaker response with a scale proportion of 50 dB for a frequency ratio 10 : 1	4
Figure A.4 — Example of a polar diagram with a reference circle radius corresponding to 50 dB showing sound level at a distance of 150 m from an aircraft	5
Figure A.5 — Example of a polar diagram with a reference circle radius corresponding to 25 dB showing the directional response of a radial horn loudspeaker at 8 000 Hz	6

National foreword

This British Standard has been prepared under the direction of the Electronic Equipment Standards Committee. It is identical with IEC Publication 263:1982 “*Scales and sizes for plotting frequency characteristics and polar diagrams*” published by the International Electrotechnical Commission (IEC).

Terminology and conventions. The text of the International Standard has been approved as suitable for publication as a British Standard without deviation. Some terminology and certain conventions are not identical with those used in British Standards. Attention is drawn especially to the following.

In Figure A.3 the comma has been used as a decimal marker. In British Standards it is current practice to use a full point on the baseline as the decimal marker.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 6 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.