



BS 6779: Part 1 : 1987

UDC 625.738

© British Standards Institution. No part of this publication may be photocopied or otherwise reproduced without the prior permission in writing of BSI

British Standard

Parapets for vehicle containment on highways

Part 1. Specification for parapets of metal construction

Parapets de retenue des véhicules sur autoroutes
Partie 1. Parapets de construction métallique — Spécifications

Leitplanken auf Autobahnen
Teil 1. Leitplanken aus Metall

British Standards Institution

AVA **Documents**
Document Sharing Hub

Foreword

This Part of BS 6779 has been prepared under the direction of the Road Engineering Standards Committee. It is the first Part in a series of standards; the second Part so far planned in the series is Part 2 'Specification for parapets of concrete construction'.

This Part of BS 6779 contains a number of appendices the following of which form part of the specification:

Appendix E. Method of test for dynamic testing
(see 26.1)

Appendix F. Static testing of posts

Appendix G. Parapet designs exempted from the dynamic test requirement (see 0.5).

The following appendices do not form part of the specification but are included for guidance and information only:

Appendix A. Guidance on levels of containment and derivation of theoretical design forces

Appendix B. Guidance on limit state design

Appendix C. Detailed design guidance recommendations for new designs based on tested configurations

Appendix D. Information to be provided by the supplier/purchaser

NOTE. The standard allows a number of options. The purchaser/supplier should indicate to the supplier/purchaser which of the options he requires. Appendix D forms a checklist of the items on which the purchaser/supplier should have made a decision.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Contents

	Page		Page
Foreword		Inside front cover	
Committees responsible		Back page	
Specification		D Information to be provided by the supplier/ purchaser	33
Section one. General		E Method for dynamic testing	34
0 Introduction	2	F Static testing of posts	38
1 Scope	2	G Parapet designs exempted from the dynamic test requirements	40
2 Definitions	2	Tables	
3 Symbols	3	1 Designation of vehicle parapets	3
4 Designation of vehicle parapets	3	2 Minimum thickness of members, infill panels and other components	4
Section two. General design		3 Materials of construction for steel parapets	9
5 Levels of containment	4	4 Materials of construction for aluminium alloy parapets	10
6 Wind loading	4	5 Minimum requirements for construction of parapets over or adjacent to railways, intended for British Rail use	13
7 Minimum height	4	6 Theoretical mean impact force for a 90° impact from a 30 t vehicle	24
8 Minimum section thickness	4	7 Value of γ_{fL}	26
9 Freedom from projections and depressions	4	8 Value of f_k and γ_m	27
10 Durability and protection	5	9 Designation and limiting dimensions	27
11 Requirements at joints and at the ends of parapets	5	10 Design loads for parapets of tested configuration	32
12 Anchorages, attachment systems, bedding and plinths	7	Figures	
13 Parapets of open-framed design	8	1 Dynamic testing: vehicle dimensions and angle of impact	20
Section three. Materials		2 Variation of lateral impact force F with mass of vehicle m	21
14 Materials of construction	9	3 Variation of lateral impact force F with speed of vehicle v	21
Section four. Additional design requirements for parapets for particular applications		4 Variation of lateral impact force F with position of centre of gravity c	22
15 General requirements for infilling and additional members	11	5 Variation of lateral impact force F with position of centre of gravity b	22
16 Requirements for particular types of infilling	11	6 Variation of lateral impact force F with sum of barrier deflection and depth of vehicle crumpling z	23
17 Applications not over or adjacent to railways	11	7 Variation of lateral impact force F with angle of impact θ	23
18 Applications over or adjacent to railways	12	8 Theoretical mean lateral impact forces for varying z values for two vehicles	25
Section five. Construction		9 Vehicle parapet N/1.00/O: limiting dimensions for parapets of tested configuration	28
19 Steel workmanship, inspection and testing	14	10 Vehicle/pedestrian parapet: limiting dimensions for parapets of tested configuration	29
20 Aluminium alloy workmanship, inspection and testing	14	11 Vehicle/pedestrian parapet (type L/1.00/V): limiting dimensions for parapets of tested configuration	30
21 Tolerances	14	12 Vehicle/pedestrian parapet over railways: limiting dimensions for parapets of tested configuration	31
22 Fastenings	14	13 Typical layout of cameras for recording tests	35
23 Storage and transportation	14	14 Typical details to be included in test report	36
24 Installation and site workmanship	15	15 Apparatus for load testing parapet posts	39
25 Identification marking of parapet system	15		
Section six. Performance			
26 Type tests for parapet design	16		
27 Production testing of posts	17		
Appendices			
A Guidance on levels of containment and derivation of theoretical design forces	19		
B Guidance on limit state design	26		
C Detailed design guidance recommendations for new designs based on tested configurations	27		

Section one. General

0 Introduction

0.1 This Part of BS 6779 specifies requirements for parapets of metal construction which are designed to provide specified levels of vehicle containment on highways. These parapets are installed on bridges, retaining walls or other structures. Parapets of concrete or of combined concrete and metal construction are not covered in this standard.

0.2 Containment levels are related to defined vehicle impacts and a normal level of containment and low level of containment are specified. High level of containment parapets, which may be required in extremely high risk situations, are not covered in this standard. However, appendix A, which outlines the derivation of the design forces used in arriving at normal and low levels of containment, also indicates a possible high level of containment. This parameter has been used to design some high level of containment concrete parapets, although to date no metal parapets have been constructed to this level. The normal level of containment specified in this Part of BS 6779 is considered to offer a reasonable level of protection under all but the most exceptional cases. Containment levels are further discussed in appendix A.

0.3 The main objectives of the forms of parapets defined in this Part of BS 6779 are:

- (a) to provide specified levels of containment to limit penetration by errant vehicles;
- (b) to protect highway users and others in the vicinity by redirecting the errant vehicles with minimum deceleration forces on to a path as close as possible to the line of the parapet and to reduce the risk of the vehicle overturning.

0.4 The difficulty of predicting response to dynamic effects makes it impossible to give complete theoretical design criteria which could be guaranteed to produce satisfactory designs, and in consequence full-scale acceptance testing using a vehicle with appropriate impact characteristics is required for the approval of new designs. A method for acceptance testing is given in appendix E.

0.5 Parapets currently in general use in the UK for the applications covered in this Part of BS 6779 have been designed to Department of Transport requirements. These requirements were determined for the same vehicle impacts specified in this Part of BS 6779 applied to the particular parapet configurations. For such configurations detailed design guidance was derived and this is given in appendix C. Those designs (listed in appendix G) which have in the past received Department of Transport approval are deemed to meet the acceptance testing requirements of this Part of BS 6779 without further test.

1 Scope

This Part of BS 6779 specifies requirements for the design, materials, construction (including storage, transportation and installation) and testing of metal parapets not less than 12 m long (see note 2). The parapets covered in this Part

are mounted on plinths not greater than 100 mm high and are intended to provide specified levels of containment for vehicles on highways.

General information is provided in appendices A, B and C for designers wishing to produce new designs, and to guide prospective purchasers as to acceptable designs and indicate the principles on which existing designs are based.

NOTE 1. For barriers in and about buildings, see BS 6180. For pedestrian guard rails, see BS 3049. For safety fences and barriers for highways, see BS 6579.

NOTE 2. The containment characteristic of metal parapets is generally provided through absorption of the energy of the vehicle impact by progressive collapse of the support system over a length of parapet. A parapet of less than 12 m length may not provide the specified level of containment.

NOTE 3. The titles of the publications referred to in this standard are listed on the inside back cover.

2 Definitions

For the purposes of this Part of BS 6779 the following definitions apply.

2.1 parapet. A barrier at the edge of a bridge, or on top of a retaining wall or similar structure.

2.2 safety fence. An installation provided for the protection of users of the highway consisting of horizontal beams mounted on posts.

2.3 vehicle parapet. A parapet designed to provide a level of containment for errant vehicles in situations from which pedestrians and animals are normally excluded.

2.4 vehicle pedestrian parapet. A parapet designed to provide a level of containment for errant vehicles and to safeguard pedestrians (or deter pedestrians) from crossing the line of the parapet.

2.5 front face of a member. The face nearest to the traffic.

2.6 plinth. A continuous upstand on the edge of a structure upon which the parapet is mounted.

2.7 main structure. Any part of the bridge retaining wall or similar structure upon which the parapet is mounted including the plinth.

2.8 adjoining paved surface. The paved area on the traffic side of a parapet, immediately adjacent to the plinth or base of a parapet.

2.9 attachment system. The system of attachment of the parapet to the anchorage usually consisting of holding-down bolts.

2.10 anchorage. That part contained within the main structure to which the parapet is directly fixed by means of the attachment system; for example, a cast-in anchorage cradle in a reinforced concrete edge beam and plinth.

2.11 datum for height considerations. The highest level of footway, verge, carriageway or any other part of the road construction within 1.5 m of, and on a line at right angles to, the traffic face. This will normally be the adjoining paved surface.

2.12 effective longitudinal member. Those longitudinal members of a post-and-rail type parapet which become effective in restraining a vehicle in an impact.

2.13 non-effective longitudinal member. An additional longitudinal member above the effective longitudinal members provided to give additional height to the parapet for the protection of pedestrians or animals or to support noise barriers.

2.14 main longitudinal member. An effective longitudinal member of a post-and-rail type parapet with its centreline between 535 mm and 685 mm above the datum.

2.15 traffic face of a parapet. A vertical plane containing the front face of the main longitudinal member and the front face of the plinth.

2.16 infilling panel. A panel used to cover the spaces between members on the front face of a parapet to safeguard pedestrians.

NOTE. Where required infilling panels may also be used as a protection against splash and/or noise.

2.17 vertical infill bar. Infilling vertical members providing protection to pedestrians and animals by infilling between longitudinal members.

2.18 safety barrier. An installation provided for the protection of users of the highway which is continuously in contact with its supporting foundation.

3 Symbols

The following is a list of the symbols used in this standard to represent variables. Other symbols used for designation purposes are listed in table 1.

- a Mean deceleration (m/s^2)
- b Distance of the centre of gravity of the vehicle from the side (m)
- c Distance of the centre of gravity of the vehicle from the front (m)
- D Nominal bolt diameter (mm)
- F Mean impact force (kN)
- f_k Characteristic (or nominal) strength of the material
- m Vehicle mass (kg)
- n Number of effective longitudinal members
- Q^* Design loads (kN)
- Q_k Nominal loads (kN)
- R^* Design resistance
- S^* Design load effects
- v Approach velocity (m/s)
- z Sum of barrier deflection and depth of vehicle crumpling (m)
- γ_{fL} Partial load factor
- γ_{f3} Partial factor for load effects
- γ_m Partial factor on material strength
- σ_{vb} Minimum ultimate tensile strength of bolt material (N/mm^2)

σ_{ya} Minimum yield strength of anchorage material (N/mm^2)

θ Angle of path of vehicle (degrees)

4 Designation of vehicle parapets

For the purposes of an abbreviated description, vehicle parapets shall be designated by three characters indicating:

- (a) level of containment;
- (b) height of parapet;
- (c) type and height of infill.

Where appropriate, designations shall be supplemented by relevant information, e.g. materials, protection, infill treatment, anchorage type (see appendix D). Designation details are set out in table 1.

Table 1. Designation of vehicle parapets

Item	Designation	Clause ref.
(a)	Levels of containment N = normal level of containment L = low level of containment	5 5.1 5.2
(b)	Overall height of parapet 1.00 = 1 m height; 1.25 = 1.25 m height; 1.50 = 1.50 m height, etc.	7 figures 9, 10, 11 and 12
(c)	Infill for parapets not over railways O = no infill M = mesh infill to full height m = mesh infill to part height W = solid infill to full height w = solid infill to part height S = acoustic barrier V = vertical bar X = special design	16 16(b) 16(b) 16(d) 16(d) 16(e) 16(a)
	Infill for parapets over railways B = solid infill to full height b = solid infill to part height R = rail mesh to full height r = rail mesh to part height X = special design	16 16(d) 16(d) 16(c) 16(c)

NOTE. Examples of designation:

N/1.00/O indicates a parapet of 1 m height above the datum, of normal level of containment to 5.1 and with no infill component.

L/1.00/V indicates a parapet of 1 m height above the datum, of low level containment to 5.2 and with vertical bar infill to clause 16(a).

N/1.25/r indicates a parapet of 1.25 m height above the datum, of normal level of containment to 5.1 and with rail mesh infill of part height to clause 16(c).



Documents

Document Sharing Hub

BS 6779 : Part 1 : 1987
Section two

Section two. General design

5 Levels of containment

NOTE. Appendix A gives guidance on the derivation of forces from these criteria. Appendix B gives guidance on the method of design for general purposes and appendix C gives more detailed design guidance for new parapet designs based on tested configurations.

5.1 Normal level of containment

The normal level of containment shall be that required to resist penetration from the following vehicle impact characteristics:

Vehicle type	Saloon car
Mass	1500 kg
Height of centre of gravity	600 mm
Angle of impact	20°
Speed	113 km/h (70 mile/h)

NOTE. The normal level of containment is that suitable for general use.

5.2 Low level of containment

Low level of containment shall be that required to resist penetration from the following vehicle impact characteristics:

Vehicle type	Saloon car
Mass	1500 kg
Height of centre of gravity	600 mm
Angle of impact	20°
Speed	80 km/h (50 mile/h)

NOTE 1. The low level of containment is only suitable for use in 48 km/h (30 mile/h) speed restricted areas.

NOTE 2. The 80 km/h (50 mile/h) speed adopted for the test is considered to provide the minimum acceptable level of containment.

6 Wind loading

Wind loading shall be derived from the appropriate sub-clauses of 5.3 of BS 5400 : Part 2 : 1978 (see B.2.1).

Wind loading and vehicle impact forces shall not be considered coexistent.

NOTE. Where large areas of solid sheeting (e.g. acoustic barriers) are fixed to or form part of a parapet the effect of wind loading may be critical.

7 Minimum height

The height of the parapet shall be not less than 1.00 m measured above the datum for height consideration.

NOTE. Particular applications require greater heights of parapet to be used (see section four).

8 Minimum section thickness

The minimum thickness of section of all metal parts shall be in accordance with table 2.

9 Freedom from projections and depressions

9.1 The traffic face shall present a smooth surface, free from sharp edges.

9.2 Projections or depressions shall be permitted only at joints in longitudinal members. These shall not exceed 20 mm on the traffic face of the parapet.

Table 2. Minimum thickness of members, infill panels and other components

Material	Section	Minimum thickness			
		Primary load carrying members	Non-load carrying members and secondary elements of load carrying	Infilling panels, bars and mesh	Clips, covers fixings, etc
Steel	Hollow ¹⁾ sections, galvanized inside or out or fully sealed	mm 3	mm 3	mm 3	mm 3
	All other sections	4	3	3	3
Aluminium alloy	All	3	1.2	3	1.2
Stainless steel	All	2	1	2	0.5

¹⁾ See 10.4.

10 Durability and protection

10.1 Corrosion protection

10.1.1 Aluminium parapets shall be constructed of alloys inherently resistant to corrosion in roadside conditions and the materials specified in clause 14 shall be used.

NOTE. The aluminium alloys specified in clause 14 are satisfactory for all the usual exposure conditions but undue corrosion has been found to occur where salt can accumulate and the normal cleansing effects of weather are absent. An example is a parapet on a multi-level junction subject to spray from de-icing salt and sheltered by a bridge structure overhead. In such cases protective coatings should be considered.

10.1.2 Steel parapets shall be treated with a suitable protective system in accordance with the intended parapet environment and life requirement.

NOTE 1. Suitable systems are described in:

(a) BS 5493

(b) Department of Transport Specification for Highway Works (published by HMSO).

NOTE 2. The purchaser should state his requirements for the protective system to be used as indicated in appendix D.

NOTE 3. Roadside conditions may be highly corrosive. Where unsealed steel hollow sections are used (see 10.4) corrosion may take place internally. This has been found to affect a limited area around drainage holes, open ends, etc., the extent being to some degree affected by exposure conditions. Where hollow sections are hot dip galvanized, the internal galvanizing will be sufficient protection against this. Table 2 calls for extra thickness of such members where they are not galvanized but, although this may give the desired life, the products of corrosion may be unsightly.

10.1.3 Corrosion protection of attachment systems and anchorages shall be as specified in clause 12.

10.2 Accessibility for maintenance

Adequate clearance or means of access shall be provided around all parts requiring maintenance.

10.3 Mixing different materials

Parts requiring maintenance against corrosion shall not be incorporated into a parapet which is constructed of corrosion resistant materials. This requirement shall not preclude galvanized steel mesh being used on aluminium parapets.

10.4 Sealing and drainage

Hollow sections shall either be drained to prevent corrosion and damage occurring due to the freezing of water which may accumulate inside them or be sealed by all joints being made with continuous welds of structural quality.

Holes for galvanizing and/or drainage shall have a diameter not greater than one-twelfth of the circumference of the member, with a minimum diameter of 8 mm prior to galvanizing or 6 mm if not galvanized and a maximum diameter of 15 mm. Holes shall not be spaced closer than 700 mm if they are to be left open.

NOTE 1. Consideration should be given to the effect on the strength of members by the design, location and making of the holes.

NOTE 2. Moisture can collect in a section not open to direct penetration by condensation of water vapour drawn in by the breathing effect caused by changes in air temperature and pressure.

10.5 Vandalism

The need of the parapet to resist vandalism shall be taken into account in its design. It shall be ensured that fixings and fasteners are not so easily loosened as to allow parts of the parapet to be wilfully removed, simply and quickly using minimal tools, or to be damaged for example by blows (see appendix D).

11 Requirements at joints and at the ends of parapets

11.1 Post-and-rail type parapets

11.1.1 *Joints for total movements 0 mm to 50 mm.* Joints providing continuity between lengths of rails or across expansion or rotational joints where the total longitudinal movement at rail level is 50 mm or less shall comply with the following.

(a) *Rails in tension.* The joint shall be capable of transmitting 66 % of the tensile strength of the theoretical gross rail section.

(b) *Rails in bending.* The joint shall be capable of transmitting the full maximum design requirement of the rail in bending at any extension of the joint.

11.1.2 *Joints for total movements greater than 50 mm.* Joints across expansion or rotational joints where the total longitudinal movement at rail level is greater than 50 mm shall comply with the following.

(a) *Rails in tension.* No requirement to transmit tension.

(b) *Rails in bending.* Joints shall be capable of transmitting the full maximum design requirement of the rail in bending at any extension up to the full design movement at the joint plus 100 mm.

(c) *Posts.* Special end posts shall be provided at each side of the joint spaced as close together as is possible and not exceeding 1.5 m between centres (see 11.1.5).

11.1.3 *Joints where complex movements take place.* Joints where significant movement takes place in a vertical or transverse horizontal direction shall where possible comply with 11.1.1 and/or 11.1.2. Where compliance with 11.1.1 and/or 11.1.2 is not possible a discontinuity of the parapet shall be permitted. In such a case, special end posts shall be provided at each side of the joint spaced as close together as is possible and at centres not exceeding 1.5 m. The gap between the ends of the rails shall not exceed the expected closing at the joint plus 25 mm.

NOTE. It is emphasized that this discontinuity is only to be resorted to in extreme cases and it is most desirable that some form of bridging of the ends of the rails is devised to prevent, as far as is practicable, a vehicle which is in contact with a deflected length of parapet directly striking the end of an undeflected length.

When a bridging piece is used it shall be securely attached to the end of the rail on the approach side.

11.1.4 Ends of parapets

11.1.4.1 *Parapets with a safety fence.* Where a safety fence is provided on the approaches to each end of a parapet it shall, except as provided for in the following, be made

BS 6779 : Part 1 : 1987
Section two

continuous with the parapet by a connection capable of resisting an ultimate tensile force of not less than 330 kN (see note 1).

NOTE 1. Safety fences on the approaches provide protection to the end of the parapet and will normally be present on motorway or motorway type roads and on new major roads in rural areas. Problems can occur, however, particularly where structures are being replaced, where land take, environmental and other considerations may militate against the provision of safety fences. Such sites will have to be considered in the light of the particular circumstances pertaining and the best compromise available provided.

Where such a connection is not practicable, a full height anchorage capable of resisting an ultimate tensile force of not less than 330 kN shall be provided to the safety fence, either close to the parapet or at the transition from a tensioned to an untensioned safety fence. A connection capable of resisting an ultimate tensile force of not less than 50 kN shall also be made with the parapet having sufficient overlap to maintain support for a movement of 100 mm. The final parapet post shall be a special end post complying with 11.1.5.

NOTE 2. It will be necessary to have a special detail at the ends of the parapet where the safety fence is connected to it, to provide resistance to an ultimate tensile force of not less than 330 kN. This may give additional transverse stiffness, although there is no requirement for this. Ideally, the safety fence should be connected to transmit the force into the main structure within the shortest period of time. In the case of a post-and-rail parapet, by connecting to the first two or last two parapet posts, which may be strengthened and be at closer centres than elsewhere in the parapet, advantage is taken of the bending strength of the safety fence and the resistance is transferred directly into the main structure.

Alternatively, a suitable detail may be designed to transfer the tensile forces into the main structure over a number of bays through end and/or intermediate parapet posts. Rail expansion joints catering for movements of greater than ± 10 mm should not be included in such a detail and special attention should be given to the rail-to-post connections.

On short span structures (not exceeding 15 m total span), connections that are capable of resisting a minimum ultimate tensile force of 330 kN may be made to the main and lower effective longitudinal members on the approach and departure ends of the parapet, provided that any expansion joints in the rails are capable of resisting the residual tensile force at these joints.

Details of approved connections between the types of safety fence covered by BS 6579 : Parts 1, 4¹⁾, 5 and 6¹⁾ and the existing post-and-rail parapet designs exempted from dynamic testing under 26.2 of this Part of BS 6779 are given in BS 6579. These details do not necessarily cover all of the preceding requirements of this clause but are deemed to satisfy as they have successfully withstood dynamic testing and have been proved in service.

The end panel or panels of the parapet shall be strengthened, as necessary, to resist the minimum ultimate tensile force of 330 kN or 50 kN, as appropriate. (See note 2).

Rails at the ends of parapets situated above the level of the safety fence, which could be struck by a vehicle, shall oversail the final post of the parapet by not more than 600 mm and each shall be cranked back from the traffic face beyond the final post, or radiused, to give an angle of between 35° and 45° with the main axis of the rail so that the set back achieved is not less than 170 mm. The strength of the rail in bending shall be maintained to not less than 75 % of the normal rail strength.

11.1.4.2 *Parapets without a safety fence.* Where there is no safety fence on the approach to each end of a parapet the following shall apply.

(a) Such precautions as are practicable under the circumstances shall be taken to prevent errant vehicles colliding directly with the end of the parapet (see note 1 to 11.1.4.1).

(b) The final post at each end of the parapet shall be a special end post complying with 11.1.5.

11.1.5 *Special end posts.* A special end post shall have a design strength in the longitudinal direction equal to the design strength of an intermediate post in the transverse direction.

NOTE. This may be achieved by the combination of two intermediate posts spaced as close together as possible and not exceeding 1 m.

11.2 Other parapet configurations

11.2.1 *General.* When parapet designs of configurations other than post-and-rail are being considered the general principle embodied in 11.1 shall be followed, together with the requirements given in 11.2.2 and 11.2.3.

11.2.2 *Joints.* Joints shall comply with the following.

(a) *Joints for total movement 0 mm to 50 mm.*

Adequate continuity shall be provided in tension and bending.

(b) *Joints for total movement greater than 50 mm.*

Adequate continuity of bending shall be provided and the need for additional vertical stiffness assessed and provided if necessary.

(c) *At joints where complex movements occur.*

Discontinuity is permitted but the need for additional vertical stiffness shall be assessed and provided for if necessary.

NOTE. It is most desirable to provide some form of bridging (see 11.1.3).

11.2.3 Ends of parapets

11.2.3.1 Where a safety fence is provided on the approaches to each end of a parapet it shall, except as provided for in the following, be made continuous with the parapet by a connection capable of resisting an ultimate tensile force of at least 330 kN.

Where such a connection is not practicable, a full height anchorage capable of resisting an ultimate tensile force of at least 330 kN shall be provided to the safety fence, either close to the parapet or at the transition from a tensioned to an untensioned safety fence. A connection capable of resisting an ultimate tensile force of not less than 50 kN shall also be made with the parapet having sufficient overlap to maintain support for a movement of not less than 100 mm.

Any part of the parapet which projects above the safety fence shall be cranked back from the traffic face to give an angle of between 35° and 45° with the main axis of the parapet, so that the set back achieved is not less than 170 mm, so as to avoid the possibility of an errant vehicle

¹⁾ In preparation.

impacting directly with a vertical end. Adequate strength in bending shall be maintained to assist in deflecting an errant vehicle.

11.2.3.2 Where there is no safety fence on the approach to each end of a parapet, such precautions as are practicable under the circumstances shall be taken to prevent errant vehicles colliding directly with the end of the parapet (see note 1 in 11.1.4.1).

12 Anchorages, attachment systems, bedding and plinths

12.1 General

The anchorage, attachment system and the main structure, including the plinth, shall be designed to resist without damage all loads which the parapet is theoretically capable of transmitting, up to and including failure, in any mode which may be induced by vehicular impact.

NOTE. Appendix B gives guidance on suitable partial factors to cover these requirements in normal circumstances.

The design of parapet attachment systems and anchorages shall be such that removal and replacement of damaged sections of parapet may be readily achieved.

12.2 Fixings using base plates

Parapets which use base plates, such as post-and-rail systems, shall be fixed to the main structure via the base plates by stainless steel holding-down bolts engaging with an anchorage.

12.3 Engagement of holding-down bolts

NOTE. See also note 1 in 24.4.

Each holding-down bolt shall have a length of engagement into the anchorage of twice the nominal bolt diameter or that given by the following expression, whichever is the greater:

$$0.7 \times \frac{\sigma_{vb}}{\sigma_{va}} \times D$$

where

σ_{vb} is the minimum ultimate tensile strength of the bolt (N/mm^2);

σ_{va} is the minimum yield strength of the anchorage (N/mm^2);

D is the nominal bolt diameter (mm).

NOTE 1. This is to ensure that bolt failure occurs prior to anchorage thread failure.

NOTE 2. If the type of holding-down bolt used requires an initial torque to be effective this torque should be specified.

12.4 Anchorages in concrete main structures

Anchorages in concrete shall be either cast-in cradle anchorages, or cast-in or drilled individual bolt anchorages that are of purpose design or of proprietary manufacture. It shall be ensured that they will provide the necessary resistance taking into account the effect of possible overlap of stress cones from individual bolts and any bursting forces from expanding type anchorages.

NOTE 1. The concrete of the main structure may need additional local reinforcement to resist without damage the forces which may be transmitted from the parapet.

NOTE 2. Static testing of the proposed assembly may be considered advisable if other evidence is not available covering the particular application.

NOTE 3. It is good practice to fill any voids in anchorages such as those around bolts in holes drilled for individual anchorages, with a non-setting passive filler to prevent the collection of water which may freeze and engender bursting stresses.

12.5 Bedding

Any bedding used, e.g. between base plates and plinth, shall be capable of permanently transmitting the loads involved, safely and without undue deformation. The finished bedding shall not contain voids and shall be resistant to penetration by water. It shall have a minimum thickness of 10 mm and a maximum thickness of 30 mm plus allowance for falls on the top of the plinth (see clause 24 and note 1 to 24.4). Due regard shall be given to the bearing stresses developed in any bedding or in the concrete plinth.

12.6 Plinth

Where the main structure is of concrete, the parapet shall be mounted on a plinth having an upstand above datum of not less than 50 mm at the traffic face and not more than 100 mm at any point on the cross section and having its front edge in line with the traffic face of the parapet. The width of the plinth shall be sufficient to accommodate the maximum wheel penetration recorded in the dynamic test with a minimum of 500 mm for normal level of containment parapets and 350 mm for low level of containment parapets.

12.7 Resistance to corrosion and frost damage

The following requirements shall be observed in addition to the general requirements of this Part of BS 6779.

(a) Aluminium which is to be in contact with concrete or mortar shall be coated with at least two applications of bituminous coating solution in accordance with BS 3416 or with hot-dip bitumen, applied to a clean degreased surface.

(b) Metal-to-metal contact between dissimilar materials shall be avoided by the use of non-metallic sleeves, washers or coatings to prevent galvanic corrosion.

(c) Parts of anchorages within 50 mm of the surface of the plinth shall be suitably protected against corrosion.

NOTE. The use of corrosion resistant materials or of steel galvanized in accordance with BS 729 is suitable.

BS 6779 : Part 1 : 1987
Section two

13 Parapets of open-framed design

Parapets of open-framed design, such as post-and-rail, shall comply with the following.

- (a) The effective longitudinal members shall not be so narrow or so shaped as to cause undue damage to an impacting vehicle.

NOTE 1. A 50 mm overall depth with a blunt profile to the traffic face has been found satisfactory in existing designs.

- (b) Effective longitudinal members shall not be so widely spaced as to allow undue penetration by parts of impacting vehicles and the supporting members shall be set far enough back from the traffic face to avoid direct impact from parts of vehicles that do penetrate between longitudinal members.

NOTE 2. A combination of a maximum gap between effective longitudinal members of 300 mm and a set back of 150 mm between the traffic face and the front face of the post at the base of the posts has been found satisfactory in existing designs.

Section three. Materials

14 Materials of construction

14.1 Steel parapets

Steel used for parapets shall comply with the appropriate British Standards listed in table 3.

Table 3. Materials of construction for steel parapets		
Form of material	Specification	
	BS number	Requirements specified
Hot rolled sections Hot rolled hollow sections Equal and unequal angle sections	BS 4 : Part 1 BS 4848 : Part 2 BS 4848 : Part 4	Dimensions and sectional properties (see BS 4360 for other relevant requirements)
Weldable structural steels (includes appropriate requirements for items above)	BS 4360	Physical properties, chemical composition, and dimensional tolerances
Plate, sheet and strip: Carbon steel Stainless steel	BS 1449 : Part 1 BS 1449 : Part 2	Physical properties, chemical composition, material condition and dimensional tolerances
Bars, rods Welded wire mesh Expanded metal: carbon steel stainless steel	BS 970 : Part 1 BS 4483 BS 1449 : Part 1 BS 1449 : Part 2	Physical properties, chemical composition and dimensional tolerances General requirements Properties, chemical compositions, material condition and dimensional tolerances
Fasteners (see note) ISO metric black hexagon bolts, screws and nuts ISO metric precision hexagon bolts, screws and nuts Washers Spring washers Corrosion resistant stainless steel fasteners High strength friction grip bolts	BS 4190 BS 3692 BS 4320 BS 4464 BS 6105 BS 4395 : Part 1	Dimensions, sizes, physical properties, chemical compositions, grades, tolerances and marking
NOTE. The standards listed in this table relating to the form of fasteners do not cover special bolts, nuts, screws, etc. which may be used for particular fixings where it is not possible to incorporate bolts, screws, etc. of standard dimensions or where special fixings are required to resist vandalism (see 10.5).		

BS 6779 : Part 1 : 1987
Section three

14.2 Aluminium alloy parapets

Aluminium alloys used for parapets shall comply with the appropriate British Standards listed in table 4.

Table 4. Materials of construction for aluminium alloy parapets

Form of material (see note 1)	Specification	
	BS number and designation	Requirements specified
Extruded sections	BS 1474, alloys 6061, 6063 and 6082	Chemical composition, properties and tolerances
Drawn tube	BS 1471, alloys 6061, 6063 and 6082	Chemical composition, properties and tolerances
Seam welded tube	BS 4300/1, alloy 5251	Tolerances, properties and mechanical tests
Plate and sheet	BS 1470, alloys 1200, 3103, 5083, 5251 and 6082	Chemical composition, properties and tolerances
Rivets	BS 1473, alloys 5154A and 6082 BS 1474, alloy 5065A	Chemical composition, properties and tolerances
Castings	BS 1490, alloys LM6 and LM25	Chemical composition, dimensions, properties and chemical tests
Welding filler rods and wire	BS 2901 : Part 4	Chemical composition, properties, diameters and tolerances
Welded wire mesh	BS 4483	General requirements
Expanded metal	BS 1470	Properties, chemical composition, material condition and dimensional tolerances
Fasteners (see note 2): ISO metric black hexagon bolts, screws and nuts ISO metric precision hexagon bolts, screws and nuts Washers Spring washers Corrosion resistant stainless steel fasteners High strength friction grip bolts	BS 4190 BS 3692 BS 4320 BS 4464 BS 6105 BS 4395 : Part 1	Dimensions, sizes and tolerances Chemical composition and physical properties
NOTE 1. The physical properties of aluminium alloys may be modified by welding. A method of dealing with this effect for design purposes is given in B.2.3. NOTE 2. The standards listed in this table relating to the form of fasteners do not cover special bolts, screws, etc. which may be used for particular fixings where it is not possible to incorporate bolts, screws, etc. of standard dimensions or where special fixings are required to resist vandalism.		

Section four. Additional design requirements for parapets for particular applications

NOTE. This section deals with those applications which call for requirements such as pedestrian protection in addition to vehicular containment. The usual need is to fill gaps in open parapets, such as post-and-rail types.

Cladding made to parapets for the purpose of meeting those requirements could affect performance in respect of vehicle containment, appropriate standard treatments are given for the most common requirements. These are considered to be satisfactory for the situations described and care should be taken if there are any departures to ensure that additional hazards are not created.

15 General requirements for infilling and additional members

Infilling or additional members for particular applications shall comply with the following.

- (a) There shall be no footholds or projections on the traffic face where pedestrians have access.
- (b) All cladding shall be securely fixed and shall not be easily detachable (see 10.5).
- (c) No reflective surfaces shall be used which might create a hazard for users of any road or railway.

16 Requirements for particular types of infilling

Infilling used for the protection of pedestrians and/or livestock and acoustic barriers shall be of one of the following (see note 1).

- (a) *Vertical bars.* Vertical bar infilling spanning between effective longitudinal members shall comply with the following and be in accordance with figure 11. This shall only be used for low level of containment parapets. The product of the nominal yield stress, or 0.2 % proof stress, and the plastic modulus of the vertical bars forming the infilling shall be not less than the moment induced by a design point load Q^* of 10 kN applied in any direction.

Each connection to the longitudinal members shall develop at least half the strength of the infilling bar in bending and tension and the strength of the bar in shear. The longitudinal member at the connection shall not fail by local buckling due to forces applied by the infilling.

- (b) *Wire mesh and expanded metal for applications not over or adjacent to railways.* Wire mesh and expanded metal shall have apertures with a perimeter not exceeding 200 mm. The minimum metal thickness shall be in accordance with table 2 and the maximum metal thickness shall not exceed the minimum requirement by more than 1.5 mm.

Expanded metal shall be supplied in a deburred and pressure roll flattened condition so that the strands are in the same plane as the sheet.

- (c) *Wire mesh and expanded metal for railway applications.* Wire mesh and expanded metal sheet shall have a minimum metal thickness in accordance with table 2 and the maximum metal thickness shall not exceed the required minimum thickness by more than 1.5 mm.

Wire mesh infill shall have apertures not exceeding 25 mm x 25 mm.

Expanded metal sheet infill shall have openings not exceeding 45 mm x 20 mm and shall be fixed vertically with the long dimension horizontal. It shall be supplied in a deburred and flattened condition so that the strands are in the same plane as the sheet.

- (d) *Solid panels.* Solid infill panels shall present a smooth surface to the traffic face. Joint gaps shall not exceed 3 mm. The minimum metal thickness shall be in accordance with table 2. The maximum metal thickness shall not exceed the required minimum thickness by more than 1 mm generally and 2 mm in the case of acoustic barriers (see notes 1, 2, 3 and 4).

- (e) *Acoustic barriers.* On occasions it will be necessary to combine a noise barrier with a vehicle parapet with or without pedestrian access. The noise attenuation requirements may give variable heights and thicknesses of infill and each case shall be considered on its merits observing the general requirements of this section (see note 5).

NOTE 1. A grit blasted finish or a patterned surface with maximum depth of 1 mm may be used on solid panels to offset the risk of dazzle (see note 3).

NOTE 2. Solid infill may also be used for anti-splash or anti-dazzle purposes.

NOTE 3. Deeply corrugated infill panels can present a hazard on vehicle impact. They should not be located on the traffic face.

NOTE 4. Wind loading should be considered where solid infill is used (see appendix B).

NOTE 5. Where acoustic barriers are large or heavy compared with the solid infill requirements it will be necessary to attach them to the non-traffic face of the parapet.

17 Applications not over or adjacent to railways

17.1 The following requirements shall be observed.

- (a) *Pedestrian protection.* Mesh or solid infill shall extend from not more than 25 mm above the plinth at the traffic face to the full height of the parapet with the exception that vertical bar infill may be used for low containment parapets.

- (b) *Livestock protection.* Vehicle pedestrian parapets on accommodation bridges requiring to contain livestock, including horses, shall be of a minimum height of 1.5 m. This height shall be achieved by the use of an additional 'non-effective' longitudinal member. Infilling shall be provided in accordance with clause 16.

BS 6779 : Part 1 : 1987

Section four

NOTE. In some cases on bridges carrying farm accommodation roads, it has been considered reasonable to provide low level of containment, 1.5 m high, full-height mesh type parapets (L/1.5/M). Such roads are provided to restore severed access to farms and are not public highways. They are not usually of such a standard as to allow high approach speeds, the bridges are generally narrow, restricting the angle of impact possible, and use is limited and mainly by drivers familiar with the road. Three such parapets are in current use and are included in the list in appendix G.

17.2 Non-effective longitudinal members shall be designed to withstand a horizontal ultimate loading of 1.4 kN/m and the parapet posts shall be checked to prove that they are capable of providing support for the consequent effects.

This loading shall not be considered coexistent with the loading required for vehicle containment.

18 Applications over or adjacent to railways

Minimum requirements for railways, intended for British Rail use, shall be as summarized in table 5.

NOTE. For specific applications reference should be made to British Rail or other appropriate railway authority.