

CONFIRMED OCTOBER 1985

**Detail specification for
cold welded seal quartz
crystal units for
oscillator applications —
DN, DQ and DP
enclosures, 0.8 to 20 MHz
and 3.0 to 30 MHz
frequency ranges —
Fundamental
thickness-shear mode,
AT-cut, for operation
over narrow temperature
ranges (temperature
controlled) —
Full assessment level**

UDC 621.373.5:621.382

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents**AVA**

Document Sharing Hub

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 7 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
1 Ratings	1
2 Characteristics at reference temperature $25 \pm 2^{\circ}\text{C}$	1
3 Marking	1
4 Related documents	2
5 Ordering information	2
6 Certified test records	2
7 Inspection requirements	4
Table 1 — Resonance resistance limits for AT-cut crystals in style DN enclosures	2
Table 2 — Resonance resistance limits for AT-cut crystals in style DP and DQ enclosures	3
Table 3 — Ratings and characteristics	3

