BRITISH STANDARD

BS 9612 N018: 1979

CONFIRMED
OCTOBER 1985

Detail specification for resistance welded seal quartz crystal units for oscillator applications — DN, DZ, DQ and DP enclosures, 17 to 75 MHz frequency range — Third overtone thickness-shear mode, AT-cut, for operation over wide temperature ranges (non-temperature controlled) — Full assessment level

UDC 621.373.5:621.382

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

Document Sharing Hub

Full document details: BS 9612 N018:1979

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 7 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

Amendments issued since publication

Amd. No.	Date	Comments

© BSI 04-2000

Committee reference ECL/11

ISBN 0 580 10726 4

Documents
Document Sharing Hub

Full document details: BS 9612 N018:1979

Contents

		Page
1	Rating	1
2	Characteristics at reference temperature 20 ± 2 °C	2
3	Marking	2
4	Related documents	2
5	Ordering information	2
6	Certified test records	2
7	Inspection requirements	4
Table 1 — Rating and characteristics		3

© BSI 04-2000

Documents
Document Sharing Hub
Full document details: BS 9612 N018:1979

blank

Documents
Document Sharing Hub

Full document details: BS 9612 N018:1979