

Blank detail specification for

**Fixed insulated
(unshielded) r.f.
inductors at the full
assessment level**

Confirmed
January 2011

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 11 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

Amendments issued since publication

Amd. No.	Date of issue	Comments
3773	November 1981	
5588	February 1987	Indicated by a sideline in the margin

Contents

	Page
1 Scope	1
2 Additional inspection requirements	1
3 Detail specification	1
4 Ordering information	5
5 Certified test records	5
6 Delayed delivery	5
7 Additional information (not for inspection purposes)	5
8 Inspection requirements	5
Figure 1 — Derating curve	4
Table 1 — Dimensions and ratings	3
Table 2 — Electrical characteristics	11

1 Scope

This standard lists the ratings, characteristics, inspection requirements and additional information for fixed insulated (unshielded) r.f. inductors at the full assessment level which are to be included as minimum mandatory requirements in the detail specification. It constitutes therefore a blank detail specification derived from BS 9750: Specification for fixed r.f. inductors of assessed quality: Generic data and methods of tests.

2 Additional inspection requirements

Only those tests listed in BS 9750 shall be used for the comparison of parts. A scheme for the inspection of structurally similar components is included in Appendix B of BS 9750.

The tests of BS 9750 shall be used to prove the performance requirements of parts, although additional or alternative tests may be specified by a manufacturer subject to the provisions of **2.4.2** of BS 9000. In addition to alternative tests, a manufacturer may also specify at his discretion more stringent inspection and acceptance quality levels, more severe environments and increased test durations where applicable.

Where alternative test methods are possible for a particular test, the detail specification shall state clearly which method is to be used.

3 Detail specification

The blank detail specification which follows, when completed where necessary as indicated by an asterisk, will form the relevant detail specification.