

Methods of test for motor vehicle paints —

Part 2: Resistance to continuous salt spray

UDC 629.113:667.613:620.193.272

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

This British Standard, having been approved by the Automobile Industry Standards Committee, was published under the authority of the Executive Board of the Institution on 31 March 1969

© BSI 02-2000

The following BSI reference relates to the work on this standard:
Committee reference AUE/-

ISBN 0 580 05238 9

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Foreword	ii
1 Scope	1
2 Correlation and limitations of test	1
3 Supplementary information	1
4 Test specimens	1
5 Test equipment	1
6 Position of specimens during test	2
7 Test solution	2
8 Air supply	2
9 Test conditions	3
10 Procedure	3
11 Report of test	3
Figure 1 — Salt spray cabinet for test condition T25	4
Figure 2 — Salt spray jet for test condition T25	5
Figure 3 — Salt spray cabinet for test condition T35	6
Figure 4 — Walk-in chamber, 1.5 m by 2.5 m and upward in overall size for test condition T35	7

Foreword

This Part of this British Standard has been prepared under the authority of the Automobile Industry Standards Committee and is based on Information Sheet No. NM – 5X of the Society of Motor Manufacturers and Traders Ltd. (SMMT).

Tests for paints for general purposes are given in BS 3900¹⁾ and, wherever possible, reference has been made to that standard.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

¹⁾ BS 3900, “*Methods of test for paints*”.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 7 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.