

Tyres and wheels —

Part 1: Tyres —

Section 7: Moped tyres —

Subsection 7.1 Specification for tyre designations, dimensions and load ratings

[ISO title: Moped tyres and rims — Part 1: Tyres]

UDC 629.113.012.5:(083.3):629.118.35:006.3/8

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Automobile Standards Committee (AUE/-) to Technical Committee AUE/4, upon which the following bodies were represented:

- Agricultural Engineers' Association
- Automobile Association
- British Industrial Truck Association
- British Pressure Gauge Manufacturers' Association
- British Rubber Manufacturers' Association
- Bus and Coach Council
- Department of Transport
- Freight Transport Association
- Ministry of Defence
- Motor Cycle Association of Great Britain
- Motor Industry Research Association
- Retread Manufacturers' Association
- Road Haulage Association Ltd.
- Society of Motor Manufacturers and Traders Ltd.

This British Standard, having been prepared under the direction of the Automobile Standards Committee, was published under the authority of the Board of BSI and comes into effect on 28 February 1989

© BSI 02-2000

The following BSI references relate to the work on this standard:
Committee reference AUE/4
Draft for comment 78/71455 DC

ISBN 0 580 17133 7

Amendments issued since publication

Amd. No.	Date of issue	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
1 Scope	1
2 Field of application	1
3 References	1
4 Definitions	1
Section 1. Tyre designation and dimensions	
5 Tyre designation	1
6 Tyre dimensions	1
7 Method of measurement of tyre dimensions	2
Section 2. Load ratings	
8 Load capacities and inflation pressures	3
Annex Tyres for small cubic capacity motorcycles and mopeds	6
Table 1 — Nominal rim diameter code	1
Table 2 — Section height	1
Table 3 — Moped tyres in highway service — Designation and dimensions — Rim diameter code: 14 to 22	2
Table 4 — Moped tyres in highway service — Designation and dimensions — Rim diameter code: 8 to 12	3
Table 5 — Maximum load capacity for corresponding inflation pressure — Rim diameter code: 14 to 22	4
Table 6 — Maximum load capacity for corresponding inflation pressure — Rim diameter code: 8 to 12	5
Table 7 — Load capacities and relevant inflation pressures	6
Publications referred to	Inside back cover

National foreword

This Subsection of this Part of BS AU 50, prepared under the direction of the Automobile Standards Committee, is identical with ISO 5995-1:1982 (confirmed 1987) “*Moped tyres and rims — Part 1: Tyres*” published by the International Organization for Standardization (ISO). Other Parts of the standard are:

- *Part 2: Wheels and rims;*
- *Part 3: Valves.*

Terminology and conventions. The text of the International Standard has been approved as suitable for publication as a British Standard without deviation. Some terminology and certain conventions are not identical with those used in British Standards; attention is drawn especially to the following.

Wherever the words “International Standard” appear, referring to this standard, they should be read as “Subsection of BS AU 50”.

The comma has been used as a decimal marker. In British Standards it is current practice to use a full point on the baseline as the decimal marker.

Cross-references. There are no corresponding British Standards for ISO 3833:1977 or ISO 4223-1:1978. The Technical Committee has reviewed the provisions of ISO 3833 and ISO 4223-1 and has decided that they are acceptable for use in conjunction with this standard.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 6, an inside back cover and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.