

Tyres and wheels —

Part 4: Rim profiles and dimensions —

Section 6: Motorcycle rims —

Subsection 6.3 Specification for code designated series (diameter codes 4 to 12) rims

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Automobile Standards Policy Committee (AUE/-) to Technical Committee AUE/4, upon which the following bodies were represented:

- Agricultural Engineers' Association
- Automobile Association
- British Industrial Truck Association
- British Pressure Gauge Manufacturers' Association
- British Rubber Manufacturers' Association
- Bus and Coach Council
- Department of Transport
- Freight Transport Association
- Institute of Road Transport Engineers (Incorporated)
- Motor Cycle Industry's Association of Great Britain Ltd.
- Motor Industry Research Association
- National Tyre Distributors' Association
- Retread Manufacturers' Association
- Road Haulage Association Ltd.
- Royal Automobile Club
- Society of Motor Manufacturers and Traders Ltd.

This British Standard, having been prepared under the direction of the Automobile Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 31 January 1992

© BSI 01-2000

The following BSI references relate to the work on this standard:
Committee reference AUE/4
Draft for comment 89/75746 DC

ISBN 0 580 20377 8

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
1 Scope	1
2 Normative reference	1
3 Finish	1
4 Designation	1
5 Divided rims	1
6 Drop centre rims	1
7 Tapered bead seat rims (MT type)	1
8 Recommended rim widths	1
9 Rim circumference measurement	1
Annex A (normative) Rim circumference measurement	6
Figure 1 — Divided rim contour	2
Figure 2 — Drop centre rims — Contour dimensions	3
Figure 3 — 5° tapered bead seat rim contours (MT type)	4
Figure 4 — Bead seat contours for MT rims without hump	5
Table 1 — Divided rims — Contour dimensions	2
Table 2 — Divided rims — Diameters	3
Table 3 — Drop centre rims — Contour dimensions	3
Table 4 — Drop centre rims — Diameters	4
Table 5 — Dimensions of tapered bead seat rims	4
Table 6 — Bead seat contours for MT rims without hump	5
Table 7 — Recommended rim widths	5
Table A.1 — Mandrel diameters and tape circumferences	6
Publication(s) referred to	Inside back cover

National foreword

This Subsection of this Part of BS AU 50, prepared under the direction of the Automobile Standards Policy Committee, is identical with ISO 6054-2:1990 “*Motorcycle tyres and rims (code-designated series) — Diameter codes 4 to 12 — Part 2: Rims*”, published by the International Organization for Standardization (ISO). The corresponding tyre details are dealt with in Part 1 (Subsection 6.3). Other Parts of the standard are:

- *Part 1: Tyres;*
- *Part 2: Wheels and rims;*
- *Part 3: Valves.*

Part 4 of BS AU 50 (covering rim profiles and dimensions) has been introduced to assist cross-referencing between tyre specifications and the corresponding rim specifications. Subsections of Part 4 will partially supersede the information contained in BS AU 50-2.1b:1980 which has been amended accordingly.

Cross-references

The Technical Committee has reviewed the provisions of ISO 3911, to which reference is made in the text, and has decided that they are acceptable for use in conjunction with this standard.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 6, an inside back cover and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.