

Harmonized system of quality
assessment for electronic components

Capability detail specification: Flex-rigid multilayer printed boards with through connections

ICS 31.180

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW



Document Sharing Hub

National foreword

This British Standard is the English language version of CECC 23600-801:1998 published by the European Eelectronic Components Committee (CECC) of the European Committee for Electrotechnical Standardization (CENELEC).

This standard should be read in conjunction with the most recent editions of BS EN 123000 and BS EN 123600.

The UK participation in its preparation was entrusted to Technical Committee EPL/501, Electronic assembly technology, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the CECC title page, pages 2 to 19 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

This British Standard, having been prepared under the direction of the Electrotechnical Sector Board, was published under the authority of the Standards Board and comes into effect on 15 June 1998

© BSI 05-1999

ISBN 0 580 29890 6

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
National foreword	Inside front cover
Foreword	2
Text of CECC 23 600-801	3

English version

Capability Detail Specification: Flex-rigid multilayer printed boards with through connections

Spécification particulière d'Agrément:
Cartes imprimées multicouches flexorigides
avec connexions transversales

Bauartspezifikation zur Anerkennung der
Befähigung:
Starr-flexible Mehrlagen-Leiterplatten mit
Durchverbindungen



This Capability Detail Specification was approved on 1997-08-06.

Up-to-date lists and bibliographical references of other detail specifications relating to EN 123000:1991 and EN 123600:1996 may be obtained on application to the Central Secretariat or to any CENELEC member.

This CECC Detail Specification exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B-1050 Brussels

Foreword

This Capability Detail Specification has been prepared by CENELEC/TC CECC/SC 52, Printed Boards (formerly designated CECC Working Group 23).

It was approved as CECC 23 600-801 on 1997-08-06.

It should be read in conjunction with EN 123000:1991 and EN 123600:1996 and with the current regulations for the CECC System.

Contents

	Page
Foreword	2
1 General	3
1.1 Scope	3
1.2 Object	3
2 Capability qualifying component	3
2.1 Materials	3
2.2 Surface finishes	4
2.2.1 Metallic finishes	4
2.2.1.1 Accelerated ageing	4
2.2.2 Organic finishes	4
2.3 Variant designation	5
3 Capability approval	5
3.1 Range of capability approval	5
3.2 QPL information	5
4 Capability test programme	5
4.1 Capability demonstration	5
4.1.1 Other metallic surface finishes	5
4.1.2 Organic surface finishes	6
5 Additional capability	6
6 Traceability	6
Annex A Edge connector imperfections	18
Annex B Circumferential defects in plated-through holes	19
Table I — Capability approval test schedule	7
Table IIa — Additional metallic conductor finishes	12
Table IIb — Additional contact finishes	15
Table III — Permanent organic finishes	16

1 General

1.1 Scope

This Capability Detail Specification (CapDS) is based upon EN 123600. It relates to flex-rigid multilayer printed boards with through connections, made with materials and surface finishes as specified in clause 2.

1.2 Object

To specify the Capability Qualifying Component (CQC), its characteristics to be tested, the test methods and conditions to be applied and the requirements to be fulfilled for testing basic and extended capability.

2 Capability Qualifying Component (CQC)

Test boards to be used as CQCs for basic capability shall:

- be made from a combination of the materials specified in 2.1 of this CapDS. The construction shall be as given in 8.3 of EN 123600.
- bear the composite test pattern (CTP) specified in 8.3 of EN 123600 (or equivalent CTP), for basic and other metallic finishes. CTPs as specified in 8.2 of EN 123200 (or equivalent CTP) shall be used to demonstrate organic surface finishes and external bonded heat sinks.
- have one of the surface finishes specified by groups 11, 12, 13, 14, 15, 16, or 18 in 2.2 of this CapDS.

Requirements for test boards to be used as modified CQCs for the demonstration of additional capability are detailed in clause 5 of this CapDS.

2.1 Materials

Material group designation	Specification	Base Material		Base material (thickness range)	Cu thickness (µm)
		Type	Grade		
A	EN 60249-2-11	Epoxide woven glass	General purpose	0,05 0,8 mm	18, 35, 70, 105
	EN 60249-2-12	Epoxide woven glass	Defined flammability	≥ 0,05 mm	
	EN 60249-3-1G EN 60249-3-1GF	Prepreg Prepreg	General purpose Defined flammability	≥ 0,05 mm	n.a.
B	EN 60249-2-8	Polyester (PETP) film	General Purpose	12,5 125 µm	18, 35, 70
	EN 60249-2-13	Polyimide film	General purpose	12,5 125 µm	
	EN 60249-2-15	Polyimide film	Defined flammability	12,5 125 µm	

2.2 Surface finishes

2.2.1 *Metallic finishes*

Finish group Designation	Surface finish	Abbreviation for QPL	Remarks
11	Bare copper	Cu	
12	Copper with solderable organic protective coating	Cu(opc)	
13	Copper with oxide	Cu(CuO)	
14	Tin, Tin-Lead	Sn, SnPb	
15	Tin-Lead (fused)	SnPb(f)	
16	Tin-Lead (dipped and levelled)	SnPb(dl)	
17			not assigned
18	Immersion Gold over Electroless Nickel	AuNi(smt)	
19			not assigned
20			not assigned
21	Specimen K 5 µm, gold plated on copper, remainder using finish group 11–17 (see below)	5AuCu	
22	Specimen K 0,7 µm, gold plated on nickel, remainder using finish group 11–17 (see below)	0,7AuNi	
23	Specimen K 2,5 µm, gold plated on copper, remainder using finish group 11–17 (see below)	2,5AuCu	
24	Specimen K 2,5 µm, gold plated on nickel, remainder using finish group 11–17 (see below)	2,5AuNi	

The demonstration of metallic group finishes 21, 22, 23 or 24 shall be combined with a finish from groups 11, 12, 13, 14, 15, 16 or 18. Each claimed combination of metallic finishes shall be tested separately. Selective and non-selective finishes of the same material, where claimed, shall be demonstrated separately.

2.2.1.1 *Accelerated ageing*

The ability of finish groups 11, 12, 13, 14, 15, 16 or 18 to solder after extended or adverse storage conditions is demonstrated using accelerated ageing. This test shall be carried out on those finishes where accelerated ageing is claimed. Each finish that has complied with the requirements of the ageing test is highlighted by the inclusion of an asterisk (*) adjacent to that finish in the manufacturers abstract of capability as published in the QPL.

2.2.2 *Organic finishes (where claimed)*

Finish group designation	Organic finish	Abbreviation for QPL
a	Adhesive Coated film coverlayer	AFC
b	Dry film solder mask	DSM
c	Wet resist solder mask/coverlayer	WSM
d	Liquid photopolymer solder mask	LSM
e	Liquid Photopolymer coverlayer	LPC
f	Marking inks	MI
g	Conductive Ink	CI

The demonstration of organic finish groups a, b, c,d, e, f or g shall be over a finish from groups 11, 12, 13, 14, 15, 16, or 18. All claimed types of solder resist shall be tested separately.