

Offshore containers — Design, construction, testing, inspection and marking

The European Standard EN 12079:1999 has the status of a
British Standard

ICS 55.180.10

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW



Document Sharing Hub

National foreword

This British Standard is the English language version of EN 12079:1999. It supersedes BS 7072:1989 which is withdrawn.

The UK participation in its preparation was entrusted by Technical Committee PKW/5, Freight containers and transport, to Subcommittee PKW/5/1, Offshore containers, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 29 and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

This British Standard, having been prepared under the direction of the Consumer Products and Services Sector Committee, was published under the authority of the Standards Committee and comes into effect on 15 October 1999

© BSI 10-1999

ISBN 0 580 32633 0

Amendments issued since publication

Amd. No.	Date	Comments

EUROPEAN STANDARD

EN 12079

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 1999

ICS 55.180.10

English version

Offshore containers — Design, construction, testing, inspection and marking

Conteneurs pour utilisation en mer — Conception,
construction essais, inspection et marquage

Offshore-Container — Bemessung, Konstruktion,
Prüfung, Überwachung und Kennzeichnung

This European Standard was approved by CEN on 13 February 1999.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization
Comité Européen de Normalisation
Europäisches Komitee für Normung

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

© 1999 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.
Ref.No. EN 12079:1999 E

Contents

	Page
Foreword	2
1 Scope	3
2 Normative references	3
3 Definitions	4
4 Symbols	6
5 Design	6
6 Materials	13
7 Type testing	16
8 Production	18
9 Marking	21
10 Plating of containers	22
11 Certificate of conformity	24
12 Periodic examination, tests and repairs	25
Annex A (informative) Recommended knowledge and experience of staff responsible for inspection of offshore containers	29
Annex B (informative) Guidance on pre-trip inspections	29
Annex C (informative) Bibliography	29
Table 1 — Charpy impact test temperature: structural steel for primary structural members	13
Table 2 — Chemical composition (ladle analysis) ¹⁾	14
Table 3 — Mechanical properties	15
Table 4 — Aluminium alloys and tempers for rolled products	15
Table 5 — Aluminium alloys and tempers for extruded products	16
Table 6 — Documentation of materials	16
Table 7 — Non-destructive examination (NDE) of structural welds	19
Table 8 — Number of containers required for lifting test	20
Table 9 — Schedule of examination and tests	26

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 280, Offshore containers, the Secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 1999, and conflicting national standards shall be withdrawn at the latest by September 1999.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, and the United Kingdom.

1 Scope

This standard specifies transport related requirements for the design, construction and marking of offshore freight and service containers with maximum gross mass not exceeding 25 000 kg, intended for repeated use to, from, and between offshore installations and ships. It establishes a system for plating of offshore containers, linked to a defined scheme for periodic examination and test, and introduces a requirement for pre-trip inspection of offshore containers.

Guidance as to the knowledge and experience required by those responsible for carrying out inspections in relation to the system of periodic inspections specified in this standard is given in annex A.

Requirements for the lifting set and for non-transport related requirements, relating to offshore service containers, e.g. requirements for installation and use, are outside the scope of the standard.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

EN 287-1, *Approval testing of welders — Fusion welding — Part 1: Steels.*

EN 287-2, *Approval testing of welders — Fusion welding — Part 2: Aluminium and aluminium alloys.*

EN 288-1, *Specification and qualification of welding procedures for metallic materials — Part 1: General rules for fusion welding.*

EN 288-2, *Specification and approval of welding procedures for metallic materials — Part 2: Welding procedure specification for arc welding.*

EN 288-3, *Specification and approval of welding procedures for metallic materials — Part 3: Welding procedure tests for the arc welding of steels.*

EN 288-4, *Specification and approval of welding procedures for metallic materials — Part 4: Welding procedure tests for the arc welding of aluminium and its alloys.*

EN 970, *Non-destructive examination of fusion welds — Visual examination.*

EN 1011-1, *Welding — Recommendations for welding of metallic materials — Part 1: General guidance for arc welding.*

prEN 1011-2, *Recommendations for welding of metallic materials — Part 2: Guidance for ferritic steels.*

EN 10002-1, *Metallic materials — Tensile testing — Part 1: Method of test (at ambient temperature).*

EN 10025, *Hot-rolled products of non-alloy structural steels — Technical delivery conditions.*

prEN 10250-2, *Open die steel forgings for general engineering purposes — Part 2: Non-alloy quality and special steels.*

prEN 10250-3, *Open die steel forgings for general engineering purposes — Part 3: Low alloy special steels.*

EN 10113-1, *Hot-rolled products in weldable fine grain structural steels — Part 1: General delivery conditions.*

EN 10113-2, *Hot-rolled products in weldable fine grain structural steels — Part 2: Delivery conditions for normalized/normalized rolled steels.*

EN 10113-3, *Hot-rolled products in weldable fine grain structural steels — Part 3: Delivery conditions for thermomechanical rolled steels.*

EN 10204, *Metallic products — Types of inspection documents.*

EN 10045-1, *Metallic materials — Charpy impact test — Part 1: Test method.*

EN ISO 9002, *Quality systems — Model for quality assurance in production, installation and servicing (ISO 9002:1994).*

EN 45004, *General criteria for the operation of various types of bodies performing inspections.*

ISO 209-1, *Wrought aluminium and aluminium alloys — Chemical composition and forms of products — Part 1: Chemical composition.*

ISO 1161, *Series 1 freight containers — Corner fittings — Specification.*

ISO 1496-1, *Series 1 freight containers — Specification and testing — Part 1: General cargo containers for general purposes.*

ISO 1496-3, *Series 1 freight containers — Specification and testing — Part 3: Tank containers for liquids, gases and pressurized dry bulk.*

ISO 1496-4, *Series 1 freight containers — Specification and testing — Part 4: Non-pressurized containers for dry bulk.*

3 Definitions

For the purposes of this standard, the following definitions apply.

3.1

offshore container

portable unit for repeated use in the transport of goods or equipment, handled in open seas, to, from, and between fixed and/or floating installations and ships

NOTE The unit incorporates permanently installed equipment for lifting and handling and may include equipment for filling, emptying, cooling, heating, etc.

3.2

permanent equipment

equipment that is attached to the container and which is not cargo

NOTE This may include, e.g., lifting sets, refrigeration units, shelves, securing points, garbage compactors.

3.3

primary structure

load carrying and supporting frames and load carrying panels. Primary structure is divided into two subgroups:

3.3.1

essential and non-redundant primary structure

main structural elements which transfer the cargo load to the crane hook (i.e. forming the “load path” from the payload to the lifting sling) and will include, at least:

- top and bottom side rails;
- top and bottom end rails;
- corner posts;
- pad eyes

although other primary structure may also be considered as essential/non-redundant

3.3.2

non-essential primary structure

other structural elements for which the main function is other than that described in 3.3.1, e.g. floor plates and protective frame members. Side and roof panels, including corrugated panels, are not considered to be part of the primary structure

3.4

secondary structure

parts which are not considered as load carrying for the purposes of the design calculations, including the following components:

- doors, wall and roof panels;
- panel stiffeners and corrugations;
- structural components used for tank protection only;
- internal securing points

NOTE Not all container walls are corrugated.

3.5

offshore freight container

offshore container built for the transport of goods

NOTE Examples of offshore freight containers are:

- general cargo container: a closed container with doors;
- cargo basket: an open top container for general or special cargo;
- tank container: a container for the transport of dangerous or non-dangerous fluids;
- bulk container: a container for the transport of solids in bulk;
- special container: a container for the transport of special cargo, e.g. garbage containers, equipment boxes, gas cylinder racks.

3.6

offshore service container

offshore container built and equipped for a special service task, usually as a temporary installation, e.g. laboratories, workshops, stores, power plants, control stations

3.7

waste skip

open or closed offshore container used for the storage and removal of waste

NOTE Normally constructed from flat steel plate forming the load bearing sections of the container, with bracing in the form of steel profiles, e.g. channel or hollow section, being fitted horizontally and/or vertically around sides and ends. In addition to the pad eyes for the lifting set, these containers may have side mounted lugs suitable for use with the lifting equipment mounted on a skip lift vehicle.

3.8

prototype

equipment item, used for type testing, considered to be representative of the product for which conformity is being claimed. It may either be fabricated especially for type testing or selected at random from a production series

3.9

owner

legal owner of the offshore container or his delegated nominee

3.10

lifting set

items of integrated lifting equipment used to connect the offshore container to the lifting appliance

4 Symbols

- R : the rating, i.e. the maximum gross mass of the container and its cargo, in kg;
- T : the tare mass, i.e. the mass of an empty container (without cargo and excluding lifting set), in kg;
- P : the payload, i.e. the maximum permissible mass of cargo which may be safely transported by the container, in kg;

NOTE 1 $P = R - T$.

NOTE 2 R , T and P are, by definition in units of mass, kilograms (kg). Where design requirements are based on the gravitational forces derived from these values, those forces are indicated thus: R_g , T_g and P_g , the units of which are newtons or multiples thereof.

- T_D : the design air temperature, i.e. a minimum reference temperature used for the selection of steel grades used in offshore containers and equipment expressed in degrees centigrade;
- σ_c : the von Mises equivalent stress, expressed in MPa or N/mm²;
- R_c : the specified minimum yield stress, expressed in MPa or N/mm².

5 Design

5.1 General

An offshore container shall have sufficient strength to allow loading and unloading from supply vessels offshore operating in a sea state with significant wave heights of 6 m and to withstand impact from heavy seas.

NOTE Local impacts, e.g. from hitting other deck cargo or rigid parts of the ship structure, may cause extreme loads in such conditions.

To prevent the containers from overturning (tipping) on a moving deck, they shall be designed to withstand tilting at 30° in any direction, without overturning when loaded at its maximum gross mass, with the centre of gravity considered to be at the half height of the container.

Protruding parts on the outside of the offshore container that may catch other containers or structures shall be avoided. Protruding parts (door handles, hatch cleats, etc.) shall be so placed or so protected that they do not catch the lifting set.

Where containers are designed for stacking, and the lifting set hangs over the side of the top frame they shall be fitted with a method of protection for those exposed parts, e.g. corners raised to sufficient height above the frame and roof to prevent unintentional contact with, and damage to, the lifting set.

Containers shall be designed as structural frames (primary structure), with non-load bearing cladding where necessary (secondary structure). Only the primary structure shall be considered in the design calculations; however, on certain types of containers, e.g. waste skips with trapezium shaped sides, with only a non-stressed cover above the bracing where the pad eyes are attached, the whole structure may be considered as a primary structure, and the design calculations may treat such a container as a monocoque construction.

T_D shall not be higher than the (statistically) lowest daily mean temperature for the area where the offshore container is to operate and in no case shall be higher than -20 °C.

NOTE For containers with exposed aluminium, the danger of sparks caused by the impact of aluminium against corroded steel (the thermite reaction) should be taken into account.

5.2 Structural strength

5.2.1 General

The required strength of a container shall be determined by calculation and verified by type tests, as described in clause 7.

5.2.2 Lifting loads

5.2.2.1 For design loads defined in 5.2.2.2 and 5.2.2.3, no equivalent stress level, σ_e , shall exceed the figure as calculated as $\sigma_e = 0,85C$, where:

- for steel: $C = R_e$;
- for aluminium:
 - base material: $C = R_{0,2}$ for aluminium outside the heat affected zone;
 - heat affected zone: $C = 0,7\beta R_m$

where

R_m is the tensile strength of aluminium;
 β is 0,8 for ISO AlMg4,5Mn-HAR/AA5083 (H329 see Table 4);

or is 0,7 for all other aluminium alloys and tempers.

5.2.2.2 Lifting with lifting set

The design force on the primary structure shall be calculated as $2,5R_g$.

To achieve this the internal load shall be taken as $(2,5R - T)_g$ evenly distributed over the container floor. For tank containers, the actual distribution of the tare mass shall be used for the calculations.

Pad eyes shall be designed for a total vertical force of $3R_g$.

The force shall be considered to be evenly distributed between $(n - 1)$ pad eyes where n is the actual number of pad eyes.

To determine the resulting sling force on the pad eyes, the sling angle shall be taken into account, so that the resulting sling force on each pad eye is calculated as follows:

$$F = \frac{3R_g}{(n-1) \cos \nu}$$

where

F is the resulting sling force, in newtons;
 n is the actual number of pad eyes (for calculation purposes n shall not exceed 4 and shall be not less than 2);
 ν is the angle between a sling leg and the vertical, in degrees and shall be assumed to be 45° for design purposes with ISO 10' containers. For lengths less than 10', ν should be defined differently by arrangement between the purchaser/manufacturer.

NOTE For containers with only one pad eye, that pad eye shall be designed for a total vertical force of $5R_g$.

5.2.2.3 Lifting with fork lift truck

The design force on the primary structure shall be calculated as $1,6R_g$.

To achieve this the internal load shall be taken as $(1,6R - T)_g$ evenly distributed over the container floor. Where fork pockets are intended only for handling of the empty container, the design load shall be taken as $1,6T_g$.

5.2.3 Impact loads

5.2.3.1 General

Impact loads are dynamic loads of very short duration. Ideally, dynamic calculations or tests should be carried out to verify the ability of a container to withstand such loads. However, for most applications it shall be sufficient to carry out simplified static calculations as specified in 5.2.3.2 and 5.2.3.3 and to perform a drop test for vertical impact on corners, in accordance with 7.4.

When simplified calculations are used, and each beam is considered separately, any assumptions concerning support conditions shall be stated.

5.2.3.2 Horizontal impact

The main frame structure shall be dimensioned to withstand a local horizontal impact force acting at any point. This force may act in any horizontal direction on the corner post. On all other frame members in the sides the load may be considered as acting at right angles to the side.

The calculated (static equivalent) stresses due to impact shall be combined with the lifting stresses resulting from static lifting forces (R_g).

Equivalent stresses shall not exceed:

$$\sigma_e = C \text{ (see 5.2.2.1).}$$

The following values shall be used for the static equivalents to an impact force:

- for container posts and side rails of the bottom structure: $-0,25R_g$;
- for other frame members of the side structure, including the top rails: $-0,15R_g$.

Maximum calculated deflections at these loadings shall not exceed:

- for corner posts and bottom side rails: $\frac{l_n}{250}$

where

l_n is the total length of the rail or post in mm.

- for other frame members: $\frac{l_n}{250}$

where

l_n is the length of the shortest edge of the wall being considered.

NOTE l_n is a (nominal) reference length and will often be different from the actual span of a beam. For horizontal impact on tank containers for dangerous cargoes see 5.5.4.

5.2.3.3 Vertical impact

A vertical impact test shall be carried out in accordance with 7.4. In addition, the side rails and end rails in the base shall be able to withstand vertical point forces of $0,25R_g$ at the centre span.