

Bar coding — Terminology

The European Standard EN 1556:1998 has the status of a
British Standard

ICS 01.090.35; 35.040

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents



Document Sharing Hub

National foreword

This British Standard is the English language version of EN 1556:1998.
The UK participation in its preparation was entrusted to Technical Committee IST/34, Bar coding, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 23 and a back cover.

This British Standard, having been prepared under the direction of the DISC Board, was published under the authority of the Standards Committee and comes into effect on 15 December 1998

© BSI 1998

ISBN 0 580 29913 9

Amendments issued since publication

Amd. No.	Date	Text affected

ICS 01.090.35; 35.040

Descriptors: data processing, character recognition, optical recognition, bar codes, vocabulary

English version

Bar coding — Terminology

Codes à barres — Terminologie

Strichcodierung — Terminologie

This European Standard was approved by CEN on 28 February 1998.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization
Comité Européen de Normalisation
Europäisches Komitee für Normung

Central Secretariat: rue de Stassart 36, B-1050 Brussels

© 1998 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 225, Bar coding, the Secretariat of which is held by NNI.

Organizations contributing to the development of the standard include:

- AIM Europe
- International Article Numbering Association EAN

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 1998, and conflicting national standards shall be withdrawn at the latest by September 1998.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Contents

	Page
Foreword	2
Introduction	3
1 Scope	3
2 Normative references	3
3 Definitions of terms	3
Annex A (informative) Maintenance	18
Annex B (informative) Tri-lingual cross-reference	18

Introduction

CEN Technical Committee 225 is responsible for a series of European Standards and Pre-standards covering both technical and applications aspects of bar code technology. Many of these standards use specialist technical and other terms and this standard defines a number of terms which may be encountered in more than one standard or in bar coding standards produced by other organizations, with the aim of encouraging consistency of usage and reducing the risk of ambiguity or misunderstanding.

1 Scope

This European Standard defines a number of technical and other terms applicable to bar code technology, which are used in the standards produced by CEN TC225 and may be encountered elsewhere in bar coding standards produced by other organizations. Definitions given are in the context of bar coding and the terms so defined may customarily have a wider meaning than that shown in this standard. Translations of the terms defined into the two other official languages of CEN are also shown to facilitate cross-reference.

2 Normative references

This European Standard incorporates by dated or undated references provisions from other publications. These normative references are cited at appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

ISO 646, *Information technology — ISO 7-bit coded character set for information interchange*.

ISO 8859, *Information processing — 8-bit single-byte coded graphic character sets*.

3 Definitions of terms

3.1

algorithm

a set of steps to be taken to effect a desired calculation.

French = algorithme

German = Algorithmus

3.2

alphanumeric

alphabetic and numeric including punctuation marks.

French = alphanumérique

German = alphanumerisch

3.3

aperture

the opening in an optical device, such as a scanner, photometer, or camera, which determines its field of view. Most apertures are circular, but they may be rectangular or elliptical.

French = ouverture

German = Blende

3.4

application standard

specification defining the method by which and conditions under which bar code technology may be applied to a particular purpose, prescribing, for example, data formats, optical requirements and symbology-related parameters as subsets of the range defined by relevant technical standards.

French = norme d'application

German = Anwendungsstandard

3.5

ASCII

American Standard Code for Information Interchange: a computer code, as described in ISO 646, consisting of 128 alphanumeric and control characters, each encoded with 7 bits (8 including parity check), used for the exchange of information between computerized systems.

French = ASCII

German = ASCII

3.6

autodiscrimination

the ability of a bar code reader to distinguish automatically between two or more symbologies.

French = autodiscrimination

German = Autodiskrimination

3.7

auxiliary character

a non-data character – e.g. start character, stop character, centre pattern, delineator pattern, latch character, mode indicator, shift character, code subset change characters, and function characters. See overhead.

French = caractère auxiliaire

German = Hilfszeichen

3.8

background

the light area between and surrounding the dark elements of a printed symbol. The background can be the substrate on which the symbol is printed or an over-printing of a suitable light colour.

French = arrière-plan

German = Hintergrund

3.9

bar

any of the dark lines in a printed bar code symbol.

French = barre

German = Strich

3.10

bar code

an array of parallel rectangular bars and spaces arranged according to the encodation rules of a particular symbol specification in order to represent data in machine readable form.

French = code à barres

German = Strichcode

3.11

bar code character

see symbol character.

French = caractère de code à barres

German = Strichcodezeichen

3.12

bar code density (symbol density)

the number of characters that can be represented in a bar code symbol per unit of measure, usually expressed as characters per inch (cpi) or per centimetre for linear bar codes and per square inch or per square centimetre for multi-row symbologies. The width of the narrowest bar or space, the wide to narrow ratio, the number of bars and spaces per character and the width of the intercharacter gap, if any, are the controlling factors.

French = densité du code à barres

German = Strichcodedichte

3.13

bar code master

the original film or other image of a bar code symbol, produced to close tolerances and intended for reproduction by conventional printing processes (e.g. for incorporation in a printed packaging design).

French = code à barres de base

German = Strichcode-Master

3.14

bar code reader

a device used to capture the data encoded in a bar code symbol. It consists of two parts: a) the scanner, an input device which sends signals proportional to the reflectivity of each successive element of the symbol to the decoder, and b) the decoder, which examines the signals from the scanner and translates them into recognizable or computer-compatible data. The decoder itself is sometimes erroneously called a reader.

French = lecteur de code à barres

German = Strichcode-Lesegerät

3.15

bar code symbol

the combination of symbol characters and features required by a particular symbology, including quiet zones, start and stop characters, data characters, check characters and other auxiliary patterns, which together form a complete scannable entity.

French = symbole de code à barres

German = Strichcodesymbol

3.16

bar height

the dimension of the individual bars in a linear bar code symbol or in a row of a multi-row bar code symbol, measured perpendicular to the scanning direction. See also Y dimension.

French = hauteur de barre

German = Strichhöhe

3.17

bar width

the transverse dimension of an individual bar in a bar code symbol, measured parallel to the scanning direction. The number of possible width variations within a particular printed symbol depends on the symbology used.

French = largeur de barre

German = Strichbreite

3.18

bar width gain/loss

see print gain/loss.

French = gain/perte de la largeur de barre

German = Strichbreitenzuwachs/-verlust

3.19

bar width reduction/increase

the extent by which the width of the bars on the bar code master is reduced/increased in order to correct for expected print gain/loss.

French = réduction/augmentation de la largeur de barre

German = Strichbreitenverringern/-vergrößerung

3.20

bearer bar

a bar abutting the tops and bottoms of the bars in a bar code symbol, or a frame surrounding the entire symbol, intended to equalize the pressure exerted by the printing plate over the entire surface of the symbol, and/or to prevent a short scan by the bar code reader.

French = barre porteuse

German = Trägerbalken/Trägerstrich

3.21

bi-directional

in two directions – viz. backwards and forwards. Denoting that a bar code symbol can be read successfully either backwards or forwards. Denoting a scanner that can operate successfully either backward or forwards.

French = bi-directionnel

German = bi-direktional

3.22

binary

denoting a numbering system to base 2 in which numbers are expressed as combinations of the digits 0 and 1, with positional weighting based on powers of 2. In computing these can be represented electrically by “off” and “on” respectively, or in bar codes by narrow and wide elements or by the absence or presence of a bar module.

French = binaire

German = binär

3.23

binary coded decimal (BCD)

a method of representing decimal numbers in binary code as groups of four bits, with weighting values 8, 4, 2, 1 reading from left to right, each group representing one decimal digit, for example 0010 0011 for 23.

French = décimal codé binaire (BCD)

German = binär verschlüsselte Dezimalziffern (BCD)

3.24

binary symbology

see two-width symbology.

French = système de symbolisation binaire

German = binäre Symbologie

3.25

BIT

abbreviation for binary digit.

1) A single element (0 or 1) in a binary number.

2) A unit of information capacity in a binary storage device.

French = BIT

German = BIT, Binärzeichen

3.26

CCD (charge-coupled device)

an electronic light-sensitive component used in a linear or two-dimensional array as the light-collecting element in certain types of bar code reader.

French = CCD – dispositif à couplage de charge

German = CCD – Charge-Coupled Device

3.27

character

see character set, data character, symbol character, human readable character.

French = caractère

German = Zeichen

3.28

character set

the total range of letters, numbers, and symbols that can be encoded in a particular symbology. See code page, code set.

French = jeu de caractères

German = Zeichensatz

3.29

check digit/character

a digit or character calculated from other characters in a code by means of a defined algorithm and used to check that the code is correctly composed. See symbol check character, data check character/digit.

French = caractère de contrôle/clé de contrôle

German = Prüfziffer/Prüfzeichen

3.30

clear area

see quiet zone.

French = zone de repos

German = Hellzone

3.31

closed application environment (system)

an application which is intended for use by a closed group of users, typically within a single organization or subject to a specific agreement. Compare open application environment.

French = système fermé

German = geschlossene Anwendungsumgebung

3.32

closed system

see closed application environment.

French = système fermé

German = geschlossenes System

3.33

code page

a table showing the character allocated to each byte value in a coded character set.

French = page de code

German = Codiertabelle

3.34

code set

a subset of the character set of a particular symbology. See character set.

French = jeu de code

German = spezifischer Zeichensatz

3.35

coded character set

a set of unambiguous rules establishing a character set and the relationship between the characters of the set and their byte values.

French = jeu de caractères codés

German = Zeichensatzreferenz

3.36

codeword

a symbol character value. An intermediate level of coding between source data and the graphical encodation in a symbol.

French = mot de code

German = Codewort

3.37

column

the horizontal symbol character position in a row of a multi-row symbology.

French = colonne

German = Spalte

3.38

concatenation

the linking or chaining together (1) of separate items of data in a bar code symbol, or (2) of the data contained in two or more separate bar code symbols (also referred to as “message append” and “structured append”).

French = concaténation

German = Verkettung

3.39

continuous code

a symbology in which there is no intercharacter gap, i.e. the final element of one symbol abuts the first element of the next symbol character and all the elements carry data continuously. Compare discrete code.

French = code à barres continu

German = kontinuierlicher Code

3.40

conventional printing process

one of the printing processes typically using a printing plate (or cylinder) and wet ink to produce multiple impressions of an image on a substrate. Includes lithography, letterpress, flexography, photogravure, screen process, hot foil stamping. Compare on-demand printing.

French = procédé d'impression conventionnel

German = übliches Druckverfahren

3.41

corner marks

marks which indicate the four corners of a bar code symbol including the light margins on a bar code master. Corner marks are not normally printed.

French = marques de coins

German = Eckpunkte

3.42

CPI (Characters per inch)

used as a measure of bar code density.

French = CPI (Caractères par pouce)

German = CPI (Zeichen pro Zoll)

3.43

data character

a single numeric digit, alphabetic character or punctuation mark, or control character, which represents information. Compare symbol character.

French = caractère de données

German = Datenzeichen

3.44

data check character/digit

a digit or character calculated from data and appended as part of the data string to ensure that the data is correctly composed and transmitted. Compare symbol check character.

French = caractère de contrôle de données

German = Datenprüfzeichen/-ziffer

3.45

data codeword

A codeword which encodes data according to one of the compaction schemes of a symbology.

French = mot code de données

German = verdichtetes Codewort

3.46

data compaction (or data compaction scheme)

a mechanism or algorithm to process the original data so that it is represented efficiently in as few codewords as possible in a symbology.

French = compression des données (ou schéma de compression des données)

German = Datenverdichtung

3.47

data region

that part of a symbol used to encode data codewords as opposed to other symbol overhead.

French = zone de données

German = Datenfeld