



BSI Standards Publication

Aerospace series — Cables, electrical, for general purpose, single and multicore assembly — XLETFE Family

Part 009: BJ — Nickel plated copper —
Operating temperatures, between $-65\text{ }^{\circ}\text{C}$
and $150\text{ }^{\circ}\text{C}$ — Single extruded wall for use
as cable cores or within equipment in
areas of high vibrations, cable flexing and
fluid contamination — UV laser printable
— Product Standard

National foreword

This British Standard is the UK implementation of EN 4611-009:2012.

The UK participation in its preparation was entrusted to Technical Committee ACE/6, Aerospace avionic electrical and fibre optic technology.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012. Published by BSI Standards Limited 2012

ISBN 978 0 580 75706 8

ICS 49.060

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 29 February 2012.

Amendments issued since publication

Date	Text affected
------	---------------

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 4611-009

February 2012

ICS 49.060

English Version

Aerospace series - Cables, electrical, for general purpose, single and multicore assembly - XLETFE Family - Part 009: BJ - Nickel plated copper - Operating temperatures, between -65 °C and 150 °C - Single extruded wall for use as cable cores or within equipment in areas of high vibration, cable flexing and fluid contamination - UV laser printable - Product standard

Série aérospatiale - Câbles, électriques, d'usage général, mono et multiconducteurs - Famille XLETFE - Partie 009 : BJ - Cuivre nickelé - Températures de fonctionnement comprises entre -65 °C et 150 °C - Fil simple isolé utilisé comme âme de câbles ou dans les équipements dans les zones à hautes vibrations, flexion de câbles et pollution des fluides - Marquable au laser UV - Norme de produit

Luft- und Raumfahrt - Ein- und mehradrige elektrische Leitungen zur allgemeinen Verwendung, XLETFE-Familie - Teil 009: BJ, Kupfer vernickelt, Betriebstemperaturen zwischen -65 °C und 150 °C, einfach extrudierte Isolierung zur Verwendung in Verseilungen oder in Geräten in Bereichen mit hoher Vibration, Bewegung der Leitung und Kontakt mit Flüssigkeiten, UV-Laser bedruckbar - Produktnorm

This European Standard was approved by CEN on 17 September 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms, definitions, symbols and abbreviations	4
4 Materials and construction	5
4.1 Materials	5
4.2 Construction.....	5
4.3 Number of cores	5
4.4 Colour coding of cores	5
5 Required characteristics	5
6 Quality assurance	8
7 Designation	8
8 Identification and marking	8
9 Packaging, labelling and delivery lengths	8
10 Technical specification	8