

Methods of measurement for radio transmitters —

Part 15: Amplitude-modulated transmitters for sound broadcasting

The European Standard EN 60244-15:2000 has the status of a
British Standard

ICS 33.060.20

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents



Document Sharing Hub

National foreword

This British Standard is the official English language version of EN 60244-15:2000. It is identical with IEC 60244-15:1999.

The UK participation in its preparation was entrusted to Technical Committee EPL/103, Transmitting equipment for radiocommunication, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

From 1 January 1997, all IEC publications have the number 60000 added to the old number. For instance, IEC 27-1 has been renumbered as IEC 60027-1. For a period of time during the change over from one numbering system to the other, publications may contain identifiers from both systems.

Cross-references

Attention is drawn to the fact that CEN and CENELEC Standards normally include an annex which lists normative references to international publications with their corresponding European publications. The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 27 and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

This British Standard, having been prepared under the direction of the Electrotechnical Sector Committee, was published under the authority of the Standards Committee and comes into effect on 15 May 2000

© BSI 05-2000

Amendments issued since publication

Amd. No.	Date	Comments

ISBN 0 580 34693 5

English version

Methods of measurement for radio transmitters
Part 15: Amplitude-modulated transmitters for sound broadcasting
(IEC 60244-15:1999)

Méthodes de mesure applicables aux
émetteurs radioélectriques
Partie 15: Emetteurs de radiodiffusion
sonore à modulation d'amplitude
(CEI 60244-15:1999)

Meßverfahren für Funksender
Teil 15: Amplitudenmodulierte Sender
für Tonrundfunk
(IEC 60244-15:1999)

This European Standard was approved by CENELEC on 2000-01-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

© 2000 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Ref. No. EN 60244-15:2000 E

 **Documents**
Document Sharing Hub

Foreword

The text of document 103/15/FDIS, future edition 1 of IEC 60244-15, prepared by IEC TC 103, Transmitting equipment for radiocommunication, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60244-15 on 2000-01-01.

This European Standard partly supersedes HD 236.2 S1:1977, HD 236.3 S1:1977 and HD 236.4 S2:1978.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2000-10-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2003-01-01

This standard is intended to be used in conjunction with EN 60244-1:2000.

Annexes designated "normative" are part of the body of the standard.

Annexes designated "informative" are given for information only.

In this standard, annex ZA is normative and annexes A, B and C are informative.

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60244-15:1999 was approved by CENELEC as a European Standard without any modification.

In the official version, for annex C, Bibliography, the following notes have to be added for the standards indicated:

IEC 60244-12-1 NOTE: Harmonized as EN 60244-12-1:1993 (not modified).

IEC 60244-12-2 NOTE: Harmonized as EN 60244-12-2:1993 (not modified).

IEC 60215 NOTE: Harmonized as EN 60215:1989 (not modified).

IEC 60864-1 NOTE: Harmonized, together with its amendment 1:1987, as HD 577 S1:1990 (not modified).

IEC 60864-2 NOTE: Harmonized as EN 60864-2:1997 (not modified).

CONTENTS

	Page
Page	
1 Scope.....	4
2 Normative references	4
3 Definitions	5
4 General conditions of operation	5
5 General conditions of measurement	6
5.1 Input and output measurement arrangements.....	6
5.2 Measuring equipment.....	6
5.3 Modulation and output power conditions.....	6
6 General characteristics	7
6.1 Rated output power	7
6.2 DSB output power.....	7
6.3 SSB output power.....	8
7 Transmission performance characteristics.....	9
7.1 Modulation.....	9
7.2 DSB modulation	9
7.3 DCC modulation	10
7.4 SSB modulation	11
7.5 Amplitude/radiofrequency characteristic.....	12
7.6 Amplitude/audiofrequency characteristic	12
7.7 Modulation capability	13
7.8 Long-term stability	13
7.9 RF intermodulation	14
7.10 Audiofrequency harmonic distortion	14
7.11 Audiofrequency intermodulation	15
7.12 AM noise level	16
7.13 Unwanted synchronous phase-modulation.....	16
7.14 Carrier amplitude variation (carrier shift)	17
7.15 Out-of-band emission.....	17
7.16 Suppression of the unwanted sideband	18
7.17 Measurement of supplementary signals.....	18
Figure 1 Configuration of measuring arrangements	20
Figure 2 RF envelopes of double-sideband (DSB) emissions with full carrier	21
Figure 3 RF envelopes of single-sideband (SSB) emissions with 6 dB carrier reduction	21
Figure 4 RF envelopes of single-sideband (SSB) emissions with 12 dB carrier reduction ..	21
Figure 5 Signal spectra for DSB transmission.....	22
Figure 6 Signal spectra for SSB transmission.....	22
Annex A (informative) Noise-weighting filters.....	23
Annex B (informative) Out-of-band spectrum	24
Annex C (informative) Bibliography	26
Annex ZA (normative) Normative references to international publications with their corresponding European publication.....	27

METHODS OF MEASUREMENT FOR RADIO TRANSMITTERS –

Part 15: Amplitude-modulated transmitters for sound broadcasting

1 Scope

This part of IEC 60244 contains the methods of measurement to assess the performance characteristics of amplitude-modulated transmitters for sound broadcasting in the LF, MF and HF bands.

This standard is intended to be used for type tests and acceptance or factory tests.

Fewer or additional measurements may be carried out by agreement between customer and manufacturer. Any additional measurements should preferably be in accordance with relevant standards published by the IEC or by other international bodies.

This part of IEC 60244 does not specify limiting values for acceptable performance as these are usually given in the equipment specification or in requirements laid down by the responsible regulating bodies. However, some values are quoted, where appropriate, for guidance in the presentation of the results.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 60244. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of IEC 60244 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60244-1,— *Methods of measurement for radio transmitters – Part 1: General characteristics for broadcast transmitters* ¹⁾

ITU-R Recommendation 326, *Determination and measurement of the power of radio transmitters*

ITU-R Recommendation 559-1, *Interference protection evaluation model for the radio-navigation-satellite service in the 1 559-1 610 MHz band*

ITU-R Recommendation 640, *Single sideband (SSB) system for HF broadcasting*

ITU-R Report 458, *Characteristics of system in LF, MF and HF broadcasting*

ITU-R Report 1059, *Characteristics of single-sideband system in HF broadcasting*

¹⁾ To be published.

3 Definitions

For the purposes of this part of IEC 60244, the following definitions apply.

3.1

amplitude-modulated sound transmitter

radio transmitting equipment whose primary purpose is to convert audiofrequency signals into amplitude-modulated radiofrequency transmission

This definition covers double-sideband (DSB) transmitters with full carrier, including dynamic carrier-controlled systems (DCC), and single-sideband (SSB) transmitters with or without carrier reduction.

NOTE Particular examples of dynamic carrier-controlled systems include dynamic amplitude modulation (DAM) and AM companding (AMC). See figures 5 and 6 for ideal spectra for DSB, DCC and SSB transmissions.

3.2

description of the transmission system for AM sound broadcasting

Relevant information concerning transmission systems for AM sound broadcasting is given in ITU-R Recommendations 326 and 640, and in ITU-R Reports 458 and 1059.

3.3

definitions of performance characteristics

For convenience, the definitions of particular performance characteristics are included in clause 6 describing the method of measurement.

4 General conditions of operation

Any device for the suppression of unwanted signals, irrespective of whether or not the device is located inside the transmitter, shall be considered as a part of the transmitter for the purpose of this standard.

Unless otherwise specified, the measurements shall be made under normal operating conditions and at rated output power. If required, they shall be repeated under extreme environmental conditions, in accordance with the equipment specification.

The transmitting mode and the measured output power of the transmitter under test shall be stated.

The mains supply and the environmental conditions shall be stated with the measurement results.

The transmitter shall be connected to a test load having a VSWR, relative to the nominal load impedance of the transmitter, not greater than

- 1,2:1 at frequencies within the designated broadcasting band;
- 1,5:1 at frequencies of any measured unwanted frequency up to ten times the highest frequency of the designated broadcasting band.

If the transmitter includes filters at the audiofrequency input to control the audiofrequency band transmitted, all characteristics shall be measured with the filters in circuit.

5 General conditions of measurement

5.1 Input and output measurement arrangements

For the purposes of measurement, the input and output signal arrangements are given in the form of diagrams.

Where required, the impedance of the test equipment, of the transmitter under test and of all the connections between them shall be appropriately matched.

5.2 Measuring equipment

At the input:

- the modulating signals for the transmitter under test shall be provided by one or two low-distortion low-frequency test signal generators covering frequencies up to 10 kHz, or an ITU-R coloured noise generator;
- if required, auxiliary equipment for supplementary signals shall be used.

At the output:

the following measuring instruments may be used.

a) For measurements within the radiofrequency domain:

- RF oscilloscope;
- RF spectrum analyser;
- RF phase meter.

b) For measurements within the audiofrequency domain using:

- test demodulator;

For SSB transmitters, synchronous detection shall be used. For DSB transmitters synchronous or envelope detection can be used.

- AF spectrum analyser;
- AF distortion meter.

NOTE 1 Because the results of the measurements are critically dependent on the performance of the test equipment, it is desirable to check the test arrangement first by making measurements without the transmitter in circuit.

NOTE 2 RF measurements carried out by an RF analyser may differ from those obtained by measuring at the output of an envelope detector, as the influence of the carrier phase variation due to the modulation signal is not compensated for. The analyser cannot discriminate between amplitude and phase modulation sideband components located on the same sideband frequencies.

5.3 Modulation and output power conditions

The modulation signal or signals for each measurement are stated in the clauses describing the method of measurement.

The output power of the transmitter is dependent on the modulating signal(s) and on the transmission mode. The appropriate reference power level shall be used in accordance with ITU-R Recommendation 326.

6 General characteristics

The methods of measurement for the general characteristics of transmitters such as input impedance, output power and frequency stability are described in IEC 60244-1.

Specific aspects related to the output power of AM sound broadcasting transmitters are described in 6.1 to 6.3.

6.1 Rated output power

6.1.1 Introduction

The output power capability of a transmitter is given by its rated output power.

6.2 DSB output power

6.2.1 Definition

The rated output power of an amplitude-modulated DSB transmitter is defined by the level of its carrier power, when unmodulated (see figure 5).

The rated power of a DCC transmitter is defined by its maximum carrier power level.

The power levels at the RF output of a DSB transmitter are as follows.

- a) Without modulation:
carrier power P_c (rated power).
- b) With full modulation:
Mean power $P_m = 1,5 P_c$;
Peak envelope power $PEP = 4 P_c$.

6.2.2 Measuring arrangement

Measuring arrangement A (see figure 1) shall be used with one test signal generator at the input. The test load measures the mean RF power.

6.2.3 Measuring procedure

- Adjust the output of the unmodulated transmitter to its rated power.
- Establish a reference line on the oscilloscope.
- Modulate the transmitter with an 800 Hz or 1 000 Hz audio signal to full modulation so that the peak envelope amplitude on the RF oscilloscope is twice the carrier reference amplitude.
- Note the voltage of the audio signal for the transmitter under test as the reference value for full modulation.

6.2.4 Calculation and presentation of results

The results may be presented as a table stating the rated output power of the transmitter and detailing the power levels measured, together with the modulating frequency used.

State the measured reference level of the modulating signal for full modulation.