

Fixed capacitors for use in electronic equipment —

Part 4: Sectional specification — Aluminium electrolytic capacitors with solid (MnO₂) and non-solid electrolyte

The European Standard EN 60384-4:2007 has the status of a
British Standard

ICS 31.060.50

National foreword

This British Standard is the UK implementation of EN 60384-4:2007. It is identical to IEC 60384-4:2007. It supersedes BS EN 130300:1998 which is withdrawn. Together with BS EN 60384-4-1:2007 and BS EN 60384-4-2:2007 it supersedes BS QC 300300:1998 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee EPL/40X, Capacitors and resistors for electronic equipment.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2007

© BSI 2007

ISBN 978 0 580 56138 2

Amendments issued since publication

Amd. No.	Date	Comments

**Fixed capacitors for use in electronic equipment -
Part 4: Sectional specification -
Aluminium electrolytic capacitors
with solid (MnO₂) and non-solid electrolyte
(IEC 60384-4:2007)**

Condensateurs fixes utilisés
dans les équipements électroniques -
Partie 4: Spécification intermédiaire -
Condensateurs électrolytiques
en aluminium à électrolyte solide (MnO₂)
et non solide
(CEI 60384-4:2007)

Festkondensatoren zur Verwendung
in Geräten der Elektronik -
Teil 4: Rahmenspezifikation -
Aluminium-Elektrolyt-Kondensatoren
mit festen (MnO₂) und
flüssigen Elektrolyten
(IEC 60384-4:2007)

This European Standard was approved by CENELEC on 2007-04-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 40/1759/CDV, future edition 4 of IEC 60384-4, prepared by IEC TC 40, Capacitors and resistors for electronic equipment, was submitted to the IEC-CENELEC parallel Unique Acceptance Procedure and was approved by CENELEC as EN 60384-4 on 2007-04-01.

This European Standard supersedes EN 130300:1998.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2008-01-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2010-04-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60384-4:2007 was approved by CENELEC as a European Standard without any modification.

CONTENTS

1	General	5
1.1	Scope.....	5
1.2	Object	5
1.3	Normative references	5
1.4	Information to be given in a detail specification	6
1.5	Terms and definitions	7
1.6	Marking	7
2	Preferred ratings and characteristics	8
2.1	Preferred characteristics	8
2.2	Preferred values of ratings	8
3	Quality assessment procedures	10
3.1	Primary stage of manufacture	10
3.2	Structurally similar components	10
3.3	Certified records of released lots	10
3.4	Qualification approval procedures	10
3.5	Quality conformance inspection	23
4	Test and measurement procedures.....	25
4.1	Pre-conditioning (for non-solid electrolyte capacitors only)	25
4.2	Visual examination and check of dimensions	25
4.3	Electrical tests.....	25
4.4	Robustness of terminations	28
4.5	Resistance to soldering heat	28
4.6	Solderability	28
4.7	Rapid change of temperature	29
4.8	Vibration.....	29
4.9	Bump	29
4.10	Shock.....	30
4.11	Climatic sequence	30
4.12	Damp heat, steady state.....	31
4.13	Endurance.....	31
4.14	Surge	32
4.15	Reverse voltage (if required by the detail specification)	33
4.16	Pressure relief (if required by the detail specification)	33
4.17	Storage at high temperature	34
4.18	Storage at low temperature (for non-solid electrolyte capacitors only)	34
4.19	Characteristics at high and low temperature	34
4.20	Charge and discharge (if required by the detail specification)	34
4.21	High surge current (for solid electrolyte capacitors only and if required by the detail specification)	35
4.22	Voltage transient overload.....	35
	Annex ZA (normative) Normative references to international publications with their corresponding European publications	36

Table 1 – Fixed sample size test plan for qualification approval, assessment level EZ	12
Table 2 – Test schedule for qualification approval.....	13
Table 3 – Lot-by-lot inspection	24
Table 4 – Periodic inspection	24
Table 5 – Leakage current requirements	25
Table 6 – Amplitude and acceleration options	29
Table 7 – Preferred severities	30

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 4: Sectional specification – Aluminium electrolytic capacitors with solid (MnO₂) and non-solid electrolyte

1 General

1.1 Scope

This part of IEC 60384 applies to aluminium electrolytic capacitors with solid (MnO₂) and non-solid electrolyte primarily intended for d.c. applications for use in electronic equipment. It covers capacitors for long-life applications and capacitors for general-purpose applications.

Capacitors for special-purpose applications may need additional requirements.

Capacitors for fixed surface mount aluminium electrolytic capacitors are not included but they are covered by IEC 60384-18.

1.2 Object

The principal object of this standard is to prescribe preferred ratings and characteristics and to select from IEC 60384-1 the appropriate quality assessment procedures, tests and measuring methods and to give general performance requirements for this type of capacitor. Test severities and requirements prescribed in detail specifications referring to this sectional specification shall be of equal or higher performance level, because lower performance levels are not permitted.

1.3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60063, *Preferred number series for resistors and capacitors*

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-17, *Environmental testing – Part 2-17: Tests – Test Q: Sealing*

IEC 60068-2-54, *Environmental testing – Part 2-54: Tests – Test Ta: Solderability testing of electronic components by the wetting balance method*

IEC 60384-1:1999, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

IEC 60384-4-1, *Fixed capacitors for use in electronic equipment – Part 4-1: Blank detail specification – Fixed aluminium electrolyte capacitors with non-solid electrolyte – Assessment level EZ*

IEC 60384-4-2, *Fixed capacitors for use in electronic equipment – Part 4-2: Blank detail specification – Fixed aluminium electrolyte capacitors with solid (MnO₂) electrolyte – Assessment level EZ*

ISO 3, *Preferred numbers – Series of preferred numbers*

1.4 Information to be given in a detail specification

Detail specifications shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic, sectional or blank detail specification. When more severe requirements are included, they shall be listed in 1.9 of the detail specification and indicated in the test schedules, for example, by an asterisk.

NOTE The information given in 1.4.1 may, for convenience, be presented in tabular form.

The following information shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

1.4.1 Outline drawing and dimensions

There shall be an illustration of the capacitor as an aid to easy recognition and for comparison of the capacitor with others.

Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be given in the detail specification. All dimensions shall preferably be stated in millimeters; however, when the original dimensions are given in inches, the converted metric dimensions in millimetres shall be added.

Normally, the numerical values shall be given for the length of the body, the width and height of the body and the wire spacing, or for cylindrical types, the body diameter, and the length and diameter of the terminations. When necessary, for example, when a number of items (capacitance values/voltage ranges) are covered by a detail specification, the dimensions and their associated tolerances shall be placed in a table below the drawing.

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the capacitor. When the capacitor is not designed for use on printed boards, this shall be clearly stated in the detail specification.

1.4.2 Mounting

The detail specification shall specify the method of mounting to be applied for normal use and for the application of the vibration and the bump or shock tests. The capacitors shall be mounted by their normal means. The design of the capacitor may be such that special mounting fixtures are required in its use. In this case, the detail specification shall describe the mounting fixtures and they shall be used in the application of the vibration and bump or shock tests.

1.4.3 Ratings and characteristics

The ratings and characteristics shall be in accordance with the relevant clauses of this specification, together with the following.

1.4.3.1 Rated capacitance range

See 2.2.1.

NOTE When products approved to the detail specification have different ranges, the following statement should be added: "The range of values available in each voltage range is given in IEC QC 001005.".

1.4.3.2 Particular characteristics

Additional characteristics may be listed when they are considered necessary to specify adequately the component for design and application purposes.

1.4.3.3 Soldering

The detail specification shall prescribe the test methods, severities and requirements applicable for the solderability and the resistance to soldering heat test.

1.4.4 Marking

The detail specification shall specify the content of the marking on the capacitor and on the package. Deviations in 1.6 of this sectional specification shall be specifically stated.

1.5 Terms and definitions

For the purposes of this document, the following terms and definitions, in addition to the applicable terms and definitions of IEC 60384-1, apply.

1.5.1

capacitance of an electrolytic capacitor

capacitance of an equivalent circuit having capacitance and resistance in series measured with alternating current approximately sinusoidal waveform at a specified frequency

1.5.2

long-life grade capacitors

capacitors intended for applications where a high degree of stability of characteristics over a long life is essential. The materials are chosen and the manufacture carried out so that improved performance is obtained with consequent increase in life

1.5.3

general-purpose grade capacitors

capacitors intended for applications where the high performance level of long-life grade capacitors is not required

1.5.4

reverse voltage (for polar capacitors only)

voltage applied to the capacitor terminals in the reverse polarity direction

1.6 Marking

According to 2.4 of IEC 60384-1, with the following details.

1.6.1 The information given in the marking is normally selected from the following list; the relative importance of each item is indicated by its position in the list:

- a) rated capacitance;
- b) rated voltage (d.c. voltage may be indicated by the symbol: --- or ---);
- c) category voltage and category temperatures (for long-life grade capacitors only);
- d) polarity of the terminations: for multi-section capacitors, the rated capacitance and rated voltage of the sections connected to each termination shall be shown in an unambiguous way. The termination of a capacitor section which is intended for direct connection to the rectifier (so-called reservoir section) shall be marked with the number 1 or with the colour red;
- e) tolerance on rated capacitance;

- f) reference to the grade (for long-life grade capacitors only). The abbreviation LL may be used for marking purposes;
- g) year and month (or week) of manufacture;
- h) manufacturer's name or trade mark;
- i) climatic category;
- j) manufacturer's type designation;
- k) reference to the detail specification.

1.6.2 The capacitor shall be clearly marked with a), b), c), d), e) and f) above with as many as possible of the remaining items as is considered necessary. Any duplication of information in the marking on the capacitor should be avoided.

1.6.3 The package containing the capacitor(s) shall be clearly marked with all the information listed in 1.6.1.

1.6.4 Any additional marking shall be so applied that no confusion can arise.

2 Preferred ratings and characteristics

2.1 Preferred characteristics

The values given in detail specifications shall preferably be selected from the following.

2.1.1 Preferred climatic categories

The capacitors covered by this specification are classified into climatic categories according to the general rules given in IEC 60068-1.

The lower and upper category temperature and the duration of the damp-heat steady-state test shall be chosen from the following.

Lower category temperature:	–55 °C, –40 °C, –25 °C and –10 °C
Upper category temperature:	+85 °C, +100 °C, +105 °C and +125 °C
Duration of the damp-heat steady-state test:	10, 21 and 56 days

The severities for the cold and dry heat tests are the lower and upper category temperatures respectively.

2.2 Preferred values of ratings

2.2.1 Rated capacitance (C_R)

Preferred values of rated capacitance are chosen from the E3 series of IEC 60063 and their decimal multiples.

If other values are needed, they shall preferably be chosen from the E6 series.

2.2.2 Tolerance on rated capacitance

Preferred values of tolerances on rated capacitance are:

–10/+10 %	–10/+75 %
–10/+30 %	–10/+100 %
–10/+50 %	–20/+20 %

2.2.3 Rated voltage (U_R)

Preferred values of rated direct voltages taken from the R5 and R10 series of ISO 3 are:

For voltage values <250 V: 1 V, 1,6 V, 2,5 V, 4 V, 6,3 V and their decimal multiples (R5 series), also 35 V, 50 V, 80 V and 200 V;

For voltage values ≥250 V: 250 V, 315 V, 350 V, 400 V, 450 V and 500 V (250 V, 315 V, 400 V and 500 V are in accordance with the R10 series; 350 V and 450 V are permitted in addition).

2.2.4 Category voltage (U_C)

The category voltage is equal to the rated voltage, unless otherwise stated in the detail specification.

2.2.5 Ripple voltage

An alternating voltage may be applied provided that the peak voltage resulting from the alternating voltage superimposed on the direct voltage does not exceed the value of rated direct voltage and that the rated ripple current (see 2.2.8) and the permissible reverse voltage (see detail specification) are not exceeded.

2.2.6 Reverse voltage

The permissible reverse voltage shall be given in the detail specification.

2.2.7 Surge voltage ratio

The surge voltage shall be 1,15 times the rated or category voltage for rated voltages ≤315 V or 1,10 times the rated or category voltage for rated voltages >315 V.

See also 4.14.

2.2.8 Rated ripple current

The rated ripple current at 100 Hz or 120 Hz and at upper category temperature shall be given in the detail specification. Alternatively, for capacitors for switched mode power supply application, the rated ripple current shall be stated at the relevant frequency.

NOTE This value is determined by the dimensions of the capacitor and several other factors, for example, the tangent of loss angle and the permissible temperature rise.

See also 2.2.5.

3 Quality assessment procedures

3.1 Primary stage of manufacture

For capacitors with solid electrolyte, the primary stage of manufacture is the etching or formation of the anode body.

For capacitors with non-solid electrolyte, the primary stage of manufacture is the capacitor manufacturer's evaluation of the formed anode foil.

3.2 Structurally similar components

Capacitors considered as being structurally similar are capacitors produced with similar processes and materials, though they may be of different case sizes and values.

3.3 Certified records of released lots

The information required in 3.9 of IEC 60384-1 shall be made available when prescribed in the detail specification and when requested by a purchaser. After the endurance test the parameters for which variables information is required are the capacitance change, $\tan \delta$ and the leakage current.

3.4 Qualification approval procedures

The procedures for qualification approval testing are given in 3.5 of IEC 60384-1.

The schedule to be used for qualification approval testing on the basis of lot-by-lot and periodic tests is given in 3.5 of this specification. The procedure using a fixed sample size schedule is given in 3.4.1 and 3.4.2 below.

3.4.1 Qualification approval on the basis of the fixed sample size procedure

Sampling

The fixed sample size procedure is described in 3.5.3b) of IEC 60384-1. The sample shall be representative of the range of capacitors for which approval is sought. This may or may not be the complete range covered by the detail specification.

The sample shall consist of specimens having the lowest and highest voltages and, for these voltages, the smallest and largest case size. When the range of rated voltages exceeds 200 V, an intermediate voltage shall also be tested. In each of these case size/voltage combinations (values), the highest capacitance shall be chosen. Thus, for the approval of a range, testing is required of either four or six values. When the range consists of less than four values, the number of specimens to be tested shall be that required for four values.

Spare specimens are permitted as follows.

- a) One per value which may be used to replace the permitted defective in Group 0.
- b) One per value which may be used as replacements for specimens which are defective because of incidents not attributable to the manufacturer.

The numbers given in Group 0 assume that all groups are applicable. If this is not so, the numbers may be reduced accordingly.

When additional groups are introduced into the qualification approval test schedule, the number of specimens required for Group 0 shall be increased by the same number as that required for the additional groups.