

BS EN 60745-2-5:2010



BSI Standards Publication

Hand-held motor-operated electric tools — Safety

Part 2-5: Particular requirements
for circular saws

bsi.

...making excellence a habit.
AVA Documents™
Document Sharing Hub

National foreword

This British Standard is the UK implementation of EN 60745-2-5:2010. It is derived from IEC 60745-2-5:2010. It supersedes BS EN 60745-2-5:2007+A11:2009, which will be withdrawn on 1 October 2013.

The CENELEC common modifications have been implemented at the appropriate places in the text and are indicated by tags (e.g. C C1).

The UK participation in its preparation was entrusted to Technical Committee CPL/116, Portable motor-operated tools.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© BSI 2011

ISBN 978 0 580 59001 6

ICS 25.140.20; 25.140.30

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2011.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

**Hand-held motor-operated electric tools -
Safety -
Part 2-5: Particular requirements for circular saws
(IEC 60745-2-5:2010, modified)**

Outils électroportatifs à moteur -
Sécurité -
Partie 2-5: Règles particulières
pour les scies circulaires
(CEI 60745-2-5:2010, modifiée)

Handgeführte motorbetriebene
Elektrowerkzeuge -
Sicherheit -
Teil 2-5: Besondere Anforderungen
für Kreissägen
(IEC 60745-2-5:2010, modifiziert)

This European Standard was approved by CENELEC on 2010-10-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 116/41/FDIS, future edition 5 of IEC 60745-2-5, prepared by TC 116, Safety of hand-held motor-operated electric tools, was submitted to the IEC-CENELEC parallel vote.

A draft amendment, which covers common modifications towards future IEC 60745-2-5 (116/41/FDIS), was prepared by CENELEC Technical committee TC 116, Safety of hand-held motor operated electric tools. It was submitted to the formal vote.

The combined texts were approved by CENELEC as EN 60745-2-5 on 2010-10-01.

This European Standard supersedes EN 60745-2-5:2007 + A11:2009.

Main changes include: in Clause 17, Endurance: introduction of endurance tests in practical use for the guards of all types of saws; in Clause 19, Mechanical hazards: clarifications and editorial improvement in respect to the guarding; and in Annex M, Safety of working stands for operation with hand-held motor-operated electric tools: editorial improvements.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- latest date by which the amendment has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2011-10-01
- latest date by which the national standards conflicting
with the amendment have to be withdrawn (dow) 2013-10-01

This European Standard is divided into two parts:

Part 1: General requirements which are common to most hand-held electric motor operated tools (for the purpose of this standard referred to simply as tools) which could come within the scope of this standard;

Part 2: Requirements for particular types of tools which either supplement or modify the requirements given in Part 1 to account for the particular hazards and characteristics of these specific tools.

This European Standard has been prepared under Mandate M/396 given to CENELEC by the European Commission and the European Free Trade Association and covers essential requirements of EC Directive 2006/42/EC. See Annex ZZ.

Compliance with the clauses of Part 1 together with this Part 2 provides one means of conforming with the essential health and safety requirements of the Directive concerned.

CEN/TC 255 is producing standards for non-electric circular saws (EN 792-12).

Warning: Other requirements and other EC Directives can be applicable to the products falling within the scope of this standard.

This standard follows the overall requirements of EN ISO 12100-1 and EN ISO 12100-2.

This Part 2-5 is to be used in conjunction with EN 60745-1:2009. When this standard states "addition", "modification" or "replacement", the relevant text in Part 1 is to be adapted accordingly.

Subclauses, tables and figures which are additional to those in Part 1 are numbered starting from 101; additional annexes are lettered AA, BB, etc.

Subclauses, tables and figures which are additional to those in IEC 60745-2-5:2010 are prefixed "Z".

Annex ZZ has been added by CENELEC.

NOTE In this standard the following print types are used:

- requirements proper; in roman type
- *test specifications: in italic type;*
- explanatory matter: in smaller roman type.

Endorsement notice

The text of the International Standard IEC 60745-2-5:2010 was approved by CENELEC as a European Standard with agreed common modifications.

CONTENTS

1	Scope.....	6
2	Normative references	6
3	Terms and definitions	6
4	General requirements	7
5	General conditions for the tests	7
6	Environmental requirements	7
7	Classification	9
8	Marking and instructions.....	9
9	Protection against access to live parts.....	12
10	Starting	12
11	Input and current	12
12	Heating	12
13	Leakage current	12
14	Moisture resistance	12
15	Electric strength	12
16	Overload protection of transformers and associated circuits	12
17	Endurance	13
18	Abnormal operation	15
19	Mechanical hazards.....	15
20	Mechanical strength	20
21	Construction	20
22	Internal wiring.....	21
23	Components	21
24	Supply connection and external flexible cords	21
25	Terminals for external conductors.....	21
26	Provision for earthing	21
27	Screws and connections.....	21
28	Creepage distances, clearances and distances through insulation.....	21
29	Resistance to heat, fire and tracking.....	21
30	Resistance to rusting.....	21
31	Radiation, toxicity and similar hazards.....	22
	Annexes	31
	Annex K (normative) Battery tools and battery packs	31
	Annex L (normative) Battery tools and battery packs provided with mains connection or non-isolated sources.....	31
	Annex M (normative) Safety of working stands for operation with hand-held motor- operated electric tools	32
	Annex AA (normative) Additional requirements for saws with a riving knife	47
	Annex BB (normative) Additional requirements for lower guards for saws without a riving knife	50
	Bibliography	51
	Annex ZZ (informative) Coverage of Essential Requirements of Directive 2006/42/EC	52

Figure 101 – Circular saw with outer pendulum guard	22
Figure 102 – Circular saw with inner pendulum guard	22
Figure 103 – Circular saw with tow guard	22
Figure 104 – Plunge type saw	22
Figure 105 – Test probe 'a'	23
Figure 106 – Use of test probe 'a' on circular saw guards	23
Figure 107 – Distance from the gripping surface to the blade's cutting zone	24
Figure 108 – Height restriction of the viewing aperture (see 19.101.2.1)	25
Figure 109 – Distance from the edge of the lateral side of the upper guard to the base plate	26
Figure 110 – Test probe 'b'	26
Figure 111 – Accessibility to the front cutting edge zone	27
Figure 112 – Blade exposure angle of the lower guard	28
Figure 113 – Principal dimensions of the base plate	28
Figure 114 – Flange characteristics	29
Figure Z101 – Positions of transducers for circular saws	30
Figure M.301 – Saw table fitted with hand-held circular saw	41
Figure M.302 – Testing the stability of the guard support	42
Figure M.303 – Saw table dimensions	43
Figure M.304 – Position of the outfeed end of the rip fence	44
Figure M.305 – Rip fence in low position	44
Figure M.306 – Examples of shapes of slot for locating cross-cut fence on saw tables	45
Figure M.307 – Examples of push stick and push blocks	46
Figure AA.101 – Riving knife stability test	49
Figure AA.102 – Riving knife adjustment	49
Table M.301 – Riving knife testing – strength of riving knife	36

HAND-HELD MOTOR-OPERATED ELECTRIC TOOLS – SAFETY –

Part 2-5: Particular requirements for circular saws

1 Scope

This clause of Part 1 is applicable, except as follows:

Addition:

This standard applies to circular saws, which hereinafter will be referred to as saws.

This standard does not apply to saws designed for use with abrasive wheels.

NOTE Saws designed for use with abrasive wheels as cut-off machines are covered by IEC 60745-2-22.

2 Normative references

☐ This clause of Part 1 is applicable, except as follows:

Addition:

EN 847-1:1997 ¹⁾, *Tools for woodworking – Safety requirements – Part 1: Milling tools and circular saw blades* ☐

3 Terms and definitions

This clause of Part 1 is applicable, except as follows:

Additional definitions:

3.101

circular saw

tool intended for cutting various materials with a rotating toothed blade

3.102

cutting edge zone

the outer 20 % of the blade's radius

3.103

base plate

the part supporting the saw on the material being cut (see Figure 113)

3.104

lower guard

movable blade-covering device which, in the closed or rest position, is mainly situated below the base plate

3.105

upper guard

fixed and/or movable cover of the blade situated above the base plate

3.106

riving knife

metal part placed in the plane of the saw blade with the intent of preventing the workpiece from closing on the rear part of the saw blade

¹⁾ Superseded by EN 847-1:2005, *Tools for woodworking – Safety requirements – Part 1: Milling tools and circular saw blades*.

3.107

saw with outer pendulum guard

saw having a lower guard which swings outside the upper guard (see Figure 101)

3.108

saw with inner pendulum guard

saw having a lower guard which swings inside the upper guard (see Figure 102)

3.109

saw with tow guard

saw having a lower guard which slides along the upper guard (see Figure 103)

3.110

kickback

sudden reaction to a pinched, bound or misaligned saw blade, causing an uncontrolled saw to lift up and out of the workpiece

3.111

plunge type saw

saw having only an upper guard into which the saw blade retracts when not in use (see Figure 104)

4 General requirements

This clause of Part 1 is applicable.

5 General conditions for the tests

This clause of Part 1 is applicable.

6 Environmental requirements

This clause of Part 1 is applicable, except as follows:

6.1.2.4 Modification:

Circular saws are suspended in such a way as to correspond to normal use.

6.1.2.5 Modification:

Circular saws are tested at no-load.

6.2 Vibration

6.2.4.2 Location of measurement

Addition:

Figure Z101 shows the positions on the main handle and the auxiliary handle, if applicable.

6.2.6.3 Operating conditions

Addition:

Circular saws intended to cut wood are tested under load observing the conditions shown in Table Z101.

NOTE The values for sawing wood are also representative for sawing plastics.

Circular saws intended to cut metal are tested under load observing the conditions shown in Table Z102.

Circular saws with speed setting devices shall be adjusted to the settings to cut the work piece material required in the test. 



Table Z101 – Operating conditions for circular saws cutting wood

Orientation	Cutting a horizontal piece of chipboard with minimum dimensions 800 mm x 600 mm and a thickness depending on maximum cutting depth of the circular saw: - maximum cutting depth ≤ 40 mm: chipboard thickness 19 mm; - maximum cutting depth > 40 mm: chipboard thickness 38 mm. The board shall be firmly fixed by screws, clamps air cylinders or the like to a test bench using resilient material. It shall be mounted so that it does not have any significant resonance in the frequency range that can influence the test result. The board excess end shall be 250 mm from the clamped area and shall be readjusted at the beginning of each series of tests.
Tool bit	New blade as recommended by the manufacturer for cutting chipboard.
Feed force	Just sufficient to cut at a brisk pace. Equal force shall be applied to both handles, if applicable. Excessive grip forces shall be avoided.
Test cycle	One test cycle is given by cutting off one approximately 10 mm wide strip (set by rip fence if available) across the 600 mm width of the chipboard. The measurement starts when the blade enters the wood and finishes when the blade leaves the wood.

Table Z102 – Operating conditions for circular saws cutting metal

Orientation	Cutting a horizontal piece of sheet aluminium with the minimum length of 600 mm, a width of 300 mm and a thickness of 3 mm. The work piece shall be supported on resilient material and firmly fixed by screws, clamps, air cylinders or the like to a test rig. The metal sheet excess shall be at least 100 mm from the clamped area and shall be readjusted at the beginning of each series of tests, which consists of five test cycles.
Tool bit	New saw blade as specified for sawing aluminium.
Feed force	Just sufficient to cut at a brisk pace. Equal force shall be applied to both handles, if applicable. Excessive grip forces shall be avoided.
Test cycle	Cutting off an approximately 10 mm wide strip across the 300 mm width of the metal sheet. Measurement starts when the saw blade enters the metal sheet and stops when the saw leaves the metal sheet.

6.2.7.1 Reported vibration value

Addition:

If more than one operating mode was measured, the result a_h for each operating mode applicable shall be reported.

$a_{h,W}$ = mean vibration “cutting wood”

$a_{h,M}$ = mean vibration “cutting metal” 

6.2.7.2 Declaration of the vibration total value

Addition:

The vibration total value a_h of the handle with the highest emission and the uncertainty K shall be declared

- for saws for cutting wood
the value of $a_{h,W}$, with the work mode description “cutting wood”;
- for saws for cutting metal
the value of $a_{h,M}$, with the work mode description “cutting metal” 

7 Classification

This clause of Part 1 is applicable.

8 Marking and instructions

This clause of Part 1 is applicable, except as follows:

8.1 *Addition:*

Saws shall be marked with:

- direction of rotation of the spindle, indicated on the tool by an arrow, raised or recessed or by any other means no less visible and indelible;
- rated no-load speed of the output spindle;
- specified blade diameter or blade diameter range.

Additional subclause:

8.12.1.101 The following additional safety instructions shall be given. If in English they shall be verbatim and in the following order as applicable and equivalent in any other language. This part may be printed separately from the general safety instructions.

All notes are not to be printed, they are information for the designer of the manual.

8.12.1.101.1 Safety instructions for all saws

Cutting procedures

- a)  **DANGER: Keep hands away from cutting area and the blade. Keep your second hand on auxiliary handle, or motor housing. If both hands are holding the saw, they cannot be cut by the blade.**
NOTE For circular saws with 140 mm or smaller diameter blades, the "Keep your second hand on auxiliary handle, or motor housing" may be omitted.
- b) **Do not reach underneath the workpiece. The guard cannot protect you from the blade below the workpiece.**
- c) **Adjust the cutting depth to the thickness of the workpiece. Less than a full tooth of the blade teeth should be visible below the workpiece.**
- d) **Never hold piece being cut in your hands or across your leg. Secure the workpiece to a stable platform. It is important to support the work properly to minimize body exposure, blade binding, or loss of control.**
- e) **Hold the power tool by insulated gripping surfaces only, when performing an operation where the cutting tool may contact hidden wiring or its own cord. Contact with a "live" wire will also make exposed metal parts of the power tool "live" and could give the operator an electric shock.**

- f) **When ripping, always use a rip fence or straight edge guide.** *This improves the accuracy of cut and reduces the chance of blade binding.*
- g) **Always use blades with correct size and shape (diamond versus round) of arbour holes.** *Blades that do not match the mounting hardware of the saw will run eccentrically, causing loss of control.*
- h) **Never use damaged or incorrect blade washers or bolt.** *The blade washers and bolt were specially designed for your saw, for optimum performance and safety of operation.*

8.12.1.101.2 Further safety instructions for all saws

Kickback causes and related warnings

- kickback is a sudden reaction to a pinched, bound or misaligned saw blade, causing an uncontrolled saw to lift up and out of the workpiece toward the operator;
- when the blade is pinched or bound tightly by the kerf closing down, the blade stalls and the motor reaction drives the unit rapidly back toward the operator;
- if the blade becomes twisted or misaligned in the cut, the teeth at the back edge of the blade can dig into the top surface of the wood causing the blade to climb out of the kerf and jump back toward the operator.

Kickback is the result of saw misuse and/or incorrect operating procedures or conditions and can be avoided by taking proper precautions as given below.

- a) **Maintain a firm grip with both hands on the saw and position your arms to resist kickback forces. Position your body to either side of the blade, but not in line with the blade.** *Kickback could cause the saw to jump backwards, but kickback forces can be controlled by the operator, if proper precautions are taken.*

NOTE For circular saws with 140 mm or smaller diameter blades, the words "with both hands" may be omitted.

- b) **When blade is binding, or when interrupting a cut for any reason, release the trigger and hold the saw motionless in the material until the blade comes to a complete stop. Never attempt to remove the saw from the work or pull the saw backward while the blade is in motion or kickback may occur.** *Investigate and take corrective actions to eliminate the cause of blade binding.*
- c) **When restarting a saw in the workpiece, centre the saw blade in the kerf and check that saw teeth are not engaged into the material.** *If saw blade is binding, it may walk up or kickback from the workpiece as the saw is restarted.*
- d) **Support large panels to minimise the risk of blade pinching and kickback.** *Large panels tend to sag under their own weight. Supports must be placed under the panel on both sides, near the line of cut and near the edge of the panel.*
- e) **Do not use dull or damaged blades.** *Unsharpened or improperly set blades produce narrow kerf causing excessive friction, blade binding and kickback.*
- f) **Blade depth and bevel adjusting locking levers must be tight and secure before making cut.** *If blade adjustment shifts while cutting, it may cause binding and kickback.*
- g) **Use extra caution when sawing into existing walls or other blind areas.** *The protruding blade may cut objects that can cause kickback.*

8.12.1.101.3 Safety instructions for saws shown in Figures 101, 102 and 103

Lower guard function

- a) **Check lower guard for proper closing before each use. Do not operate the saw if lower guard does not move freely and close instantly. Never clamp or tie the lower guard into the open position.** *If saw is accidentally dropped, lower guard may be bent. Raise the lower guard with the retracting handle and make sure it moves freely and does not touch the blade or any other part, in all angles and depths of cut.*

NOTE Alternate wording may be substituted for "retracting handle."

- b) **Check the operation of the lower guard spring. If the guard and the spring are not operating properly, they must be serviced before use.** *Lower guard may operate sluggishly due to damaged parts, gummy deposits, or a build-up of debris.*
 - c) **Lower guard may be retracted manually only for special cuts such as "plunge cuts" and "compound cuts".** Raise lower guard by retracting handle and as soon as blade enters the material, the lower guard must be released. *For all other sawing, the lower guard should operate automatically.*
- NOTE Alternate wording may be substituted for "retracting handle."
- d) **Always observe that the lower guard is covering the blade before placing saw down on bench or floor.** *An unprotected, coasting blade will cause the saw to walk backwards, cutting whatever is in its path. Be aware of the time it takes for the blade to stop after switch is released.*

8.12.1.101.4 Safety instructions for saws shown in Figure 104

Guard function

- a) **Check guard for proper closing before each use. Do not operate the saw if guard does not move freely and enclose the blade instantly. Never clamp or tie the guard so that the blade is exposed.** *If saw is accidentally dropped, guard may be bent. Check to make sure that guard moves freely and does not touch the blade or any other part, in all angles and depths of cut.*
- b) **Check the operation and condition of the guard return spring. If the guard and the spring are not operating properly, they must be serviced before use.** *Guard may operate sluggishly due to damaged parts, gummy deposits, or a build-up of debris.*
- c) **Assure that the base plate of the saw will not shift while performing the "plunge cut" when the blade bevel setting is not at 90°.** *Blade shifting sideways will cause binding and likely kick back.*
- d) **Always observe that the guard is covering the blade before placing saw down on bench or floor.** *An unprotected, coasting blade will cause the saw to walk backwards, cutting whatever is in its path. Be aware of the time it takes for the blade to stop after switch is released.*

8.12.1.101.5 Additional safety instructions for all saws with riving knife

Riving knife function

- a) **Use the appropriate saw blade for the riving knife.** *For the riving knife to function, the body of the blade must be thinner than the riving knife and the cutting width of the blade must be wider than the thickness of the riving knife.*
 - b) **Adjust the riving knife as described in this instruction manual.** *Incorrect spacing, positioning and alignment can make the riving knife ineffective in preventing kickback.*
 - c) **Always use the riving knife except when plunge cutting.** *Riving knife must be replaced after plunge cutting. Riving knife causes interference during plunge cutting and can create kickback.*
- NOTE This warning is not applicable for plunge type saws with a spring loaded riving knife
- d) **For the riving knife to work, it must be engaged in the workpiece.** *The riving knife is ineffective in preventing kickback during short cuts.*
 - e) **Do not operate the saw if riving knife is bent.** *Even a light interference can slow the closing rate of a guard.*

8.12.2 a) Addition:

- 101) Instructions not to use any abrasive wheels.

- 102) For saws with riving knife the instruction shall include the following:
- instructions to ensure that the riving knife is adjusted so that the distance between the riving knife and the rim of the blade is not more than 5 mm, and the rim of the blade does not extend more than 5 mm beyond the lowest edge of the riving knife;
 - information about the allowed range of saw blade body thickness and the tooth set of the blade.
- 103) Instructions to use only blade diameter(s) in accordance with the markings.

☐ Z101) For tools intended to cut wood, instruction on the correct use of the dust collection system

Z102) For tools intended to cut wood, instruction to wear a dust mask

Z103) Instruction to only use saw blades recommended

Z104) Instruction to always wear hearing protection ☐

8.12.2 b) Addition:

- 101) Instructions for the blade changing procedure.
- 102) Instruction how to check the function of all blade guard operations.
- 103) Information regarding what materials can be cut. Instructions to avoid overheating the blade tips and, if cutting plastics is permitted, to avoid melting the plastic.
- 104) Instruction on the correct use of the dust collection system.

☐ Z101) Maximum cutting depth ☐

8.12.2 c) Addition:

- 101) Instructions how to properly clean the tool and guarding system.

9 Protection against access to live parts

This clause of Part 1 is applicable.

10 Starting

This clause of Part 1 is applicable.

11 Input and current

This clause of Part 1 is applicable.

12 Heating

This clause of Part 1 is applicable.

13 Leakage current

This clause of Part 1 is applicable.

14 Moisture resistance

This clause of Part 1 is applicable.

15 Electric strength

This clause of Part 1 is applicable.

16 Overload protection of transformers and associated circuits

This clause of Part 1 is applicable.

17 Endurance

This clause of Part 1 is applicable, except as follows:

Additional subclauses:

17.101 To provide sufficient endurance for extended use, the lower guard as shown in Figures 101, 102 and 103, or the guarding system as shown in Figure 104, shall have a longevity of 50 000 operating cycles.

Compliance is checked by a new saw sample completing the following test.

The saw is to be set for 90° with the base plate in horizontal position and the blade removed. The lower guard, or the guarding system as shown in Figure 104, is retracted from the fully closed position to the maximum open working position and then released. This sequence is repeated at a rate not less than 10 cycles per minute.

The sample used for this test may be positioned in a manner other than horizontal provided that it can be shown that the alternate position is equal or more severe.

After completion of cycling test as specified above, the saw shall then comply with the tests of 17.101.1 and 17.101.2.

17.101.1 *The test and measurement is carried out at maximum depth of cut and 90°. The saw is held by the handles with the base plate in a horizontal position, the upper guard being at the top.*

Without any restoration or cleaning, the lower guard as shown in Figures 101, 102 and 103, or the guarding system as shown in Figure 104, is retracted fully and then allowed to close. The closing time from the fully open position to the fully closed position shall not exceed 0,3 s.

17.101.2 *The following tests and measurements are carried out at maximum depth of cut, at 90° and in the following positions:*

- a) The saw is held with the base plate in the horizontal position, with the upper guard being at the top.*
- b) The saw is then held with the base plate in the vertical position, with the front of the saw pointing upwards.*

For saws using a guarding system as shown in Figures 101 and 102, the lower guard is retracted fully and then allowed to close. Without any alteration, the final position of the lower guard in both cases shall be in contact with the lower guard stopper and shall not change as a result of moving the base plate to a minimum depth of cut setting and the guarding shall comply with the requirements of 19.102.3.

For saws using a guarding system as shown in Figures 103 and 104, the lower guard, or the guarding system as shown in Figure 104, is fully retracted, released and then shall lock in the blade covering position.

17.102 The lower guard, or the guarding system as shown in Figure 104, shall be resistant against environmental and foreseeable dust accumulation.

Compliance is checked by the tests of 17.102.1 and 17.102.2, as applicable.

17.102.1 *For a saw intended to cut wood based materials, a new saw sample is subjected to 1 000 cuts through each of the materials and in the order as specified below:*

- d) crosscutting soft wood;*
- e) crosscutting plywood with a minimum of 5 layers;*
- f) cutting standard medium density fibreboard (MDF) with a density between 650 kg/m³ and 850 kg/m³.*

The materials are stored indoors for 72 h prior to sawing. The thickness and length of each material to be cut may vary in size, provided the thickness of the material is minimum 10 mm and the cross sectional area of each cut is at least $30 \text{ mm} \times D$, where D is the blade diameter.

During each cut, the lower guard or the guarding system shall cycle from the fully closed position to the maximum open working position for each cutting cycle, without manual assistance. Moreover, for plunge saws with a spring loaded riving knife, the riving knife shall cycle from its fully extended to the fully retracted position.

If the lower guard, guarding system or the riving knife fails to return to its normal position at any time during the test, this is considered a failure.

Each cut is made with the saw set to 90° and maximum depth of cut. The cutting is conducted with a general purpose combination blade or the blade provided with the tool. An external dust extraction system attached to the saw shall not be used. A non-detachable dust collection system shall be maintained per 8.12.2. b) 104).

NOTE Adequate room ventilation and use of personal protective equipment is recommended.

After completion of all cuts as specified above, the saw is conditioned for 24 h in air at a relative humidity of $(93 \pm 3) \%$. The temperature of the air is maintained within 1 K of any convenient value between 20°C and 30°C .

The saw shall then comply with the tests of 17.101.1 and 17.101.2.

17.102.2 *For a saw intended to cut materials such as plastic, metal or masonry, a new saw sample for each specified material is subjected to the tests as specified below.*

- *Plastics: 1 000 cuts through PVC. The thickness and length of the material may vary in size, provided the cross sectional area of each cut is at least $0,012 \times D^2$, where D is the blade diameter.*

NOTE 1 The above formula simulates the cross sectional area of typical PVC pipes of a diameter approximately equal to 2/3 of the maximum cutting capacity of the saw. Sawing of such pipes is the predominant application for plastic.

- *Metals: 200 cuts through soft steel. The thickness and length of the material may vary in size, provided the cross sectional area of each cut is at least $0,13 \times D^{1,46}$ in mm^2 , where D is the blade diameter in mm.*

NOTE 2 The above formula simulates the cross sectional area of typical metal pipes of a diameter approximately equal to 1/2 of the maximum cutting capacity of the saw. Sawing of such pipes is the predominant application for metal.

- *Masonry: 500 cuts through masonry fibreboard (fibre cement board). The thickness and length of the fibreboard may vary in size, provided the thickness of the material is minimum 10 mm and the cross sectional area of each cut is at least $30 \text{ mm} \times D$, where D is the blade diameter.*

During each cut, the lower guard or the guarding system shall cycle from the fully closed position to the maximum open working position for each cutting cycle, without manual assistance. Moreover, for plunge saws with a spring loaded riving knife, the riving knife shall cycle from its fully extended to the fully retracted position.

If the lower guard, guarding system or the riving knife fails to return to its normal position at any time during the test, this is considered a failure.

Each cut is made with the saw set to 90° . The depth of cut, the saw blade and the rate of sawing shall be as specified for the respective material. An external dust extraction system attached to the saw shall not be used. A non-detachable dust collection system shall be maintained per 8.12.2. b) 104).

NOTE 3 Adequate room ventilation and use of personal protective equipment is recommended.

After completion of all cuts as specified above, the saw is conditioned for 24 h in air at a relative humidity of (93 ± 3) %. The temperature of the air is maintained within 1 K of any convenient value between 20 °C and 30 °C.

The saw shall then comply with the tests of 17.101.1 and 17.101.2.

18 Abnormal operation

This clause of Part 1 is applicable, except as follows:

18.10.4 Addition:

During these tests, the speed of the spindle shall not exceed 130 % of the rated no-load speed.

19 Mechanical hazards

This clause of Part 1 is applicable, except as follows:

19.1 Replacement of the first paragraph:

Moving and dangerous parts other than the rotating blade shall be so arranged or enclosed that, in normal use, adequate protection against injury is provided. The guarding of rotating blade is covered in 19.1.101.

Additional subclause:

19.1.101 Saws shall be so guarded as to minimise the risk of accidental access to the rotating blade during conditions of normal use. Guarding systems shall not be removable without the aid of a tool.

There are four commonly used guarding systems for saws, as shown in Figures 101, 102, 103 and 104. Guarding systems can be designed with the blade on the right or on the left side of the saw. These guarding systems shall comply with the requirements of 19.101 and 19.102. Each one of these guarding system types can be designed with or without the riving knife (item 6 in the figures).

- If a guarding system is designed with a riving knife, it shall meet the additional requirements of Annex AA.
- If a guarding system is designed without a riving knife, it shall meet the additional requirements of Annex BB.

Other means of achieving the necessary degree of mechanical safety are allowed, provided that these are as equally effective and reliable as those specified.

Compliance is checked by inspection.

19.3 This subclause is not applicable.

Additional subclauses:

19.101 Guarding above the base plate

19.101.1 The blade above the base plate shall be guarded by the upper guard.

Compliance is checked by inspection.

19.101.2 Apertures in the guarding system above the base plate, unless otherwise specified in 19.101.2.1 to 19.101.2.4, shall be designed to prevent contact with the cutting edge zone of any specified blade.

Compliance is checked with the test probe 'a' of Figure 105, which is inserted at any angle and to the depth possible. The test is performed with the saw set for 90° and maximum depth of cut.