

Optical fibre cables —

**Part 2-50: Indoor cables — Family
specification for simplex and duplex
cables for use in terminated cable
assemblies**

ICS 33.180.10

National foreword

This British Standard is the UK implementation of EN 60794-2-50:2008. It is identical to IEC 60794-2-50:2008.

The UK participation in its preparation was entrusted by Technical Committee GEL/86, Fibre optics, to Subcommittee GEL/86/1, Optical fibres and cables.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 29 August 2008

© BSI 2008

ISBN 978 0 580 56291 4

Amendments/corrigenda issued since publication

Date	Comments

**Optical fibre cables -
Part 2-50: Indoor cables -
Family specification for simplex and duplex cables
for use in terminated cable assemblies
(IEC 60794-2-50:2008)**

Câbles à fibres optiques -
Partie 2-50: Câbles intérieurs -
Spécification de famille pour
les câbles simplex et duplex utilisés
dans les ensembles de câbles équipés
(CEI 60794-2-50:2008)

Lichtwellenleiterkabel -
Teil 2-50: LWL-Innenkabel -
Familienspezifikation
für Simplex- und Duplexkabel
für den Einsatz als Patchkabel
(IEC 60794-2-50:2008)

This European Standard was approved by CENELEC on 2008-06-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 86A/1204/FDIS, future edition 1 of IEC 60794-2-50, prepared by SC 86A, Fibres and cables, of IEC TC 86, Fibre optics, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60794-2-50 on 2008-06-01.

This standard is to be used in conjunction with EN 60794-1-1, EN 60794-1-2 and EN 60794-2.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2009-03-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2011-06-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60794-2-50:2008 was approved by CENELEC as a European Standard without any modification.

CONTENTS

1	Scope.....	5
2	Normative references	5
3	Terms and definitions	6
4	Construction.....	6
4.1	General.....	6
4.2	Optical fibres and primary coating	6
4.3	Buffer	6
4.4	Tube.....	7
4.5	Strength and anti-buckling members	7
4.6	Sheath	7
4.7	Sheath marking	7
4.8	Examples of cable constructions	7
5	Tests.....	7
5.1	Dimensions	8
5.2	Mechanical requirements.....	8
5.2.1	Tensile performance	8
5.2.2	Crush	8
5.2.3	Impact	9
5.2.4	Repeated bending	9
5.2.5	Bend.....	9
5.2.6	Torsion	10
5.2.7	Bend at low temperature.....	10
5.2.8	Kink	10
5.2.9	Sheath pull-off force	10
5.2.10	Buffered fibre movement in compression	11
5.3	Environmental requirements	11
5.3.1	Temperature cycling	11
5.3.2	Sheath shrinkage.....	12
5.4	Transmission requirements	12
5.5	Fire performance	12
Annex A (informative)	Examples of some types of cable construction	13
Annex B (normative)	METHOD E21 – Sheath pull-off force for optical fibre cable for use in patch cords	16
Annex C (normative)	METHOD F11 – Sheath shrinkage for optical fibre cable for use in patchcords	21
Annex D (normative)	METHOD E22 – Buffered fibre movement under compression in optical fibre cables for use in patchcords	23
Annex E (normative)	METHOD F12 – Temperature cycling for optical fibre cable for use in patchcords	25
Annex F (normative)	Guidance on the selection of tests applicable to optical fibre cables for use in patchcords	27
Annex ZA (normative)	Normative references to international publications with their corresponding European publications	31
Bibliography		30

Figure A.1 – Simplex loose non-buffered fibre cable	13
Figure A.2 – Simplex ruggedized fibre cable	13
Figure A.3 – Duplex loose non-buffered fibre cable	13
Figure A.4 – Duplex ruggedized fibre cable	14
Figure A.5 – Duplex ruggedized fibre zip cord	14
Figure A.6 – Duplex ruggedized flat cable	14
Figure A.7 – Duplex ruggedized round cable	15
Figure B.1 – Schematic of test arrangement	18
Figure B.2 – Example of pulling jig	19
Figure B.3 – Cable sample preparation	20
Figure D.1 – Test set up for fibre movement under compression	24
Table 1 – Dimensions of buffered fibres	7
Table 2 – Temperature cycling severities	11
Table F.1 – Cable test method summary	27
Table F.2 – Cable testing agreement	29

OPTICAL FIBRE CABLES –

Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies

1 Scope

This part of IEC 60794 is a family specification that covers requirements for simplex and duplex optical fibre cables for use in terminated cable assemblies or for termination with optical fibre passive components.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

They complete the normative references already listed in the generic specification (IEC 60794-1-1 and IEC 60794-1-2) or in the sectional specification (IEC 60794-2 series).

IEC 60068-2-14, *Environmental testing – Part 2: Tests. Test N: Change of temperature*

IEC 60189-1, *Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods*

IEC 60793-1-1:2008, *Optical fibres – Part 1-1: Measurement methods and test procedures – General and guidance*

IEC 60793-1-20, *Optical fibres – Part 1-20: Measurement methods and test procedures – Fibre geometry*

IEC 60793-1-21, *Optical fibres – Part 1-21: Measurement methods and test procedures – Coating geometry*

IEC 60793-1-40, *Optical fibres – Part 1-40: Measurement methods and test procedures – Attenuation*

IEC 60793-1-46, *Optical fibres – Part 1-46: Measurement methods and test procedures – Monitoring of changes in optical transmittance*

IEC 60793-2-10, *Optical fibres – Part 2-10: Product specifications – Sectional specification for category A1 multimode fibres*

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-1-1, *Optical fibre cables – Part 1-1: Generic specification – General*

IEC 60794-1-2:2003, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures*

IEC 60794-2, *Optical fibre cables – Part 2: Indoor cables – Sectional specification*

IEC 60811-1-3, *Common test methods for insulating and sheathing materials of electric and optical cables – Part 1-3: General application – Methods for determining the density – Water absorption tests – Shrinkage test*

IEC 60811-1-4:1985, *Common test methods for insulating and sheathing materials of electric cables – Part 1: Methods for general application – Section Four: Tests at low temperature*
Amendment 1 (1993)
Amendment 2 (2001)

ISO/IEC 11801, *Information technology – Generic cabling for customer premises*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

terminated cable assembly

short length of cable provisioned with a connector at both ends

NOTE Examples from ISO/IEC 11801 are:

Patchcords are used to establish connections on a patch panel. Typical length of the patchcord 1 m to 10 m.

Work area cords are used to connect outlet to the terminal equipment. Typical length of the work area cords according to this specification is between 1 m and 35 m.

Equipment cords should fulfill the requirements of patchcords or work area cords depending on their application.

4 Construction

4.1 General

In addition to the constructional requirements in IEC 60794-2, the following considerations apply to simplex and duplex indoor cables for use in terminated cable assemblies.

It is not the intention of this standard to specify the finished terminated cable assembly complete with terminations.

The cable shall be designed and manufactured for an expected operating lifetime of 15 years. The materials in the cable shall not present a health hazard within its intended use.

There shall be no fibre splice in a delivery length. It shall be possible to identify each individual fibre throughout the length of the cable.

4.2 Optical fibres and primary coating

Multimode or single-mode optical fibres meeting the requirements of IEC 60793-2-10, type A1a and A1b, and IEC 60793-2-50, type B, shall be used.

4.3 Buffer

If a tight or semi-tight (loosely applied) buffer is required, it shall consist of one or more layers of inert material. Semi-tight tubes may be filled. Unless otherwise specified, the buffer shall be removable in one operation over a length of 15 mm.

Buffer dimensions are shown in Table 1.

Table 1 – Dimensions of buffered fibres

Nominal diameter (mm)	0,3 – 1,3
Tolerances (mm)	± 0,05

4.4 Tube

One or two primary coated or buffered fibres are packaged (loosely or not) in a tube construction which may be filled. The tube may be reinforced with a composite wall.

If required the suitability of the tube shall be determined by an evaluation of its kink resistance in accordance with IEC 60794-1-2, Method G7.

4.5 Strength and anti-buckling members

The cable shall be designed with sufficient strength members to meet the requirements of this standard.

The strength and/or anti-buckling member may be either metallic or non-metallic and may be located in the cable core and/or under the sheath and/or in the sheath.

4.6 Sheath

The cable shall have a uniform overall protective sheath. The cable diameter shall be specified in the relevant detail specification (or product specification). Sheath removal is an important feature of these cables. This is tested by the method E21 described in Annex B of this standard.

4.7 Sheath marking

If required, the cable shall be marked as agreed between the customer and supplier. The marking shall be resistant to abrasion.

4.8 Examples of cable constructions

Examples of some main types of cable construction are shown in Figures A.1 to A.7.

Other configurations are not excluded if they meet the mechanical, environmental, transmission and termination requirements given in this standard.

5 Tests

Compliance with the specification requirements shall be verified by carrying out tests selected from the following subclauses. It is not intended that all tests be carried out in all cases, and Annex F provides guidance on the selection of tests. The tests to be applied and the frequency of testing shall be agreed between the customer and supplier.

Some of the following tests can be performed on a short sample length of cable which is still an integral part of a longer length, thus making it possible to detect permanent changes in attenuation.

Single-mode cables shall be measured at 1 550 nm and 1 625 nm and multimode¹⁾ cables shall be measured at 1 300 nm unless otherwise agreed. Measurements shall be carried out according to IEC 60793-1-40.

If loops are used within a test to fix the ends of a cable, the diameter shall not be so small as to cause excessive mode filtering in multimode fibre.

Unless otherwise specified, all tests shall be carried out at ambient temperature, as described in IEC 60793-1-1, Clause 5.

5.1 Dimensions

The fibre dimensions and tolerances shall be checked in accordance with test method of IEC 60793-1-20 or IEC 60793-1-21. The diameter of the buffer and of the cable, as well as the thickness of the sheath, shall be measured in accordance with the methods of IEC 60189-1.

5.2 Mechanical requirements

5.2.1 Tensile performance

Method: IEC 60794-1-2-E1A.

Diameter of chuck drums and transfer devices: not less than the minimum dynamic bending diameter specified for the cable, at least 250 mm diameter.

Rate of transfer device: either 100 mm/min or 100 N/min.

Load: 100 N applied for 5 min for simplex cables, 200 N for 5 min for duplex cables.

Length of sample: sufficient to achieve the desired accuracy of measurement of attenuation change and shall be agreed between the customer and the supplier.

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

5.2.2 Crush

Method: IEC 60794-1-2-E3.

Force: 500 N.

Duration: 1 min.

Length between test locations: 500 mm.

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

NOTE For cables having a non-circular cross section, the force should be applied in the direction of the minor axis (perpendicular to the major axis).

¹⁾ OM3 multimode cables should be tested at 850 nm and may be tested at 1 300 nm in addition, all other multimode cables should be tested at 1 300 nm.

5.2.3 Impact

Method: IEC 60794-1-2-E4.

Radius of striking surface: 12,5 mm.

Impact energy: 1,0 J.

Number of impacts: at least 3, each separated at least 500 mm.

Requirements: the maximum increase in attenuation after the test shall be specified in the product specification and there shall be no fibre breakage or damage to the cable elements. Any imprint of the striking surface on the cable sheath is not considered as a mechanical damage.

NOTE For cables having a non-circular cross section, the force should be applied in the direction of the minor axis (perpendicular to the major axis).

5.2.4 Repeated bending

Method: IEC 60794-1-2-E6.

Bending radius: 30 mm for simplex, 20 times cable diameter for duplex (for non-circular cables, the cable diameter is the minor dimension).

Number of cycles: 200.

Mass of weights: sufficient to contour the apparatus e.g. 1 kg to 2 kg.

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

NOTE For cables having a non-circular cross section, the bend requirements are determined using the minor axis as the cable diameter with bending in the direction of the preferential bend.

5.2.5 Bend

Method: IEC 60794-1-2-E11A.

Mandrel diameter: 60 mm.

Number of turns per helix: 6.

Number of cycles: 3.

Length of sample: sufficient to carry out the test.

Prior to bending: at both ends of the sample all the cable components shall be fixed together, e.g. by loops or glue.

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

NOTE For cables having a non-circular cross section, the bend requirements are determined using the minor axis as the cable diameter with bending in the direction of the preferential bend.