

Fixed inductors for electromagnetic interference suppression —

Part 2: Sectional specification

The European Standard EN 60938-2:1999, incorporating amendment A1:2007, has the status of a British Standard

ICS 29.180; 33.100.01; 29.100.10; 31.020

National foreword

This British Standard was published by BSI. It is the UK implementation of EN 60938-2:1999, incorporating amendment A1:2007. It is identical with IEC 60938-2:1999, incorporating amendment 1:2006. It supersedes BS EN 138100:1997 which is withdrawn.

The start and finish of text introduced or altered by amendment is indicated in the text by tags **A1** **A1**. Tags indicating changes to IEC text carry the number of the amendment. For example, text altered by IEC amendment 1 is indicated in the text by **A1** **A1**.

The UK participation in its preparation was entrusted to Technical Committee EPL/40, Capacitors and resistors for electronic equipment.

A list of organizations represented on EPL/40 can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard, having been prepared under the direction of the Electrotechnical Sector Committee, was published under the authority of the Standards Committee and comes into effect on 15 April 2000

© BSI 2007

ISBN 0 580 34296 4

Amendments issued since publication

Amd. No.	Date	Comments
17010	31 May 2007	See national foreword

English version

**Fixed inductors for electromagnetic interference suppression -
Part 2: Sectional specification
(IEC 60938-2:1999)**

Inductances fixes d'antiparasitage -
Partie 2: Spécification intermédiaire
(CEI 60938-2:1999)

Drosseln zur Unterdrückung
elektromagnetischer Störungen -
Teil 2: Rahmenspezifikation
(IEC 60938-2:1999)

This European Standard was approved by CENELEC on 1999-12-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

© 1999 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Ref. No. EN 60938-2:1999 E

AVA Documents
Document Sharing Hub

Foreword

The text of document 40/1111/FDIS, future edition 2 of IEC 60938-2, prepared by IEC TC 40, Capacitors and resistors for electronic equipment, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60938-2 on 1999-12-01.

This European Standard supersedes EN 138100:1996.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2000-09-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2002-12-01

Annexes designated "normative" are part of the body of the standard.
In this standard, annexes A, B, C, D and ZA are normative.
Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60938-2:1999 was approved by CENELEC as a European Standard without any modification.

Foreword to amendment A1

The text of amendment 1:2007 to the International Standard IEC 60938-2:1999, prepared by IEC TC 40, Capacitors and resistors for electronic equipment, was submitted to the formal vote and was approved by CENELEC as amendment A1 to EN 60938-2:1999 on 2007-02-01 without any modification.

The following dates were fixed:

- latest date by which the amendment has to be
implemented at national level by publication of
an identical national standard or by endorsement (dop) 2008-02-01
- latest date by which the national standards conflicting
with the amendment have to be withdrawn (dow) 2010-02-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of amendment 1:2006 to the International Standard IEC 60938-2:1999 was approved by CENELEC as an amendment to the European Standard without any modification.

CONTENTS

Clause	Page
1 General	5
1.1 Scope	5
1.2 Object	5
1.3 Normative references	5
1.4 Information to be given in a detail specification	6
1.5 Definitions	7
1.6 Marking	7
2 Preferred ratings and characteristics	7
2.1 Climatic categories	7
2.2 Values of ratings	8
3 Quality assessment procedures	8
3.1 Primary stage of manufacture	8
3.2 Structurally similar inductors	8
3.3 Certified records of released lots	9
3.4 Qualification approval	9
3.5 Quality conformance inspection	13
4 Test and measurement procedures	13
4.1 Visual examination and check of dimensions	13
4.2 Voltage proof	14
4.3 Insulation resistance	14
4.4 Inductance	15
4.5 DC line resistance	15
4.6 Robustness of terminations	15
4.7 Resistance to soldering heat	15
4.8 Solderability	15
4.9 Rapid change of temperature	15
4.10 Vibration	16
4.11 Bump	16
4.12 Shock	17
4.13 Container sealing	17
4.14 Climatic sequence	17
4.15 Damp heat, steady state	18
4.16 Temperature rise (applies only to inductors with a mass >5 g)	18
4.17 Impulse voltage (applies to inductors with more than one winding)	19
4.18 Endurance	20
4.19 Passive flammability (if applicable)	21
4.20 Component solvent resistance (if applicable)	21
4.21 Solvent resistance of marking (if applicable)	21

Annex A (normative) Test schedule for safety tests only approval	22
Annex B (normative) Test schedule for safety tests and performance tests for qualification approval, assessment level D.....	25
Annex C (normative) Example of a suitable circuit for the endurance test voltage	30
Annex D (normative) Declaration of design (confidential to the manufacturer and the certification body)	31
Annex E (normative) Test methods for thyristor electromagnetic interference suppression inductors	32
Annex ZA (normative) Normative references to international publications with their corresponding European publications	34

**FIXED INDUCTORS FOR ELECTROMAGNETIC
INTERFERENCE SUPPRESSION –**

Part 2: Sectional specification

1 General

1.1 Scope

This International Standard applies to fixed inductors designed for electromagnetic interference suppression and which fall within the scope of the generic specification, IEC 60938-1. It is restricted to fixed inductors for which safety tests are appropriate. This implies that inductors specified according to this specification will either be connected to mains supplies, when compliance with the mandatory tests of table 1 is necessary, or used in other circuit positions where the equipment specification prescribes that some or all of these safety tests are required.

This standard applies to fixed inductors which will be connected to an a.c. mains or other supply with a nominal voltage not exceeding 1 000 V a.c. (r.m.s.) or d.c. between conductors and with a nominal frequency not exceeding 400 Hz.

1.2 Object

The object of this standard is to prescribe standard requirements for safety tests and standard ratings and characteristics, to select from IEC 60938-1 the appropriate methods of test and to give general performance requirements for suppression inductors. Test severities and performance requirements prescribed in detail specifications referring to this sectional specification shall be of equal or higher performance level. In addition, the minimum requirements for safety tests specified herein always apply.

1.3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60060-1:1989, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60063:1963, *Preferred number series for resistors and capacitors*
Amendment 1 (1967)
Amendment 2 (1977)

IEC 60085:1984, *Thermal evaluation and classification of electrical insulation*

IEC 60279:1969, *Measurement of the winding resistance of an a.c. machine during operation at alternative voltage*

IEC 60938-1:1999, *Fixed inductors for electromagnetic interference suppression – Part 1: Generic specification*

ISO 3:1973, *Preferred numbers – Series of preferred numbers*

Ⓐ CISPR 16-1-1:2003, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus* Ⓐ

1.4 Information to be given in a detail specification

1.4.1 General

Detail specifications shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic or sectional specification. When more severe requirements are included they shall be listed in 1.8 of the detail specification and indicated in the test schedules, for example by an asterisk.

NOTE – The information given in 1.4.2 may, for convenience, be presented in tabular form.

The information given in 1.4.2 to 1.4.5 shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

1.4.2 Outline drawing and dimensions

There shall be an illustration of the inductor as an aid to easy recognition and for comparison of the inductor with others. Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be indicated upon the drawing. All dimensions shall be stated in millimetres.

Normally the numerical values shall be given for the length of the body, the width and height of the body or for cylindrical types, the body diameter, and the length and diameter of the terminations. When necessary, for example when a number of items (inductance values/voltage ranges) are covered by a detail specification, the dimensions and their associated tolerances shall be placed in a table below the drawing.

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the inductor. When the inductor is not designed for use on printed boards, this shall be clearly stated in the detail specification.

1.4.3 Mounting

The detail specification shall specify the method of mounting to be recommended for normal use and the method which is mandatory for the application of the vibration, bump and shock tests. The design of the inductor may be such that special mounting fixtures are required in its use. In this case, the detail specification shall describe the mounting fixtures and they shall be used in the application of the bump, shock and vibration tests. The specified heat sink shall be used in the application of the endurance test.

1.4.4 Ratings and characteristics

The ratings and characteristics shall be in accordance with the relevant clauses of this specification.

1.4.4.1 Additional characteristics may be listed, when they are considered necessary to specify adequately the inductor for design and application purposes.

1.4.5 Marking

Deviations from 1.6 of this sectional specification, shall be specifically stated in the detail specification.

1.5 Definitions

For the purpose of this International Standard, the definitions in IEC 60938-1 apply.

1.6 Marking

1.6.1 The information given in the marking is normally selected from the following list; the relative importance of each item is indicated by its position in the list:

- a) manufacturer's name (or trade mark);
- b) manufacturer's type designation;
- c) recognized approval mark;
- d) rated inductance and tolerance;
- e) rated voltage;
- f) rated current;
- g) identification of terminations or circuit diagram;
- h) rated temperature;
- i) climatic category;
- j) year and month (or week) of manufacture (this may be in code form);
- k) reference to the detail specification.

1.6.2 Marking of the inductor may be omitted when the manufacturer considers that there is insufficient space, and this fact is recorded in the detail specification. When present, the marking shall be sufficient to provide a clear identification of the inductor. Any duplication of information in the marking on the inductor should be avoided.

1.6.3 The packaging containing the inductor(s) shall be clearly marked with all the information listed in 1.6.1, except g).

1.6.4 Any additional marking shall be so applied that no confusion can arise.

2 Preferred ratings and characteristics

2.1 Climatic categories

Electromagnetic interference suppression inductors covered by this specification are classified into climatic categories according to the general rules given in IEC 60068-1. The lower and upper category temperatures and the duration of the damp heat, steady state test shall be selected from the following:

Lower category temperature: -65°C , -55°C , -40°C , -25°C and -10°C .

Upper category temperature: $+85^{\circ}\text{C}$, $+100^{\circ}\text{C}$, $+125^{\circ}\text{C}$ and $+155^{\circ}\text{C}$.

Duration of the damp heat, steady state test: 21 and 56 days.

The severities for the cold and dry heat tests are the lower and upper category temperatures respectively.

2.2 Values of ratings

2.2.1 Rated inductance and tolerance

Preferred values of rated inductance are values chosen from the E 6 series of preferred values given in IEC 60063.

The preferred tolerances on rated inductance are as follows:

$\pm 30\%$; -30% / $+50\%$.

2.2.2 Rated voltage (U_R)

Preferred values for rated voltages are:

AC inductors: 50 V, 125 V, 250 V, 400 V, 440 V, 480 V and 760 V.

DC inductors: 50 V, 160 V, 250 V and 500 V.

NOTE – Electromagnetic interference suppression inductors are normally chosen to have their rated voltage equal to or greater than the nominal voltage of the supply system to which they are to be connected. It should, however, be borne in mind that the voltage of the system may rise up to 10 % above the nominal voltage.

2.2.3 Category voltage (U_C)

The category voltage is equal to the rated voltage, unless otherwise stated in the detail specification.

2.2.4 Rated temperature

The rated temperature shall not be lower than $+40\text{ }^{\circ}\text{C}$.

2.2.5 Rated current

The preferred values of rated current are selected from the R10 series of ISO 3.

2.2.6 Passive flammability

When specified, the minimum category of passive flammability permitted is category C.

3 Quality assessment procedures

3.1 Primary stage of manufacture

See 3.2 of IEC 60938-1.

3.2 Structurally similar inductors

Inductors are structurally similar when for their range of inductance values they have the following common characteristics:

- a) essentially the same materials;
- b) similar design features and manufacturing techniques;
- c) same rated voltage.

3.3 Certified records of released lots

When certified test records are requested by a purchaser, they shall be specified in the detail specification.

3.4 Qualification approval

The procedures for qualification approval testing for structurally similar inductors are given in 3.4 of IEC 60938-1.

3.4.1 Qualification approval on the basis of the fixed sample size procedures

3.4.1.1 Sampling

This standard covers procedures for qualification approval tests only. Two alternative test procedures are given, namely the full test procedure covering both safety tests and performance requirements, and a restricted test procedure covering safety tests.

Table 1 and annex A form the schedule limited to tests for safety tests only approval. Prior to the approval testing for safety tests only it is necessary to submit to the certification body a declaration of design (annex D) registering essential data and basic design details of the inductors for which approval is sought.

Table 2 and annex B form the full schedule for safety tests and performance approval.

Each rated voltage shall be separately qualified. The total number of inductors of each rated voltage to be tested in each group is given in table 1 or 2. For each rated voltage the sample shall contain equal numbers of specimens of the highest and lowest inductance and the highest and lowest rated current in the range to be qualified. Where only one inductance value or rated current value is involved, the total number of inductors as stated in table 1 or 2 shall be tested.

Spare specimens are permitted as follows:

- a) one per inductance/rated current combination which may be used to replace the permitted non-conforming items in group 0;
- b) one per inductance/rated current combination which may be used as replacements for specimens lost due to incidents not attributable to the manufacturer or the test sequence;
- c) the remainder of the spares may be required if it is necessary to repeat any test according to the provisions of note 1 to table 1 or 2;
- d) spares may be kept at the premises of the manufacturer instead of being sent to the testing station.

The number of samples given in group 0 assume that all groups are applicable. If this is not so the numbers may be reduced accordingly.

When additional groups are introduced into the qualification approval test schedule, the number of specimens required for group 0 shall be increased by the same number as that required for the additional groups.

3.4.1.2 Tests

The complete series of tests specified in either table 1 or 2 is required for the approval of a series of structurally similar inductors of one rated voltage. The tests of each group shall be carried out in the order given.

The whole sample shall be subjected to the tests of group 0 and then divided for the other groups.

Non-conforming items found during the tests of group 0 shall not be used for the other groups.

"One non-conforming item" is counted when an inductor has not satisfied the whole or part of the tests of a group.

The approval is granted when the number of non-conformances does not exceed the specified number of permissible non-conforming items for each group or subgroup and the total number of permissible non-conformances indicated in table 1 or 2.

NOTE – Table 1 and annex A or table 2 and annex B together form the fixed sample size test schedule, for which table 1 or 2 includes the details for the sampling and permissible non-conforming items for the different tests or groups of tests, whereas annexes A or B together with the details of test contained in clause 4 give a complete summary of test conditions and performance requirements and indicate where, for example for the test method or conditions of test, a choice has to be made in the detail specification. The conditions of test and performance requirements for the fixed sample size test schedule shall be identical to those prescribed in the detail specification.