BRITISH STANDARD

BS EN 60958-3:2003

Digital audio interface —

Part 3: Consumer applications

The European Standard EN 60958-3:2003 has the status of a British Standard

ICS 33.160.01

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI Documents Document Sharing Hub British Standards

Full document details: BS EN 60958-3:2003

National foreword

This British Standard is the official English language version of EN 60958-3:2003. It is identical with IEC 60958-3:2003. It supersedes BS EN 60958-3:2000 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee EPL/100, Audio, video and multimedia systems and equipment, which has the responsibility to:

— aid enquirers to understand the text;

— present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;

— monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

From 1 January 1997, all IEC publications have the number 60000 added to the old number. For instance, IEC 27-1 has been renumbered as IEC 60027-1. For a period of time during the change over from one numbering system to the other, publications may contain identifiers from both systems.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled "International Standards Correspondence Index", or by using the "Search" facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 46, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2003

© BSI 31 July 2003

ISBN 0 580 42338 7

Documents
Document Sharing Hub

Full document details: BS EN 60958-3:2003

EUROPEAN STANDARD **EN 60958-3**

NORME EUROPÉENNE

EUROPÄISCHE NORM April 2003

ICS 33.160.01

Supersedes EN 60958-3:2000

English version

Digital audio interface
Part 3: Consumer applications
(IEC 60958-3:2003)

Interface audionumérique
Partie 3: Applications grand public
(CEI 60958-3:2003)

Digitalton-Schnittstelle
Teil 3: Allgemeingebrauch
(IEC 60958-3:2003)

This European Standard was approved by CENELEC on 2003-03-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and United Kingdom.

CENELEC
European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

© 2003 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Ref. No. EN 60958-3:2003 E

AVA Documents
Document Sharing Hub

Full document details: BS EN 60958-3:2003

Foreword

The text of document 100/559/FDIS, future edition 2 of IEC 60958-3, prepared by IEC TC 100, Audio, video and multimedia systems and equipment, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60958-3 on 2003-03-01.

This European Standard supersedes EN 60958-3:2000.

The following dates were fixed:

– latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2003-12-01

– latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2006-03-01

Annexes designated "normative" are part of the body of the standard.
Annexes designated "informative" are given for information only.
In this standard, annexes A to H, J to P and ZA are normative and annex Q is informative.
Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60958-3:2003 was approved by CENELEC as a European Standard without any modification.

Documents
Document Sharing Hub

Full document details: BS EN 60958-3:2003

CONTENTS

Page

Clause
1 Scope 5
2 Normative references 5
3 Interface format 6
4 Channel status 6
4.1 General 6
4.2 Application 6
4.2.1 Channel status general format 6
4.2.2 Mode 0 channel status format for digital audio equipment for consumer use 9
4.3 Copyright management guidelines for consumer application of the digital audio interface 11
4.3.1 General 11
4.3.2 Category code groups 12
5 User data 15
5.1 General 15
5.2 Application 15
5.2.1 User data message structure 15
5.2.2 Equipment classification 16
5.2.3 User data message length and contents 17
6 Electrical and optical requirements 19
6.1 General 19
6.2 Timing accuracy 19
6.2.1 Accuracy of sampling frequency (clock accuracy) 19
6.2.2 Receiver locking range 19
6.3 Unbalanced line 19
6.3.1 General characteristics 19
6.3.2 Line driver characteristics 20
6.3.3 Line receiver characteristics 21
6.3.4 Connectors 22
6.4 Optical connection 22

Annex A (normative) Application of the digital audio interface in the compact disc digital audio system 23

Annex B (normative) Application of the digital interface in the 2-channel pcm encoder/decoder 26

Annex C (normative) Application of the digital interface in the 2-channel digital audio tape recorder in the consumer mode 27

Annex D (normative) Application of the digital interface in laser optical digital audio systems for which no other category code is defined 31

Annex E (normative) Application of the digital interface in digital audio mixers in the consumer mode 32

Annex F (normative) Application of the digital interface in a sampling rate converter in the consumer mode 33

AVA Documents
Document Sharing Hub

Full document details: BS EN 60958-3:2003

Page

Annex G (normative) Application of the digital interface in digital sound samplers in the consumer mode 34
Annex H (normative) Application of the digital interface in 2-channel digital broadcast receivers (Japan) in the consumer mode 35
Annex J (normative) Application of the digital interface in 2-channel digital broadcast receivers (Europe) in the consumer mode 36
Annex K (normative) Application of the digital interface in 2-channel digital broadcast receivers (USA) in the consumer mode 37
Annex L (normative) Application of the digital interface in 2-channel electronic software delivery in the consumer mode 38
Annex M (normative) Application of the digital interface in the digital compact cassette system in the consumer mode 39
Annex N (normative) Application of the digital interface in the mini disc system in the consumer mode 44
Annex O (normative) Application of the digital interface in the digital sound processor in the consumer mode 45

Figure 1 – Example of message structure using information units 16
Figure 2 – Simplified example of the configuration of the circuit (unbalanced) 20
Figure 3 – Rise and fall times 20
Figure 4 – Intrinsic jitter measurement filter 21
Figure 5 – Eye diagram 22
Figure 6 – Receiver jitter tolerance template 22
Figure C.1 – Example of different combinations of start-ID and shortening-ID 30

Table 1 – Channel status general format for consumer use 7
Table 2 – Mode 0 channel status format for consumer use 9
Table 3 – Category code groups 12
Table 4 – Category code groups for laser optical products 13
Table 5 – Category code groups for digital/digital converter and signal processing products 13
Table 6 – Category code groups for magnetic tape or magnetic disc based products 13
Table 7 – Category code groups for broadcast reception of digitally encoded audio with/without video signals 14
Table 8 – Category code groups for musical instruments, microphones and other sources that create original sound 14
Table 9 – Category code groups for A/D converters for analogue signals without copyright information 14
Table 10 – Category code groups for A/D converters for analogue signals with copyright information 15
Table 11 – Category code groups for solid state memory based products 15
Table A.1 – Example of 2-channel compact disc format 25
Table C.1 – Use of Cp-bit, L-bit and category code for DAT 28
Table C.2 – User data application in the DAT system 29
Table M.1 – Deck status codes 41

Documents
Document Sharing Hub

Full document details: BS EN 60958-3:2003

DIGITAL AUDIO INTERFACE –

Part 3: Consumer applications

1 Scope

This International Standard describes an application of a serial, uni-directional, self-clocking interface as defined in IEC 60958-1, for the interconnection of digital audio equipment for consumer applications.

When used in a consumer digital processing environment, the interface is primarily intended to carry stereophonic programmes, with a resolution of up to 20 bits per sample, an extension to 24 bits per sample being possible.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60268-11:1987, *Sound system equipment – Part 11*: *Application of connectors for the interconnection of sound system components*

IEC 60841:1988, *Audio recording – PCM encoder/decoder system*

IEC 60908:1999, *Audio recording – Compact disc digital audio system*

IEC 60958-1:1999, *Digital audio interface – Part 1*: *General*

IEC 60958-4:1999, *Digital audio interface – Part 4*: *Professional applications*

IEC 61119-1:1992, *Digital audio tape cassette system (DAT) – Part 1: Dimensions and characteristics*

IEC 61119-6:1992, *Digital audio tape cassette system (DAT) – Part 6: Serial copy management system*

Documents
Document Sharing Hub

Full document details: BS EN 60958-3:2003

3 Interface format

The interface format as defined in IEC 60958-1 shall be used.

4 Channel status

4.1 General

For every sub-frame, the channel status provides information related to the audio channel that is carried in that same sub-frame.

Channel status information is organized in a 192-bit block, subdivided into 24 bytes, numbered 0 to 23 (see table 1). The first bit of each block is carried in the frame with preamble “B”.

The individual bits of a block are numbered 0 to 191.

The primary application is indicated by channel status bit 0.

As stated in IEC 60958-1, for professional application this first channel status bit equals “1”.

For the consumer digital audio applications described in this standard, this first channel status bit equals “0”.

Secondary applications may be defined within the framework of these primary applications.

4.2 Application

4.2.1 Channel status general format

For each channel, channel status is used for the following information.

Documents
Document Sharing Hub
Full document details: BS EN 60958-3:2003

Table 1 – Channel status general format for consumer use

Byte									
0		a = “0”	b	c	d			Mode	
	bit	0	1	2	3	4	5	6	7
1									
	bit	8	9	10	11	12	13	14	15
2									
	bit	16	17	18	19	20	21	22	23
3									
	bit	24	25	26	27	28	29	30	31
4									
	bit	32	33	34	35	36	37	38	39
5									
	bit	40	41	42	43	44	45	46	47
6									
	bit	48	49	50	51	52	53	54	55
7									
	bit	56	57	58	59	60	61	62	63
8									
	bit	64	65	66	67	68	69	70	71
9									
	bit	72	73	74	75	76	77	78	79
10									
	bit	80	81	82	83	84	85	86	87
11									
	bit	88	89	90	91	92	93	94	95
12									
	bit	96	97	98	99	100	101	102	103
13									
	bit	104	105	106	107	108	109	110	111
14									
	bit	112	113	114	115	116	117	118	119
15									
	bit	120	121	122	123	124	125	126	127
16									
	bit	128	129	130	131	132	133	134	135
17									
	bit	136	137	138	139	140	141	142	143
18									
	bit	144	145	146	147	148	149	150	151
19									
	bit	152	153	154	155	156	157	158	159
20									
	bit	160	161	162	163	164	165	166	167
21									
	bit	168	169	170	171	172	173	174	175
22									
	bit	176	177	178	179	180	181	182	183
23									
	bit	184	185	186	187	188	189	190	191

a: use of channel status block.
b: linear PCM identification.
c: copyright information.
d: additional format information.

Documents
Document Sharing Hub
Full document details: BS EN 60958-3:2003

Byte 0: General control and mode information

Control:

Bit 0	“0”	Consumer use of channel status block.

NOTE The significance of byte 0, bit 0 is such that transmission from an interface conforming to IEC 60958-4 can be identified.

Bit 1	“0”	Audio sample word represents linear PCM samples.
	“1”	Audio sample word used for other purposes.
Bit 2	“0”	Software for which copyright is asserted.
	“1”	Software for which no copyright is asserted.

NOTE Bit 2 is referred to as the “Cp-bit”. It should be indicated whether copyright protection has been asserted.

The copyright status may be unknown for certain applications. The above interpretation is therefore not valid in combination with some category codes (see annexes). The Cp-bit can alternate between 0 and 1 at a rate between 4 Hz and 10 Hz (see annex A).

Bits 3-5 Additional format information, meaning depends on bit 1.

When bit 1 = “0”, linear PCM audio mode:

bit	3 4 5	
state	“0 0 0”	2 audio channels without pre-emphasis.
	“1 0 0”	2 audio channels with 50/15 μs pre-emphasis.
	“0 1 0”	Reserved (for 2 audio channels with pre-emphasis).
	“1 1 0”	Reserved (for 2 audio channels with pre-emphasis).

All other states of bits 3-5 are reserved and shall not be used until further defined.

When bit 1 = “1”, other than linear PCM applications:

bit	3 4 5	
state	“0 0 0”	Default state for applications other than linear PCM.

All other states of bits 3-5 are reserved and shall not be used until further defined.

Bits 6-7 Channel status mode, indicates one of four possible channel status formats (bytes 1 to 23). There are four possible modes for each of the states of bit 1.

bit	6 7	
state	“0 0”	Mode 0, refer to 4.2.2.

All other states of bits 6-7 are reserved and shall not be used until further defined.

The contents of bits 8 to 191 depend on the mode as indicated by bits 6 and 7. If not defined otherwise, the default value is “0”.

Documents
Document Sharing Hub
Full document details: BS EN 60958-3:2003

4.2.2 Mode 0 channel status format for digital audio equipment for consumer use

When the audio sample word represents linear PCM and the channel status mode is mode 0, the following channel status format should be applied:

Table 2 – Mode 0 channel status format for consumer use

Byte									
0		a = "0"	b = "0"	c	d			Mode = "0 0"	
	bit	0	1	2	3	4	5	6	7
1		Category code							
	bit	8	9	10	11	12	13	14	15
2		Source number				Channel number			
	bit	16	17	18	19	20	21	22	23
3		Sampling frequency				Clock accuracy			
	bit	24	25	26	27	28	29	30	31
4		Word length							
	bit	32	33	34	35	36	37	38	39
5									
	bit	40	41	42	43	44	45	46	47
6									
	bit	48	49	50	51	52	53	54	55
7									
	bit	56	57	58	59	60	61	62	63
8									
	bit	64	65	66	67	68	69	70	71
9									
	bit	72	73	74	75	76	77	78	79
10									
	bit	80	81	82	83	84	85	86	87
11									
	bit	88	89	90	91	92	93	94	95
12									
	bit	96	97	98	99	100	101	102	103
13									
	bit	104	105	106	107	108	109	110	111
14									
	bit	112	113	114	115	116	117	118	119
15									
	bit	120	121	122	123	124	125	126	127
16									
	bit	128	129	130	131	132	133	134	135
17									
	bit	136	137	138	139	140	141	142	143
18									
	bit	144	145	146	147	148	149	150	151
19									
	bit	152	153	154	155	156	157	158	159
20									
	bit	160	161	162	163	164	165	166	167
21									
	bit	168	169	170	171	172	173	174	175
22									
	bit	176	177	178	179	180	181	182	183
23									
	bit	184	185	186	187	188	189	190	191
		a: use of channel status block. b: linear PCM identification.				c: copyright information. d: additional format information.			

Documents
Document Sharing Hub
Full document details: BS EN 60958-3:2003

Byte 0 as defined in 4.2.1, with:

Bit 1	“0”	Audio sample word represents linear PCM samples.
Bits 6-7	“0 0”	Mode 0.

Byte 1: Category code

The category code indicates the kind of equipment that generates the digital audio interface signal. See the relevant annexes for the assignments. Bit 8 = LSB, bit 15 = MSB.

Byte 2: Source and channel number

Bits 16-19 Source number, bit 16 = LSB, bit 19 = MSB.

bit	16 17 18 19	
state	“0 0 0 0”	Do not take into account.
	“1 0 0 0”	1
	“0 1 0 0”	2
	“1 1 0 0”	3
	.....	
	“1 1 1 1”	15

Bits 20-23 Channel number (audio channel), bit 20 = LSB, bit 23 = MSB.

bit	20 21 22 23	
state	“0 0 0 0”	Do not take into account.
	“1 0 0 0”	A (left channel for stereo channel format).
	“0 1 0 0”	B (right channel for stereo channel format).
	“1 1 0 0”	C
	.....	
	“1 1 1 1”	O

Byte 3: Sampling frequency and clock accuracy

Bits 24-27 Sampling frequency

bit	24 25 26 27	
state	“0 0 0 0”	44,1 kHz
	“0 1 0 0”	48 kHz
	“1 1 0 0”	32 kHz

All other combinations are reserved and shall not be used until further defined.

Bits 28-29 Clock accuracy.

bit	28 29	
state	“0 0”	Level II.
	“1 0”	Level I.
	“0 1”	Level III.
	“1 1”	Reserved.

Documents
Document Sharing Hub

Full document details: BS EN 60958-3:2003

Byte 4: Word length

Bit 32	“0”	Maximum audio sample word length is 20 bits.
	“1”	Maximum audio sample word length is 24 bits.

Bits 33-35 Sample word length

bit	33 34 35	Audio sample word length if maximum length is 24 bits as indicated by bit 32.	Audio sample word length if maximum length is 20 bits as indicated by bit 32.
state	“0 0 0”	Word length not indicated (default)	Word length not indicated (default)
	“1 0 0”	20 bits	16 bits
	“0 1 0”	22 bits	18 bits
	“0 0 1”	23 bits	19 bits
	“1 0 1”	24 bits	20 bits
	“0 1 1”	21 bits	17 bits

All other combinations are reserved and shall not be used until further defined.

NOTE The first edition of IEC 60958 had bits 32 to 35 reserved and set to zero. Therefore, the all zero state for these bits on a received signal may be an indicator that the word length indication has not been implemented.

Unless otherwise specified in the annexes, the following specification is applicable:

- Audio sample word has a length of 20 bits/sample. The auxiliary sample bits are an optional expansion of the audio sample, if not used = “0”.
- User data is not used, all bits = “0”.
- Channel status is identical for all channels, with the exception of the channel number, if not equal to zero.

4.3 Copyright management guidelines for consumer application of the digital audio interface

4.3.1 General

Category codes are defined for all consumer products that are capable of supplying a digital signal to consumer digital audio recorders, except for products that are fully transparent from input to output.

Category codes for products have been grouped by general function of the product. This makes it possible to take into account future digital recording products not yet defined in detail. Such a product then deals with the group code under a general rule. These rules define whether a digital recorder is enabled to record a copyright protected digital signal.

Unless otherwise specified, any consumer equipment capable of transferring digital audio information from an input terminal to an output terminal, if not fully transparent and regardless of the delay or kind of transformation of the audio content of the signal, shall copy channel status bits 0, 1, 3, 4, 5, 6 and 7 from the source. Bit 2 shall be copied from the source, unless otherwise specified in the annexes.

Bit 15 is referred to as the “L-bit”. It shall indicate the “generation status” of the digital audio signal.

Documents
Document Sharing Hub
Full document details: BS EN 60958-3:2003

"Generation status" means:

- whether the signal emanates from a source that has been produced or published or authorized by the rights owner of the material, such as commercially released pre-recorded compact discs or DAT tapes or a digital broadcast (referred to herein as "original") and for which copyright has been asserted;
- or whether the signal emanates from a recording made from such "original" material (referred to herein as "a home-copy of generation 1 or higher").

Generally the L-bit is specified as:

Bit 15	"0"	No indication.
	"1"	Commercially released pre-recorded software.

For historical reasons, the reverse situation is valid for the signals originating from:

laser optical products (category code "100 XXXXL");

broadcast reception (category codes "001 XXXXL" and "011 1XXXL").

For these category codes the L-bit shall indicate:

Bit 15	"0"	Commercially released pre-recorded software.
	"1"	No indication.

The generation status may be unknown for certain applications. The above interpretation is therefore not valid in combination with some category codes such as:

- general (category code "000 00000");
- analogue/digital converters for analogue signals without copyright information (category code "011 00XXL").

4.3.2 Category code groups

4.3.2.1 The category code groups are defined in table 3.

Table 3 – Category code groups

Bit 8.... 15	Category
"000 00000"	General. Used temporarily
"100 XXXXL"	Laser optical products
"010 XXXXL"	Digital/digital converters and signal processing products
"110 XXXXL"	Magnetic tape or disc based products
"001 XXXXL" and "011 1XXXL"	Broadcast reception of digitally encoded audio signals with or without video signals
"101 XXXXL"	Musical instruments, microphones and other sources without copyright information
"011 00XXL"	Analogue/digital converters for analogue signals without copyright information
"011 01XXL"	Analogue/digital converters for analogue signals which include copyright information in the form of "Cp-bit and L-bit status"
"000 1XXXL"	Solid state memory based products
"000 0001L"	Experimental products not for commercial sale
"111 XXXXL"	Not defined. Reserved
"000 0XXXL"	Not defined. Reserved, except "000 00000" and "000 0001L"

Documents
Document Sharing Hub
Full document details: BS EN 60958-3:2003

4.3.2.2 Within a group a further indication of the kind of source is given.

4.3.2.2.1 For the general category code (“000 00000”) the following applies:

– used temporarily;
– applied specifically for digital audio broadcast reception with or without a video signal, for example digital satellite reception in Japan in the case where no copyright information is transmitted. (See also annex H.)

4.3.2.2.2 For the group of laser optical products (category code = “100 XXXXL”) the category codes are defined in table 4.

Table 4 – Category code groups for laser optical products

Bit 8.... 15	Category
“100 00000”	Compact disc digital audio signal compatible with IEC 60908 (see annex A)
“100 1000L”	Laser optical digital audio systems for which no other category code is defined (see annex D)
“100 1001L”	Mini disc system (see annex N)
“100 1100L”	Digital versatile disc (DVD)
“100 others”	Reserved

4.3.2.2.3 For the group of digital/digital converters and signal processing products (category code = “010 XXXXL”), the category codes are defined in table 5.

Table 5 – Category code groups for digital/digital converter and signal processing products

Bit 8... 15	Category
“010 0000L”	PCM encoder/decoder (see annex B)
“010 0100L”	Digital signal mixer (see annex E)
“010 1100L”	Sampling rate converter (see annex F)
“010 0010L”	Digital sound sampler (see annex G)
“010 1010L”	Digital sound processor (see annex O)
“010 others”	Reserved

4.3.2.2.4 For the group of magnetic tape or magnetic disc based products (category code = “110 XXXXL”), the category codes are defined in table 6.

Table 6 – Category code groups for magnetic tape or magnetic disc based products

Bit 8... 15	Category
“110 0000L”	DAT (see annex C)
“110 1000L”	Video tape recorder with digital sound
“110 0001L”	Digital compact cassette (see annex M)
“110 others”	Reserved

Documents
Document Sharing Hub
Full document details: BS EN 60958-3:2003