

Multimedia systems and equipment — Colour measurement and management —

Part 8: Multimedia colour scanners

The European Standard EN 61966-8:2001 has the status of a British Standard

ICS 33.160.60; 35.180

National foreword

This British Standard is the official English language version of EN 61966-8:2001. It is identical with IEC 61966-8:2001.

The UK participation in its preparation was entrusted to Technical Committee EPL/100, Audio, video and multimedia systems and equipment, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

From 1 January 1997, all IEC publications have the number 60000 added to the old number. For instance, IEC 27-1 has been renumbered as IEC 60027-1. For a period of time during the change over from one numbering system to the other, publications may contain identifiers from both systems.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

This British Standard, having been prepared under the direction of the Electrotechnical Sector Policy and Strategy Committee, was published under the authority of the Standards Policy and Strategy Committee on 03 December 2001

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 38, an inside back cover and a back cover.

The BSI copyright date displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

© BSI 03 December 2001

ISBN 0 580 38732 1

EUROPEAN STANDARD

EN 61966-8

NORME EUROPÉENNE

EUROPÄISCHE NORM

May 2001

ICS 33.160.60; 35.180

English version

**Multimedia systems and equipment -
Colour measurement and management
Part 8: Multimedia colour scanners
(IEC 61966-8:2001)**

Systèmes et appareils multimédia -
Mesure et gestion de la couleur
Partie 8: Numériseurs couleur
(CEI 61966-8:2001)

Multimediasysteme und -geräte -
Farbmessung und Farbmanagement
Teil 8: Multimedia-Farbscanner
(IEC 61966-8:2001)

This European Standard was approved by CENELEC on 2001-04-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

© 2001 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Foreword

The text of document 100/192/FDIS, future edition 1 of IEC 61966-8, prepared by IEC TC 100, Audio, video and multimedia systems and equipment, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 61966-8 on 2001-04-01.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (don) 2002-01-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2004-04-01

Annexes designated "normative" are part of the body of the standard.

Annexes designated "informative" are given for information only.

In this standard, annexes A, B and ZA are normative and annex C is informative.

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 61966-8:2001 was approved by CENELEC as a European Standard without any modification.

CONTENTS

	Page
INTRODUCTION	6
1 Scope and object	9
2 Normative references.....	9
3 Terms and definitions	10
4 Letters and symbols.....	11
5 Conditions	11
5.1 General conditions.....	11
5.2 Output digital image data	12
6 Measurement equipment and target of scan.....	12
6.1 Spectrophotometer	12
6.2 Spectroradiometer	12
6.3 Specification of the target	13
7 Spectral power distribution of the built-in light source	15
7.1 Characteristics to be measured	15
7.2 Measurement conditions	15
7.3 Presentation of results	15
8 Tone characteristics.....	17
8.1 Characteristics to be measured	17
8.2 Measurement conditions	17
8.3 Method of measurement	17
8.4 Calculation of results	17
8.5 Presentation of results	18
9 Inverse tone characteristics	19
9.1 Characteristics to be calculated	19
9.2 Method of calculation.....	19
9.3 Presentation of results	20
10 Spectral responsivity characteristics	20
10.1 Characteristics to be measured	20
10.2 Measurement conditions	21
10.3 Method of measurement	21
10.4 Presentation of results	21
11 Spatial non-uniformity	25
11.1 Characteristics to be measured	25
11.2 Measurement conditions	25
11.3 Method of measurement	25
11.4 Presentation of results	27
12 Mid-term instability.....	28
12.1 Characteristics to be measured	28
12.2 Measurement conditions	28
12.3 Method of measurement	29
12.4 Presentation of results	29

13	Large area spatial crosstalk	29
13.1	Characteristics to be measured	29
13.2	Measurement conditions	29
13.3	Method of measurement	30
13.4	Presentation of results	31
Annex A	(normative) Estimation of multiband of wavelength sensitivities	32
A.1	Quantities to be estimated	32
A.2	Input to the algorithm	32
A.3	Output to the algorithm	33
A.4	Internal variables of the algorithm	33
A.5	Estimation algorithm	33
Annex B	(normative) Scanner model output data from estimated multiband sensitivities	35
Annex C	(informative) Examples for the application of the spectral characteristics	36
C.1	Calculation of the ICC profiles	36
C.2	Calculation of an optimized conversion for sRGB colour space	36
Annex ZA	(normative) Normative references to international publications with their corresponding European publications	38
	Bibliography	37
	Figure 1 – Specification of the target for characterization of multimedia colour scanners	13
	Figure 2 – Example of graphical representation of multiband spectral reflection of a colour patch	14
	Figure 3 – Scanning area and the points of measurement	15
	Figure 4 – Example of the normalized spectral power distribution of the built-in light source	16
	Figure 5 – Example of reporting form of tone characteristics, light flux Φ vs. output data	19
	Figure 6 – An example of multiband spectral responsivity, s_R , s_G and s_B	24
	Figure 7 – Example of reporting form of the overall multiband spectral responsivity, $S_n s_{R_n}$, $S_n s_{G_n}$ and $S_n s_{B_n}$	25
	Figure 8 – Measurement points for spatial non-uniformity	26
	Figure 9 – Example of report of mid-term instability	29
	Figure 10 – Target for the measurement of spatial crosstalk	30
	Table 1 – Example of reporting form of a spectral table	14
	Table 2 – Example of multiband spectral characteristics of the light source	16
	Table 3 – Example of reporting form of the polynomial coefficients of the red, green and blue channel	18
	Table 4 – Example of reporting form of the polynomial coefficients of the red, green and blue channels	20
	Table 5 – Example of reporting form of the multiband responsivity characteristics	22
	Table 6 – Reporting form for the measurement of spatial non-uniformity	28
	Table 7 – Reporting form for the measurement of spatial crosstalk	31

Table 8 – Reporting form of average data and maximum crosstalk given by relative maximum differences and relative standard deviations of data in red, green and blue channels (8 bits per channel)	31
--	----

INTRODUCTION

This introduction is intended to distinguish the field of application of ISO 12641 and IEC 61966-8.

In order to standardize the calibration procedure for input scanners used in the printing and prepress industry, ISO 12641 was published in 1997. This part of IEC 61966 targets colour scanners for multimedia applications by providing characterization data necessary for colour management in open multimedia systems. It characterizes any multimedia colour scanners for consumer use, typically being connected to personal computers so as to capture colour images and display the colour information, either locally or distributed worldwide.

In such applications, colour management is important. Any red – green – blue data should have their colorimetric attributes clearly specified. The characterization data reported from this part of IEC 61966 will be used for the calculation of equipment specific colorimetric characterization so that colour management in open systems can be conducted.

The capture of colour information in a prepress input scanner usually assumes that the source is a positive film (transparent) original. The second most common type of original is positive photographic printing paper (reflective). Recently, prepress input scanners can support various types of reflective originals in addition to printing paper and can also capture an image directly from a negative film, although this is not yet very common. Due to these circumstances, ISO 12641 was established for prepress digital data exchange corresponding to transparent and reflective originals. However, a standard colour target for transparent film negative originals has not yet been established.

Spectral sensitivity characteristics of prepress scanners are not derived from the calculation based on a special colour system or the spectral distribution of printing ink; but are base signals relatively close to the three primary colours (red, green, blue) acquired for calibration purposes. The characteristics of the prepress input scanners are guaranteed by the experience of the operator or the sophistication of the colour processing application so that subtle variations among the colours appear in the printed result. In fact, printing and prepress scanners have many settings that are made available to professional users, and the operator can control the input scanner characteristics in a non-linear fashion to suit their objectives. In older input scanners, these controls were part of the stand-alone scanner system itself. For the scanners of the printing industry, these controls are typically part of the colour processing application software which processes the signals after capture and transfers them to the general purpose computer (workstation or server). In other words, a highly experienced and skilled operator can adjust the settings to freely change scanner characteristics such as tone and colour separation as he desires. Furthermore, scanner characteristics can be changed to correct and compensate for the characteristics of the original image target, such as colour fogging, as well as absorb them, and the operator can even change scanner colour separation conditions (typically cyan, yellow, magenta and black) in anticipation of the later printing process so as to obtain the most feasible printed result. As such, on the site of the prepress scanner, good colour separation (reproduction) is and has been dependent on the skill of the operator.

All prepress input scanners show variation in colour sensitivity characteristics depending on types, manufacturers, manufactured time and condition. Prepress input scanners tend to show less variation than other general-purpose multimedia colour scanners because of their usage in critical colour capturing in a closed system in comparison with the worldwide open system such as the Internet. There has never been an attempt to standardize the colour characteristics of prepress input scanners put on the market by different manufacturers.

However, it is demanded that the printing process should produce essentially the same results from the same original regardless of the input scanner used. This demand has been accomplished by the skill of the operator. For this reason, the process of scanning, including colour processing for the raw data, should involve the human operator, and the total system be considered as one system. In this human-machine interaction system, the characteristics can be understood as unified or standardized.

Under these circumstances, and in consideration of the actual work process, ISO/TC 130 (Graphic technology) has established a method using a colour target as stipulated in ISO 12641 for prepress input scanner calibration that includes functions capable of handling colour changes accompanying local distortions in colour regions. These targets for both positive reflective material (photographic printing paper) and positive transmission material (photographic film) are implemented by the photographic manufacturers on their specific materials of their particular products.

Multimedia colour scanners for general use which are much less expensive in comparison with prepress input scanners, are available for small office/home office personal computers. Targets for scanning are not specified as in prepress input scanners. Images of natural objects such as the petals of violets, green plants or human skin will be most important. As many of the users of multimedia colour scanners are not colour experts, it is preferable to have an automatic system requiring minimal adjustment. The manufacturers of this type of colour scanner do not provide colorimetric specifications of the red – green – blue data obtained from their scanner on one hand. On the other hand, the data obtained from the multimedia colour scanner are easily compressible and compatible to the World Wide Web and anonymous users will use the colour information in colour reproduction without having available the specific features of the original generator.

Prepress scanners have been used for many years in the printing and prepress industry and an environment has already been created in which only prepress scanners meeting certain critical criteria are selected. This being the case, there is no need for a new evaluation of prepress input scanner performance. In such an environment, however, the maintenance of input scanner quality is important and it is necessary and sufficient to calibrate a scanner using the appropriate target. The internationally standardized target in ISO 12641 exists for this purpose.

However, open multimedia systems and composing equipment creates a new environment different from the conventional printing industry, and the colour scanners used for multimedia systems have not undergone a similar evaluation process in related industries. In the multimedia environment, it is assumed that multimedia colour scanners will be used for a variety of purposes. This means that the initially assumed environment will vary and the functions required for individual multimedia colour scanners will also vary. In other words, the multimedia colour scanners supplied to the market and bought by general users might be designed for different purposes and will not all assure the same quality and characteristics. This will not be the case if multimedia colour scanner specifications are unified in the future; however, there is currently no movement in this direction.

Therefore, it would be a great advantage to the general user, if he could evaluate the characteristics of the multimedia colour scanner he is about to buy and judge whether it suits his purpose. In other words, knowing the colour reproduction characteristics of each scanner before making a decision, would allow the user to select a multimedia colour scanner having characteristics suited to his purpose.

While there is hope that scanners used in a multimedia environment will undergo critical evaluation in the market over time, the ability to quantitatively evaluate the colour reproduction of such multimedia colour scanners would be of direct benefit to the critical issue of colour management that we now face.

The purpose of IEC 61966-8 is to provide a method for evaluating the colour reproduction of multimedia colour scanners used in a multimedia environment and allows the specification of their colour reproduction characteristics from spectral transmission functions, which can be used for colour management. In an environment such as multimedia that has not yet matured and is constantly developing, the most critical consideration is determining whether or not a multimedia colour scanner is suited to the intended purpose. For this reason, IEC 61966-8 must be viewed separately from strict standards (such as ISO 12641) applicable to the equipment once characteristics have reached a certain level. As such, IEC 61966-8 is presented as a critical, though interim tool, during the undetermined period of evolution of these types of scanners.

Colour control within the equipment is out of the scope of this part. This is because the output data of a multimedia colour scanner depend on the spectral characteristics of the colour pigments or colour inks of the original and a large variety of originals with different pigments or inks has to be considered in office and multimedia applications, for example, photographic colour pigments, offset printing colours, ink jet colours, painting art colours, etc. The output data of the multimedia colour scanner are the result of the spectral reflection of a colour of a document under the in-built light source and the respective selection by the spectral sensitivity curves of the three sensor channels of the multimedia colour scanner. Since the spectral sensitivity curves of multimedia colour scanners do not fit a linear combination of the colour matching functions in ISO/CIE 10527, metameric colours scanned from different colour originals will result in different output data.

Due to this fact, colour control and management requires the restriction to certain classes of colour inks of the originals to be scanned. The multimedia colour scanner characterization of this standard therefore focuses on the characterization of spectral transfer functions of the three channels as multiband sensitivities and achromatic tone characteristics. This enables the user of the standard to optimize colour management for his own class of originals. An example for the use of the spectral characterization defined in this standard to specify sRGB values according to IEC 61966-2-1 is given in annex C.

MULTIMEDIA SYSTEMS AND EQUIPMENT – COLOUR MEASUREMENT AND MANAGEMENT –

Part 8: Multimedia colour scanners

1 Scope and object

This part 8 of IEC 61966 is applicable to the characterization and assessment of multimedia colour scanners used in computer systems, multimedia and similar applications.

The methods of measurement standardized in this part are designed to make possible the characterization and objective performance assessment of multimedia colour scanners which can capture colour images and output colour information such as red, green and blue data from reflective originals. The measured results are intended to be used for the purpose of colour management in multimedia systems. Measurement conditions, possible methods of measurement and characterization are defined to make colour management possible.

Colour control within the equipment is out of the scope of this part. For calibration of prepress input scanners, ISO 12641 will be applied.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 61966. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of IEC 61966 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60050(845)/CIE 17.4:1987, *International Electrotechnical Vocabulary (IEV) – Chapter 845: Lighting – International Lighting Vocabulary* (IEC/CIE joint publication)

IEC 61966-2-1:1999, *Multimedia systems and equipment – Colour measurement and management – Part 2-1: Colour management – Default RGB colour space – sRGB*

CIE 15.2:1986, *Colorimetry*

ISO 5-4:1995, *Photography – Density measurements – Part 4: Geometric conditions for reflection density*

ISO 9241-8:1997, *Ergonomic requirements for office work with visual display terminals (VDTs) – Part 8: Requirements for displayed colours*

ISO 12641:1997, *Graphic technology – Prepress digital data exchange – Colour targets for input scanners calibration*

ISO 13655:1996, *Graphic technology – Spectral measurement and colorimetric computation for graphic arts images*

ISO/CIE 10527:1991, *CIE standard colorimetric observers*

3 Terms and definitions

For the purpose of this part of IEC 61966, the definitions given in IEC 60050(845)/CIE 17.4 and the following apply.

3.1

illuminant E

illuminant of constant spectral power distribution $S_n = 1$ where S_n represents the relative radiant power in the n -th interval per 10 nm bandwidth

3.2

input scanner

equipment capable of converting the light reflected by a photographic paper into electronic signals, where the electronic signals are arranged to have an organized relationship to the spatial areas of the paper evaluated

3.3

multimedia colour scanner

electrotechnical equipment with a light source illuminating a scanning area where an original is placed, which provides means to sense colour signals from the light reflected from specified picture elements within the scanning area in digital form as output data

3.4

driver software

computational function to control the multimedia colour scanner from internal parameters and parameters specified by the user such as scaling of scan, spatial resolution, etc. comprising a colour control function to convert the colour signals of the multimedia colour scanner into approximate components of a defined colour space such as the sRGB colour space in IEC 61966-2-1 or an equipment independent colour space such as the CIE 1931 XYZ colour space or the CIELAB colour space in CIE 15.2

3.5

light flux

incident radiant power valued by physical spectral responsivities

3.6

scanning area

dimension of the area to be scanned, given in square centimetres or the number of resolved picture elements along the vertical and the horizontal directions from which digital image data are made readily available at the output

3.7

spatial resolution

number of picture elements used to describe a region of an image of fixed spatial size

3.8

scaling of scan

magnification or reduction of pieces of the scanning area and corresponding image data

3.9

target

image composed of grey patches or colour patches for use in the measurement for characterization of multimedia colour scanners

3.10

original

reflective material, for example, a sheet of paper, a photograph, a hardcopy, etc. to be scanned to obtain corresponding red, green and blue data

4 Letters and symbols

The notations consistently adopted in this part of IEC 61966 are summarized below.

- Φ_R : normalized light flux reflected from the target and captured by the red channel. See also 3.5 for the definition of light flux
- Φ_G : normalized light flux reflected from the target and captured by the green channel. See also 3.5 for the definition of light flux
- Φ_B : normalized light flux reflected from the target and captured by the blue channel. See also 3.5 for the definition of light flux
- D_R : integer data obtained from the red channel of the multimedia colour scanner averaged for more than 10×10 picture elements corresponding to the centre of a patch of the target
- D_G : integer data obtained from the green channel of the multimedia colour scanner averaged for more than 10×10 picture elements corresponding to the centre of a patch of the target
- D_B : integer data obtained from the blue channel of the multimedia colour scanner averaged for more than 10×10 picture elements corresponding to the centre of a patch of the target
- d_R : normalized D_R by $2^N - 1$
- d_G : normalized D_G by $2^N - 1$
- d_B : normalized D_B by $2^N - 1$
- N : the number of bits per channel
- Y : luminance factor. One of the tristimulus values in the CIE 1931 XYZ colour space with the reference illuminant E
- λ_n : the n -th wavelength at the centre of 10 nm wavelength band
- S_n : spectral power of a built-in light source at the centre wavelength λ_n
- p_{R_n} : physical spectral sensitivities at the centre wavelength λ_n of the red channel
- p_{G_n} : physical spectral sensitivities at the centre wavelength λ_n of the green channel
- p_{B_n} : physical spectral sensitivities at the centre wavelength λ_n of the blue channel
- s_{R_n} : effective spectral sensitivities at the centre wavelength λ_n as response of light flux being captured by the red channel; it is a linear combination of p_{R_n} , p_{G_n} and p_{B_n}
- s_{G_n} : effective spectral sensitivities at the centre wavelength λ_n as response of light flux being captured by the green channel; it is a linear combination of p_{R_n} , p_{G_n} and p_{B_n}
- s_{B_n} : effective spectral sensitivities at the centre wavelength λ_n as response of light flux being captured by the blue channel; it is a linear combination of p_{R_n} , p_{G_n} and p_{B_n}
- r_{k_n} : spectral reflectance of the k -th colour patch at the centre wavelength λ_n
- K : the number of usable colour patches

5 Conditions

5.1 General conditions

Unless otherwise specified, automatic functions shall be disabled to prevent the multimedia colour scanner from responding automatically to the target and from establishing scanning conditions. This condition shall not be changed during the period of the test.