

Digital radio mondiale (DRM) —

Part 2: Digital radio in the bands below 30 MHz — Methods of measurement for DRM transmitters

The European Standard EN 62272-2:2007 has the status of a
British Standard

ICS 33.060.20

National foreword

This British Standard was published by BSI. It is the UK implementation of EN 62272-2:2007. It is identical with IEC 62272-2:2007.

The UK participation in its preparation was entrusted to Technical Committee EPL/103, Transmitting equipment for radio communication.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2007

© BSI 2007

ISBN 978 0 580 50825 7

Amendments issued since publication

Amd. No.	Date	Comments

**Digital radio mondiale (DRM) -
Part 2: Digital radio in the bands below 30 MHz -
Methods of measurement for DRM transmitters
(IEC 62272-2:2007)**

Digital radio mondiale (DRM) -
Partie 2: Radiodiffusion numérique
dans les bandes de fréquences
en dessous de 30 MHz -
Méthodes de mesure des émetteurs DRM
(CEI 62272-2:2007)

Digital radio mondiale (DRM) -
Teil 2: Digitaler Rundfunk
in den Bändern unterhalb 30 MHz -
Messverfahren für DRM-Sender
(IEC 62272-2:2007)

This European Standard was approved by CENELEC on 2007-04-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 103/64/FDIS, future edition 1 of IEC 62272-2, prepared by IEC TC 103, Transmitting equipment for radio communication, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62272-2 on 2007-04-01.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2008-01-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2010-04-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 62272-2:2007 was approved by CENELEC as a European Standard without any modification.

CONTENTS

1	Scope	4
2	Normative references	4
3	Terms, definitions and abbreviations	5
3.1	Terms and definitions	5
3.2	Abbreviations	5
4	General conditions of operation	6
5	General conditions of measurement	6
5.1	Input and output measurement arrangements	6
5.2	Temperature and humidity	7
5.3	Conditions for primary power supply	7
5.4	Output power	7
6	General characteristics	7
6.1	Output power	7
6.2	Frequency	8
7	Transmission performance characteristics	10
7.1	Spurious emissions	10
7.2	Out-of-band emissions (spectrum mask)	11
7.3	Modulation error ratio (MER)	12
7.4	Bit error ratio (BER)	12
8	Protection against atmospheric discharge	13
9	Acoustic noise	14
10	Safety	14
	Annex A (informative) Measuring arrangements	15
	Annex B (informative) Out-of-band emission limits for DRM transmitters	17
	Annex C (informative) Additional measuring details	19
	Annex ZA (normative) Normative references to international publications with their corresponding European publications	20
	Figure 1 – Spectrum occupancy for 9 kHz channels	9
	Figure 2 – Spectrum occupancy for 10 kHz channels	9
	Figure 3 – PRBS generator	13
	Figure A.1 – Arrangement A	15
	Figure A.2 – Arrangement B	15
	Figure A.3 – Arrangement C	16
	Figure A.4 – Arrangement D	16
	Figure B.1 – Out-of-band emission limits (upper half only of a symmetrical spectrum mask shown)	17
	Table B.1 – Out-of-band emission limits	17

DIGITAL RADIO MONDIALE (DRM) –**Part 2: Digital radio in the bands below 30 MHz –
Methods of measurement for DRM transmitters****1 Scope**

This part of IEC 62272 describes the methods of measurement to assess the performance characteristics of digital modulated radio transmitters in the bands below 30 MHz for sound and/or data broadcasting in the LF, MF and HF bands, and to facilitate the comparison of measurements which are carried out by different personnel.

It contains details of specially selected methods for determining the most important performance parameters of digital radio transmitters. The measurement methods described apply to a limited number of performance parameters, i.e. those which can give rise to ambiguous interpretation due to the use of different methods and conditions. They are neither restrictive nor mandatory: measurements can be chosen for each particular case.

The measurement methods described in this standard are intended to be used for type approval tests, quality control tests or acceptance test measurements in factories and on site.

Fewer or additional measurements may be carried out by agreement between customer and supplier. Any additional test should comply with standards which have been established by other study groups, subcommittees of the IEC or other international or suitably accredited organizations.

This standard does not specify limiting values for acceptable performance as these are usually given in the equipment specification or in requirements laid down by the responsible regulation bodies. However, some values are quoted, where appropriate, for guidance in the presentation of the results.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60244-1, *Methods of measurement for radio transmitters – Part 1: General characteristics for broadcast transmitters*

IEC 60244-15, *Methods of measurement for radio transmitters – Part 15: Amplitude-modulated transmitters for sound broadcasting*

IEC 60215, *Safety requirements for radio transmitting equipment*

ITU *Radio Regulations*

ITU-R Recommendation V.663, *Use of certain terms linked with physical quantities*

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

DRM standard

digital modulation standard for frequencies in the bands below 30 MHz for the purposes of audio and data broadcasting

3.1.2

DRM transmitters

sound broadcasting transmitters operating in the bands below 30 MHz and incorporating digital modulation in accordance with IEC 62272-1¹

3.1.3

power definitions

nominal output power is the continuous DRM mean power for which the transmitter is designed

maximum output power is the maximum possible continuous DRM mean power which the transmitter can deliver. The maximum output power might be concordant with the nominal output power

minimum output power is the minimum possible continuous DRM mean power for which the transmitter is designed

3.1.4

necessary bandwidth

for a given class of emission, the width of a frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions (ITU definition)

For the practical purposes of this standard, the necessary bandwidth for a DRM signal can be considered to be the same as the allocated channel bandwidth, for example, 10 kHz for a standard HF channel.

3.2 Abbreviations

BER	Bit Error Ratio
BS	Broadcasting Service
DRM	Digital Radio Mondiale
FAC	Fast Access Channel
HF	High Frequency
IEC	International Electrotechnical Commission
ISO	International Organization for Standardization
ITU	International Telecommunications Union
ITU-R	International Telecommunications Union – Radiocommunications Sector
LF	Low Frequency
MER	Modulation Error Ratio
MF	Medium Frequency
MLC	Multi-Level Coding
MSC	Main Service Channel

¹ IEC 62272-1, *Digital radio mondiale – Part 1: System specification*

OFDM	Orthogonal Frequency Division Multiplex
PRBS	Pseudo-Random Bit Sequence
QAM	Quadrature Amplitude Modulation
RF	Radiofrequency
SDC	Service Description Channel
SM	Spectrum Management
Tx	Transmitter

4 General conditions of operation

Any device for the suppression of unwanted signals, irrespective of whether or not the device is located inside the transmitter, shall be considered as part of the transmitter for the purposes of this standard.

Feeders and antennas to which the transmitter might be connected are not considered part of the transmitter and therefore excluded.

Unless otherwise specified, the measurements shall be made under normal operating and environmental conditions and at the nominal output power. If required, they shall be repeated under extreme operating and environmental conditions and at any lower output power in accordance with the equipment specification.

The transmitting mode and the measured output power of the transmitter under test shall be stated.

The mains supply and the environmental conditions shall be stated with the measurement results.

The transmitter shall be connected to a test load having a VSWR relative to the nominal load impedance of the transmitter not greater than

- 1,2:1 at frequencies within the designated broadcast band;
- 1,5:1 at all frequencies outside the designated broadcast band up to a frequency of 10 times the highest frequency in the designated band.

If the transmitter includes devices to control the frequency band transmitted, all the characteristics shall be measured with the devices in the circuit.

Measurement uncertainty should be calculated and techniques employed to minimize its range. This uncertainty should be applied to the limit and any measurement falling below the range is deemed acceptable.

If a digital transmitter can also operate in analogue mode, the requirements of IEC 60244-1 and IEC 60244-15 shall also apply, in addition to the requirements of this standard.

5 General conditions of measurement

5.1 Input and output measurement arrangements

For the purposes of measurement, the input and output signal arrangements are given in the form of diagrams.

Where required, the impedance of the test equipment of the transmitter under test and of all the connections between them shall be appropriately terminated, taking into account the transmitter's specification and the termination impedance of any test equipment.