



BSI Standards Publication

Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery — Safety

Part 4-2: Particular requirements for hedge trimmers

National foreword

This British Standard is the UK implementation of EN 62841-4-2:2019+A1:2022. It is derived from IEC 62841-4-2:2017, incorporating amendment 1:2022. It supersedes BS EN 62841-4-2:2019, which will be withdrawn on 1 November 2023.

The start and finish of text introduced or altered by amendment is indicated in the text by tags. Tags indicating changes to IEC text carry the number of the IEC amendment. For example, text altered by IEC amendment 1 is indicated by **A1** **A1**.

The UK participation in its preparation was entrusted to Technical Committee CPL/116, Safety of motor-operated electric tools.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication has been prepared under a mandate given to the European Standards Organizations by the European Commission and the European Free Trade Association. It is intended to support requirements of the EU legislation detailed in the European Foreword. A European Annex, usually Annex ZA or ZZ, describes how this publication relates to that EU legislation.

For the Great Britain market (England, Scotland and Wales), if UK Government has designated this publication for conformity with UKCA marking (or similar) legislation, it may contain an additional National Annex. Where such a National Annex exists, it shows the correlation between this publication and the relevant UK legislation. If there is no National Annex of this kind, the relevant Annex ZA or ZZ in the body of the European text will indicate the relationship to UK regulation applicable in Great Britain. References to EU legislation may need to be read in accordance with the UK designation and the applicable UK law. Further information on designated standards can be found at www.bsigroup.com/standardsandregulation.

For the Northern Ireland market, UK law will continue to implement relevant EU law subject to periodic confirmation. Therefore Annex ZA/ZZ in the European text, and references to EU legislation, are still valid for this market.

UK Government is responsible for legislation. For information on legislation and policies relating to that legislation, consult the relevant pages of www.gov.uk.

© The British Standards Institution 2022
Published by BSI Standards Limited 2022

ISBN 978 0 539 17353 6

ICS 25.140.20; 65.060.80

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 August 2019.

Amendments/corrigenda issued since publication

Date	Text affected
31 October 2022	Implementation of IEC amendment 1:2022 with CENELEC endorsement A1:2022

English Version

**Electric motor-operated hand-held tools, transportable tools and
lawn and garden machinery - Safety - Part 4-2: Particular
requirements for hedge trimmers
(IEC 62841-4-2:2017/AMD1:2022)**

Outils électroportatifs à moteur, outils portables et machines
pour jardins et pelouses - Sécurité - Partie 4-2: Exigences
particulières pour les taille-haies
(IEC 62841-4-2:2017 , modifiée + COR1:2018)

Elektrische motorbetriebene handgeführte Werkzeuge,
transportable Werkzeuge und Rasen- und
Gartenmaschinen - Sicherheit - Teil 4-2: Besondere
Anforderungen für Heckenscheren
(IEC 62841-4-2:2017 , modifiziert + COR1:2018)

This European Standard was approved by CENELEC on 2018-01-18. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 116/346/FDIS, future edition 1 of IEC 62841-4-2, prepared by IEC/TC 116 "Safety of motor-operated electric tools" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62841-4-2:2019.

A draft amendment, which covers common modifications to IEC 62841-4-2, was prepared by CLC/TC 116 "Safety of motor-operated electric tools" and approved by CENELEC.

The following dates are fixed:

- latest date by which this document has to be implemented (dop) 2019-12-28
at national level by publication of an identical
national standard or by endorsement
- latest date by which the national standards conflicting (dow) 2023-06-28
with this document have to be withdrawn

EN 62841-4-2:2019 supersedes EN 60745-2-15:2009 + A1:2010.

This European Standard is divided into four parts:

- Part 1: General requirements which are common to most hand-held electric motor operated tools (for the purpose of this standard referred to simply as tools) which could come within the scope of this standard;
- Part 2, 3 or 4: Requirements for particular types of tools which either supplement or modify the requirements given in Part 1 to account for the particular hazards and characteristics of these specific tools.

This Part 4-2 is to be used in conjunction with EN 62841-1:2015.

This Part 4-2 supplements or modifies the corresponding clauses in EN 62841-1:2015, so as to convert it into the European Standard: Particular requirements for hedge trimmers.

Where a particular subclause of Part 1 is not mentioned in this Part 4-1, that subclause applies as far as relevant. When this standard states "addition", "modification" or "replacement", the relevant text in Part 1 is to be adapted accordingly.

The following print types are used:

- requirements; in roman type
- *test specifications: in italic type;*
- notes: in smaller roman type.

The terms defined in Clause 3 are printed in **bold typeface**.

Subclauses, notes, tables and figures which are additional to those in Part 1 are numbered starting from 101.

Clauses, subclauses, notes, tables, figures and annexes which are additional to those in IEC 62841-4-2:2017 are prefixed "Z".

This European Standard follows the overall requirements of EN ISO 12100.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s), see informative Annex ZZ, which is an integral part of this document.

Compliance with the clauses of Part 1 together with this Part 4-2 provides one means of conforming with the essential health and safety requirements of the Directive concerned.

Endorsement notice

The text of the International Standard IEC 62841-4-2:2017 and COR1:2018 was approved by CENELEC as a European Standard with agreed common modifications.

European foreword to Amendment 1

The text of document 116/578/FDIS, future IEC 62841-4-2/AMD1, prepared by IEC/TC 116 "Safety of motor-operated electric tools" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62841-4-2:2019/A1:2022.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2023-05-30
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2026-05-30

EN 62841-4-2:2019/A1:2022 introduces various clarifications and corrections to different clauses, in particular for the moisture resistance of hedge trimmers. In addition, corrections to the noise test code are made.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a Standardization Request given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s) / Regulation(s).

For the relationship with EU Directive(s) / Regulation(s), see informative Annex ZZ, which is an integral part of EN 62841-4-2:2019/A1:2022.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice to Amendment 1

The text of the International Standard IEC 62841-4-2:2017/AMD1:2022 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC 62841-4-5 NOTE Harmonized as EN IEC 62841-4-5

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

The Annex ZA from EN 62841-1:2015 is applicable with the following changes:

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
<i>Addition:</i>				
IEC 61672-1	-	Electroacoustics – Sound level meters – Part 1: Specifications	EN 61672-1	
ISO 354	2003	Acoustics – Measurement of sound absorption in a reverberation room	EN ISO 354	2003
ISO 11684	-	Tractors, machinery for agriculture and forestry, powered lawn and garden equipment – Safety signs and hazard pictorials – General principles	-	-
ISO 22868	2011	Forestry and gardening machinery – Noise test code for portable hand-held machines with internal combustion engine – Engineering method (Grade 2 accuracy)	EN ISO 22868	2011
<i>Replacement:</i>				
ISO 3744	2010	Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Engineering methods for an essentially free field over a reflecting plane	EN ISO 3744	2010

Annex ZZ

(informative)

Relationship between this European Standard and the essential requirements of Directive 2006/42/EC [2006 OJ L157] aimed to be covered

This European Standard has been prepared under a Commission's standardisation request M/396 to provide one voluntary means of conforming to essential requirements of Directive 2006/42/EC of the European Parliament and of the Council of 17 May 2006 on machinery, and amending Directive 95/16/EC.

Once this standard is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of this standard given in Table ZZ.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

Table ZZ.1 – Correspondence between this European Standard and Annex I of Directive 2006/42/EC

Essential Requirements of Directive 2006/42/EC Clause numbers of Annex I	Clause(s) / sub-clause(s) of this EN	Remarks / Notes:
1.1.2 (Principles of safety integration)	4	
1.1.3 (Materials and products)	5, 6.1, 21.6, K/L.5, L.21	
1.1.5 (Design of machinery to facilitate its handling)	5, 19.101, 19.103.3, 19.106, 19.109, 19.110, K/L.5, K.19.101, K.19.103.3, K/L.19.109, K.21.301, L.21.301	
1.1.6 (Ergonomics)	5, 19.5, 21.18.102.2, K/L.5, L.21	
1.2.1 (Safety and reliability of control systems)	5, 18.6, 18.8, 23.1.6, 23.1.10, 23.1.11, 23.3, K/L.5, K/L.18.6, K/L.18.8, K/L.23.1.10, K.23.1.201, L.18	
1.2.2 (Control devices)	5, 8.5, 8.9, 8.10, 8.11, 21.1, 21.2., 21.4, 21.17, 21.18.101 – 21.18.102, K/L.5, K.21.17.1.2, L.21	
1.2.3 (Starting)	5, 21.17, K/L.5, K.21.17.1.2, L.21	
1.2.4.1 (Normal stop)	5, 21.17, K/L.5, K.21.17.1.2, L.21	
1.2.6 (Failure of the power supply)	5, 21.18.102.2, 23.3, K/L.5, L.21	
1.3.2 (Risk of break-up during operation)	5, 8.14.2 c), 13.1, 14.4, 17, 19.107, 19.108, 20, 21.23, 24.11, 24.12, 24.13, 27, K/L.5, K/L.13.1, K/L.17, K.19.107, K/L.20, K/L.24.301, K.27.1, L.21	

Essential Requirements of Directive 2006/42/EC Clause numbers of Annex I	Clause(s) / sub-clause(s) of this EN	Remarks / Notes:
1.3.3 (Risk due to falling or ejected objects)	5, 18.3, K/L.5, L.18	
1.3.4 (Risks due to surfaces, edges or angles)	19.2, 19.103, 21.24, K.19.103, L.21	
1.3.7 (Risks related to moving parts)	5, 19.1, 19.102, 19.103, 19.104, K/L.5	
1.3.8.1 (Moving transmission parts)	5, 19.1, K/L.5	
1.3.8.2 (Moving parts involved in the process)	5, 19.1, 19.102, 19.103.2, K/L.5	
1.4.1 (General requirements (for guards and protective devices))	5, 19.1, 19.102, 19.106, 20.1, 20.2, 20.3, 20.4, 21.22, K/L.5, K.20.1, K.20.3, L.20, L.21	
1.4.2.1 (Special requirements for fixed guards)	5, 19.1, 19.9, K/L.5	
1.4.2.3 (Special requirements for adjustable guards restricting access)	5, 19.1, K/L.5	
1.5.1 (Risks due to electricity supply)	5, 7, 9, 10, 11, 12, 14, 15, 16, 17, 18.1 - 18.7, 20.5, 21.3, 21.5 - 21.16, 21.19 - 21.22, 21.25 - 21.34, 22, 23.1.1 - 23.1.5, 23.1.7 - 23.1.9, 23.2, 23.4, 23.5, 24, 25, 26, 27, 28, K/L.5, K.7, K/L.9, K/L.10, K/L.11, K/L.12, K/L.14, K/L.16, K/L.17, K.18.1 - K.18.7, K.21.5 - K.21.16, K.21.19 - K.21.22, K.21.25 - K.21.34, K/L.22, K/L.24, K/L.25, K/L.26, K.27.1, K/L.28.1, K.28.2, L.7.1, L.18, L.18.201, L.20, L.21, Annex C	
1.5.4 (Risks due to errors of fitting)	5, 8.7, 8.8, 8.13, 8.14.2, 21.7, 21.8, 21.19, 27.1, K/L.5, K.8.7, K.8.8, K/L.19.201, K/L.21.201, K/L.21.203, K.27.1, L.21	
1.5.5 (Risks due to extreme temperatures)	5, 12.5, K/L.5, K.12.1	
1.5.6 (Risks due to fire)	5, 13, 18.1, 18.2, 18.4, 18.6, 28.1, K/L.5, K/L.12.201, K/L.13, K.18.1, K.18.6, K/L.18.201, K/L.18.202, K/L.18.203, K.20.1, K.20.3, K/L.21.201, K/L.21.203, K/L.23.201, K/L.23.202, K/L.28.1, L.18, L.18.204, L.20.201, L.20.202, L.28.201	

Essential Requirements of Directive 2006/42/EC Clause numbers of Annex I	Clause(s) / sub-clause(s) of this EN	Remarks / Notes:
1.5.7 (Risks due to explosion)	5, K/L.5, K/L.12.201, K.18.201, K/L.18.202, K/L.18.203, K/L.10.202, K.20.1, K.20.3, K/L.21.202, K/L.21.203, L.18.204, L.20.201, L.20.202	
1.5.8 (Risks due to noise)	1.2.Z1	
1.5.9 (Risks due to vibrations)	1.3.Z1	
1.5.10 (Risks due to radiation)	5, 6.1, 6.3, K/L.5	
1.5.11 (Risks due to external radiation)	5, 18.8, K/L.5, K/L.18.8	
1.5.12 (Risks due to laser radiation)	6.2	
1.6.1 (Machinery maintenance)	24.1, K/L.21.18.Z101	
1.6.3 (Isolation of energy sources)	24.1, K.21.18.Z101, L.21.18.Z101, K.24.302, L.21.302	
1.7.1 (Information and warnings on machinery)	8.1, 8.2, 8.4, 8.6, K/L.8.1, K/L.8.4	
1.7.2 (Warning of residual risks)	8.2	
1.7.3 (Marking of machinery)	8.3, 8.4, 8.12, K/L.8.3, K/L.8.4	
1.7.4 (Instructions)	8.14, K/L.8.14.1.1, K/L.8.14.1.101, K/L.8.14.2	
2.2.1 (General requirements for portable hand-held and/or hand-guided machinery)	5, 19.5, 19.101, 21.18.102, K/L.5, K.19.101, L.21	
2.2.1.1 (Instructions for portable hand-held and/or hand-guided machinery)	5, 8.14.2 Za) 3), 1.3.6.2, K/L.5	

WARNING 1: Presumption of conformity stays valid only as long as a reference to this European standard is maintained in the list published in the Official Journal of the European Union. Users of this standard should consult frequently the latest list published in the Official Journal of the European Union.

WARNING 2: Other Union legislation may be applicable to the product(s) falling within the scope of this standard.

CONTENTS

FOREWORD	5
INTRODUCTION	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	9
4 General requirements	10
5 General conditions for the tests	10
6 Radiation, toxicity and similar hazards	11
7 Classification	11
8 Marking and instructions	11
9 Protection against access to live parts	14
10 Starting	14
11 Input and current	14
12 Heating	14
13 Resistance to heat and fire	14
14 Moisture resistance	14
15 Resistance to rusting	15
16 Overload protection of transformers and associated circuits	15
17 Endurance	15
18 Abnormal operation	15
19 Mechanical hazards	16
20 Mechanical strength	30
21 Construction	33
22 Internal wiring	36
23 Components	37
24 Supply connection and external flexible cords	39
25 Terminals for external conductors	40
26 Provision for earthing	40
27 Screws and connections	40
28 Creepage distances, clearances and distances through insulation	40
Annexes	67
Annex I (informative) Measurement of noise and vibration emissions	68
Annex K (normative) Battery tools and battery packs	77
Annex L (normative) Battery tools and battery packs provided with mains connection or non-isolated sources	90
Annex AA (normative) Safety signs for safety instructions and warnings	96
Annex BB (informative) Example of a material and construction for fulfilling the requirements for an artificial surface	99
Bibliography	101
Figure 101 – Pictorial representation of some definitions	45
Figure 102 – Pictorial representation of some definitions	45

Figure 103 – Measurement of cutting length	46
Figure 104 – Handles positioning	47
Figure 105 – Measurement of handle gripping length	49
Figure 106 – Adjustable front handle limits for side to side handle rotation	49
Figure 107 – Adjustable rear handle limits for side to side handle rotation	50
Figure 108 – Measurement of reach distance	51
Figure 109 – Front hand barrier dimensions	52
Figure 110 – Front hand barrier width for category 3a with adjustable cutting device	52
Figure 111 – Examples of compliant/non-compliant handle distances and handle attachments for category 1	53
Figure 112 – Measurement of distance from the cutter blade to handles and grasping surfaces	54
Figure 113 – Measurement method for minimum length of blunt extensions along the axis of the cutting device	55
Figure 114 – Cutting device configuration examples for categories 1 and 2 (see Table 101 and Table 102)	56
Figure 115 – Cutting device configuration example for categories 3a and 3b (see Table 101 and Table 102)	56
Figure 116 – Cutting device configuration example for category 4 (see Table 101 and Table 102)	57
Figure 117 – Adjustable cutting device side to side limits	58
Figure 118 – Lower barrier	58
Figure 119 – Measurement of the force necessary to maintain an extended-reach hedge trimmer in a horizontal orientation	59
Figure 120 – Hedge trimmer positions for drop test of 20.3.1	61
Figure 121 – Additional drop test of 20.3.1 for extended-reach hedge trimmers	62
Figure 122 – Impact test fixture for handle insulation	63
Figure 123 – Mounting and application of force for the test of 20.101.3.3	64
Figure 124 – Example of an operator presence sensor	64
Figure 125 – Test assembly for accessibility of attachment plug blades	65
Figure 126 – Application of steel rod when rotated around the rear handle	65
Figure 127 – Application of steel rod when applied in the direction perpendicular to the rear handle axis	66
Figure I.101 – Microphone positions on the hemisphere (see Table I.101)	68
Figure I.102 – Positions of transducers for hedge trimmers, except for extended-reach hedge trimmers	74
Figure I.103 – Positions of transducers for extended-reach hedge trimmers	75
Figure AA.1 – Safety sign illustrating – "DANGER – Keep hands away from blade"	96
Figure AA.2 – Alternative safety sign illustrating – "DANGER – Keep hands away from blade"	96
Figure AA.3 – Safety sign illustrating – "Do not expose to rain"	96
Figure AA.4 – Safety sign illustrating – "Remove plug from the mains immediately if the cable is damaged or cut"	97
Figure AA.5 – Safety signs illustrating – "Wear eye protection"	97
Figure AA.6 – Optional safety sign illustrating – "Wear eye and head protection"	98
Figure AA.7 – Safety sign illustrating – "Wear ear protection"	98

Figure BB.1 – Sketch of the measurement surface covered with an artificial surface..... 100

Table 4 – Required performance levels	16
Table 101 – Hedge trimmer categories (excluding extended-reach hedge trimmers)	23
Table 102 – Extended-reach hedge trimmer categories.....	24
Table 7 – Switch trigger force	34
Table 103 – Test cycle for two-handed blade controls with non-sequential operation	38
Table 104 – Test cycle for two-handed blade controls with sequential operation	38
Table 12 – Minimum creepage distances and clearances	42
Table I.101 – Coordinates of microphone positions	70
Table I.102 – Absorption coefficients	70
Table K.301 – Pull and torque value	86
Table K.1 – Minimum creepage distances and clearances between parts of different potential.....	88
Table K.2 – Minimum total sum of creepage distances and clearances to accessible surfaces.....	89

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRIC MOTOR-OPERATED HAND-HELD TOOLS, TRANSPORTABLE TOOLS AND LAWN AND GARDEN MACHINERY – SAFETY –

Part 4-2: Particular requirements for hedge trimmers

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 62841-4-2 edition 1.1 contains the first edition (2017-12) [documents 116/346/FDIS and 116/352/RVD], its corrigendum (2018-06) and its amendment 1 (2022-05) [documents 116/578/FDIS and 116/586/RVD].

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

International Standard IEC 62841-4-2 has been prepared by IEC technical committee 116: Safety of motor-operated electric tools.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

This Part 4-2 is to be used in conjunction with the first edition of IEC 62841-1 (2014).

This Part 4-2 supplements or modifies the corresponding clauses in IEC 62841-1, so as to convert it into the IEC Standard: Particular requirements for hedge trimmers.

Where a particular subclause of Part 1 is not mentioned in this Part 4-2, that subclause applies as far as relevant. Where this standard states “addition”, “modification” or “replacement”, the relevant text in Part 1 is to be adapted accordingly.

The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type;*
- notes: in small roman type.

The terms defined in Clause 3 are printed in **bold typeface**.

Subclauses, notes, tables and figures which are additional to those in Part 1, except as described for Annex K and Annex L below, are numbered starting from 101.

Subclauses, notes, tables and figures in Annex K and Annex L which are additional to those in the main body of this Part 4-2 as well as Annex K and Annex L of Part 1 are numbered starting from 301.

A list of all parts of the IEC 62841 series, under the general title: *Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery – Safety*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under webstore.iec.ch in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

NOTE The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 36 months from the date of publication.

INTRODUCTION

 The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent. IEC takes no position concerning the evidence, validity, and scope of this patent right.

The holder of this patent right has assured IEC that s/he is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from the patent database available at patents.iec.ch.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those in the patent database. IEC shall not be held responsible for identifying any or all such patent rights. 

ELECTRIC MOTOR-OPERATED HAND-HELD TOOLS, TRANSPORTABLE TOOLS AND LAWN AND GARDEN MACHINERY – SAFETY –

Part 4-2: Particular requirements for hedge trimmers

1 Scope

This clause of Part 1 is applicable, except as follows:

Addition:

This standard applies to hand-held **hedge trimmers** which are designed for use by one operator for trimming hedges and bushes, including **extended-reach hedge trimmers** with a maximum length of 3,5 m.

NOTE 101 The measurement of the length for **extended-reach hedge trimmers** is specified in 21.101.

This standard is not applicable to **hedge trimmers** with a rotating blade.

This standard is not applicable to scissors type grass shears.

NOTE 102 Scissors type grass shears are covered by IEC 60335-2-94 or IEC 62841-4-5. 

2 Normative references

This clause of Part 1 is applicable, except as follows:

Addition:

 IEC 60664-3:2016, *Insulation coordination for equipment within low-voltage systems – Part 3: Use of coating, potting or moulding for protection against pollution*

IEC 60664-4:2005, *Insulation coordination for equipment within low-voltage systems – Part 4: Consideration of high-frequency voltage stress* 

IEC 61672-1, *Electroacoustics – Sound level meters – Part 1: Specifications*

ISO 354:2003, *Acoustics – Measurement of sound absorption in a reverberation room*

ISO 11684, *Tractors, machinery for agriculture and forestry, powered lawn and garden equipment – Safety signs and hazard pictorials – General principles*

ISO 22868:2011, *Forestry and gardening machinery – Noise test code for portable hand-held machines with internal combustion engine – Engineering method (Grade 2 accuracy)*

Replacement:

ISO 3744:2010, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Engineering methods for an essentially free field over a reflecting plane*

3 Terms and definitions

This clause of Part 1 is applicable, except as follows:

3.101

blade control

device activated by the operator's hand or fingers in order to start or stop the operation of the **cutting device**

3.102

blade stopping time

elapsed time from the release of the **blade control** until the moving parts of the **cutting device** stop

3.103

blade tooth

part of the **cutter blade** which is sharpened or has sharp edges to perform the shearing action (see Figures 101 and 102)

3.104

blunt extension

blunt part of the **cutting device** or a part of an unsharpened plate fitted to the **cutting device** which extends beyond the **blade teeth** (see Figures 101 and 102)

3.105

cutter blade

part of the **cutting device** having **blade teeth** which cut by shearing action either against other **blade teeth** or against a **shear plate** (see Figures 101 and 102)

3.106

cutting device

part of the assembly of **cutter blade** and **shear plate** or of two **cutter blades** together with any supporting part which performs the cutting action, which may be either single or double sided (see Figures 101, 102, 104 a) and 104 b))

3.107

cutting length

effective cutting length of the **cutting device** measured from the inside edge of the first **blade tooth** or **shear plate** tooth to the inside edge of the last **blade tooth** or **shear plate** tooth (see Figure 103)

Note 1 to entry: Where both **cutter blades** move, the **cutting length** is measured when the first and last **blade teeth** are furthest apart.

3.108

extended-reach hedge trimmer

hedge trimmer with a fixed or adjustable elongated construction, including additional separable extensions, if any, such that the **cutting device** is distanced from the handles or grasping surfaces during use

3.109

front handle

grasping surface located at or towards the **cutting device** (see Figure 104)

3.110

hedge trimmer

hand-held machine provided with a linearly reciprocating **cutting device** intended for trimming bushes and hedges

3.111 maximum speed

A1 highest steady-state cutting device speed attainable under all conditions of normal use, including no-load, when adjusted in accordance with the manufacturer's specifications and/or instructions

Note 101 to entry: The steady-state **cutting device** speed excludes transients such as overshoot that may occur before attaining a steady-state condition. **A1**

3.112 operator presence sensor

device to detect the presence of an operator's hand

3.113 rear handle

grasping surface located furthest from the **cutting device** (see Figure 104)

3.114 shaft

fixed or extendable element of an **extended-reach hedge trimmer** that distances the **cutting device** from the **rear handle**

3.115 shear plate

moving or stationary unsharpened part of the **cutting device** which assists cutting by shearing action against a **cutter blade** (see Figure 101)

4 General requirements

This clause of Part 1 is applicable.

5 General conditions for the tests

This clause of Part 1 is applicable, except as follows:

5.8 Addition:

*If different **cutting devices** can be mounted on the **hedge trimmer** in accordance with 8.14.2 a) and 8.14.2 b), the **cutting devices** are regarded as **attachments**.*

5.17 Addition:

*The mass of the machine excludes the **cutting device** cover and shoulder harness, if any, but includes:*

– *the auxiliary handle, if any;*

and

– *for **extended-reach hedge trimmers**, the auxiliary extension **shaft** attachment, if any.*

5.101 *The tests are carried out on the machine as supplied. However, a machine constructed as a single machine but supplied in a number of units is tested after assembly in accordance with 8.14.2.*

5.102 *Unless otherwise specified, for Clauses 19 and 21, machines are tested in each operating configuration as described in 8.14.2.*

A1 5.103 For machines that do not attain **maximum speed** under no load conditions, the manufacturer shall provide samples with special hardware and/or software in order to perform the required tests. **A1**

6 Radiation, toxicity and similar hazards

This clause of Part 1 is applicable.

7 Classification

This clause of Part 1 is applicable.

8 Marking and instructions

This clause of Part 1 is applicable, except as follows:

8.2 Addition:

Hedge trimmers shall be marked with safety information which shall be written in one of the official languages of the country in which the machine is to be sold or marked with the appropriate symbol.

For all **hedge trimmers**:

- A1** – "Wear ear protection", a relevant safety sign of ISO 7010 or the safety sign specified in Figure AA.7. This marking may be omitted if the measured emission sound pressure level at the operator's ear in accordance with Annex I does not exceed 85 dB(A); and
- "⚠ DANGER – Keep hands away from blade" or the safety sign specified in Figure AA.1 or the safety sign specified in Figure AA.2. **A1**

The DANGER marking or symbol shall be readily visible to the user and shall not be located on the underside of the machine.

For all **hedge trimmers** with a degree of protection of less than IPX4:

- A1** – "⚠ WARNING – Do not expose to rain" or the safety sign specified in Figure AA.3.
- "⚠ WARNING – Remove plug from the mains immediately if the cable is damaged or cut" or the safety sign specified in Figure AA.4. **A1**

For all **hedge trimmers** except for Category 1 in Table 101:

- "Wear eye protection" or a relevant safety sign of ISO 7010 or one of the safety signs shown in Figure AA.5.

Additionally, for **extended-reach hedge trimmers**:

- A1** – "⚠ DANGER – Keep sufficient distance away from electrical power lines" or symbol C.2.30 of ISO 11684. **A1**
- "Wear head protection" or a relevant safety sign of ISO 7010.

A combination of ISO safety signs, such as eye and head protection, is allowed. In addition, a combination of safety signs as specified in Figure AA.6 is allowed.

8.12 Replacement of the first paragraph:

Markings required by the standard shall be legible and durable. Signs shall be in contrast such as colour, texture, or relief, to their background such that the information or instructions provided by the signs are clearly legible when viewed with normal vision from a distance of (500 ± 50) mm. Signs need not be in accordance with the colour requirements of ISO 3864-2. If markings are embossed, stamped or moulded, contrasting colours are not required.

8.14.1 Addition:

The additional safety instructions as specified in 8.14.1.101 shall be given for all **hedge trimmers**. The additional safety instructions as specified in 8.14.1.102 shall be given for all **extended-reach hedge trimmers**. This part may be printed separately from the "General Machine Safety Warnings".

NOTE 101 "General Machine Safety Warnings" are referred to as "General Power Tool Safety Warnings" in Part 1.

8.14.1.1 Addition to item 2) c):

For machines classified at least IPX4, the warning may be replaced as specified below.

- c) **Do not operate the machine in rain or wet conditions.** *Water entering the machine may increase the risk of electric shock or malfunction that could result in personal injury.* 

8.14.1.101 Safety instructions for hedge trimmers

For Category 1 **hedge trimmers** that can be converted to a grass shear, the term "hedge trimmer" may be replaced by alternate wording (e.g. "grass shear/hedge trimmer" or "grass shear/shrub shear"). For this case, the verbatim warnings below need not be repeated for the two configurations.

Hedge trimmer safety warnings:

- a) **Do not use the hedge trimmer in bad weather conditions, especially when there is a risk of lightning.** *This decreases the risk of being struck by lightning.*
- b) **Keep all power cords and cables away from cutting area.** *Power cords or cables may be hidden in hedges or bushes and can be accidentally cut by the blade.*
- c) **Wear ear protection.** Adequate protective equipment will reduce the risk of hearing loss.
NOTE 101 This warning can be omitted if the measured emission sound pressure level at the operator's ear in accordance with Annex I does not exceed 85 dB(A).
- d) **Hold the hedge trimmer by insulated gripping surfaces only, because the blade may contact hidden wiring or its own cord.** *Blades contacting a "live" wire may make exposed metal parts of the hedge trimmer "live" and could give the operator an electric shock.*
- e) **Keep all parts of the body away from the blade. Do not remove cut material or hold material to be cut when blades are moving.** *Blades continue to move after the switch is turned off. A moment of inattention while operating the hedge trimmer may result in serious personal injury.*
- f) **When clearing jammed material or servicing the hedge trimmer, make sure all power switches are off and the power cord is disconnected.** *Unexpected actuation of the hedge trimmer while clearing jammed material or servicing may result in serious personal injury.*
- g) **Carry the hedge trimmer by the handle with the blade stopped and taking care not to operate any power switch.** *Proper carrying of the hedge trimmer will decrease the risk of inadvertent starting and resultant personal injury from the blades.*
- h) **When transporting or storing the hedge trimmer, always use the blade cover.** *Proper handling of the hedge trimmer will decrease the risk of personal injury from the blades.* 

8.14.1.102 Additional safety instructions for extended-reach hedge

trimmers Extended-reach hedge trimmer safety warnings:

- a) **Always use head protection when operating the extended-reach hedge trimmer overhead.** *Falling debris can result in serious personal injury.*

NOTE 101 Alternate wording for "extended-reach" is possible, e.g. "pole" or "long reach".

- b) **Always use two hands when operating the extended-reach hedge trimmer.** *Hold the extended-reach hedge trimmer with both hands to avoid loss of control.*
- c) **To reduce the risk of electrocution, never use the extended-reach hedge trimmer near any electrical power lines.** *Contact with or use near power lines may cause serious injury or electric shock resulting in death.* 

8.14.2 a) Addition:

- 101) If applicable, information on **cutting devices** and **attachments** permitted to be used with the **hedge trimmer**, e.g. a device attached to the **cutting device** to aid removal of hedge trimmings.

8.14.2 b) Addition:

- 101) Advice to check the hedges and bushes for foreign objects, e.g. wire fences and hidden wiring;
- 102) Recommendation for the use of a **residual current device** with a tripping current of 30 mA or less;
- 103) Identification of gripping surfaces of handle(s) and grasping surface(s) required by 19.101 and 19.102;
- 104) Instruction to hold the **hedge trimmer** properly, e.g. with both hands if two handles are provided;
- 105) Advice that the **hedge trimmer** is intended to be used by the operator at ground level and not on ladders or any other unstable support;
- 106) Advice that before operating the **hedge trimmer**, the user should make sure the locking device(s) of any moving elements (e.g. the extended **shaft** and pivoting element), if any, are in the locked position;
- 107) Instructions for location and use of **blade control(s)** for the operation of the **hedge trimmer**;
- 108) Instructions for configuring the machine, including any handle or **cutter blade** adjustment;
- 109) Instructions for the use and adjustment of any provided shoulder harness in accordance with 19.110 and instructions for release or removal;
- 110) Identification of centre position and other operating positions for handles that can rotate while in operation as allowed in 19.101.3.

8.14.2 c) Addition:

- 101) If applicable, advice to have any adjustable stopping mechanism maintained at regular intervals.

Replacement of the NOTE:

NOTE In Europe (EN IEC 62841-4-2), the following additional requirements apply:

Emissions

- 1) The noise emission, measured in accordance with Clause I.2, as follows:
- A-weighted emission sound pressure level L_{pA} and its uncertainty K_{pA} , where L_{pA} exceeds 70 dB(A). Where L_{pA} does not exceed 70 dB(A), this fact shall be indicated;
 - the A-weighted measured and guaranteed sound power levels L_{WA} ;

- 2) Recommendation for the operator to wear hearing protection.
- 3) The vibration total value and its uncertainty measured in accordance with Clause I.3. When the vibration total value does not exceed $2,5 \text{ m/s}^2$, this shall be stated. When the vibration total value exceeds $2,5 \text{ m/s}^2$, its value shall be given in the instructions.
- 4) The following information:
 - that the declared vibration total value(s) and the declared noise emission value(s) has been measured in accordance with a standard test method and may be used for comparing one machine with another;
 - that the declared vibration total value(s) and the declared noise emission value(s) may also be used in a preliminary assessment of exposure.
- 5) A warning:
 - that the vibration during actual use of the machine can differ from the declared total value depending on the ways in which the machine is used; and
 - of the need to identify safety measures to protect the operator that are based on an estimation of exposure in the actual conditions of use (taking account of all parts of the operating cycle such as the times when the machine is switched off and when it is running idle in addition to the trigger time). 

9 Protection against access to live parts

This clause of Part 1 is applicable.

10 Starting

This clause of Part 1 is applicable.

11 Input and current

This clause of Part 1 is applicable.

12 Heating

This clause of Part 1 is applicable, except as follows:

12.2.1 Replacement:

The load conditions for the heating test of 12.2 are as follows:

*The machine is operated with a torque load applied such that **rated input** or **rated current** is drawn. The machine is operated for 30 min in its most unfavourable configuration in accordance with 8.14.2 b) 108). During this period, the torque load is adjusted as necessary to maintain **rated input** or **rated current**.*

13 Resistance to heat and fire

This clause of Part 1 is applicable.

14 Moisture resistance

This clause of Part 1 is applicable, except as follows:

14.2.1 Replacement:

The machine is not connected to the supply.

The machine is placed in its normal rest position on a perforated turntable. The turntable is then turned continuously at $(1 \pm 0,1)$ r/min during the test.

Detachable parts are removed and subjected, if necessary, to the relevant treatment with the main part. Movable covers that are **non-detachable parts** and are not self-restoring are placed in the most unfavourable position.

NOTE Examples of self-restoring covers include those that are spring loaded or close by gravity. A1

14.2.2 Add the following new text:

Replacement of the last paragraph:

A1 Immediately after the appropriate treatment, the machine shall withstand the electric strength test of Annex D between **live parts** and **accessible parts**, the test voltage being 2 500 V. Then the machine is connected to the supply. It shall not start with the **power switch** in the "off" position.

*Afterwards, inspection shall show that there is no trace of water on insulation which could result in a reduction of **creepage distances** between bare conductors of different potential below the values specified in 28.1. For all instances where **creepage distances** could be reduced below the values specified in 28.1, a short circuit is introduced between adjacent conductors. The machine is then evaluated for*

- *the risk of fire in accordance with item a) of 18.6.1; and*
- *the loss of any **SCF**, unless the machine is rendered into a safe state.* A1

15 Resistance to rusting

This clause of Part 1 is applicable.

16 Overload protection of transformers and associated circuits

This clause of Part 1 is applicable.

17 Endurance

This clause of Part 1 is applicable, except as follows:

17.2 Modification:

This subclause of Part 1 is applicable as for **hand-held tools**.

Addition:

The machine is operated in its most unfavourable configuration in accordance with 8.14.2 b) 108).

A1 Care shall be taken to avoid overheating the **cutting device** by operating continuously and therefore appropriate interruptions for cooling and lubrication may be introduced. A1

18 Abnormal operation

This clause of Part 1 is applicable, except as follows:

18.5 Modification:

The requirements for tools other than **lawn and garden machinery** are applicable.

18.8 Replacement of Table 4 by the following:**Table 4 – Required performance levels**

Type and purpose of SCF	Minimum performance level (PL)
Blade control(s) – prevent unwanted switch-on	c
Blade control(s) – provide desired switch-off for any category in Table 101 or Table 102	b
Blade control(s) – blade stopping time not exceeding 1 s more than the required time for Category 3a, 3b and 4 only in Table 101 or Table 102	a
Prevent exceeding thermal limits as in Clause 18	a
Any device to prevent operation in a configuration not permitted by this standard as required in 19.101.1.1	a
Operator presence sensor as in 21.18.102	a
Lock-off function as required in 21.18.102	a
Visible or audible indicator as referenced in 21.18.102	Not an SCF
Prevent self-resetting as required in 23.3	a

19 Mechanical hazards

This clause of Part 1 is applicable, except as follows:

19.1 *Replacement of the first paragraph:*

All power-driven hazardous parts (e.g. gears), other than those moving parts (e.g. **cutting device**), barriers and covers which are separately covered by 19.102, 19.103, 19.105 and 19.106, shall be so positioned or enclosed to provide adequate protection. The requirements of this subclause apply to all operating configurations as described in 8.14.2. 

19.3 This subclause of Part 1 is not applicable.

19.4 This subclause of Part 1 is not applicable.

NOTE Requirements for handles are given in 19.101.

19.6 This subclause of Part 1 is not applicable.

19.7 This subclause of Part 1 is not applicable.

19.8 This subclause of Part 1 is not applicable.

19.101 Handles**19.101.1 Hedge trimmer handles****19.101.1.1 General**

For all **hedge trimmers** except for **extended-reach hedge trimmers**, the minimum number of handles shall be in accordance with Table 101.

If a part containing the motor complies with the dimensions for a handle, it may be considered as a handle.

A1 The handles shall be designed in such a way that each one can be grasped with one hand. Handles shall be suitably shaped to be grasped securely and have a perimeter P between 63 mm and 170 mm as illustrated in Figure 105 a), 105 b) or 105 c). The perimeter is determined by a chain measurement with the **blade control**, if any, fully depressed. The gripping length of the handle(s) required in Table 101 shall be at least 100 mm. **A1**

If applicable, the part of the handle containing the **blade control** shall be counted as part of the handle gripping length.

If there are finger grips or similar superimposed profiles, the handle gripping length shall not be measured along the surface, but only the arc or straight line distance of the gripping surface, as applicable, shall be taken into account.

Handles shall be locked in position during operation except as allowed by 19.101.3. If they are adjustable without tools to different positions in accordance with 8.14.2 b), it shall not be possible to operate the machine when adjusted to a position which contravenes other provisions of this standard.

NOTE The requirements for endurance and integrity of adjustments are covered in 19.107 and 19.108.

Compliance is checked by inspection and by measurements.

19.101.1.2 Dimensions of bail or closed handles

A1 On bail or closed handles (U-shaped handles) the gripping length is related to the inner length of the gripping surface. There shall be a minimum radial clearance of 25 mm around the gripping length. In addition, for a handle incorporating a **blade control**, there shall be a minimum radial clearance of 25 mm around the **blade control** actuator with the **blade control** not depressed. **A1**

If a bail or closed handle is used, the gripping length L in Figure 105 a) shall be measured using lengths A and B as follows:

- the length A is measured within region X where the radius is at least 100 mm;
- the length(s) B are measured within region(s) Y where the transition radius is less than 100 mm, but each length B cannot exceed 10 mm in each region Y of the gripping surface.

Compliance is checked by inspection and by measurements.

19.101.1.3 Dimensions of handles supported centrally (T-type)

If a handle is supported centrally (i.e. T-type), there shall be a minimum radial clearance of 25 mm around the gripping length. The gripping length shall be calculated as follows (see Figure 105 b)):

- for handles with a perimeter P (not including the support) of less than 80 mm, the gripping length is the sum of the two parts of the gripping length $X + Y$ on either side of the support;
- for handles with a perimeter P (not including the support) of 80 mm or more, the gripping length is the complete length Z from end to end.

A1 In addition, for a handle incorporating a **blade control**, there shall be a minimum radial clearance of 25 mm around the **blade control** actuator with the **blade control** not depressed. **A1**

Compliance is checked by inspection and by measurements.

19.101.1.4 Dimensions of handles that are formed by the shaft

The gripping length L in Figure 105 c) shall be measured using the straight portion of the handle, not including any transition radius, finger grips or similar superimposed profiles.

Compliance is checked by inspection and by measurements.

19.101.2 Extended-reach hedge trimmer handles

19.101.2.1 General

For **extended-reach hedge trimmers**, the minimum number of handles shall be in accordance with Table 102.

If a part containing the motor complies with the dimensions for a handle, it may be considered as a handle.

A **shaft** may be used as a handle if specified in accordance with 8.14.2.

A1) The handles shall be designed in such a way that each one can be grasped with one hand. Handles shall be suitably shaped to be grasped securely and have a perimeter P between 63 mm and 170 mm as illustrated in Figure 105 a), 105 b) or 105 c). The perimeter P is determined by a chain measurement with the **blade control**, if any, fully depressed. The gripping length of the **front handle** and the **rear handle** shall be at least 100 mm long. In addition, for a handle incorporating a **blade control**, there shall be a minimum radial clearance of 25 mm around the **blade control** actuator with the **blade control** not depressed. **A1)**

If applicable, the part of the handle containing the **blade control** shall be counted as part of the handle gripping length.

If there are finger grips or similar superimposed profiles, the handle gripping length shall not be measured along the surface, but only the arc or straight line distance of the gripping surface, as applicable, shall be taken into account.

If handles are adjustable to different positions without tools in accordance with 8.14.2 b), it shall not be possible to inadvertently operate the machine when locked in a position which contravenes other provisions of this standard. This may be achieved by at least one **blade control** requiring two separate and dissimilar actions before the **cutting device** operates as described in 21.18.102 for **power switches** and also meet the requirements of 21.17.1 for self-restoring lock-off devices.

Compliance is checked by inspection and by measurements.

19.101.2.2 Dimensions of bail or closed handles

A1) On bail or closed handles (U-shaped handles), the gripping length is related to the inner length of the gripping surface. There shall be a minimum radial clearance of 25 mm around the gripping length. In addition, for a handle incorporating a **blade control**, there shall be a minimum radial clearance of 25 mm around the **blade control** actuator with the **blade control** not depressed. **A1)**

If a bail or closed handle is used, the gripping length L in Figure 105 a), shall be measured using lengths A and B as follows:

- the length A is measured within region X where the radius is at least 100 mm;
- the length(s) B are measured within region(s) Y where the transition radius is less than 100 mm, but each length B cannot exceed 10 mm in each region Y of the gripping surface.

Compliance is checked by inspection and by measurements.

19.101.2.3 Dimensions of handles supported centrally (T-type)

If a handle is supported centrally (i.e. T-type), there shall be a minimum radial clearance of 25 mm around the gripping length. The gripping length shall be calculated as follows (see Figure 105 b)):

- for handles with a perimeter P (not including the support) of less than 80 mm, the gripping length is the sum of the two parts of the gripping length $X + Y$ on either side of the support;
- for handles with a perimeter P (not including the support) of 80 mm or more, the gripping length is the complete length Z from end to end.

In addition, for a handle incorporating a **blade control**, there shall be a minimum radial clearance of 25 mm around the **blade control** actuator with the **blade control** not depressed.

Compliance is checked by inspection and by measurements.

19.101.2.4 Dimensions of handles that are formed by the shaft

The gripping length L in Figure 105 c) shall be measured using the straight portion of the handle, not including any transition radius, finger grips or similar superimposed profiles.

Compliance is checked by inspection and by measurements.

19.101.3 Handles that are adjustable during operation

19.101.3.1 Hedge trimmers, except for **extended-reach hedge trimmers**, with handles that are adjustable by side-to-side axial rotation about an axis between them without the use of a tool while the **cutting device** is operating as permitted in Table 101 shall comply with the requirements of 19.101.3.2 to 19.101.3.6.

No more than one of the handles to be held in operation may be adjustable while the machine is operating.

Extended-reach hedge trimmers shall not incorporate handles that are intended to be adjusted in accordance with 8.14.2 while the **cutting device** is operating.

Compliance is checked by inspection, by manual test and by the requirements of 19.101.3.2 to 19.101.3.6.

19.101.3.2  Any adjustable handle shall have a defined centre position. The handle shall have a locking detent at the centre position and at any other intended handle adjustment position of operation as described in 8.14.2. These other operating positions shall not locate the handle further than 95° from the centre position about their axis of rotation. See Figures 106 and 107. The handle movement, when locked by the detent and subjected to a torque of $(2 \pm 0,1)$ Nm, shall be limited to 5° rotation. The handle shall have a handle release control as required in 19.101.3.3 that releases the handle from the detent position. 

The handle shall automatically lock into each detent position when adjusting the handle, unless the handle release control is operated.

Compliance is checked by inspection and by measurement.

19.101.3.3 Limitation of movement of adjustable handles

19.101.3.3.1 Hedge trimmers with handles that are adjustable during operation shall be designed to prevent uncontrolled movement by fulfilling either 19.101.3.3.2 or 19.101.3.3.3.

19.101.3.3.2 The ease of rotation of an adjustable handle shall be limited after the handle release control is activated.

Compliance is checked by the following test:

*With the **cutting device** clamped securely and the handle release control activated, a 1 Nm torque is applied to the adjustable handle about its axis of rotation. There shall be no more than 5° of rotation of the handle within 2 s. The test is then repeated in the opposite direction of rotation.*

19.101.3.3.3 After the release of the handle from the centre position by the momentary activation of the handle release control, the extent of movement of the adjustable handle of the machine shall be limited.

The rotating handle shall have

- a maximum rotation of 60°; or
- one or more intermediate locking detents limiting rotation to a maximum of 60°

measured from the centre position in either direction about the axis of rotation between the handle positions.

The intermediate locking detent(s) may be intentionally overridden by operation of the handle release control.

NOTE For the case where this requirement is fulfilled by the use of one or more intermediate locking detents, the requirement for maximum rotation is specified in 19.101.3.2.

Compliance is checked by inspection and by measurement.

19.101.3.4 An adjustable handle shall be provided with a momentary handle release control to unlock the handles from a locked detent position. Operation of the handle release control shall not adversely affect physical control of the **hedge trimmer**. The handle release control, while intentionally activated, may allow the handle to bypass the detent position without locking.

Compliance is checked by inspection and by manual test.

19.101.3.5 Accessibility of handle release control

19.101.3.5.1 The handle release control shall be located, designed or guarded so that unintentional activation is unlikely.

Compliance is checked by fulfilling one of the requirements specified in 19.101.3.5.2, 19.101.3.5.3 or 19.101.3.5.4.

19.101.3.5.2 The handle release control shall be located outside the gripping surface of the handle, indicated in 8.14.2 b) 103).

Compliance is checked by inspection.

19.101.3.5.3 It shall not be possible to activate the handle release control when a rigid sphere with a diameter of (100 ± 1) mm is applied to the handle release control in any direction with a single linear motion.

Compliance is checked by inspection and by manual test.

19.101.3.5.4 The handle release control shall require two separate and dissimilar actions before the handle is released. It shall not be possible to achieve these two actions with a single grasping motion or a straight line motion.

Compliance is checked by inspection and by manual test.

19.101.3.6 A handle release control shall have adequate strength and shall be sufficiently durable.

Compliance is checked by the following test:

The handle release control is actuated a total of 2 000 times, engaging all locking detent positions over the full range of travel of the adjustable handle, in both directions.

Each handle release control actuation consists of the following steps a) to d):

- a) Starting from any locking detent position, activate the handle release control;*
- b) Begin rotation of the adjustable handle to the next locking detent position;*
- c) Release the handle release control at approximately the halfway point to the next locking detent position;*
- d) Continue rotation of the adjustable handle until the handle engages with the next locking detent position.*

After the test, the machine shall withstand the electric strength test of Annex D between live parts and accessible parts and live parts shall not have become accessible, as specified in Clause 9, if the adjustment would cause stress on internal wiring.

At the conclusion of the conditioning, the handle release control shall perform as intended and shall comply with the following test:

While a handle is in any locking detent position, a torque of 6 Nm is applied for 1 min in line with the direction of its intended handle rotation, and it is applied in each direction of rotation.

*During the test, the handle shall not disengage from the locking detent position(s), and the handle shall still operate correctly after the test. Electrical connections shall not have worked loose, and there shall be no deterioration impairing safety in **normal use**.*

19.102 Hand protection

19.102.1 An operator's hand shall be protected from inadvertent contact with the moving **cutter blade** while holding the **front handle** as required in Table 101 or Table 102. Requirements for **hedge trimmers**, except for **extended-reach hedge trimmers**, are specified in 19.102.2. Requirements for **extended-reach hedge trimmers** are specified in 19.102.3.

19.102.2 Hand protection for hedge trimmers except for extended-reach hedge trimmers

19.102.2.1 **A1** The **front handle** shall be located so that the distance from the nearest cutting edge of the **cutter blade** to the furthest side of any handle, except for Category 1, is not less than 120 mm as shown in Figure 108 a) and Figure 108 b).

For Category 1, the shortest distance between the front of the handle grip and the nearest **blade tooth** shall be at least 120 mm (see Figure 111). The distances shall be measured along the shortest path from the front of the handle grip to the nearest cutting edge of the **cutter blade**.

For all categories in Table 101, if there is a front hand barrier, then the x_1 and x_2 distances in Figure 108 a) and Figure 108 b) shall be measured along the shortest path from the furthest side of the handle, via the edge of the front hand barrier, to the nearest cutting edge of the **cutter blade**. The front hand barrier shall not have any openings with a minor dimension larger than 10 mm.

Additionally, for category 3a **hedge trimmers**, the front hand barrier shall have a minimum shape described by:

- a height y_1 of 90 mm measured perpendicularly from the cutting plane; and
- a width y_2 of 50 mm on either side of the centreline of the **cutting device**.

Both the y_1 and y_2 measurements are made with the **cutting device** in the 0° position, if axially rotatable. See Figure 109.

Compliance is checked by inspection and by measurement. 

19.102.2.2 In addition, for category 3a **hedge trimmers** where the **cutting device** can be rotated left or right along an axis of rotation, the front hand barrier shall have a width that extends a minimum of 25 mm beyond the **cutting device** when the **cutting device** is adjusted to its full left and right rotational position (see Figure 110).

Compliance is checked by inspection and by measurement.

19.102.2.3 In addition, for category 1 **hedge trimmers**, the handle shall be constructed such that it is attached to the machine at the front of the handle grip (see Figure 111).

Compliance is checked by inspection.

19.102.3 For **extended-reach hedge trimmers**, the **front handle** shall be located so that the shortest distance from the nearest cutting edge of the **cutter blade** to

- the backside of the handle for bail and T-type handles as shown in Figure 112 a); or
- the nearest point of any gripping surface on a **shaft** used as a handle in accordance with 8.14.2 as shown in Figure 112 b)

shall be at least 250 mm, with the **cutting device** in the most unfavourable configuration in accordance with 8.14.2 where it is possible for the machine to operate.

In addition, the machine shall be constructed such that in any operating configuration described in 8.14.2 b), the shortest distance measured between the point of the **blade control** in the **rear handle** closest to the **cutter blade** and the nearest cutting edge of the **cutter blade** shall be at least 1 000 mm, otherwise the requirements of Clause 19 for **hedge trimmers** that are not **extended-reach hedge trimmers** shall also apply.

Compliance is checked by inspection and by measurement.

19.103 Cutting device

19.103.1 To safeguard against contact with the **cutter blade**, **hedge trimmers** shall be constructed to meet the requirements of one of the categories given in

- Table 101 for all **hedge trimmers**, except for **extended-reach hedge trimmers**;

or

- Table 102 for **extended-reach hedge trimmers**.

Compliance is checked by inspection and by measurement.

Table 101 – Hedge trimmer categories (excluding extended-reach hedge trimmers)

Items with requirements	Category number and requirements				
	1	2	3a	3b	4
Cutting length	≤ 200 mm	Not applicable	Not applicable	Not applicable	Not applicable
Maximum blade stopping time (Subclause 19.104)	No	No	3 s	2 s	1 s
Minimum number of handles	1	2	2	2	2
Minimum number of handles with blade control	1	1	1	2 (two with simultaneous actuation)	2 (two with simultaneous actuation)
Location of blade control	rear handle	rear handle	rear handle	Not applicable	Not applicable
Blade configuration figure	114	114	115	115	116
Lower barrier required (Subclause 19.105)	No	No	Yes	No	No
Adjustable handle during operation permitted (Subclause 19.101.3)	No	Yes	Yes	Yes	Yes
Front hand barrier required (Subclause 19.102.2)	No	No	Yes	No	No

NOTE 1 In Europe (EN 62841-4-2), Category 3a is not applicable.

NOTE 2 In Europe (EN 62841-4-2), the maximum **blade stopping time** for Category 3b machines is 1 s.

Table 102 – Extended-reach hedge trimmer categories

Items with requirements	Category number and requirements				
	1	2	3a	3b	4
Cutting length	≤ 200 mm	Not applicable	Not applicable	Not applicable	Not applicable
Maximum blade stopping time (Subclause 19.104)	3 s	3 s	3 s	3 s	3 s
Minimum number of handles	2	2	2	2	2
Minimum number of handles with blade control	1	1	1	1	1
Location of blade control	rear handle	rear handle	rear handle	rear handle	rear handle
Blade configuration figure	114	114	115 (if blunt extensions are required)	115 (if blunt extensions are required)	116 (if blunt extensions are required)
Lower barrier required (Subclause 19.105)	No	No	No	No	No
Front hand barrier required	No	No	No	No	No

19.103.2 Blunt extensions

19.103.2.1 Blunt extensions as indicated in 19.103.2.2 through 19.103.2.4 shall extend a distance of at least 400 mm

- from any point of the rear face of the **front handle**; or
- if applicable for **extended-reach hedge trimmers**, from the nearest point of any gripping surface on a **shaft** used as a handle in accordance with 8.14.2.

See Figure 113. If the **front handle** is located part way along the **cutting device**, the **blunt extensions** shall start at the first **blade tooth** and continue beyond the rear of the **front handle** until the 400 mm minimum distance is reached.

Compliance is checked by inspection and by measurement.

19.103.2.2 Hedge trimmer categories 1 and 2 (see Figure 114)

The **blade tooth** opening distance (d_1) shall be no greater than 8 mm.

The minimum depth of the **blunt extensions** (d_2), if required in accordance with 19.103.2.1, shall be no less than 8 mm.

Compliance is checked by inspection and by measurement.

19.103.2.3 Hedge trimmer categories 3a and 3b (see Figure 115)

The distance between adjacent **blunt extensions**, if required in accordance with 19.103.2.1, shall not allow a $(19,0^{+0}_{-0,1})$ mm test cylinder, applied with a force not exceeding 1 N, to contact any **blade tooth**, when the test cylinder is positioned perpendicular to the plane of the **cutting device**.

Compliance is checked by inspection and by manual test.