



BSI Standards Publication

Measuring relays and protection equipment

Part 26: Electromagnetic compatibility requirements

National foreword

This British Standard is the UK implementation of EN IEC 60255-26:2025. It is identical to IEC 60255-26:2023. It supersedes BS EN 60255-26:2013, which will be withdrawn on 30 April 2028.

The UK participation in its preparation was entrusted to Technical Committee PEL/95, Measuring relays and protection systems.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2025
Published by BSI Standards Limited 2025

ISBN 978 0 580 52356 4

ICS 29.120.70; 33.100.10; 33.100.20

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2025.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

Measuring relays and protection equipment - Part 26:
Electromagnetic compatibility requirements
(IEC 60255-26:2023)

Relais de mesure et dispositifs de protection - Partie 26:
Exigences de compatibilité électromagnétique
(IEC 60255-26:2023)

Messrelais und Schutzeinrichtungen - Teil 26:
Anforderungen an die elektromagnetische Verträglichkeit
(IEC 60255-26:2023)

This European Standard was approved by CENELEC on 2024-10-16. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 95/515/FDIS, future edition 4 of IEC 60255-26, prepared by TC 95 "Measuring relays and protection equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 60255-26:2025.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2026-04-30 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2028-04-30 document have to be withdrawn

This document supersedes EN 60255-26:2013 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 60255-26:2023 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC 61000-4 series NOTE Approved as EN 61000-4 series

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60255-1	2022	Measuring relays and protection equipment - Part 1: Common requirements	EN IEC 60255-1	2023
IEC 61000-4-2	2008	Electromagnetic compatibility (EMC) - Part 4-2: Testing and measurement techniques - Electrostatic discharge immunity test	EN 61000-4-2	2009
IEC 61000-4-3	2020	Electromagnetic compatibility (EMC) - Part 4-3 : Testing and measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test	EN IEC 61000-4-3	2020
IEC 61000-4-4	2012	Electromagnetic compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transient/burst immunity test	EN 61000-4-4	2012
IEC 61000-4-5	2014	Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test	EN 61000-4-5	2014
+ A1	2017		+ A1	2017
IEC 61000-4-6	2013	Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields	EN 61000-4-6	2014
-	-		+ AC	2015
IEC 61000-4-8	2009	Electromagnetic compatibility (EMC) - Part 4-8: Testing and measurement techniques - Power frequency magnetic field immunity test	EN 61000-4-8	2010

EN IEC 60255-26:2025 (E)

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61000-4-11	2020	Electromagnetic compatibility (EMC) - Part 4-11: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations immunity tests for equipment with input current up to 16 A per phase	EN IEC 61000-4-11	2020
-	-		+ AC	2020
-	-		+ AC	2022
IEC 61000-4-16	2015	Electromagnetic compatibility (EMC) - Part 4-16: Testing and measurement techniques - Test for immunity to conducted, common mode disturbances in the frequency range 0 Hz to 150 kHz	EN 61000-4-16	2016
IEC 61000-4-17	1999	Electromagnetic compatibility (EMC) - Part 4-17: Testing and measurement techniques - Ripple on d.c. input power port immunity test	EN 61000-4-17	1999
+ A1	2001		+ A1	2004
+ A2	2008		+ A2	2009
IEC 61000-4-18	2019	Electromagnetic compatibility (EMC) - Part 4-18: Testing and measurement techniques - Damped oscillatory wave immunity test	EN IEC 61000-4-18	2019
IEC 61000-4-29	2000	Electromagnetic compatibility (EMC) - Part 4-29: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations on d.c. input power port immunity tests	EN 61000-4-29	2000
CISPR 11 (mod)	2015	Industrial, scientific and medical equipment - Radio-frequency disturbance characteristics - Limits and methods of measurement	EN 55011	2016
+ A1	2016		+ A1	2017
-	-		+ A11	2020
+ A2	2019		+ A2	2021
CISPR 32	2015	Electromagnetic compatibility of multimedia equipment - Emission requirements	EN 55032	2015
-	-		+ AC	2016-07
+ A1	2019		+ A1	2020
-	-		+ A11	2020

CONTENTS

FOREWORD.....	5
1 Scope.....	7
1.1 General.....	7
1.2 Emission.....	7
1.3 Immunity.....	7
2 Normative references	7
3 Terms, definitions, and abbreviated terms	9
3.1 Terms and definitions.....	9
3.2 Abbreviated terms.....	12
4 Electromagnetic environmental levels.....	13
4.1 General.....	13
4.2 Zone A, severe electromagnetic environment.....	13
4.3 Zone B, typical electromagnetic environment	14
5 Emission.....	14
5.1 Radiated emission	14
5.2 Conducted emission.....	15
6 Immunity.....	16
6.1 Immunity of enclosure	16
6.2 Immunity of auxiliary power supply port	17
6.3 Immunity of signal/control port and wired network port.....	20
6.4 Immunity of input and output ports	21
6.5 Immunity of earth port.....	24
7 Test set-up and procedures	24
7.1 General.....	24
7.2 Emission.....	25
7.2.1 General	25
7.2.2 Radiated emission	26
7.2.3 Conducted emission	26
7.3 Immunity.....	26
7.3.1 General	26
7.3.2 Electrostatic discharge immunity test.....	28
7.3.3 Radiated electromagnetic field immunity test	29
7.3.4 Electrical fast transient/burst immunity test.....	31
7.3.5 Damped oscillatory wave immunity test	32
7.3.6 Surge immunity test.....	33
7.3.7 Conducted RF immunity test.....	35
7.3.8 Conducted power frequency immunity test on binary inputs	37
7.3.9 Power frequency magnetic field immunity test	38
7.3.10 Voltage dips and short interruptions test (AC or DC).....	38
7.3.11 Ripple on DC input power port immunity test	39
7.3.12 Gradual shutdown / start-up tests	40
8 Criteria for acceptance	40
8.1 Emission.....	40
8.2 Immunity.....	41
9 Test report.....	42
Annex A (normative) Power frequency immunity tests on binary inputs	42

A.1	General.....	43
A.2	Test classes.....	43
A.3	Test equipment.....	43
A.3.1	General	43
A.3.2	Test generator	43
A.3.3	Verification of the test generator.....	44
A.3.4	Coupling networks	44
A.4	Test set-up	44
A.4.1	General	44
A.4.2	Earthing connections	44
A.4.3	Auxiliary equipment	44
Annex B (informative)	Background information for power frequency tests	47
Annex C (informative)	Background information about spot frequency tests	48
Annex D (informative)	EMC risk assessment.....	50
D.1	EMC design risk assessment	50
D.2	Product platform risk assessment	52
Annex E (informative)	Considerations regarding radio interfaces	54
Annex F (informative)	Immunity test to be considered in future	55
Bibliography.....		56
Figure 1	Gradual shutdown / start-up test	40
Figure A.1	Example of Zone A differential mode tests	45
Figure A.2	Example of Zone B differential mode tests	45
Figure A.3	Example of Zone A and Zone B common mode tests	46
Table 1	Radiated emission tests – Enclosure port.....	14
Table 2	Required highest frequency for radiated measurement.....	15
Table 3	Conducted emission tests – AC and DC auxiliary power supply port.....	15
Table 4	Conducted emission tests – Wired network port	15
Table 5	Immunity tests – Enclosure port	16
Table 6	Immunity tests – Auxiliary power supply port.....	17
Table 7	Immunity tests – signal/control port and wired network port.....	20
Table 8	Immunity tests – Input and output port.....	21
Table 9	Immunity tests – Earth port.....	24
Table 10	Radiated emission test	26
Table 11	Conducted emission test	26
Table 12	Electrostatic discharge immunity test.....	28
Table 13	Radiated electromagnetic field immunity test (frequency sweep)	29
Table 14	Radiated electromagnetic field immunity test (spot frequencies).....	30
Table 15	Electrical fast transient/burst immunity test.....	31
Table 16	Damped oscillatory wave immunity test	32
Table 17	Surge immunity test.....	33
Table 18	Conducted RF immunity test (frequency sweep)	35
Table 19	Conducted RF immunity test (spot frequencies).....	36
Table 20	Conducted power frequency immunity test on binary inputs.....	37

Table 21 – Power frequency magnetic field immunity test	38
Table 22 – Voltage dips and short interruptions test (AC or DC)	38
Table 23 – Ripple on DC input power port immunity test	39
Table 24 – Gradual shutdown and start-up test	40
Table 25 – Acceptance criteria for immunity tests	41
Table C.1 – Selection of spot frequencies	48
Table D.1 – Risk assessment based on a hardware design modification	51
Table D.2 – Risk assessment, selecting representative EUT configuration(s)	52
Table E.1 – Listed standard with relevance	54
Table F.1 – Immunity test to be considered in future	55

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MEASURING RELAYS AND PROTECTION EQUIPMENT –**Part 26: Electromagnetic compatibility requirements****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60255-26 has been prepared by IEC technical committee 95: Measuring relays and protection equipment. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) update of normative references
- b) introduction of a wired network port and signal/control port in accordance with CISPR 32;
- c) introduction of low-power instrument transformer (LPIT) and battery monitor port;
- d) expansion of the frequency range on radiated radio-frequency immunity test up to 6 GHz;
- e) updated requirements on electrostatic discharge tests;
- f) introduction of fast damped oscillatory wave test for Zone A applications;
- g) specification of higher immunity requirements on power frequency magnetic field tests;

- h) update of the spot frequency test and addition of a new annex with background information;
- i) addition of details and further guidance on the relay settings;
- j) additional test condition for AC voltage dips and interruptions;
- k) addition of an annex about EMC risk assessments;
- l) addition of an annex on radio interfaces.

The text of this International Standard is based on the following documents:

Draft	Report on voting
95/515/FDIS	95/525/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all the parts in the IEC 60255 series, published under the general title *Measuring relays and protection equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

MEASURING RELAYS AND PROTECTION EQUIPMENT –

Part 26: Electromagnetic compatibility requirements

1 Scope

1.1 General

This part of IEC 60255 specifies the requirements for electromagnetic compatibility for measuring relays and protection equipment. It is applicable to measuring relays and protection equipment and combinations of devices to form schemes for power system protection including the control, monitoring, communication and process interface equipment used with those systems.

Tests specified in this document are not required for equipment not incorporating electronic circuits, for example electromechanical relays.

The requirements specified in this document are applicable to measuring relays and protection equipment in a condition representative of how new equipment is provided by the manufacturer. All tests specified are type tests only.

1.2 Emission

This document specifies limits and test methods, for measuring relays and protection equipment in relation to electromagnetic emissions which might cause interference in other equipment.

These emission limits represent electromagnetic compatibility requirements and have been selected to ensure that the disturbances generated by measuring relays and protection equipment, operated normally in substations and power plants, do not exceed a specified level which could prevent other equipment from operating as intended.

Test requirements are specified for the enclosure, auxiliary power supply ports, input/output ports, signal/control ports and wired network ports.

1.3 Immunity

This document specifies the immunity test requirements for measuring relays and protection equipment in relation to continuous and transient, conducted and radiated disturbances, including electrostatic discharges.

These test requirements represent the electromagnetic compatibility immunity requirements and have been selected so as to ensure an adequate level of immunity for measuring relays and protection equipment, operated normally in substations and power plants.

NOTE 1 Product safety considerations are not covered in this document.

NOTE 2 In special cases, situations will arise where the levels of disturbance could exceed the levels specified in this document, for example where a hand-held transmitter or a mobile telephone is used close to measuring relays and protection equipment. In these instances, special precautions and procedures could be needed.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies.

For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60255-1:2022, *Measuring relays and protection equipment – Part 1: Common requirements*

IEC 61000-4-2:2008, *Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test*

IEC 61000-4-3:2020, *Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test*

IEC 61000-4-4:2012, *Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test*

IEC 61000-4-5:2014, *Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test*
IEC 61000-4-5:2014/AMD1:2017

IEC 61000-4-6:2013, *Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields*

IEC 61000-4-8:2009, *Electromagnetic compatibility (EMC) – Part 4-8: Testing and measurement techniques – Power frequency magnetic field immunity test*

IEC 61000-4-11:2020, *Electromagnetic compatibility (EMC) – Part 4-11: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations immunity tests for equipment with input current up to 16 A per phase*

IEC 61000-4-16:2015, *Electromagnetic compatibility (EMC) – Part 4-16: Testing and measurement techniques – Test for immunity to conducted, common mode disturbances in the frequency range 0 Hz to 150 kHz*

IEC 61000-4-17:1999, *Electromagnetic compatibility (EMC) – Part 4-17: Testing and measurement techniques – Ripple on d.c. input power port immunity test*
IEC 61000-4-17:1999/AMD1:2001
IEC 61000-4-17:1999/AMD2:2008

IEC 61000-4-18:2019, *Electromagnetic compatibility (EMC) – Part 4-18: Testing and measurement techniques – Damped oscillatory wave immunity test*

IEC 61000-4-29:2000, *Electromagnetic compatibility (EMC) – Part 4-29: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations on d.c. input power port immunity tests*

CISPR 11:2015, *Industrial, scientific and medical equipment – Radio-frequency disturbance characteristics – Limits and methods of measurement*
CISPR 11:2015/AMD1:2016
CISPR 11:2015/AMD2:2019

CISPR 32:2015, *Electromagnetic compatibility of multimedia equipment – Emission requirements*
CISPR 32:2015/AMD1:2019

3 Terms, definitions, and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1

analogue output port

port that generates an analogue output signal to drive actuators, analogue panel meters, etc.

Note 1 to entry: Typically a current or voltage less than or equal to 20 mA or 10 V DC respectively.

[SOURCE: IEC 60255-1:2022, 3.1.3]

3.1.2

auxiliary equipment

AE

equipment necessary to provide the equipment under test (EUT) with the signals required for normal operation and to verify the performance of the EUT

3.1.3

auxiliary power supply port

AC or DC auxiliary energizing input

Note 1 to entry: Some modern relays have a single auxiliary power supply port that can be energized with both AC and/or DC.

3.1.4

battery monitor port

port intended for connection to the station battery for the purpose of battery voltage monitoring

[SOURCE: IEC 60255-1:2022, 3.1.6]

3.1.5

binary input port

port intended for inputs which have an on or off state given by direct connection to an energizing quantity without any communications protocol

[SOURCE: IEC 60255-1:2022, 3.1.7]

3.1.6

binary output port

port intended for outputs which have an on or off state given by direct connection to an energizing quantity without any communications protocol

[SOURCE: IEC 60255-1:2022, 3.1.8]

3.1.7

common mode

CM

mode between each active conductor and a specified reference, usually earth or ground reference plane

3.1.8

cabinet

free-standing and self-supporting enclosure for housing electrical and/or electronic equipment

Note 1 to entry: A cabinet is usually fitted with doors and/or side panels, which may or may not be removable.

[SOURCE: IEC 60050-581:2008, 581-25-02]

3.1.9

coupling network

electrical circuit or device for the purpose of transferring energy from one circuit to another with a defined impedance

3.1.10

coupling/decoupling network

CDN

electrical circuit incorporating the functions of both the coupling and decoupling networks

3.1.11

decoupling network

electrical circuit for the purpose of preventing test voltages applied to the EUT from affecting other devices, equipment, or systems which are not under test

3.1.12

differential mode

DM

mode between any two of a specified set of active conductors

3.1.13

earth port

point where a cable intended for connection to earth for functional or safety purposes can be connected

3.1.14

enclosure port

physical boundary of the EUT through which electromagnetic fields can radiate or impinge

[SOURCE: IEC 60050-445:2010, 445-07-04, modified – The term "time relay" has been replaced by "EUT" and "can" has been replaced by "may".]

3.1.15

equipment under test

EUT

equipment submitted to a test, including any accessories such as communication modules, plug-in power supplies, etc. unless otherwise specified

[SOURCE: IEC 60255-1:2022, 3.1.15]

3.1.16

highest internal frequency

F_X

highest fundamental frequency generated or used within the EUT or highest frequency at which it operates

Note 1 to entry: This includes frequencies which are solely used within an integrated circuit.

3.1.17**input port**

port through which the EUT is energized or controlled in order to perform its function(s)

EXAMPLE 1 Analogue current transformer (LPCT/CT) input, analogue voltage transformer (LPVT or VT) input, binary input, battery monitor input, etc.

[SOURCE: IEC 60255-1:2022, 3.1.18]

3.1.18**low-power instrument transformer****LPIT**

arrangement, consisting of one or more current or voltage transformer(s) which may be connected to transmitting systems and secondary converters, all intended to transmit a low-power analogue or digital output signal to measuring instruments, meters and protective or control devices or similar apparatus

EXAMPLE An arrangement consisting of three current sensors, three voltage sensors connected to one merging unit delivering one digital output is considered an LPIT.

Note 1 to entry: LPITs are commonly called non-conventional instrument transformers (NCIT).

Note 2 to entry: The output power produced by these devices is typically lower or equal to 1 VA.

[SOURCE: IEC 61869-6:2016, 3.1.601]

3.1.19**low-power current transformer****LPCT**

low-power instrument transformer for current measurement

[SOURCE: IEC 61869-6:2016, 3.1.602]

3.1.20**low-power voltage transformer****LPVT**

low-power instrument transformer for voltage measurement

[SOURCE: IEC 61869-6:2016, 3.1.603]

3.1.21**output contact**

arrangement of contact members, with their insulation, which close or open their contact circuit by their relative movement

[SOURCE: IEC 60050-444:2002, 444-04-03, modified – The term "contact" has been replaced by "output contact", the domain "for elementary relays" and the figure have been omitted.]


3.1.22**output port**

port through which the EUT produces predetermined changes

[SOURCE: IEC 60255-1:2022, 3.1.27]

3.1.23**port**

particular interface of the specified EUT with the external electromagnetic environment



3.1.24

rated value

value of a quantity used for specification purposes, established for a specified set of operating conditions of a component, device, equipment, or system

[SOURCE: IEC 60050-447:2020, 447-03-11]

3.1.25

signal/control port

port intended for the interconnection of components of an EUT, or between an EUT and local AE and used in accordance with relevant functional specifications (for example, for the maximum length of cable connected to it)

Note 1 to entry: Examples include EIA-232, Universal Serial Bus (USB), High-Definition Multimedia Interface (HDMI®), IEEE Standard 1394 ("FireWire"), IRIG-B Interface.

3.1.26

small equipment

equipment, either positioned on a tabletop or standing on the floor which, including its cables, fits in a cylindrical test volume of 1,2 m in diameter and 1,5 m above the ground plane

Note 1 to entry: For small equipment, emission testing at distances under 10 m is accepted.

3.1.27

wired network port

port for the connection of voice, data and signalling transfers intended to interconnect widely dispersed systems by direct connection to a single-user or multi-user communication network

Note 1 to entry: Examples of these ports include CATV, PSTN, ISDN, xDSL, LAN, EIA-485 and similar networks.

Note 2 to entry: These ports may support screened or unscreened cables and may also carry AC or DC power (e.g. PoE) where this is an integral part of the telecommunication specification.

Note 3 to entry: A port generally intended for interconnection of components of a system under test (e.g. EIA-232, IEEE Standard 1284 (parallel printer), Universal Serial Bus (USB), IEEE Standard 1394 ("Fire Wire"), etc.) and used in accordance with its functional specifications (e.g. for the maximum length of cable connected to it), is not considered to be a wired network port.

3.2 Abbreviated terms

AAN	Asymmetric artificial network
AE	Auxiliary equipment
AMN	Artificial mains network
CATV	Communal (broadcasting) antenna/cable TV network
CDN	Coupling/decoupling network
CCC	Capacitive coupling clamp
CM	Common mode
CVP	Capacitive voltage probe
DM	Differential mode

EMC	Electromagnetic compatibility
ESD	Electrostatic discharge
EUT	Equipment under test
FW	Firmware
HW	Hardware
IED	Intelligent electronic device
ISDN	Integrated services digital network
LAN	Local area network
LPCT	Low-power current transformer
LPIT	Low-power instrument transformer
LPVT	Low-power voltage transformer
PCBA	Printed circuit board assembly
PCB	Printed circuit board
PSTN	Public switched telephone network
RF	Radio frequency
RTD	Resistance temperature detector
UFA	Uniform field area
USB	Universal serial bus
xDSL	Generic term for all types of DSL (digital subscriber line) technology

4 Electromagnetic environmental levels

4.1 General

The environmental levels shall be selected in accordance with the most realistic installation and environmental conditions in which the EUT is expected to operate.

Based on common installation practices, the recommended selection of test levels is given in 4.2 and 4.3.

4.2 Zone A, severe electromagnetic environment

The installation is characterized by the following attributes:

- no suppression of electrical fast transients/bursts in the power supply and control and power circuits which are switched by relays and high-power contactors;
- no separation of the industrial circuits from other circuits associated with environments of higher severity levels;
- no separation between power supply, control, signal and communication cables;
- use of common multi-core cables for control and signal lines;
- interconnections that are running as outdoor cables along with power cables, even to the high voltage equipment; a special case of this environment is when the electronic equipment is connected to the telecommunication network within a densely populated area. There is no systematically constructed grounding network outside the electronic equipment, and the grounding system consists only of pipes, cables, etc.

The outdoor area of industrial process equipment, power stations, open-air HV substation switchyards and gas insulated switchgear may be representative of this environment.

4.3 Zone B, typical electromagnetic environment

The installation is characterized by the following attributes:

- no suppression of electrical fast transients/bursts in the power supply and control circuits which are switched by relays;
- poor separation of the industrial circuits from other circuits associated with environments of higher severity levels;
- dedicated cables for power supply, control, signal and communication lines;
- poor separation between power supply, control, signal and communication cables;
- the interconnection cables can be partly outdoor cables, but close to the grounding network;
- availability of earthing system represented by conductive pipes, ground conductors in the cable trays (connected to the protective earth system) and by a ground mesh.

The area of industrial process equipment, power plants and the relay room of open-air HV substations may be representative of this environment.

Measuring relays and protection equipment shall meet Class A emission limits for both environmental conditions (Zone A and Zone B).

5 Emission

5.1 Radiated emission

Table 1 – Radiated emission tests – Enclosure port

Item	Environmental phenomena	Frequency range	Limits	Reference standard	Test procedure (reference to this document)
1.1	Radiated emission (below 1 GHz) ^a	30 MHz to 230 MHz	40 dB (μV/m) quasi-peak at 10 m 50 dB (μV/m) quasi-peak at 3 m	CISPR 11	See 7.2.2
		230 MHz to 1 000 MHz	47 dB (μV/m) quasi-peak at 10 m 57 dB (μV/m) quasi-peak at 3 m		
1.2	Radiated emission (above 1 GHz)	1 GHz to 3 GHz	56 dB (μV/m) average at 3 m 76 dB (μV/m) peak at 3 m	CISPR 32	See 7.2.2
		3 GHz to 6 GHz	60 dB (μV/m) average at 3 m 80 dB (μV/m) peak at 3 m		
^a Measuring relays and protection equipment are apparatus which satisfy the class A limits. Limits can be measured at a nominal distance of 3 m or 10 m or 30 m. A measuring distance less than 10 m is allowed only for equipment which complies with the definition for "small equipment" given in 3.1.26. In the case of measurements at a separation distance of 30 m, an inverse proportionality factor of 20 dB per decade shall be used to normalize the measured data to the specified distance for determining compliance.					
At the transition frequency, the more stringent limit shall apply.					

Table 2 shows the highest frequency up to which radiated emission measurements shall be performed.