



BSI Standards Publication

Fire hazard testing

Part 7-2: Toxicity of fire effluent — Summary and relevance of test methods

National foreword

This British Standard is the UK implementation of EN IEC 60695-7-2:2021. It is identical to IEC 60695-7-2:2021. It supersedes BS EN 60695-7-2:2011, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee GEL/89, Fire hazard testing.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2022
Published by BSI Standards Limited 2022

ISBN 978 0 539 03697 8

ICS 13.220.40; 29.020

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2022.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

Fire hazard testing - Part 7-2: Toxicity of fire effluent - Summary
and relevance of test methods
(IEC 60695-7-2:2021)

Essais relatifs aux risques du feu - Partie 7-2: Toxicité des
effluents du feu - Résumé et pertinence des méthodes
d'essai
(IEC 60695-7-2:2021)

Prüfungen zur Beurteilung der Brandgefahr - Teil 7-2:
Toxizität von Rauch und/oder Brandgasen - Auswertung
und Sachdienlichkeit von Prüfverfahren
(IEC 60695-7-2:2021)

This European Standard was approved by CENELEC on 2021-12-02. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 89/1489/CDV, future edition 2 of IEC 60695-7-2, prepared by IEC/TC 89 “Fire hazard testing” was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 60695-7-2:2021.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2022-09-02
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2024-12-02

This document supersedes EN 60695-7-2:2011 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 60695-7-2:2021 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60695-1-11 NOTE Harmonized as EN 60695-1-11

IEC 60695-1-12 NOTE Harmonized as EN IEC 60695-1-12

IEC 60695-4 NOTE Harmonized as EN IEC 60695-4

ISO 5659-2 NOTE Harmonized as EN ISO 5659-2

IEC 60695-6-2 NOTE Harmonized as EN IEC 60695-6-2

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60695-1-10	-	Fire hazard testing - Part 1–10: Guidance for assessing the fire hazard of electrotechnical products - General guidelines	EN 60695-1-10	-
IEC 60695-7-1	-	Fire hazard testing - Part 7–1: Toxicity of fire effluent - General guidance	EN 60695-7-1	-
IEC 60695-7-3	-	Fire hazard testing - Part 7–3: Toxicity of fire effluent - Use and interpretation of test results	EN 60695-7-3	-
IEC Guide 104	-	The preparation of safety publications and the use of basic safety publications and group safety publications	-	-
ISO/IEC Guide 51	-	Safety aspects - Guidelines for their inclusion in standards	-	-
ISO 13943	2017	Fire safety - Vocabulary	EN ISO 13943	2017
ISO 13344	-	Estimation of the lethal toxic potency of fire - effluents	-	-
ISO 13571	2007	Life-threatening components of fire - Guidelines for the estimation of time available for escape using fire data	-	-
ISO/TR 16312-2	-	Guidance for assessing the validity of physical fire models for obtaining fire effluent toxicity data for fire hazard and risk assessment - Part 2: Evaluation of individual physical fire models	-	-
ISO 19706	-	Guidelines for assessing the fire threat to people	-	-
ISO 29903	2012	Guidance for comparison of toxic gas data - between different physical fire models and scales	-	-

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	9
4 Role of small-scale toxicity tests.....	13
4.1 General.....	13
4.2 <i>Toxic potency</i>	13
4.3 Toxic hazard, <i>exposure dose and fractional effective dose (FED)</i>	14
4.4 <i>Fractional effective concentration (FEC)</i>	14
4.5 Generic toxic potencies.....	14
5 General aspects of small-scale toxicity tests.....	15
5.1 General.....	15
5.2 Physical fire models.....	15
5.3 Fire stages in a compartment fire.....	16
5.4 Methods of analysis	16
5.4.1 General	16
5.4.2 Chemical analysis based methods	19
5.4.3 Methods based on animal exposure.....	19
6 Summary of published chemical analysis based test methods	19
6.1 General.....	19
6.2 UK Ministry of Defence – DEF STAN 02-713.....	19
6.2.1 Summary	19
6.2.2 Purpose and principle	20
6.2.3 Test specimen	20
6.2.4 Test method	20
6.2.5 Repeatability and reproducibility	21
6.2.6 Relevance of test data and special observations.....	21
6.3 Airbus industry.....	22
6.3.1 Summary	22
6.3.2 Purpose and principle	22
6.3.3 Test specimen	22
6.3.4 Test method	22
6.3.5 Repeatability and reproducibility	22
6.3.6 Relevance of test data and special observations.....	23
6.4 Comitato Elettrotecnico Italiano (CEI)	23
6.4.1 Summary	23
6.4.2 Purpose and principle	23
6.4.3 Test specimen	23
6.4.4 Test method	23
6.4.5 Repeatability and reproducibility	23
6.4.6 Relevance of test data and special observations.....	23
6.5 Norme Française (NF)	24
6.5.1 Summary	24
6.5.2 Purpose and principle	24
6.5.3 Test specimen	24

6.5.4	Test method	24
6.5.5	Repeatability and reproducibility	24
6.5.6	Relevance of test data and special observations	24
6.6	ISO test methods	25
6.6.1	ISO/TS 19021	25
6.6.2	ISO/TS 19700	26
6.7	International Maritime Organization (IMO)	27
6.7.1	Summary	27
6.7.2	Purpose and principle	27
6.7.3	Test specimen	27
6.7.4	Test method	27
6.7.5	Repeatability and reproducibility	28
6.7.6	Relevance of test data and special observations	28
6.8	Toxicity test for rolling stock cables	28
6.8.1	Summary	28
6.8.2	Purpose and principle	29
6.8.3	Test specimen	29
6.8.4	Test method	29
6.8.5	Repeatability and reproducibility	29
6.8.6	Relevance of test data and special observations	30
6.9	Toxicity test of materials and components (other than cables) used in railway applications	30
6.9.1	Summary	30
6.9.2	Purpose and principle	30
6.9.3	Test specimen	30
6.9.4	Test method	30
6.9.5	Repeatability and reproducibility	31
6.9.6	Relevance of test data and special observations	31
7	Summary of published test methods relating to animal exposure	31
7.1	General	31
7.2	Deutsches Institut für Normung, DIN 53436	31
7.2.1	Summary	31
7.2.2	Purpose and principle	31
7.2.3	Test specimen	31
7.2.4	Test method	32
7.2.5	Repeatability and reproducibility	32
7.2.6	Relevance of test data and special observations	32
7.3	National Bureau of Standards (NBS)	33
7.3.1	Summary	33
7.3.2	Purpose and principle	33
7.3.3	Test specimen	33
7.3.4	Test method	33
7.3.5	Repeatability and reproducibility	33
7.3.6	Relevance of test data and special observations	34
7.3.7	Reference documents	34
7.4	National Institute of Standards and Technology, NIST Radiant furnace	34
7.4.1	Summary	34
7.4.2	Purpose and principle	34
7.4.3	Test specimen	34

7.4.4	Test method	35
7.4.5	Repeatability and reproducibility	35
7.4.6	Relevance of test data and special observations	35
7.4.7	Reference documents	36
7.5	University of Pittsburgh, Upitt Box furnace	36
7.5.1	Summary	36
7.5.2	Purpose and principle	36
7.5.3	Test specimen	36
7.5.4	Test method	36
7.5.5	Repeatability and reproducibility	37
7.5.6	Relevance of test data and special observations	37
7.5.7	Reference documents	37
7.6	Japanese fire toxicity test for building components	37
7.6.1	Summary	37
7.6.2	Purpose and principle	37
7.6.3	Test specimen	37
7.6.4	Test method	38
7.6.5	Repeatability and reproducibility	38
7.6.6	Relevance of test data and special observations	38
8	Overview of methods and relevance of data	38
	Bibliography	41
	Figure 1 – Different phases in the development of a fire within a compartment	16
	Table 1 – Characteristics of fire types (ISO 19706)	18
	Table 2 – C_f values for various gases	21
	Table 3 – <i>Volume fraction</i> limits for gas components	22
	Table 4 – Decomposition conditions	26
	The results are expressed as gas <i>volume fractions</i> . Maximum permitted values are given below (see Table 5 – <i>Volume fraction</i> limits for gas component	28
	Table 5 – <i>Volume fraction</i> limits for gas component	28
	Table 6 – CC_Z values taken from EN 50305	29
	Table 7 – Reference concentrations of the gas components	31
	Table 8 – Overview of toxicity test methods	39
	Table 9 – Overview of toxicity test methods (continued, with comments)	40

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIRE HAZARD TESTING –

**Part 7-2: Toxicity of fire effluent –
Summary and relevance of test methods**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60695-7-2 has been prepared by IEC technical committee 89: Fire hazard testing.

This second edition cancels and replaces the first edition published in 2011. This edition constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- New text in the introduction;
- New text in the scope;
- Clause 2 has been updated;
- Many terms and definitions in Clause 3 reproduced from ISO 13943 have been deleted. Other terms and definitions have been added.
- New text in Subclauses 4.3 and 4.4;
- New text in Subclause 6.1;

- References to IEC 60695-7-50 and -51 (now withdrawn) have been removed;
- Reference to DEF STAN 07-247 has been added;
- Details of ISO/TS 19021 have been added;
- Details of EN 17084 have been added;
- New text added concerning ISO/TS 19700;
- New text added concerning the IMO FTP toxicity test;
- New Subclause 7.1 has been added;
- The Annex in Edition 1 has been replaced by new Clause 8;
- The bibliography has been updated.

The text of this International Standard is based on the following documents:

Draft	Report on voting
89/1489/CDV	89/1508/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

It has the status of a basic safety publication in accordance with IEC Guide 104.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all the parts in the 60695 series, under the general title *Fire hazard testing*, can be found on the IEC website.

IEC 60695-7 consists of the following parts:

- Part 7-1: *Toxicity of fire effluent – General guidance*
- Part 7-2: *Toxicity of fire effluent – Summary and relevance of test methods*
- Part 7-3: *Toxicity of fire effluent – Use and interpretation of test results*

In this document the following print types are used:

- Words *in italics* in the text are defined in Clause 3.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

In the design of an electrotechnical product, the risk of fire and the potential hazards associated with fire need to be considered. In this respect the objective of component, circuit and equipment design, as well as the choice of materials, is to reduce the risk of fire to a tolerable level even in the event of reasonably foreseeable (mis)use, malfunction or failure.

IEC 60695-1-10, IEC 60695-1-11 [1]¹, and IEC 60695-1-12 [2] provide guidance on how this is to be accomplished.

Fires involving electrotechnical products can also be initiated from external non-electrical sources. Considerations of this nature are dealt with in an overall fire hazard assessment.

The aim of the IEC 60695 series of standards is to save lives and property by reducing the number of fires or reducing the consequences of the fire. This can be accomplished by:

- trying to prevent ignition caused by an electrically energised component part and, in the event of ignition, to confine any resulting fire within the bounds of the enclosure of the electrotechnical product;
- trying to minimise flame spread beyond the product's enclosure and to minimise the harmful effects of fire effluents including heat, smoke, and toxic or corrosive combustion products.

Electrotechnical products, primarily as the objects of a fire, may contribute to the fire hazard due to the release of toxic effluent, which may be a significant contributing factor to the overall fire hazard.

The IEC 60695-7 series provides guidance to IEC product committees on the adoption and implementation of the recommendations of ISO for the minimization of toxic hazard from fires involving electrotechnical products. This part of IEC 60695-7 describes fire effluent toxicity test methods in common use to assess electrotechnical products or materials used in electrotechnical products.

IEC product committees incorporating requirements for the assessment of toxic hazard from fire in product standards should note that *toxic potency* and other measurements of toxicity which are described in this part of IEC 60695 should not be used directly in product specifications. Data from *toxic potency* test methods should only be used as part of a toxic hazard assessment, in conjunction with other product-based reaction to fire data such as mass loss rate.

¹ Numbers in square brackets refer to the bibliography.

FIRE HAZARD TESTING –

Part 7-2: Toxicity of fire effluent – Summary and relevance of test methods

1 Scope

This part of IEC 60695-7 gives a brief summary of the test methods that are in common use in the assessment of the toxicity of fire effluent. It includes special observations on their relevance to real fire scenarios and gives recommendations on their use.

It advises which tests provide *toxic potency* data that are relevant to real fire scenarios, and which are suitable for use in fire hazard assessment and fire safety engineering.

The list of test methods is not to be considered exhaustive.

This summary cannot be used in place of published standards which are the only valid reference documents.

This basic safety publication is intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications. The requirements, test methods or test conditions of this basic safety publication will not apply unless specifically referred to or included in the relevant publications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60695-1-10, *Fire hazard testing - Part 1-10: Guidance for assessing the fire hazard of electrotechnical products - General guidelines*

IEC 60695-7-1, *Fire hazard testing - Part 7-1: Toxicity of fire effluent - General guidance*

IEC 60695-7-3, *Fire hazard testing - Part 7-3: Toxicity of fire effluent - Use and interpretation of test results*

IEC GUIDE 104, *The preparation of safety publications and the use of basic safety publications and group safety publications*

ISO/IEC Guide 51, *Safety aspects – Guidelines for their inclusion in standards*

ISO 13943:2017, *Fire safety – Vocabulary*

ISO 13344, *Estimation of the lethal toxic potency of fire effluents*

ISO 13571:2007, *Life-threatening components of fire – Guidelines for the estimation of time available for escape using fire data*

ISO/TR 16312-2, *Guidance for assessing the validity of physical fire models for obtaining fire effluent toxicity data for fire hazard and risk assessment – Part 2: Evaluation of individual physical fire models*

ISO 19706, *Guidelines for assessing the fire threat to people*

ISO 29903:2012, *Guidance for comparison of toxic gas data between different physical fire models and scales*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13943:2017, some of which are reproduced below for the user's convenience, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

acute toxicity

toxicity that causes rapidly occurring toxic effects

Note 1 to entry: Compare with the term *toxic potency* (3.16).

[ISO 13943:2017, definition 3.8]

3.2

asphyxiant

toxicant (3.17) that causes hypoxia, which can result in central nervous system depression or cardiovascular effects

Note 1 to entry: Loss of consciousness and ultimately death may occur.

[ISO 13943:2017, definition 3.23]

3.3

concentration

mass of a dispersed or dissolved material in a given volume

Note 1 to entry: For a fire effluent the typical unit is $\text{g} \cdot \text{m}^{-3}$.

Note 2 to entry: For toxic gas, concentration is usually expressed as a *volume fraction* (3.18) at $T = 298 \text{ K}$ and $P = 1 \text{ atm}$, with typical units of $\mu\text{L/L}$ ($= \text{cm}^3/\text{m}^3 = 10^{-6}$).

Note 3 to entry: The concentration of a gas at a temperature, T , and a pressure, P , can be calculated from its volume fraction (assuming ideal gas behaviour) by multiplying the volume fraction by the density of the gas at that temperature and pressure.

Note 4 to entry: Pascal (Pa) is the SI unit for pressure; however, atmosphere (atm) is typically used in this context, where $1 \text{ atm} = 101,3 \text{ kPa}$.

[ISO 13943:2017, definition 3.62]

3.4 effective concentration 50

*EC*₅₀

concentration (3.3) of a toxic gas or fire effluent, statistically calculated from concentration-response data, that causes a specified effect in 50 % of a population of a given species within a specified exposure time and post-exposure time

Note 1 to entry: Compare with the term *IC*₅₀ (ISO 13943:2017, 3.211).

Note 2 to entry: For fire effluent, the typical unit is g × m⁻³.

Note 3 to entry: For toxic gas, the typical unit is µL/L (*T* = 298 K and *P* = 1 atm); see *volume fraction* (3.18).

Note 4 to entry: The observed effect is usually a behavioural response, *incapacitation* (3.8), or death. The *EC*₅₀ for incapacitation is termed the *IC*₅₀. The *EC*₅₀ for lethality is termed the *LC*₅₀ (3.11).

3.5 exposure dose

measure of the maximum amount of a toxic gas or fire effluent that is available for inhalation, calculated by integration of the area under a *concentration*-time curve

Note 1 to entry: For fire effluent, the typical unit is g × min × m⁻³.

Note 2 to entry: For toxic gas, the typical unit is µL × min × L⁻¹ (*T* = 298 K and *P* = 1 atm); see *volume fraction* (3.18).

[ISO 13943:2017, definition 3.107]

3.6 fractional effective concentration

FEC

ratio of the *concentration* (3.3) of an *irritant* (3.9) to that concentration expected to produce a specified effect on an exposed subject of average susceptibility

Note 1 to entry: Compare with the term *F* factor (ISO 13943:2017, 3.112).

Note 2 to entry: As a concept, *FEC* may refer to any effect, including *incapacitation* (3.8), lethality or other endpoints.

Note 3 to entry: When not used with reference to a specific irritant, the term *FEC* represents the summation of *FEC* values for all irritants in a fire-generated atmosphere.

Note 4 to entry: The *FEC* is dimensionless.

[ISO 13943:2017, definition 3.187]

3.7 fractional effective dose

FED

ratio of the *exposure dose* (3.5) for an *asphyxiant* (3.2) to that exposure dose of the asphyxiant expected to produce a specified effect on an exposed subject of average susceptibility

Note 1 to entry: As a concept, *FED* may refer to any effect, including *incapacitation* (3.8), lethality or other endpoints.

Note 2 to entry: When not used with reference to a specific asphyxiant, the term *FED* represents the summation of *FED* values for all asphyxiants in a combustion atmosphere.

Note 3 to entry: The *FED* is dimensionless.

[ISO 13943:2017, definition 3.188]

3.8 incapacitation

state of physical inability to accomplish a specific task

Note 1 to entry: An example of a specific task is to accomplish escape from a fire.

[ISO 13943:2017, definition 3.225]

3.9

irritant, noun

<sensory/upper respiratory> gas or aerosol that stimulates nerve receptors in the eyes, nose, mouth, throat and respiratory tract, causing varying degrees of discomfort and pain with the initiation of numerous physiological defence responses

Note 1 to entry: Physiological defence responses include reflex eye closure, tear production, coughing, and bronchoconstriction.

[ISO 13943:2017, definition 3.237]

3.10

irritant, noun

<pulmonary> gas or aerosol that stimulates nerve receptors in the lower respiratory tract, which may result in breathing discomfort

Note 1 to entry: Examples of breathing discomfort are dyspnoea and an increase in respiratory rate. In severe cases, pneumonitis or pulmonary oedema (which may be fatal) may occur some hours after exposure.

[ISO 13943:2017, definition 3.238]

3.11

lethal concentration 50

LC_{50}

concentration (3.3) of a toxic gas or fire effluent, statistically calculated from concentration-response data, that causes death of 50 % of a population of a given species within a specified exposure time and post-exposure time

Note 1 to entry: Compare with the term *effective concentration 50* (3.4).

Note 2 to entry: For fire effluent, the typical unit is $\text{g} \times \text{m}^{-3}$.

Note 3 to entry: For toxic gas, the typical unit is $\mu\text{L/L}$ ($T = 25\text{ }^{\circ}\text{C}$ and $P = 1\text{ atm}$; see *volume fraction* (3.18)).

[ISO 13943:2017, definition 3.241]

3.12

lethal exposure dose 50

LCt_{50}

product of LC_{50} (3.11) and the exposure time over which it was determined

Note 1 to entry: Compare with the terms *concentration* (3.3), *effective exposure dose 50* (ISO 13943:2017, 3.87), *exposure dose* (3.5) and *lethal exposure time 50* (ISO 13943:2017, 3.243).

Note 2 to entry: LCt_{50} is a measure of *lethal toxic potency* (3.13).

Note 3 to entry: For fire effluent, the typical unit is $\text{g} \cdot \text{min} \cdot \text{m}^{-3}$.

Note 4 to entry: For toxic gas, the typical unit is $\mu\text{L} \cdot \text{min} \cdot \text{L}^{-1}$ ($T = 25\text{ }^{\circ}\text{C}$ and $P = 1\text{ atm}$); see *volume fraction* (3.18).

[ISO 13943:2017, definition 3.242]

3.13

lethal toxic potency

toxic potency (3.16) where the specific toxic effect is death