



BSI Standards Publication

Industrial communication networks - Fieldbus specifications

Part 3-21: Data-link layer service definition - Type 21 elements

National foreword

This British Standard is the UK implementation of EN IEC 61158-3-21:2019. It is identical to IEC 61158-3-21:2019. It supersedes BS EN 61158-3-21:2012, which will be withdrawn on 29 May 2022.

The UK participation in its preparation was entrusted to Technical Committee GEL/65/3, Industrial communications: process measurement and control, including fieldbus.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 539 04848 3

ICS 35.100.20; 35.110; 25.040.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2019.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

**Industrial communication networks - Fieldbus specifications -
Part 3-21: Data-link layer service definition - Type 21 elements
(IEC 61158-3-21:2019)**

Réseaux de communication industriels - Spécifications des
bus de terrain - Partie 3-21: Définition des services de
couche liaison de données - Eléments de Type 21
(IEC 61158-3-21:2019)

Industrielle Kommunikationsnetze - Feldbusse - Teil 3-21:
Dienstfestlegungen des Data Link Layer
(Sicherheitsschicht) - Typ 21-Elemente
(IEC 61158-3-21:2019)

This European Standard was approved by CENELEC on 2019-05-29. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 65C/945/FDIS, future edition 2 of IEC 61158-3-21, prepared by SC 65C "Industrial networks" of IEC/TC 65 "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61158-3-21:2019.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2020-02-29
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2022-05-29

This document supersedes EN 61158-3-21:2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61158-3-21:2019 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61158-1:2019	NOTE Harmonized as EN IEC 61158-1:2019 (not modified)
IEC 61158-5-21:2019	NOTE Harmonized as EN IEC 61158-5-21:2019 (not modified)
IEC 61784-2:2019	NOTE Harmonized as EN IEC 61784-2:2019 (not modified)
IEC 61918:2018	NOTE Harmonized as EN IEC 61918:2018 (not modified)

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ISO/IEC 7498-1	-	Information technology - Open Systems-Interconnection - Basic reference model: The basic model		-
ISO/IEC 7498-3	-	Information technology - Open Systems-Interconnection - Basic Reference Model: Naming and addressing		-
ISO/IEC 10731	-	Information technology - Open Systems-Interconnection - Basic Reference Model - Conventions for the definition of OSI services		-
ISO/IEC/IEEE 8802-3		Standard for Ethernet	-	-

This page deliberately left blank

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
1.1 Overview.....	8
1.2 Specifications	8
1.3 Conformance	8
2 Normative references	9
3 Terms, definitions, symbols, abbreviations, and conventions	9
3.1 Reference model terms and definitions	9
3.2 Service convention terms and definitions	11
3.3 Common data-link service terms and definitions	12
3.4 Additional Type 21 data-link specific definitions	15
3.5 Common symbols and abbreviations	15
3.6 Additional Type 21 symbols and abbreviations	16
3.7 Common conventions.....	16
3.8 Additional Type 21 conventions.....	17
4 Data-link layer services and concepts.....	17
4.1 General.....	17
4.1.1 Overview	17
4.1.2 Overview of full duplex flow control.....	17
4.1.3 Types and classes of DL-layer service.....	18
4.2 Detailed description of the data service.....	21
4.2.1 General	21
4.2.2 Sequence of primitives	21
4.2.3 Transmit/receive data	22
4.3 Detailed description of the sporadic data service	23
4.3.1 General	23
4.3.2 Sequence of Primitive.....	24
4.3.3 Transmit/receive sporadic data	24
4.4 Detailed description of network control message service.....	25
4.4.1 General	25
4.4.2 Sequence of Primitives	25
4.4.3 Transmit/receive network control message	25
5 Data-link management services	28
5.1 General.....	28
5.2 Data link management service (DLMS) facilities.....	28
5.3 Data link management service (DLMS)	28
5.3.1 Overview	28
5.3.2 Reset.....	29
5.3.3 Set-value	29
5.3.4 Get-value.....	29
5.3.5 SAP-allocation	29
5.3.6 SAP-deallocation	29
5.3.7 Get-SAP information.....	29
5.3.8 Get-diagnostic-information.....	29
5.3.9 Event.....	29

5.3.10	Get-path	29
5.4	Overview of interactions.....	29
5.5	Detailed specification of service and interactions	31
5.5.1	Reset.....	31
5.5.2	Set-value	31
5.5.3	Get-value.....	32
5.5.4	SAP-allocation	33
5.5.5	SAP-deallocation	34
5.5.6	Get-SAP-information.....	35
5.5.7	Get-diagnostic-information.....	36
5.5.8	Event.....	37
5.5.9	Get-path	38
6	MAC control service	39
6.1	General.....	39
6.2	MAC control service.....	39
6.2.1	Overview	39
6.2.2	MAC-reset	39
6.2.3	MAC-forward-control.....	39
6.3	Overview of interactions.....	39
6.4	Detailed specification of service and interactions	40
6.4.1	MAC-reset	40
6.4.2	MAC-forward-control.....	41
7	Ph-control service.....	42
7.1	General.....	42
7.2	Ph-control service	42
7.2.1	Overview	42
7.2.2	Ph-reset	42
7.2.3	Ph-get-link-status	42
7.2.4	Ph-link-status-change	42
7.3	Overview of interactions.....	42
7.4	Detailed specification of service and interactions	43
7.4.1	Ph-reset	43
7.4.2	Ph-get-link-status	44
7.4.3	Ph-link-status-change	45
	Bibliography.....	46
	Figure 1 – Full-duplex flow control	18
	Figure 2 – Sequence diagram of DL-DATA service	18
	Figure 3 – Sequence diagram of DL-SPDATA service	19
	Figure 4 – Sequence diagram of NCM service primitive	19
	Figure 5 – Relationships of DLSAPs, DLSAP-addresses, and group DL-addresses	20
	Figure 6 – DL-DATA service	21
	Figure 7 – Sequence diagram of Reset, Set-value, Get-value, SAP-allocation, SAP-deallocation, Get-SAP information and Get-diagnostic information service primitives	30
	Figure 8 – Sequence diagram of Event service primitive	31
	Figure 9 – Sequence diagram of MAC-reset and MAC-forward-control service primitive	40
	Figure 10 – Sequence diagram of Ph-reset and Ph-get-link-status service primitive	43

Figure 11 – Sequence diagram of Ph-link-status-change service primitive	43
---	----

Table 1 – Destination DL-address	20
Table 2 – Primitives and parameters used in DL-DATA service	22
Table 3 – DL-DATA Primitives and Parameters	22
Table 4 – Primitives and parameters used in DL-SPDATA service	24
Table 5 – DL-SPDATA Primitives and Parameters	24
Table 6 – Primitives and parameters used on DL-NCM_SND service	25
Table 7 – DL-NCM_SND Primitives and Parameters	26
Table 8 – Summary of Network Control Message Type	27
Table 9 – Summary of DL-management primitives and parameters	30
Table 10 – DLM-RESET primitives and parameters	31
Table 11 – DLM-SET_VALUE primitives and parameters	32
Table 12 – DLM-GET_VALUE primitives and parameters	33
Table 13 – DLM-SAP_ALLOC primitives and parameters	34
Table 14 – DLM-SAP_DEALLOC primitives and parameters	35
Table 15 – DLM-GET_SAP_INFO primitives and parameters	35
Table 16 – DLM-GET_DIAG primitives and parameters	36
Table 17 – DLM-EVENT primitives and parameters	37
Table 18 – DLM event identifier	38
Table 19 – DLM-GET_PATH primitives and parameters	38
Table 20 – Summary of MAC control primitives and parameters	40
Table 21 – MAC-RESET primitives and parameters	40
Table 22 – MAC-FW_CTRL primitives and parameters	41
Table 23 – Summary of Ph-control primitives and parameters	42
Table 24 – Ph-RESET primitives and parameters	43
Table 25 – Ph-GET_LINK_STATUS primitives and parameters	44
Table 26 – Ph-LINK_STATUS_CHANGE primitives and parameters	45

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 3-21: Data-link layer service definition –
Type 21 elements****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

Attention is drawn to the fact that the use of the associated protocol type is restricted by its intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a layer protocol type to be used with other layer protocols of the same type, or in other type combinations explicitly authorized by its intellectual-property-right holders.

NOTE Combinations of protocol types are specified in IEC 61784-1 and IEC 61784-2.

International Standard IEC 61158-3-21 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- added Network Control Message Type;
- miscellaneous editorial corrections.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
65C/945/FDIS	65C/954/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61158 series, published under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

This document is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC 61158-1.

Throughout the set of fieldbus standards, the term “service” refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the data-link layer service defined in this document is a conceptual architectural service, independent of administrative and implementation divisions.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 3-21: Data-link layer service definition – Type 21 elements

1 Scope

1.1 Overview

This part of IEC 61158 provides the common elements for basic time-critical messaging communications between devices in an automation environment. The term “time-critical” in this context means the prioritized full-duplex collision-free time-deterministic communication, of which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the required time risks the failure of the applications requesting the actions, with attendant risk to equipment, plant, and possibly human life.

This International Standard defines in an abstract way the externally visible service provided by the Type 21 data-link layer in terms of:

- a) the primitive actions and events of the service;
- b) the parameters associated with each primitive action and event, and the form that they take; and
- c) the interrelationships between these actions and events, and their valid sequences.

The purpose of this document is to define the services provided to:

- The Type 21 application layer at the boundary between the application and DLLs of the fieldbus reference model;
- Systems management at the boundary between the DLL and the systems management of the fieldbus reference model.

1.2 Specifications

The principal objective of this document is to specify the characteristics of conceptual DLL services suitable for time-critical communications, and to supplement the OSI Basic Reference Model in guiding the development of data link protocols for time-critical communications. A secondary objective is to provide migration paths from previously existing industrial communications protocols.

This document may be used as the basis for formal data link programming interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this document, including:

- a) The sizes and octet ordering of various multi-octet service parameters;
- b) The correlation of paired primitives for request and confirm, or indication and response.

1.3 Conformance

This document does not specify individual implementations or products, nor do they constrain the implementations of data-link entities within industrial automation systems.

There is no conformance of equipment to this data-link layer service definition document. Instead, conformance is achieved through implementation of the corresponding data-link protocol that fulfils the Type 21 DLL services defined in this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE All parts of the IEC 61158 series, as well as IEC 61784-1 and IEC 61784-2 are maintained simultaneously. Cross-references to these documents within the text therefore refer to the editions as dated in this list of normative references.

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC/IEEE 8802-3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Standard for Ethernet*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

3 Terms, definitions, symbols, abbreviations, and conventions

For the purposes of this document, the following terms, definitions, symbols, abbreviations and conventions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 Reference model terms and definitions

This document is based in part on the concepts developed in ISO/IEC 7498-1 and ISO/IEC 7498-3, and makes use of the following terms defined therein.

3.1.1	DL-address	[ISO/IEC 7498-3]
3.1.2	DL-address-mapping	[ISO/IEC 7498-1]
3.1.3	called-DL-address	[ISO/IEC 7498-3]
3.1.4	calling-DL-address	[ISO/IEC 7498-3]
3.1.5	centralized multi-end-point-connection	[ISO/IEC 7498-1]
3.1.6	DL-connection	[ISO/IEC 7498-1]
3.1.7	DL-connection-end-point	[ISO/IEC 7498-1]
3.1.8	DL-connection-end-point-identifier	[ISO/IEC 7498-1]
3.1.9	DL-connection-mode transmission	[ISO/IEC 7498-1]
3.1.10	DL-connectionless-mode transmission	[ISO/IEC 7498-1]
3.1.11	correspondent (N)-entities correspondent DL-entities (N=2) correspondent Ph-entities (N=1)	[ISO/IEC 7498-1]
3.1.12	DL-duplex-transmission	[ISO/IEC 7498-1]
3.1.13	(N)-entity DL-entity (N=2) Ph-entity (N=1)	[ISO/IEC 7498-1]
3.1.14	DL-facility	[ISO/IEC 7498-1]
3.1.15	flow control	[ISO/IEC 7498-1]
3.1.16	(N)-layer DL-layer (N=2) Ph-layer (N=1)	[ISO/IEC 7498-1]
3.1.17	layer-management	[ISO/IEC 7498-1]
3.1.18	DL-local-view	[ISO/IEC 7498-3]
3.1.19	DL-name	[ISO/IEC 7498-3]
3.1.20	naming-(addressing)-domain	[ISO/IEC 7498-3]
3.1.21	peer-entities	[ISO/IEC 7498-1]
3.1.22	primitive name	[ISO/IEC 7498-3]
3.1.23	DL-protocol	[ISO/IEC 7498-1]
3.1.24	DL-protocol-connection-identifier	[ISO/IEC 7498-1]
3.1.25	DL-protocol-data-unit	[ISO/IEC 7498-1]
3.1.26	DL-relay	[ISO/IEC 7498-1]
3.1.27	Reset	[ISO/IEC 7498-1]
3.1.28	responding-DL-address	[ISO/IEC 7498-3]
3.1.29	Routing	[ISO/IEC 7498-1]
3.1.30	Segmenting	[ISO/IEC 7498-1]
3.1.31	(N)-service DL-service (N=2) Ph-service (N=1)	[ISO/IEC 7498-1]

3.1.32	(N)-service-access-point	[ISO/IEC 7498-1]
	DL-service-access-point (N=2)	
	Ph-service-access-point (N=1)	
3.1.33	DL-service-access-point-address	[ISO/IEC 7498-3]
3.1.34	DL-service-connection-identifier	[ISO/IEC 7498-1]
3.1.35	DL-service-data-unit	[ISO/IEC 7498-1]
3.1.36	DL-simplex-transmission	[ISO/IEC 7498-1]
3.1.37	DL-subsystem	[ISO/IEC 7498-1]
3.1.38	systems-management	[ISO/IEC 7498-1]
3.1.39	DLS-user-data	[ISO/IEC 7498-1]

3.2 Service convention terms and definitions

This document also makes use of the following terms defined in ISO/IEC 10731 as they apply to the data-link layer.

3.2.1	acceptor
3.2.2	asymmetrical service
3.2.3	confirm (primitive); requestor.deliver (primitive)
3.2.4	deliver (primitive)
3.2.5	DL-confirmed-facility
3.2.6	DL-facility
3.2.7	DL-local-view
3.2.8	DL-mandatory-facility
3.2.9	DL-non-confirmed-facility
3.2.10	DL-protocol-machine
3.2.11	DL-provider-initiated-facility
3.2.12	DL-provider-optional-facility
3.2.13	DL-service-primitive; primitive
3.2.14	DL-service-provider
3.2.15	DL-service-user
3.2.16	DLS-user-optional-facility
3.2.17	indication (primitive); acceptor.deliver (primitive)
3.2.18	multi-peer
3.2.19	request (primitive); requestor.submit (primitive)
3.2.20	requestor