BS EN IEC 61340-4-4:2018

BSI Standards Publication

Electrostatics

Part 4-4: Standard test methods for specific applications - Electrostatic classification of flexible intermediate bulk containers (FIBC)

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

National foreword

This British Standard is the UK implementation of EN IEC 61340-4-4:2018. It is identical to IEC 61340-4-4:2018. It supersedes BS EN 61340-4-4:2012+A1:2015, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee GEL/101, Electrostatics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 95656 0

ICS 29.020; 17.220.99; 55.080

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2018.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

EN IEC 61340-4-4

April 2018

ICS 17.220.99; 29.020; 55.080

Supersedes EN 61340-4-4:2012

English Version

Electrostatics - Part 4-4: Standard test methods for specific applications - Electrostatic classification of flexible intermediate bulk containers (FIBC) (IEC 61340-4-4:2018)

Electrostatique - Partie 4-4: Méthodes d'essai normalisées pour des applications spécifiques - Classification électrostatique des grands récipients pour vrac souples (GRVS) (IEC 61340-4-4:2018)

Elektrostatik - Teil 4-4: Normprüfverfahren für spezielle Anwendungen - Einordnung flexibler Schüttgutbehälter (FIBC) in elektrostatischer Hinsicht (IEC 61340-4-4:2018)

This European Standard was approved by CENELEC on 2018-03-06. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2018 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Ref. No. EN IEC 61340-4-4:2018 E

AVA Documents Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

European foreword

The text of document 101/546/FDIS, future edition 3 of IEC 61340-4-4, prepared by IEC/TC 101 "Electrostatics" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61340-4-4:2018.

The following dates are fixed:

• latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement	(dop)	2018-12-06
• latest date by which the national standards conflicting with the document have to be withdrawn	(dow)	2021-03-06

This document supersedes EN 61340-4-4:2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61340-4-4:2018 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60079-32-2	NOTE	Harmonized as EN 60079-32-2.
IEC 61340-2-1	NOTE	Harmonized as EN 61340-2-1.

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

Annex ZA
(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

Publication	Year	Title	EN/HD	Year
IEC 60079-10-1	-	Explosive atmospheres - Part 10-1: Classification of areas - Explosive gas atmospheres	EN 60079-10-1	-
IEC 60079-10-2	-	Explosive atmospheres - Part 10-2: Classification of areas - Explosive dust atmospheres	EN 60079-10-2	-
IEC 60243-1	2013	Electric strength of insulating materials - Test methods -- Part 1: Tests at power frequencies	EN 60243-1	2013
IEC 60243-2	-	Electric strength of insulating materials - Test methods - Part 2: Additional requirements for tests using direct voltage	EN 60243-2	-
IEC 60417-DB	-	Graphical symbols for use on equipment	-	-
IEC 61340-2-3	-	Electrostatics - Part 2-3: Methods of test for determining the resistance and resistivity of solid materials used to avoid electrostatic charge accumulation	EN 61340-2-3	-
ISO 7000	-	Graphical symbols for use on equipment - Registered symbols	-	-
ISO 21898	-	Packaging - Flexible intermediate bulk containers (FIBCs) for non-dangerous goods	EN ISO 21898	-
ISO/IEC 80079-20-2	-	Explosive atmospheres - Part 20-2: Material characteristics - Combustible dusts test methods	EN ISO/IEC 80079-20-2	-
ASTM E582	-	Standard test method for minimum ignition energy and quenching distance in gaseous mixtures	-	-

Documents
Document Sharing Hub
Full document details: BS EN IEC 61340-4-4:2018

This page deliberately left blank

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

CONTENTS

FOREWORD 5
INTRODUCTION 7
1 Scope 8
2 Normative references 9
3 Terms and definitions 10
4 Classification 12
4.1 Classification for FIBC 12
4.1.1 Principles of classification 12
4.1.2 Type A 12
4.1.3 Type B 12
4.1.4 Type C 12
4.1.5 Type D 12
4.2 Principles of classification and requirements for inner liners 12
4.2.1 Components of inner liners 12
4.2.2 Surface resistivity measurements for inner liners 13
4.2.3 Breakdown voltage measurements for inner liners 13
4.2.4 Type L1 14
4.2.5 Type L1C 15
4.2.6 Type L2 15
4.2.7 Type L3 16
4.3 Combination of FIBC and inner liners 17
5 Safe use of FIBC 17
6 Labelling 19
7 Requirements for FIBC 22
7.1 General remarks 22
7.2 Requirements for dust environments with ignition energies greater than 3 mJ (apply to Type B FIBC, Type C FIBC and Type D FIBC) 22
7.3 Requirements for vapour and gas atmospheres and for dust environments with ignition energies of 3 mJ or less 23
7.3.1 Type C FIBC 23
7.3.2 Type D FIBC 23
8 Atmosphere for conditioning, calibrating and testing 24
8.1 Conditioning time 24
8.2 Electrical breakdown voltage, surface resistivity and resistance to groundable point testing 24
8.3 Surface resistivity testing 24
8.4 Ignition testing 24
9 Test procedures 24
9.1 Sampling 24
9.2 Electrical breakdown voltage 24
9.3 Ignition testing 25
9.3.1 Apparatus 25
9.3.2 Establishing correct charging current 32
9.3.3 Ignition tests 32
9.4 Resistance to groundable point 35
9.4.1 Apparatus 35

AVA Documents
Document Sharing Hub

9.4.2 Test procedure ... 35
10 Test report ... 36
10.1 General ... 36
10.2 For all types of testing ... 37
10.3 For electrical breakdown voltage testing ... 37
10.4 For ignition testing ... 37
10.5 For resistance to groundable point testing ... 37
10.6 For surface resistivity testing of inner liners, labels and document pockets ... 37
10.7 For test reports issued by accredited testing authorities ... 37
Annex A (informative) Electrical breakdown voltage – Typical voltage/time graphs ... 39
Annex B (normative) Polypropylene pellets for ignition testing ... 40
Annex C (informative) Guidance on test methods for manufacturing quality control ... 41
C.1 Introductory remarks ... 41
C.2 Test methods ... 41
C.2.1 Resistance measurements ... 41
C.2.2 Charge decay measurements ... 42
C.2.3 Charge transfer measurements ... 42
Annex D (normative) Classification of hazardous areas and zones ... 43
Annex E (informative) Risks associated with cone discharges ... 44
Annex F (informative) Explanation for resistance and resistivity limits, and thickness limits for insulating layers of inner liners ... 45
F.1 Resistance to groundable point limit for Type C FIBC ... 45
F.2 Resistivity of inner liners ... 45
F.3 Thickness of insulating layers of inner liners ... 45
Bibliography ... 47

Figure 1 – Examples of inner liners in FIBC ... 13
Figure 2 – Example of a label for Type B FIBC ... 20
Figure 3 – Example of a label for Type C FIBC ... 20
Figure 4 – Example of a label for Type D FIBC ... 21
Figure 5 – Example of labels for Type C FIBC designated earth bonding points ... 21
Figure 6 – Ignition probe ... 26
Figure 7 – Perforated metal plate for use in ignition probe ... 27
Figure 8 – Gas control and mixing apparatus (schematic) ... 28
Figure 9 – FIBC filling rig (schematic) ... 30
Figure 10 – Corona charging unit (schematic) ... 31
Figure A.1 – Example of voltage/time graph for material showing distinct breakdown ... 39
Figure A.2 – Example of voltage/time graph for material showing reduction in rate of voltage rise because of conduction within the test material ... 39

Table 1 – Permissible configurations and requirements for Type L1 inner liners (without conductive internal layers) ... 14
Table 2 – Permissible configurations and requirements for Type L1C inner liners (with conductive internal layers[a]) ... 15
Table 3 – Permissible configurations and requirements for Type L2 inner liners ... 16
Table 4 – Permissible configurations and requirements for Type L3 inner liners ... 17

AVA Documents
Document Sharing Hub
Full document details: BS EN IEC 61340-4-4:2018

Table 5 – Use of different types of FIBC 17
Table 6 – Inner liners and FIBC: combinations that are permissible and not permissible in hazardous explosive atmospheres 18
Table 7 – Volume concentrations of flammable gas mixture 27
Table 8 – Example of full sample description to be included in the test report 38
Table B.1 – Particle size distribution of polypropylene pellets 40
Table D.1 – Classification of hazardous areas in IEC 60079-10-1 and IEC 60079-10-2 43
Table D.2 – Classification of zones in IEC 60079-10-1 and IEC 60079-10-2 43

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROSTATICS –

Part 4-4: Standard test methods for specific applications – Electrostatic classification of flexible intermediate bulk containers (FIBC)

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61340-4-4 has been prepared by IEC technical committee 101: Electrostatics.

This third edition cancels and replaces the second edition, published in 2012, and Amendment 1:2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) in light of experimental evidence, the maximum resistance to ground limit for Type C FIBC, and corresponding resistance limits for inner liners used in Type C FIBC has been increased from $1{,}0 \times 10^7\ \Omega$ to $1{,}0 \times 10^8\ \Omega$;
b) the classification of Type L1 inner liners has been revised and extended to include Type L1C inner liners made from multi-layer materials with a conductive internal layer;

AVA Documents
Document Sharing Hub

c) a labelling requirement to include a reference to IEC TS 60079-32-1 for guidance on earthing has been added.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
101/546/FDIS	101/555/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61340 series, published under the general title *Electrostatics*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

INTRODUCTION

Flexible intermediate bulk containers (FIBC) are widely used for the storage, transportation and handling of powdered, flaked or granular material. Typically, they are constructed from woven polypropylene fabric in the form of cubic bags of about 1 m^3 volume, although they can vary in shape and in size from 0,25 m^3 to 3 m^3. The fabric used may be a single layer, a multi-layer laminate, or a coated fabric. Untreated polypropylene is an electrical insulator, as is often the case with the products placed in FIBC. There is ample opportunity for the generation of electrostatic charge during filling and emptying operations and in unprotected FIBC high levels of charge can quickly build up. In such cases, electrostatic discharges are inevitable and can be a severe problem when FIBC are used in hazardous explosive atmospheres.

A hazardous explosive atmosphere can be generated when handling fine powders that create dust clouds or thin layers of powder, both of which can be ignited by electrostatic discharges. A hazardous explosive atmosphere can also be generated when using gases or volatile solvents. In these industrial situations, there is clearly a need to eliminate incendive electrostatic discharges.

As with any industrial equipment, a thorough risk assessment should always be conducted before using FIBC in potentially hazardous situations. This part of IEC 61340 describes a system of classification, test methods, performance and design requirements and safe use procedures that can be used by manufacturers, specifiers and end-users as part of a risk assessment of any FIBC intended for use within a hazardous explosive atmosphere. However, it does not include procedures for evaluating the specific risks of electrostatic discharges arising from products within FIBC, for example cone discharges, from personnel or from equipment used near FIBC. Information on risks associated with cone discharges is given in Annex E.

CAUTION: The test methods specified in this document involve the use of high voltage power supplies and flammable gases that may present hazards if handled incorrectly, particularly by unqualified or inexperienced personnel. Users of this document are encouraged to carry out proper risk assessments and pay due regard to local regulations before undertaking any of the test procedures.

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

ELECTROSTATICS –

Part 4-4: Standard test methods for specific applications – Electrostatic classification of flexible intermediate bulk containers (FIBC)

1 Scope

This part of IEC 61340 specifies requirements for flexible intermediate bulk containers (FIBC) between 0,25 m^3 and 3 m^3 in volume, intended for use in hazardous explosive atmospheres. The explosive atmosphere can be created by the contents in the FIBC or can exist outside the FIBC.

The requirements include:

– classification and labelling of FIBC;
– classification of inner liners;
– specification of test methods for each type of FIBC, inner liner, labels and document pockets;
– design and performance requirements for FIBC, inner liners, labels and document pockets;
– safe use of FIBC (including those with inner liners) within different zones defined for explosion endangered environments, described for areas where combustible dusts are, or can be, present (IEC 60079-10-2), and for explosive gas atmospheres (IEC 60079-10-1);
– procedures for type qualification and certification of FIBC, including the safe use of inner liners.

NOTE 1 Guidance on test methods that can be used for manufacturing quality control is given in Annex C.

The requirements of this document are applicable to all types of FIBC and inner liners, tested as manufactured, prior to use and intended for use in hazardous explosive atmospheres: Zones 1 and 2 (Groups IIA and IIB only) and Zones 21 and 22 (see Annex D for classification of hazardous areas and explosion groups). For some types of FIBC, the requirements of this document apply only to use in hazardous explosive atmospheres with minimum ignition energy of 0,14 mJ or greater and where charging currents do not exceed 3,0 μA.

NOTE 2

0,14 mJ represents a realistic minimum ignition energy for a Group IIB gas or vapour atmosphere. Although more sensitive materials exist, 0,14 mJ is the lowest minimum ignition energy of any material that is likely to be present when FIBC are emptied. 3,0 μA is the highest charging current likely to be found in common industrial processes. This combination of minimum ignition energy and charging current represents the most severe conditions that might be expected in practice.

FIBC are not normally used in Zone 0 or Zone 20. If FIBC are used in Zone 0 or Zone 20, the requirements of this document are applicable, together with additional requirements that are beyond the scope of this document to define.

The volume contained within FIBC can be designated as Zone 20, in which case the requirements of this document are applicable.

Solids containing residual solvent can result in a hazardous explosive atmosphere within FIBC, possibly resulting in the volume being designated as Zone 1 or Zone 2; in which case the requirements of this document are applicable.

Compliance with the requirements specified in this document does not necessarily ensure that hazardous electrostatic discharges, for example cone discharges, will not be generated within

AVA Documents
Document Sharing Hub

contents in FIBC. Information on the risks associated with cone discharges is given in Annex E.

Compliance with the requirements of this document does not mitigate the need for full risk assessment. For example, metal and other conductive powders and toner powders can require additional precautions to prevent hazardous discharges from the powders.

NOTE 3 In the examples mentioned in the paragraph above, additional precautions can be necessary in the case of metal or other conductive powder because if the powder is isolated and becomes charged, incendiary sparks can occur, and in the case of toner powders, incendiary discharges can occur during rapid filling and emptying operations. IEC TS 60079-32-1 [1][1] gives guidance on additional precautions that can be necessary.

Test methods included in this document can be used in association with other performance requirements, for example when a risk assessment has shown the minimum ignition energy of concern is less than 0,14 mJ, charging currents are greater than 3,0 μA, or the ambient conditions are outside of the range specified in this document.

Compliance with the requirements specified in this document does not necessarily ensure that electric shocks to personnel will not occur from FIBC during normal use.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60079-10-1, *Explosive atmospheres – Part 10-1: Classification of areas – Explosive gas atmospheres*

IEC 60079-10-2, *Explosive atmospheres – Part 10-2: Classification of areas – Explosive dust atmospheres*

IEC 60243-1:2013, *Electric strength of insulating materials – Test methods – Part 1: Tests at power frequencies*

IEC 60243-2, *Electric strength of insulating materials – Test methods – Part 2: Additional requirements for tests using direct voltage*

IEC 60417, *Graphical symbols for use on equipment* (available at: http://www.graphical-symbols.info/equipment)

IEC 61340-2-3, *Electrostatics – Part 2-3: Methods of test for determining the resistance and resistivity of solid materials used to avoid electrostatic charge accumulation*

ISO/IEC 80079-20-2, *Explosive atmospheres – Part 20-2: Material characteristics – Combustible dusts test methods*

ISO 7000, *Graphical symbols for use on equipment – Registered symbols* (available at: http://www.graphical-symbols.info/equipment)

ISO 21898, *Packaging – Flexible intermediate bulk containers (FIBCs) for non-dangerous goods*

[1] Numbers in square brackets refer to the Bibliography.

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

ASTM E582, *Standard test method for minimum ignition energy and quenching distance in gaseous mixtures*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60079-10-1, IEC 60079-10-2 and ISO 21898 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1
multi-layer material
material comprised of more than one layer, the combination of which can be formed by coextrusion, coating, laminating or any other process that permanently bonds all layers together

3.2
quenching
effect of solid objects acting as heat sinks in close proximity to gas

3.3
critical quenching distance
maximum separation distance between opposing electrodes below which quenching prevents ignition at a specified energy

Note 1 to entry: For ignitions to take place, the gap between electrodes is greater than the critical quenching distance.

3.4
flammable substance
substance in the form of gas, vapour, liquid, solid, or mixture of these, capable of propagating combustion when subjected to an ignition source

3.5
explosive atmosphere
mixture with air, under atmospheric conditions, of flammable substances in the form of gases, vapours, mists or dusts in which, after ignition has occurred, combustion spreads to the entire unburned mixture

3.6
hazardous explosive atmosphere
explosive atmosphere present in such quantities that precautions against ignition are required

3.7
minimum ignition energy
MIE
least electrical energy of a purely capacitive spark (i.e. no added inductance) required to ignite a dust, gas or vapour

3.8
charging current
quantity of charge per unit time flowing into FIBC

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

3.9
cone discharge
electrostatic discharge running outwards across the surface from the top of highly charged, insulating powder heaps in large containers

3.10
brush discharge
electrostatic discharge from a non-conductive, solid or liquid surface

3.11
spark
electrostatic discharge from an electrically isolated conductive object or surface

3.12
propagating brush discharge
highly energetic discharge from an insulating sheet, layer or coating on a conductive surface, or a material of high resistivity and high breakdown voltage with the two surfaces highly charged to opposite polarity

3.13
inner liner
liner
integral or removable container which fits into the FIBC

3.14
surface resistivity
resistivity equivalent to the surface resistance of a square area of material having electrodes at two opposite sides

3.15
volume resistivity
resistivity equivalent to the volume resistance of a cube of material with unit length, having the electrodes at two opposite surfaces

3.16
type qualification testing
testing used to determine the type of FIBC as specified in 4.1 and to demonstrate that FIBC meet the requirements of Clause 7

3.17
quality control testing
testing designed to provide manufacturers and users with information that demonstrates all FIBC produced and delivered are substantially the same as the sample FIBC used to qualify the FIBC design

3.18
groundable point
point on FIBC designated by the manufacturer as a location to attach a grounding or earth bonding cable or other means of earthing FIBC

Documents
Document Sharing Hub

Full document details: BS EN IEC 61340-4-4:2018

4 Classification

4.1 Classification for FIBC

4.1.1 Principles of classification

FIBC are classified according to one of four types: Type A, Type B, Type C and Type D. The types are defined by the construction of the FIBC, the nature of their intended operation and associated performance requirements.

An individual design of FIBC may only be classified as one single type; for example one FIBC shall not be simultaneously classified as both Type B and Type D, or as both Type B and Type C, or as Type CD.

4.1.2 Type A

Type A FIBC are made from fabric or plastic sheet without any measures against the build up of static electricity. Any FIBC that does not meet the requirements specified in Clause 7, or which has not been tested against the requirements is classified as Type A.

4.1.3 Type B

Type B FIBC are made from fabric or plastic sheet designed to prevent the occurrence of sparks and propagating brush discharges.

Conductive materials, as used in the manufacture of Type C FIBC for example, shall not be used in the manufacture of Type B FIBC.

NOTE Type B FIBC are not normally connected to earth. Conductive material that is not connected to earth creates a risk of incendiary sparks.

4.1.4 Type C

Type C FIBC are made from conductive fabric or plastic sheet, or interwoven with conductive threads or filaments and designed to prevent the occurrence of incendiary sparks, brush discharges and propagating brush discharges. Type C FIBC are designed to be connected to earth before the commencement of filling and emptying operations and remain connected to earth during these operations.

4.1.5 Type D

Type D FIBC are made from static protective fabric designed to prevent the occurrence of incendiary sparks, brush discharges and propagating brush discharges, without the need for a connection from the FIBC to earth.

4.2 Principles of classification and requirements for inner liners

4.2.1 Components of inner liners

Materials used for inner liners can be single layer, or multi-layered materials. In the latter case, the layers are typically permanently bonded together. Examples of FIBC with a single layer inner liner and with a multi-layer inner liner are shown in Figure 1.

For the purposes of this document, and for both single layer inner liners and multi-layer inner liners, the outside surface of the inner liner is the surface that physically contacts the FIBC, and the inside surface of the inner liner is the surface that physically contacts the product with which the FIBC is filled.

In Figure 1, the multi-layer inner liner is shown as comprising of three layers. In practice, more than three layers can be used. For the purposes of this document, an internal layer is

AVA Documents
Document Sharing Hub