



BSI Standards Publication

Superconductivity

Part 22-3: Superconducting strip photon detector — Dark count rate

National foreword

This British Standard is the UK implementation of EN IEC 61788-22-3:2022. It is identical to IEC 61788-22-3:2022.

The UK participation in its preparation was entrusted to Technical Committee W/-, Consumer Products and Services Sector Policy and Strategy Committee.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2022
Published by BSI Standards Limited 2022

ISBN 978 0 539 02672 6

ICS 17.220; 29.050

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2022.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

Superconductivity - Part 22-3: Superconducting strip photon
detector - Dark count rate
(IEC 61788-22-3:2022)

Supraconductivité - Partie 22-3: Détecteur de photons à
bande supraconductrice - Taux de comptage en obscurité
(IEC 61788-22-3:2022)

Supraleitfähigkeit - Teil 22-3: Supraleitender Streifen-
Photonendetektor - Dunkelzählrate
(IEC 61788-22-3:2022)

This European Standard was approved by CENELEC on 2022-09-23. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 90/489/FDIS, future edition 1 of IEC 61788-22-3, prepared by IEC/TC 90 "Superconductivity" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61788-22-3:2022.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2023-06-23
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2025-09-23

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 61788-22-3:2022 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61788-22-1 NOTE Harmonized as EN 61788-22-1

ISO/TS 80004-2:2015 NOTE Harmonized as CEN ISO/TS 80004-2:2017 (not modified)

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	8
2 Normative references	8
3 Terms, definitions and abbreviated terms	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	10
4 Principle of the measurement method.....	10
5 Apparatus.....	11
5.1 Detector packaging	11
5.2 Cryogenic system	11
5.3 Measurement system.....	13
6 Measurement procedure	14
6.1 Measurement of temperature	14
6.2 Measurement of switching current.....	14
6.3 Measurement of R_D	15
7 Standard uncertainty	16
7.1 Type A uncertainty	16
7.2 Type B uncertainty	16
7.3 Uncertainty budget table	17
7.4 Uncertainty requirement.....	18
8 Test report.....	18
8.1 Identification of device under test (DUT)	18
8.2 Measurement conditions and results	18
8.3 Miscellaneous optional report	19
Annex A (informative) Results of the round robin test.....	20
A.1 DUT packages	20
A.2 Measurement conditions	20
A.3 Measurement results.....	21
Bibliography.....	25
Figure 1 – Example of one dark count pulse in the pulse train in inset	9
Figure 2 – Schematic curve of R_D as a function of normalized bias current.....	11
Figure 3 – Schematic diagram of a typical <i>DCR</i> measurement system.....	12
Figure 4 – Equivalent circuit of the <i>DCR</i> measurement.....	13
Figure 5 – Typical current-voltage (<i>I-U</i>) curve of an SSPD.....	15
Figure A.1 – Photograph of the DUT with an SSPD and a temperature sensor	20
Figure A.2 – <i>I-U</i> curve and R_D curves	22
Table 1 – Uncertainty budget table for R_D	18
Table A.1 – Test data of DUT.....	22
Table A.2 – Temperature sensitivity and bias current sensitivity above a normalized bias current of 0,9.....	23

Table A.3 – u_A and u_B above a normalized bias current of 0,9	23
Table A.4 – Budget table for R_D at a bias point of 5,25 μA ($I_b/I_{SW} = 0,955$)	23
Table A.5 – DCR values measured at a bias point of 5,25 μA ($I_b/I_{SW} = 0,955$)	24
Table A.6 – Temperature measurement	24

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SUPERCONDUCTIVITY –**Part 22-3: Superconducting strip photon detector – Dark count rate****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61788-22-3 has been prepared by IEC technical committee 90: Superconductivity. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
90/489/FDIS	90/491/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 61788 series, published under the general title *Superconductivity*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC 61788-22 (all parts) is a series of International Standards on superconductor electronic devices. Superconductivity enables ultra-sensitive sensing or detection of a variety of measurands. IEC 61788-22-1 [1]¹ lists various types of superconductor sensors and detectors. The strip type in this document is one of them.

A typical fundamental structure of strip type detectors is a meander superconductor line, for example, with a thickness of less than 10 nm, a width of less than 100 nm or a few 100 nm, and a length of a few mm. The structure is in the nanoscale. ISO TS 80004-2:2015 [2] defines the nanoscale as a length range approximately from 1 nm to 100 nm. Because nano-objects have one or two dimensions in the nanoscale, superconductor meander lines are categorized as a nano-object.

The term "nanowire" is frequently used for superconductor meander lines, but it is not recommended in this document. In the ISO vocabulary, a nanowire is defined as an electrically conducting or semi-conducting nanofibre with two external dimensions in the nanoscale, with the third dimension being significantly larger. The two external dimensions of the nanowires are in the nanoscale range, approximately from 1 nm to 100 nm. When the first two dimensions differ significantly, a "nanoplate," "nanoribbon," or "nanotape" shall be used for the meander line shape. However, in the field of electronics, these terms are not common. In addition to the ISO definition of nano-objects, the shape of the superconductor meander lines may not fit the shape of common wires that have a round cross-section. Although there are cases in which a superconductor line shape falls into the category of nanowire (e.g. a superconductor line with a thickness of 10 nm and a width of 100 nm), the theoretical treatment of single photon detection mechanisms still requires "strip" rather than "nanowire": the width is wider than coherence length and thus the superconductor line has a two-dimensional nature. Therefore, IEC 61788-22-1 assigns the word "strip" or "nanostrip" to the meander line shape. According to the nomenclature of the standard, the strip type detector is called superconductor strip photon detector (SSPD) or superconductor nanostrip photon detector (SNSPD). The abbreviated term SSPD is used in this document.

SSPDs are usually cooled down to a temperature well below the critical temperature and current-biased with a bias value close to, but smaller than, its switch current. The photon detection mechanisms can be described by Cooper-pair breaking, leading to hotspot formation or vortex motion, followed by electrothermal feedback creating a resistive region [3], [4]. Although an exact detection model has not been established yet, it is true that photon absorption leads to Cooper pair breaking that creates quasiparticles because the photon energy in a telecommunication wavelength band (~ 1 eV) is typically 2 to 3 orders of magnitude higher than the binding energy of a Cooper pair ($\sim$ meV). The photon absorption may create a normal-conducting local-hotspot in the nanostrip. With an electrothermal feedback process, the normal conducting domain expands across the width of the nanostrip and along the current flow direction, leading to a voltage drop in the superconductor nanostrip. Other possible models are vortex-antivortex depairing, in which two vortices move toward the opposite strip edges, and single vortex crossing. Such vortex motion also creates a voltage drop, which can be followed by resistive domain creation with the same electrothermal feedback mechanism. Because of the resistive domain in the strip, the bias current is diverted to a readout circuit. The normal conducting region will be cooled down rapidly and finally disappear. The above process produces a voltage pulse which corresponds to an event of single photon absorption.

Typical application areas of SSPDs include quantum information, laser communication, light detection and ranging, fluorescence spectroscopy and quantum computing. The SSPDs outperform such single photon detectors as photomultipliers and avalanche photodiodes in performance measures listed in the next paragraph. Due to the increasing needs for ultra-sensitive photon detection in a range of visible to mid-infrared wavelengths, the SSPD market

¹ Figures in square brackets refer to the Bibliography.