



BSI Standards Publication

Fuel cell technologies

Part 7-2: Test methods — Single cell and stack performance tests for solid oxide fuel cells

National foreword

This British Standard is the UK implementation of EN IEC 62282-7-2:2021. It is identical to IEC 62282-7-2:2021. It supersedes PD IEC/TS 62282-7-2:2014, which will be withdrawn on 19 January 2022.

The UK participation in its preparation was entrusted to Technical Committee GEL/105, Fuel cell technologies.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2021
Published by BSI Standards Limited 2021

ISBN 978 0 539 12969 4

ICS 27.070

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2021.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

Fuel cell technologies - Part 7-2: Test methods - Single cell and
stack performance tests for solid oxide fuel cells (SOFCs)
(IEC 62282-7-2:2021)

Technologies des piles à combustible - Partie 7-2:
Méthodes d'essai - Essais de performance de cellule
élémentaire et de pile pour les piles à combustible à oxyde
solide (SOFC)
(IEC 62282-7-2:2021)

Brennstoffzellentechnologien - Teil 7-2: Prüfverfahren -
Prüfungen zum Nachweis des Einzelzellen- und
Stackleistungsverhaltens von Festoxid-Brennstoffzellen
(SOFC)
(IEC 62282-7-2:2021)

This European Standard was approved by CENELEC on 2021-06-25. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 105/847/FDIS, future edition 1 of IEC 62282-7-2, prepared by IEC/TC 105 "Fuel cell technologies" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62282-7-2:2021.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2022-03-25
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2024-06-25

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62282-7-2:2021 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60352 (series)	NOTE	Harmonized as EN 60352 (series)
IEC 60359	NOTE	Harmonized as EN 60359
IEC 60512-1-1	NOTE	Harmonized as EN 60512-1-1
IEC 60512-8-1	NOTE	Harmonized as EN 60512-8-1
IEC 60512-8-2	NOTE	Harmonized as EN 60512-8-2
IEC 62282-2-100	NOTE	Harmonized as EN IEC 62282-2-100
IEC 62282-8-101	NOTE	Harmonized as EN IEC 62282-8-101

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60050-485	-	International Electrotechnical Vocabulary (IEV) - Part 485: Fuel cell technologies	-	-
IEC 60584-1	-	Thermocouples - Part 1: EMF specifications and tolerances	EN 60584-1	-
IEC 60584-3	-	Thermocouples - Part 3: Extension and compensating cables - Tolerances and identification system	EN IEC 60584-3	-
IEC 61515	-	Mineral insulated metal-sheathed thermocouple cables and thermocouples	EN 61515	-
ISO 5168	-	Measurement of fluid flow - Procedures for the evaluation of uncertainties	-	-
ISO 6141	-	Gas analysis - Contents of certificates for calibration gas mixtures	EN ISO 6141	-
ISO 6142-1	-	Gas analysis - Preparation of calibration gas mixtures - Part 1: Gravimetric method for Class I mixtures	EN ISO 6142-1	-
ISO 6143	-	Gas analysis - Comparison methods for determining and checking the composition of calibration gas mixtures	EN ISO 6143	-
ISO 6145-7	-	Gas analysis - Preparation of calibration gas mixtures using dynamic methods - Part 7: Thermal mass-flow controllers	EN ISO 6145-7	-
ISO 6974	series	Natural gas - Determination of composition with defined uncertainty by gas chromatography	EN ISO 6974	series
ISO 7066-2	-	Assessment of uncertainty in the calibration and use of flow measurement devices - Part 2: Non-linear calibration relationships	-	-
ISO 8573-1	-	Compressed air - Part 1: Contaminants and purity classes	-	-

EN IEC 62282-7-2:2021 (E)

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ISO 8756	-	Air quality; handling of temperature, pressure and humidity data	-	-
ISO 12185	-	Crude petroleum and petroleum products - Determination of density - Oscillating U-tube method	EN ISO 12185	-

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and symbols.....	8
3.1 Terms and definitions.....	8
3.2 Symbols.....	10
4 General safety conditions	11
5 Cell/stack assembly unit	11
6 Testing system	12
6.1 Subsystems in testing system	12
6.2 Maximum variation in control items of testing system	13
7 Instruments and measurement methods	14
7.1 General.....	14
7.2 Instrument uncertainty	14
7.3 Anode gas	14
7.4 Cathode gas	17
7.5 Output voltage	18
7.6 Output current.....	18
7.7 Cell/stack assembly unit temperature.....	18
7.8 Mechanical load.....	18
7.9 Total impedance	18
7.10 Ambient conditions.....	19
8 Test preparation	19
8.1 General.....	19
8.2 Standard test conditions and test range	19
8.3 Components and impurities of anode gas and cathode gas	20
8.4 Basis of the test procedure	20
8.5 Confirmation of aging conditions of unit	20
8.6 Confirmation of criteria of stable state.....	20
8.7 Data acquisition method.....	20
9 Test procedure	20
9.1 Set-up.....	20
9.2 Initial conditioning	21
9.3 Shut-down	21
10 Performance test	21
10.1 Rated power test.....	21
10.2 Current-voltage characteristics test.....	22
10.3 Effective fuel utilization dependency test	23
10.4 Long term durability test	24
10.5 Thermal cycling durability test.....	25
10.6 Internal reforming performance test	26
10.7 Resistance components identification test.....	27
11 Test report.....	28
11.1 General.....	28

11.2	Report items	28
11.3	Test unit data description	29
11.4	Test conditions description	29
11.5	Test data description	29
11.6	Uncertainty evaluation	29
Annex A (informative) Example of cell assembly unit		30
Annex B (informative) Calculation of effective fuel utilization		31
B.1	General	31
B.2	Calculation method	31
B.3	Calculation examples	32
Annex C (informative) Calculation of effective oxygen utilization		34
C.1	General	34
C.2	Calculation method	34
C.3	Calculation example	35
Annex D (informative) Maximum width of the voltage hysteresis in <i>I-V</i> characteristics test ...		36
Annex E (informative) Current-voltage characteristics test under constant effective fuel utilization		37
Annex F (informative) Test report (template)		38
F.1	Overview	38
F.2	General information	38
F.3	Test unit data description	38
F.4	Test conditions	39
F.5	Rated power test	39
F.6	Current-voltage characteristics test	39
F.7	Effective fuel utilization dependency test	40
F.8	Long-term durability test	41
F.9	Thermal cycling durability test	42
F.10	Internal reforming performance test	42
F.11	Resistance components identification test	43
Annex G (informative) Method for determining instrument uncertainty		44
Bibliography		45
Figure 1 – Testing system		12
Figure 2 – Typical diagram of complex impedance plot for SOFC		28
Figure A.1 – Example of cell assembly unit		30
Figure D.1 – Voltage hysteresis at a given sweep rate in <i>I-V</i> characteristics test		36
Figure E.1 – Example of the record in current-voltage characteristics test under constant effective fuel utilization		37
Table 1 – Symbols		10
Table B.1 – η_j for representative fuels		32
Table B.2 – Anode gas composition, flow rate of each fuel component q_j , and $\eta_j q_j$		32
Table C.1 – Cathode gas composition, q_{O_2} , and I_{theory}		35

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FUEL CELL TECHNOLOGIES –

**Part 7-2: Test methods – Single cell and
stack performance tests for solid oxide fuel cells (SOFCs)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62282-7-2 has been prepared by IEC technical committee 105: Fuel cell technologies. It is an International Standard.

This first edition cancels and replaces IEC TS 62282-7-2 published in 2014.

This edition includes the following significant technical changes with respect to IEC TS 62282-7-2:2014:

- a) users can substitute selected test methods of this document with equivalent test methods of IEC 62282-8-101 for solid oxide cell (SOC) operation for energy storage purposes, operated in reverse or reversible mode;
- b) terms and definitions are aligned with the corresponding terms and definitions in IEC 62282-8-101;
- c) symbols are aligned with the corresponding symbols in IEC 62282-8-101.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
105/847/FDIS	105/851/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 62282 series, published under the general title *Fuel cell technologies*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This part of IEC 62282 specifies test methods for a single cell and stack (denoted as "cell/stack" hereafter) that is required in power generation systems using solid oxide fuel cells (SOFCs).

SOFCs have a broad range of geometry and size. As such, in general, peripherals like current collectors and gas manifolds are unique to each cell or stack and are often incorporated into a cell or stack to form one integrated unit. In addition, they tend to have a significant effect on the power generation characteristics of the cell or stack. This document therefore introduces as its subject "cell/stack assembly units", which are defined as those units containing not only a cell or stack but also peripherals.

FUEL CELL TECHNOLOGIES –

Part 7-2: Test methods – Single cell and stack performance tests for solid oxide fuel cells (SOFCs)

1 Scope

This part of IEC 62282 applies to SOFC cell/stack assembly units, testing systems, instruments and measuring methods, and specifies test methods to test the performance of SOFC cells and stacks.

This document is not applicable to small button cells that are designed for SOFC material testing and provide no practical means of fuel utilization measurement.

This document is used based on the recommendation of the entity that provides the cell performance specification or for acquiring data on a cell or stack in order to estimate the performance of a system based on it. Users of this document can selectively execute test items suitable for their purposes from those described in this document.

Users can substitute selected test methods of this document with equivalent test methods of IEC 62282-8-101 for solid oxide cell (SOC) operation for energy storage purposes, operated in reverse or reversible mode.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-485, *International Electrotechnical Vocabulary (IEV) – Part 485: Fuel cell technologies* (available at <http://www.electropedia.org>)

IEC 60584-1, *Thermocouples – Part 1: EMF specifications and tolerances*

IEC 60584-3, *Thermocouples – Part 3: Extension and compensating cables – Tolerances and identification system*

IEC 61515, *Mineral insulated metal-sheathed thermocouple cables and thermocouples*

ISO 5168, *Measurement of fluid flow – Procedures for the evaluation of uncertainties*

ISO 6141, *Gas analysis – Contents of certificates for calibration gas mixtures*

ISO 6142-1, *Gas analysis – Preparation of calibration gas mixtures – Gravimetric method for Class I mixtures*

ISO 6143, *Gas analysis – Comparison methods for determining and checking the composition of calibration gas mixtures*

ISO 6145-7, *Gas analysis – Preparation of calibration gas mixtures using dynamic methods – Part 7: Thermal mass-flow controllers*

ISO 6974 (all parts), *Natural gas – Determination of composition with defined uncertainty by gas chromatography*

ISO 7066-2, *Assessment of uncertainty in the calibration and use of flow measurement devices – Part 2: Non-linear calibration relationships*

ISO 8573-1, *Compressed air – Part 1: Contaminants and purity classes*

ISO 8756, *Air quality – Handling of temperature, pressure and humidity data*

ISO 12185, *Crude petroleum and petroleum products – Determination of density – Oscillating U-tube method*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-485 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1

cell/stack assembly unit

unit including a single cell or stack, as well as gas supply parts, current collector parts, and any other peripherals as required for power generation tests

3.1.2

active electrode area

geometric electrode area upon which an electrochemical reaction occurs

Note 1 to entry: Usually this is the smaller of the anode and cathode areas.

3.1.3

current density

current divided by the active electrode area

3.1.4

average repeating unit voltage

cell/stack assembly unit voltage divided by the number of the cells in a series connection in the unit

3.1.5

standard temperature and pressure

STP

temperature of 0 °C and an absolute pressure of 101,325 kPa, respectively

3.1.6

anode gas

gas that is supplied to the inlet of the anode of a single cell/stack assembly unit

Note 1 to entry: Such a gas belongs to one of the following categories:

- a) pure hydrogen or mixture that contains hydrogen as a principal component with water vapour or nitrogen

- b) reformed gas of raw fuel of SOFC such as methane or kerosene premixed with water vapour or air as oxidant;
- c) simulated gas of reformat that contains hydrogen, water vapour, carbon monoxide, carbon dioxide, methane, nitrogen, etc., as main components;
- d) methane, alcohols and other raw fuels directly supplied in pure form or mixed with water vapour and/or air.

3.1.7

cathode gas

gas that is supplied to the inlet of the cathode of a single cell/stack assembly unit

Note 1 to entry: Oxygen and nitrogen are its main components.

3.1.8

current collector

conductive material in a fuel cell that collects electrons from the anode side or conducts electrons to the cathode side

3.1.9

stable state

condition of a cell/stack assembly unit at which the unit is stable enough for any controlling parameter and the output voltage or output current of the unit to remain within its tolerance range of variation

3.1.10

theoretical current

current when the supplied anode gas or cathode gas is completely consumed in electrochemical reactions divided by the number of cells in a series connection

3.1.11

effective fuel utilization

ratio of the actual output current of the cell/stack assembly unit to the theoretical current

Note 1 to entry: The effective utilization is the utilization of reactants in the electrochemical reaction due to the actual current. This may be less than the actual or total utilization if there are gas inlet and cross leaks.

Note 2 to entry: Causes of less-than-optimal currents include losses due to electronic conduction within the cell/stack assembly, gas leaks and anode gas pass-through.

Note 3 to entry: A calculation method of effective fuel utilization is given in Annex B.

3.1.12

effective oxygen utilization

ratio of the actual output current of the cell/stack assembly unit to the theoretical current

Note 1 to entry: The effective utilization is the utilization of reactants in the electrochemical reaction due to the actual current. This may be less than the actual or total utilization if there are gas inlet and cross leaks.

Note 2 to entry: A calculation method of effective oxygen utilization is given in Annex C.

3.1.13

maximum effective fuel utilization

highest effective fuel utilization that the unit can operate at, without causing unacceptable degradation

Note 1 to entry: The acceptable degradation rate is usually obtained from the developer.

3.1.14

minimum cell/stack assembly unit voltage

lowest cell/stack assembly unit voltage specified by the manufacturer

3.1.15 open circuit voltage OCV

voltage across the terminals of a fuel cell with cathode and anode gases present and in the absence of external current flow

Note 1 to entry: Also known as "no-load voltage".

3.1.16 power density

ratio of the power to the active electrode area of a cell/stack assembly unit

Note 1 to entry: Power density is calculated from the voltage multiplied by the current density ($P_d = V \times J$, where J is current density).

3.1.17 total impedance

frequency-dependent losses due to ohmic, activation, diffusion, concentration effects, stray (parasitic) capacitance and inductances

3.1.18 total resistance

real part of the low-frequency limit of total impedance

3.1.19 stoichiometric ratio

ratio between the number of moles of reactant gas flowing per unit time to that needed by the electrochemical reaction

Note 1 to entry: The terms, "stoichiometric ratio" and "reactant gas utilization," are related. The reciprocal of the fraction of the gas utilized is the stoichiometric ratio.

3.2 Symbols

Table 1 lists the symbols and units that are used in this document.

Table 1 – Symbols

Symbol	Definition	Unit
a	Error limit specified from specification of instrument	a
I	Current	A
J	Current density	A/cm ²
n	Number of transferred electrons	
N	Number of cells in a series connection	
p_a	Absolute pressure of anode gas	kPa
p_c	Absolute pressure of cathode gas	kPa
P	Output power	W
P_d	Output power density	W/cm ²
q_a	Flow rate of anode gas	l/min (STP)
q_c	Flow rate of cathode gas	l/min (STP)
q_j	Flow rate of fuel component j in anode gas	l/min (STP)
t	Time	s, min, h
T_{op}	Cell/stack assembly unit operating temperature	°C
u_l	Combined standard uncertainty for instruments	a
$u_{l,i}$	Standard uncertainty for instrument i	

Symbol	Definition	Unit
U_f	Effective fuel utilization	%
U_{O_2}	Effective oxygen utilization	%
U_I	Extended instrument uncertainty	^a
V	Voltage	V
x_i	Molar fraction of component <i>i</i> or Mole percent of component <i>i</i>	mol/mol or mol % ^b
c_i	Concentration of component <i>i</i>	mol/m ³
ζ_j	Hydrocarbon conversion rate for hydrocarbon component <i>j</i>	%
^a Denotes where the unit varies depending on the specification.		
^b Mole percent expressed as one hundred times mole fraction.		

4 General safety conditions

An operating fuel cell uses oxidizing and combustible gases. Typically, these gases are stored in high-pressure containers. The fuel cell itself may be operated at pressures greater than atmospheric pressure. Those who carry out cell/stack assembly unit testing shall be trained and experienced in the operation of test systems and specifically in safety procedures involving electrical equipment and reactive, compressed gases.

The test personnel are responsible for obtaining and following all applicable safety codes and generally accepted engineering practices related to their test system, facility, fuels (with particular attention to compressed gases), and exhaust products.

Materials which are compatible with the use and storage of the reactant gases shall be used during testing. Local safety codes and standards for working with hydrogen, hydrocarbons and carbon monoxide should be followed.

In summary, safely operating a test station requires appropriate technical training and experience as well as safety facilities and equipment, all of which are outside the scope of this document.

5 Cell/stack assembly unit

A cell/stack assembly unit includes a cell or stack, gas supply, current leads, and such other peripherals as required for power generation tests. It shall be provided with single or multiple measuring points for temperature and voltage, and one set of current lead points, all to be specified by the manufacturer.

As shown in Annex A, the boundary of a cell/stack assembly unit goes through the anode gas supply port, cathode gas supply port, temperature measuring point, current lead points, voltage measuring points and mechanical load application points.

Some cell/stack assembly units may have no exhaust port for the anode gas or cathode gas because of the configuration of the cells. In such cases, the gas flow field pattern and its material shall be determined by the method recommended by the manufacturer. The load application method shall be also based on the recommendation of the manufacturer. The maximum operating temperature from the manufacturer shall not be exceeded.

If the components of a cell/stack assembly unit other than a cell/stack are not specified by the manufacturer, the following shall be described in the test report, as a minimum:

- materials and geometry of the peripheral components to be used for testing;
- flow patterns and directions of anode and cathode gases;