



BSI Standards Publication

Field device tool (FDT) interface specification

Part 1: Overview and guidance

National foreword

This British Standard is the UK implementation of EN IEC 62453-1:2025. It is identical to IEC 62453-1:2025. It supersedes BS EN 62453-1:2017, which will be withdrawn on 31 October 2028.

The UK participation in its preparation was entrusted to Technical Committee GEL/65/3, Industrial communications: process measurement and control, including fieldbus.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2025
Published by BSI Standards Limited 2025

ISBN 978 0 539 15386 6

ICS 25.040.40; 35.100.05; 35.110

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2025.

Amendments/corrigenda issued since publication

Date	Text affected
<hr/>	

English Version

Field device tool (FDT) interface specification - Part 1: Overview
and guidance
(IEC 62453-1:2025)

Spécification des interfaces des outils des dispositifs de
terrain (FDT) - Partie 1: Vue d'ensemble et guide
(IEC 62453-1:2025)

Field Device Tool (FDT)-Schnittstellenspezifikation - Teil 1:
Überblick und Leitfaden
(IEC 62453-1:2025)

This European Standard was approved by CENELEC on 2025-09-16. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 65E/1173/FDIS, future edition 3 of IEC 62453-1, prepared by SC 65E "Devices and integration in enterprise systems" of IEC/TC 65 "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62453-1:2025.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2026-10-31 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2028-10-31 document have to be withdrawn

This document supersedes EN 62453-1:2017 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 62453-1:2025 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 61131 series	NOTE	Approved as EN IEC 61131 series
IEC 61131-3	NOTE	Approved as EN IEC 61131-3
IEC 61158 series	NOTE	Approved as EN 61158 series
IEC 61158-1	NOTE	Approved as EN IEC 61158-1
IEC 61375-3-3	NOTE	Approved as EN 61375-3-3
IEC 61499 series	NOTE	Approved as EN 61499 series
IEC 61499-1	NOTE	Approved as EN 61499-1
IEC 61784 series	NOTE	Approved as EN IEC 61784 series
IEC 61784-1 series	NOTE	Approved as EN IEC 61784-1 series
IEC 61784-2 series	NOTE	Approved as EN IEC 61784-2 series
IEC 61800-7 series	NOTE	Approved as EN 61800-7 series
IEC 61800-7-1	NOTE	Approved as EN 61800-7-1
IEC 61804-2	NOTE	Approved as EN IEC 61804-2
IEC 61804-3	NOTE	Approved as EN IEC 61804-3

IEC 61804-4	NOTE	Approved as EN IEC 61804-4
IEC 61850 series	NOTE	Approved as EN 61850 series
IEC 61915-1	NOTE	Approved as EN 61915-1
IEC 62026 series	NOTE	Approved as EN 62026 series
IEC 62026-1	NOTE	Approved as EN IEC 62026-1
IEC 62264 series	NOTE	Approved as EN IEC 62264 series
IEC 62453 series	NOTE	Approved as EN IEC 62453 series
IEC 62453-2	NOTE	Approved as EN IEC 62453-2
IEC 62453-301	NOTE	Approved as EN 62453-301
IEC 62453-302	NOTE	Approved as EN IEC 62453-302
IEC 62453-303-1	NOTE	Approved as EN 62453-303-1
IEC 62453-303-2	NOTE	Approved as EN 62453-303-2
IEC 62453-306	NOTE	Approved as EN 62453-306
IEC 62453-309	NOTE	Approved as EN IEC 62453-309
IEC 62453-315	NOTE	Approved as EN 62453-315
IEC/TR 62453-41	NOTE	Approved as CLC/TR IEC 62453-41
IEC/TR 62453-42	NOTE	Approved as CLC/TR IEC 62453-42
IEC/TR 62453-51-10	NOTE	Approved as CLC/TR IEC 62453-51-10
IEC/TR 62453-51-20	NOTE	Approved as CLC/TR 62453-51-20
IEC/TR 62453-51-31	NOTE	Approved as CLC/TR 62453-51-31
IEC/TR 62453-51-32	NOTE	Approved as CLC/TR 62453-51-32
IEC/TR 62453-51-60	NOTE	Approved as CLC/TR 62453-51-60
IEC/TR 62453-51-90	NOTE	Approved as CLC/TR 62453-51-90
IEC/TR 62453-51-150	NOTE	Approved as CLC IEC/TR 62453-51-150
IEC/TR 62453-52-31	NOTE	Approved as CLC IEC/TR 62453-52-31
IEC/TR 62453-52-32	NOTE	Approved as CLC IEC/TR 62453-52-32
IEC/TR 62453-52-90	NOTE	Approved as CLC IEC/TR 62453-52-90
IEC/TR 62453-52-150	NOTE	Approved as CLC IEC/TR 62453-52-150
IEC/TR 62453-61	NOTE	Approved as CLC/TR 62453-61
IEC/TR 62453-62	NOTE	Approved as CLC/TR IEC 62453-62
IEC 62453-71	NOTE	Approved as EN IEC 62453-71
IEC 62541 series	NOTE	Approved as EN IEC 62541 series
IEC 62541-100	NOTE	Approved as EN 62541-100
IEC 62769 series	NOTE	Approved as EN IEC 62769 series

CONTENTS

FOREWORD	5
INTRODUCTION	7
1 Scope	9
2 Normative references	9
3 Terms, definitions, symbols, abbreviated terms and conventions	9
3.1 Terms and definitions	9
3.2 Abbreviated terms	15
3.3 Conventions	15
4 FDT overview	15
4.1 State of the art	15
4.2 Objectives of FDT	16
4.2.1 General features	16
4.2.2 Device and module manufacturer benefits	17
4.2.3 System manufacturer and integrator benefits	18
4.2.4 Other applications	18
4.3 FDT model	18
4.3.1 General	18
4.3.2 Frame Applications	20
4.3.3 Device Type Manager	21
4.3.4 Communication Channel concept	22
4.3.5 Presentation object	24
5 Structure of the IEC 62453 series	24
5.1 Structure overview	24
5.2 Part 2 – Concepts and detailed description	26
5.3 Parts 3xy – Communication profile integration	26
5.3.1 General	26
5.3.2 Communication profile integration – IEC 61784 CPF 1	26
5.3.3 Communication profile integration – IEC 61784 CPF 2	27
5.3.4 Communication profile integration – IEC 61784 CP 3/1 and 3/2	27
5.3.5 Communication profile integration – IEC 61784 CP 3/4, CP 3/5 and 3/6	27
5.3.6 Communication profile integration – IEC 61784 CPF 6	27
5.3.7 Communication profile integration – IEC 61784 CPF 9	27
5.3.8 Communication profile integration – IEC 61784 CPF 15	27
5.4 Parts 4z – Object model integration profiles	27
5.4.1 General	27
5.4.2 Object model integration profile – Common object model (COM)	28
5.4.3 Object model integration profile – Common language infrastructure (CLI)	28
5.4.4 Object model integration profile – CLI and HTML	28
5.5 Parts 51-xy/52-xy/53-xy – Communication profile implementation	28
5.5.1 General	28
5.5.2 Communication profile implementation – IEC 61784 CPF 1	28
5.5.3 Communication profile implementation – IEC 61784 CPF 2	28
5.5.4 Communication profile implementation – IEC 61784 CP 3/1 and 3/2	28
5.5.5 Communication profile implementation – IEC 61784 CP 3/4, CP 3/5 and 3/6	29
5.5.6 Communication profile implementation – IEC 61784 CPF 6	29

5.5.7	Communication profile implementation – IEC 61784 CPF 9	29
5.5.8	Communication profile implementation – IEC 61784 CPF 15.....	29
5.6	Parts 6z – DTM styleguides	29
5.6.1	General	29
5.6.2	Device Type Manager (DTM) styleguide for common object model	29
5.6.3	Field Device Tool (FDT) styleguide for common language infrastructure	29
5.7	Part 71 – OPC UA Information Model for FDT	29
6	Relation of the IEC 62453 series to other standardization activities	30
7	Migration to DTM	33
8	How to read IEC 62453.....	35
8.1	Architecture	35
8.2	Dynamic behaviour	35
8.3	Structured data types.....	35
8.4	Fieldbus communication	35
Annex A (normative)	UML notation.....	36
A.1	Common model elements.....	36
A.1.1	General	36
A.1.2	Note	36
A.2	Class diagram.....	36
A.2.1	General	36
A.2.2	Class	36
A.2.3	Abstract class	37
A.2.4	Association.....	37
A.2.5	Composition	37
A.2.6	Aggregation	37
A.2.7	Dependency	38
A.2.8	Association class	38
A.2.9	Generalization	38
A.2.10	Interface	39
A.2.11	Multiplicity	39
A.2.12	Enumeration class	39
A.3	Component diagram.....	40
A.3.1	General	40
A.3.2	Component.....	40
A.4	Statechart diagram	40
A.4.1	General	40
A.4.2	State	40
A.4.3	Initial state.....	41
A.4.4	Final state	41
A.4.5	Composite state.....	41
A.5	Use case diagram	41
A.5.1	General	41
A.5.2	Actor	42
A.5.3	Use case	42
A.5.4	Inheritance relation.....	42
A.6	Sequence diagram	42
A.6.1	General	42
A.6.2	Frame.....	43

A.6.3	Object with life line	43
A.6.4	Method calls	44
A.6.5	State and constraint.....	45
A.6.6	Alternative, optional and repetitive execution sequence	45
A.6.7	Break notation	46
A.6.8	Interaction references	47
A.7	Object diagram	47
Annex B (informative)	Implementation policy.....	48
Bibliography		49
Figure 1	– Different tools and fieldbuses result in limited integration.....	16
Figure 2	– Full integration of all devices and modules into a homogeneous system.....	17
Figure 3	– General architecture and components	19
Figure 4	– FDT software architecture	21
Figure 5	– General FDT client/server relationship	22
Figure 6	– Typical FDT channel architecture	23
Figure 7	– Channel/parameter relationship.....	24
Figure 8	– Structure of the IEC 62453 series	25
Figure 9	– Standards related to IEC 62453 in an automation hierarchy	30
Figure 10	– Standards related to IEC 62453 – Grouped by purpose	33
Figure 11	– DTM implementations.....	34
Figure A.1	– Note	36
Figure A.2	– Class	36
Figure A.3	– Icons for class members	36
Figure A.4	– Association	37
Figure A.5	– Navigable Association.....	37
Figure A.6	– Composition.....	37
Figure A.7	– Aggregation	37
Figure A.8	– Dependency	38
Figure A.9	– Association class	38
Figure A.10	– Abstract class, generalization and interface	38
Figure A.11	– Interface related notations	39
Figure A.12	– Multiplicity.....	39
Figure A.13	– Enumeration datatype	40
Figure A.14	– Component	40
Figure A.15	– Elements of UML statechart diagrams.....	40
Figure A.16	– Example of UML state chart diagram	41
Figure A.17	– UML use case syntax.....	42
Figure A.18	– UML sequence diagram	43
Figure A.19	– Empty UML sequence diagram frame.....	43
Figure A.20	– Object with life line and activation	44
Figure A.21	– Method calls	44
Figure A.22	– Modelling guarded call and multiple calls	44
Figure A.23	– Call to itself.....	45

Figure A.24 – Continuation / StateInvariant.....	45
Figure A.25 – Alternative fragment.....	46
Figure A.26 – Option fragment.....	46
Figure A.27 – Loop combination fragment.....	46
Figure A.28 – Break notation	46
Figure A.29 – Sequence reference.....	47
Figure A.30 – Objects	47
Figure A.31 – Object link	47
Table 1 – Overview of IEC 62453 series	26
Table 2 – Overview of related standards	31

INTERNATIONAL ELECTROTECHNICAL COMMISSION

Field device tool (FDT) interface specification - Part 1: Overview and guidance

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62453-1 has been prepared by subcommittee 65E: Devices and integration in enterprise systems, of IEC technical committee 65: Industrial-process measurement, control and automation. It is an International Standard.

This third edition cancels and replaces the first edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) introduction of a new implementation technology (defined in IEC TS 62453-43);
- b) introduction of an OPC UA information model for FDT (defined in IEC 62453-71).

The text of this International Standard is based on the following documents:

Draft	Report on voting
65E/1173/FDIS	65E/1176/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of the IEC 62453 series, under the general title *Field Device Tool (FDT) interface specification*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

Enterprise automation employs two main data flows: a “vertical” data flow from enterprise level down to the field devices including signals and configuration data, and a “horizontal” communication between field devices operating on the same or different communication technologies.

With the integration of fieldbuses into control systems, there are a few additional tasks to be performed. They can result in a large number of fieldbus- and device-specific tools in addition to system and engineering tools. Integration of these tools into higher-level system-wide planning or engineering tools is an advantage. In particular, for use in extensive and heterogeneous control systems, typically in the area of the process industry, the unambiguous definition of engineering interfaces that are easy to use for all those involved is of great importance.

Several different manufacturer specific tools are used. The data in these tools are often invisible data islands from the viewpoint of system life-cycle management and plant-wide automation.

To ensure the consistent management of a plant-wide control and automation technology, it is important to fully integrate fieldbuses, devices and sub-systems as a seamless part of a wide range of automation tasks covering the whole automation life cycle.

IEC 62453 provides an interface specification for developers of FDT¹ (Field Device Tool) components to support function control and data access within a client/server architecture. The availability of this standard interface facilitates development of servers and clients by multiple manufacturers and supports open interoperation.

A device or module-specific software component, called a DTM (Device Type Manager) is supplied by a manufacturer with the related device type or software entity type. Each DTM can be integrated into engineering tools via defined FDT interfaces. This approach to integration is in general open for all fieldbuses and thus supports integration of different devices and software modules into heterogeneous control systems.

The IEC 62453 common application interface supports the interests of application developers, system integrators, and manufacturers of field devices and network components. It also simplifies procurement, reduces system costs and helps manage the lifecycle. Significant savings are available in operating, engineering and maintaining the control systems.

The objectives of the IEC 62453 series are to support:

- universal plant-wide tools for life-cycle management of heterogeneous fieldbus environments, multi-manufacturer devices, function blocks and modular sub-systems for all automation domains (e.g. process automation, factory automation and similar monitoring and control applications);
- integrated and consistent life-cycle data exchange within a control system including its fieldbuses, devices, function blocks and modular sub-systems;
- simple and powerful manufacturer-independent integration of different automation devices, function blocks and modular sub-systems into the life-cycle management tools of a control system.

¹ FDT® is a registered trade name of FDT Group AISBL. This information is given for the convenience of users of this document and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this document does not require use of the trade name. Use of the trade name requires permission of the trade name holder.

The FDT concept supports planning and integration of monitoring and control applications, it does not provide a solution for other engineering tasks such as "electrical wiring planning", "mechanical planning". Plant management subjects such as "maintenance planning", "control optimization", "data archiving", are not part of this FDT standard. Some of these aspects can be included in future editions of FDT publications.

1 Scope

This part of IEC 62453 presents an overview and guidance for the IEC 62453 series. It

- explains the structure and content of the IEC 62453 series (see Clause 5);
- provides explanations of some aspects of the IEC 62453 series that are common to many of the parts of the series;
- describes the relationship to some other standards;
- provides definitions of terms used in other parts of the IEC 62453 series.

2 Normative references

There are no normative references in this document.

3 Terms, definitions, symbols, abbreviated terms and conventions

3.1 Terms and definitions

For the purposes of this document and of the IEC 62453 series, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1

actor

coherent set of roles that users of use cases play when interacting with these use cases

Note 1 to entry: An actor has one role for each use case with which it communicates.

[SOURCE: ISO/IEC 19501:2005, 4.11.2.1]

3.1.2

address

communication protocol specific access identifier

3.1.3

application

software functional unit that is specific to the solution of a problem in industrial-process measurement and control

Note 1 to entry: An application may be distributed among resources, and may communicate with other applications.

3.1.4

business object

object representing specific behaviour (e.g. DTM, BTM and channel)

Note 1 to entry: The term business object has been defined originally as part of the design pattern three-tier architecture, where the business object is part of the business layer.

3.1.5

Block Type Manager

BTM

specialized DTM to manage and handle a block

Note 1 to entry: This note applies to the French language only.

3.1.6

communication

fieldbus protocol specific data transfer

3.1.7

Communication Channel

access point for communication to field device

3.1.8

configuration

system created by configuring the plant components and the topology

3.1.9

configure

setting parameters at the instance data as well as the logical association of plant components to build up the plant topology (off-line)

Note 1 to entry: See also parameterize (3.1.38).

3.1.10

connection

established data path for communication with a selected device

3.1.11

data

set of parameter values

3.1.12

data type

defined set of data objects of a specified data structure and a set of permissible operations, such that these data objects act as operands in the execution of any one of these operations

[SOURCE: ISO/IEC 2382-15:1999, 15.04.01 (2382)]

3.1.13

DCS manufacturer

system manufacturer

manufacturer of the control system

3.1.14

device

independent physical entity of an automation system capable of performing specified functions in a particular context and delimited by its interfaces

[SOURCE: IEC 61499-1:2012, 3.29, modified – The words “of an automation system” have been added, the expression “one or more specified functions” has been replaced by “specified functions” and the note has been deleted.]

3.1.15

field device

networked independent physical entity of an automation system capable of performing specified functions in a particular context and delimited by its interfaces

[SOURCE: IEC 61375-3-3:2012, 3.1.3]

3.1.16

device manufacturer

manufacturer of fieldbus devices

3.1.17

device type

device characterization based on abstract properties such as manufacturer, fieldbus protocol, device type identifier, device classification, version information or other information

Note 1 to entry: The scope of such characterizations can vary depending on the properties that are used in the definition of such a set and is manufacturer specific for each DTM.

3.1.18

distributed system

FDT objects that jointly are executed on different PCs in a network

Note 1 to entry: The implementation of such a distributed system is vendor specific (for example: DTM and Presentation are executed on different PCs or DTMs are executed in a multi-user system on different PCs).

3.1.19

documentation

human readable information about a device instance

Note 1 to entry: This can be electronic information in a database.

3.1.20

Device Type Manager

DTM

software component containing device-specific application software

Note 1 to entry: The DTM is a generic class and means "Type Manager". The D is kept because the acronym is well-known in the market.

3.1.21

DTM device type

software module for a particular device type within the DTM

Note 1 to entry: A DTM can contain one or more DTM device types.

3.1.22

entity

particular thing, such as a person, place, process, object, concept, association, or event

[SOURCE: IEC 61499-1:2012, 3.31]

3.1.23

Frame Application

FDT runtime environment

3.1.24

FDT model

interface specification for objects and object behaviour in a monitoring and control system

3.1.25

function

specific purpose of an entity or its characteristic action

[SOURCE: IEC 61499-1:2012, 3.44]

3.1.26

Generic DTM

DTM which interprets device type or domain specific device descriptions and provides the FDT interfaces

3.1.27

hardware

physical equipment, as opposed to programs, procedures, rules and associated documentation

[SOURCE: IEC 61499-1:2012, 3.49]

3.1.28

implementation

development phase in which the hardware and software of a system become operational

[SOURCE: IEC 61499-1:2012, 3.51]

3.1.29

instantiation

creation of an instance of a specified type

[SOURCE: IEC 61499-1:2012, 3.57]

3.1.30

interface

boundary between two functional units, defined by functional characteristics, signal characteristics, or other characteristics as appropriate

[SOURCE: IEC 60050-351:2013, 351-42-25, modified – The notes have been deleted.]

3.1.31

Interpreter DTM

generic DTM which interprets device descriptions

3.1.32

mapping

set of features or attributes having defined correspondence with the members of another set

[SOURCE: IEC 61499-1:2012, 3.66]

3.1.33

multi-user environment

environment which allows operation by more than one user

3.1.34

network

all of the media, connectors, repeaters, routers, gateways and associated node communication elements by which a given set of communicating devices are interconnected

Note 1 to entry: In this document, network is used to express that one or more interconnected fieldbus systems with different protocols can be applied.

[SOURCE: IEC 61158-1:2014, 3.1.5, modified – Note 1 has been added.]

3.1.35

nested communication

communication using a hierarchy of communication systems

3.1.36

operation

well-defined action that, when applied to any permissible combination of known entities, produces a new entity

[SOURCE: IEC 61499-1:2012, 3.73]

3.1.37

parameter

variable that is given a constant value for a specified application and that may denote the application

[SOURCE: IEC 61499-1:2012, 3.75]

3.1.38

parameterize

setting parameters in a device or a block or an object

Note 1 to entry: See also configure (3.1.9).

3.1.39

persistent data

stored data that is preserved through shutdown/restart and maintenance activities

3.1.40

Process Channel

representation of process value and its properties

3.1.41

service

functional capability of a resource which can be modeled by a sequence of service primitives

[SOURCE: IEC 61499-1:2012, 3.87]

3.1.42

session

instance of user interactions within the FDT model

3.1.43

synchronization

synchronization of data depending on the context where used

Note 1 to entry: For example, synchronization can occur between the DTM and the device or between several DTM instances having a reference to the same instance data.

3.1.44

system

set of interrelated elements considered in a defined context as a whole and separated from their environment

Note 1 to entry: Elements of a system may be natural or man-made material objects, as well as modes of thinking and the results thereof (for example forms of organization, mathematical methods, and programming languages).

Note 2 to entry: The system is considered to be separated from the environment and other external systems by an imaginary surface, which can cut the links between them and the considered system.

[SOURCE: IEC 60050-351:2013, 351-42-08, modified – Note 1 has been deleted.]