



BSI Standards Publication

Fibre optic interconnecting devices and passive components — Connector optical interfaces for enhanced macro bend multimode fibres

Part 2-2: Connection parameters of physically contacting 50 µm core diameter fibres — Non-angled and angled for reference connector applications

National foreword

This British Standard is the UK implementation of EN IEC 63267-2-2:2024. It is identical to IEC 63267-2-2:2024.

The UK participation in its preparation was entrusted to Technical Committee GEL/86/2, Fibre optic interconnecting devices and passive components.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2024
Published by BSI Standards Limited 2024

ISBN 978 0 539 17933 0

ICS 33.180.20

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2024.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

Fibre optic interconnecting devices and passive components -
Connector optical interfaces for enhanced macro bend
multimode fibres - Part 2-2: Connection parameters of physically
contacting 50 μm core diameter fibres - Non-angled and angled
for reference connector applications
(IEC 63267-2-2:2024)

Dispositifs d'interconnexion et composants passifs
fibroniques - Interfaces optiques de connecteurs pour fibre
multimodale à performances améliorées par
macrocourbures - Partie 2-2: Paramètres de connexion de
fibres de diamètre de cœur de 50 μm en contact physique -
Fibres inclinées et non inclinées pour les applications de
connecteurs de référence
(IEC 63267-2-2:2024)

Lichtwellenleiter-Verbindungselemente und passive
Bauelemente - Optische Schnittstellen von Steckverbindern
für Mehrmodenfasern mit verbesserter Makrobiegung - Teil
2-2: Verbindungsparameter von physikalisch
kontaktierenden Fasern mit einem Kerndurchmesser von 50
 μm - Nicht abgewinkelt und abgewinkelt für
Referenzsteckverbinderanwendungen
(IEC 63267-2-2:2024)

This European Standard was approved by CENELEC on 2024-04-19. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 86B/4857/FDIS, future edition 1 of IEC 63267-2-2, prepared by SC 86B "Fibre optic interconnecting devices and passive components" of IEC/TC 86 "Fibre optics" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 63267-2-2:2024.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2025-01-19 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2025-04-19 document have to be withdrawn

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 63267-2-2:2024 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 61300-1 NOTE Approved as EN IEC 61300-1
IEC 61300-3-4 NOTE Approved as EN IEC 61300-3-4
IEC 62614 (series) NOTE Approved as EN IEC 62614 (series)
IEC 63267 (series) NOTE Approved as EN IEC 63267 (series)
IEC 63267-1 NOTE Approved as EN IEC 63267-1

Annex ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cencenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60793-2-10	-	Optical fibres - Part 2-10: Product specifications - Sectional specification for category A1 multimode fibres	EN IEC 60793-2-10 -	
IEC 61300-3-35	-	Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 3-35: Examinations and measurements - Visual inspection of fibre optic connectors and fibre-stub transceivers	EN IEC 61300-3-35 -	

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Performance grades	6
5 Description	6
6 Criteria for a fit within the performance grade	7
7 Attenuation measurement uncertainty contribution	7
8 Visual inspection	7
Annex A (informative) Multimode attenuation measurement uncertainty contribution	9
A.1 General	9
A.2 Sources of variability	9
A.2.1 Measurement condition and setup	9
A.2.2 Geometry mismatch	9
A.3 Overall uncertainty	10
Annex B (informative) Test limits for performance grade B_m connectors against grade R_m reference connectors	12
B.1 General	12
B.2 Test limits	12
Bibliography	13
Figure 1 – Geometrical requirements for fibre core location after termination	7
Figure A.1 – Attenuation measurement uncertainty contribution for Grade R_{m1} reference connections resulting from lateral offset, NA and CD mismatch	9
Table 1 – Attenuation grades for multimode reference connections at 850 nm	6
Table 2 – Lateral offset values for grade R_m reference connections	7
Table 3 – Visual requirements for multimode PC and APC polished connection	8
Table A.1 – Evaluation of the uncertainty contribution due measurement conditions	11
Table B.1 – Performance grade test limits at 850 nm	12