

Building construction machinery and equipment — Portable, hand-held, internal combustion engine driven cut- off machines — Safety requirements and testing (ISO 19432:2006)

ICS 91.220

National foreword

This British Standard is the UK implementation of EN ISO 19432:2008. It is identical to ISO 19432:2006. It supersedes BS EN ISO 19432:2006 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee B/513, Construction equipment and plant and site safety.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2009

© BSI 2009

ISBN 978 0 580 62183 3

Amendments/corrigenda issued since publication

Date	Comments

English Version

**Building construction machinery and equipment - Portable,
hand-held, internal combustion engine driven cut-off machines -
Safety requirements and testing (ISO 19432:2006)**

Machines et matériels pour la construction des bâtiments -
Tronçonneuses à disque, portatives, à moteur à
combustion interne - Exigences de sécurité et essais (ISO
19432:2006)

Baumaschinen und -ausrüstungen - Tragbare,
handgeführte Trennschleifmaschinen mit
Verbrennungsmotor - Sicherheit und Prüfverfahren (ISO
19432:2006)

This European Standard was approved by CEN on 25 March 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

The text of ISO 19432:2006 has been prepared by Technical Committee ISO/TC 195 “Building construction machinery and equipment” of the International Organization for Standardization (ISO) and has been taken over as EN ISO 19432:2008 by Technical Committee CEN/TC 151 “Construction equipment and building material machines - Safety” the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2008, and conflicting national standards shall be withdrawn at the latest by October 2008.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 19432:2006.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EC Directive(s).

For relationship with EC Directives, see informative Annex ZA and ZB, which are integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of ISO 19432:2006 has been approved by CEN as a EN ISO 19432:2008 without any modification.

Annex ZA (informative)

Relationship between this International Standard and the Essential Requirements of EU Directive 98/37/EC, amended by Directive 98/79/EC

This International Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association to provide one means of conforming to Essential Requirements of the New Approach Directive Machinery Directive 98/37/EC, amended by Directive 98/79/EC.

Once this standard is cited in the Official Journal of the European Communities under that Directive and has been implemented as a national standard in at least one Member State, compliance with the normative clauses of this International standard confers, within the limits of the scope of this standard, a presumption of conformity with Essential Requirement 2.2 of that Directive and associated EFTA regulations.

WARNING: Other requirements and other EU Directives may be applicable to the product(s) falling within the scope of this International standard.

Annex ZB (informative)

Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association to provide a means of conforming to Essential Requirements of the New Approach Directive 2006/42/EC on machinery.

Once this standard is cited in the Official Journal of the European Communities under that Directive and has been implemented as a national standard in at least one Member State, compliance with the normative clauses of this standard confers, within the limits of the scope of this standard, a presumption of conformity with the relevant Essential Requirements of that Directive *except Essential Requirements 1.7.3 (additional marking of business address and the designation of machines), 1.7.4.2 u) (uncertainty of noise measurement) and 2.2.1.1 (uncertainty of vibration measurements)*, and associated EFTA regulations.

WARNING — Other requirements and other EU Directives may be applicable to the product(s) falling within the scope of this standard.

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 List of significant hazards	4
5 Safety requirements and verification.....	5
5.1 General.....	5
5.2 Handles	6
5.3 Speed	6
5.4 Engine stopping device.....	7
5.5 Throttle control	7
5.6 Clutch	8
5.7 Exhaust gases	8
5.8 Cutting debris discharge	8
5.9 Tank openings.....	9
5.10 Protection against contact with parts under high voltage	9
5.11 Transmission cover(s).....	9
5.12 Protection against contact with hot parts	9
5.13 Cut-off wheel guard	11
5.14 Flange locking device.....	12
5.15 Flange assembly	13
5.16 Spindle diameter	14
5.17 Special tools	14
5.18 Noise	14
5.19 Vibration	14
6 Information for use	15
6.1 Instruction handbook	15
6.2 Markings	18
6.3 Warnings.....	18
Annex A (normative) Strength test of cut-off wheel guard	19
Annex B (normative) Noise test code — Engineering method (grade 2 of accuracy)	21
Annex C (normative) Measurement of vibration values at the handles	29
Annex D (informative) Recommended pictorials and symbols	36
Bibliography	37

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 19432 was prepared by Technical Committee ISO/TC 195, *Building construction machinery and equipment*.

Introduction

The structure of safety standards in the field of machinery is as follows.

- a) Type-A standards (basis standards) give basic concepts, principles for design, and general aspects that can be applied to machinery.
- b) Type-B standards (generic safety standards) deal with one or more safety aspect(s) or one or more type(s) of safeguards that can be used across a wide range of machinery:
 - type-B1 standards on particular safety aspects (e.g. safety distances, surface temperature, noise);
 - type-B2 standards on safeguards (e.g. two-hands controls, interlocking devices, pressure-sensitive devices, guards).
- c) Type-C standards (machinery safety standards) deal with detailed safety requirements for a particular machine or group of machines.

This International Standard is a type-C standard as stated in ISO 12100-1.

When provisions of this type-C standard are different from those which are stated in type-A or type-B standards, the provisions of this type-C standard take precedence over the provisions of the other standards for machines that have been designed and built according to the provisions of this type-C standard.

The machinery concerned and the extent to which hazards, hazardous situations and events are covered as indicated in the scope of this International Standard.

This International Standard is based on EN 1454:1998 and an ANSI draft.

Building construction machinery and equipment — Portable, hand-held, internal combustion engine driven cut-off machines — Safety requirements and testing

1 Scope

This International Standard specifies safety requirements and their verification by testing for the design and construction of portable, hand-held, internal combustion engine driven, cut-off machines, intended to be used by a single operator in the cutting of construction materials, such as asphalt, concrete, stone and metal. It is applicable to those machines designed purposely for use with a rotating, bonded-abrasive and/or superabrasive (diamond) cut-off wheel having a maximum outside diameter of 406 mm, centre-mounted on, and driven by, a spindle shaft, where the top of the wheel rotates away from the operator (see Figure 1).

This International Standard deals with all significant hazards related to the hand-held use of such machines (see Clause 4). It specifies methods for the elimination or reduction of hazards arising from their use, as well as the type of information on safe working practices to be provided with the machines. Cut-off machines designed in accordance with this International Standard are intended to be used by persons who have read and understood the safety requirements given in the “instruction handbook” and who use the appropriate personal protective equipment (PPE).

Except for noise, environmental aspects are not considered by this International Standard; nor are cut-off wheel specifications given — for such specifications, see, for example, EN 12413 ^[1] and EN 13236 ^[2].

This International Standard is not applicable to machines manufactured before the date of its publication.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3744:1994, *Acoustics — Determination of sound power levels of noise sources using sound pressure — Engineering method in an essentially free field over a reflecting plane*

ISO 4871:1996, *Acoustics — Declaration and verification of noise emission values of machinery and equipment*

ISO 5348:1998, *Mechanical vibration and shock — Mechanical mounting of accelerometers*

ISO 5349-2:2001, *Mechanical vibration — Measurement and evaluation of human exposure to hand-transmitted vibration — Part 2: Practical guidance for measurement at the workplace*

ISO 7293:1997, *Forestry machinery — Portable chain-saws — Engine performance and fuel consumption*

ISO 7914:2002, *Forestry machinery — Portable chain-saws — Minimum handle clearance and sizes*

ISO 8041:1990, *Human response to vibration — Measuring instrumentation*

ISO 11201:1995, *Acoustics — Noise emitted by machinery and equipment — Measurement of emission sound pressure levels at a work station and at other specified positions — Engineering method in an essentially free field over a reflecting plane*

ISO/TR 11688-1:1995, *Acoustics — Recommended practice for the design of low-noise machinery and equipment — Part 1: Planning*

ISO 12100-1:2003, *Safety of machinery — Basic concepts, general principles for design — Part 1: Basic terminology, methodology*

ISO 12100-2:2003, *Safety of machinery — Basic concepts, general principles for design — Part 2: Technical principles*

ISO 13852:1996, *Safety of machinery — Safety distances to prevent danger zones being reached by the upper limbs*

ISO 16063-1:1998, *Methods for the calibration of vibration and shock transducers — Part 1: Basic concepts*

IEC 60745-1:2003, *Hand-held motor-operated electric tools — Safety — Part 1: General requirements*

IEC 61672-1:2002, *Electroacoustics — Sound level meters — Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12100-1 and the following apply.

3.1

cut-off wheel

wheel composed of abrasive particles bonded together by an appropriate binder and incorporating, if necessary, some appropriate form of reinforcement, or made of metal or other materials of similar properties and having diamond, CBN-particles or other suitable abrasive particles bonded to its rim

3.2

arbor hole

centre hole of the cut-off wheel used for mounting the cut-off wheel on the machine spindle

3.3

blotter

washers made from some compressible material (e.g. paper, card or similar), attached to each side of the cut-off wheel, the function of which is to smooth imperfections in the cut-off wheel and allow a limited degree of slip when the wheel stalls in use

3.4

choke

device for enriching the fuel air mixture in the carburettor, to aid starting

3.5

clutch

device for connecting and disconnecting the driven member to and from a rotating source of power

3.6

cut-off wheel guard

partial enclosure intended to deflect cutting debris, as well as pieces of the cut-off wheel in the event that the wheel is broken in operation

3.7

engine stopping device

device by which the stopping of the power source is initiated

3.8

flange contact surface

area between the inner and the outer circumference on the flange, which forms the contact surface between the flange and the cut-off wheel

3.9

flange assembly

device provided to clamp and drive the cut-off wheel

3.10

handle

device designed to facilitate safe and easy control of the machine

3.10.1

front handle

handle located at or towards the front of the engine housing

3.10.2

rear handle

handle located at or towards the rear of the power source housing

3.11

idle speed

speed at which the engine runs with no load and throttle control released and the cut-off wheel does not rotate

3.12

reactive forces

sudden and unexpected motion of the machine, which can occur when the rotating cut-off wheel contacts a foreign object during cutting or because of pinching

3.13

maximum depth of cut

t

distance to which the cut-off wheel can enter the work-piece as measured from the outside diameter of the wheel to the outside diameter of the flange

3.14

maximum cut-off wheel speed

maximum permitted speed of a new cut-off wheel marked on the cut-off wheel

3.15

maximum spindle speed

maximum speed at which the spindle rotates with full open throttle and no load

3.16

silencer

device for reducing engine exhaust noise and directing the exhaust gases

3.17

rated speed

engine speed at which maximum power occurs

3.18

spindle

shaft of the cut-off machine, which supports, retains and drives the cut-off wheel in connection with the flanges

3.19

throttle control

device for controlling the engine speed

3.20

throttle lock

device for temporarily setting the throttle in a partially open position, to aid starting

3.21

throttle lock-out

device that prevents the unintentional operation of the throttle trigger until manually released

3.22

throttle control linkage

mechanism which transmits motion from the throttle control to the throttle control valve

3.23

transmission cover

device between the engine and the cutting equipment designed to prevent unintentional contact with the transmission

4 List of significant hazards

This clause lists significant hazards, hazardous situations and events as far as they are dealt with in this document, identified by risk assessment as significant for this type of machinery, and which require action to eliminate or reduce the risk. See Table 1.

Table 1 — List of significant hazards

No.	Hazard	Clause(s) in this International Standard dealing with the hazard
1	Mechanical hazards due to cutting, impact and reactive forces (i.e. climbing, pulling and especially reactive forces) related to the cut-off wheel and the transmission to the cut-off wheel	5.2; 5.11; 5.13; 5.14; 5.15; 5.16; 6.1.2
2	Electrical hazards due to contact with parts under high voltage (direct contact) or parts which have become under high voltage under faulty conditions (indirect contact)	5.10
3	Thermal hazards resulting in burns, scalds and other injuries, by a possible contact of persons with objects or materials with high temperature including the radiation of heat sources	5.12
4	Noise, resulting in hearing losses (deafness) and other physiological disorders (e.g. loss of balance; loss of awareness) and interference with auditory signals and speech communication	5.18; 6.1; 6.3
5	Vibration (resulting in peripheral circulatory and nervous functional disturbances in the hand-arm system, such as "white finger" disease)	5.19; 6.1; 6.3
6	Contact with or inhalation of harmful fluids, gases, mists and fumes related to exhaust gases and dust related to debris of cut-off materials	5.7.1; 5.8, 5.13.1; 6.1.2, 6.3
7	Fire or explosion related to fuel spillage	5.9, 6.1.2
8	Neglecting of ergonomic principles in machine design such as hazards from unhealthy postures or excessive efforts and inadequate consideration of human hand-arm anatomy related to handle design, machine balance	5.2; 5.5; 6.1.2; 6.3
9	Unexpected start-up, unexpected overrun/over-speed from failure/disorder of the control system related to failure in the handles and position of the controls	5.2; 5.4; 5.5; 5.6;
10	Impossibility of stopping the machine in the best possible conditions related to the handle strength and position of the engine stopping device	5.2; 5.4
11	Failure of the control system related to handle strength, position of controls and marking	5.5; 6.3
12	Brake up during operation related to cut-off wheel	5.3; 5.14; 6.1; 6.3
13	Ejection of objects related to debris	5.3; 5.8; 5.13, 6.1.2; 6.3

5 Safety requirements and verification

CAUTION — Some of the tests specified in this International Standard involve processes that could lead to a hazardous situation. Any person performing tests in accordance with this International Standard shall be appropriately trained in the type of work to be carried out. All national regulatory conditions and health and safety requirements shall be followed.

5.1 General

The safe running of cut-off machines depends on both the safety requirements according to this clause and the safe working conditions associated with the use of adequate personal protection equipment (PPE), such as gloves, leg protection, boots, and eye, ear and head protection equipment (see Clause 6).

Cut-off machines shall comply with the safety requirements and/or protective measures of this clause. Cut-off machines shall also be marked according to 6.2 and wear warnings according to 6.3. In addition, the machine shall be designed according to the principles of ISO 12100-2 for hazards relevant but not significant, which are not dealt with by this document.