

Acoustics — Determination of sound power levels of noise sources using sound pressure — Engineering method in an essentially free field over a reflecting plane

The European Standard EN ISO 3744:1995 has the status of a British Standard

ICS 17.140.10

National foreword

This British Standard was published by BSI. It is the UK implementation of EN ISO 3744:1995. It is identical with ISO 3744:1994. In 1995 the European Committee for Standardization (CEN) accepted ISO 3744:1994 as European Standard EN ISO 3744:1995. As a consequence of implementing the European Standard this British Standard is renumbered as BS EN ISO 3744 and any reference to BS ISO 3744 should be read as a reference to BS EN ISO 3744.

The UK participation in its preparation was entrusted to Technical Committee EH/1, Acoustics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2007

© BSI 2007

ISBN 0 580 23478 9

Amendments issued since publication

Amd. No.	Date	Comments

ICS 17.140.10

Descriptors: Acoustics, sound sources, noise(sound), tests, acoustic tests, determination, sound power, sound pressure, acoustic measurements, testing conditions, rules of calculation

English version

Acoustics — Determination of sound power levels of noise
sources using sound pressure —
Engineering method in an essentially free field over a
reflecting plane

(ISO 3744 : 1994)

Acoustique — Détermination des niveaux de
puissance acoustique émis par les sources de
bruit à partir de la pression acoustique —
Méthode d'expertise dans des conditions
approchant celles du champ libre sur plan
réfléchissant
(ISO 3744 : 1994)

Akustik — Bestimmung der Schalleistungspegel
von Geräuschquellen aus
Schalldruckmessungen —
Hüllflächenverfahren der Genauigkeitsklasse 2 für
ein im wesentlichen freies Schallfeld über einer
reflektierenden Ebene
(ISO 3744 : 1994)

This European Standard was approved by CEN on 1995-07-01. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization
Comité Européen de Normalisation
Europäisches Komitee für Normung

Central Secretariat: rue de Stassart 36, B-1050 Brussels

© 1995 All rights of reproduction and communication in any form and by any means reserved in all countries to CEN and its members.

EN ISO 3744:1995

Foreword

The text of the International Standard from ISO/TC 43, Acoustics, of the International Organization for Standardization (ISO) has been taken over as a European Standard by the Technical Committee CEN/TC 211, Acoustics.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 1996, and conflicting national standards shall be withdrawn at the latest by March 1996.

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EC Directive(s).

According to the CEN/CENELEC Internal Regulations, the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

INTERNATIONAL STANDARD

ISO
3744

Second edition
1994-05-01

Acoustics — Determination of sound power levels of noise sources using sound pressure — Engineering method in an essentially free field over a reflecting plane

*Acoustique — Détermination des niveaux de puissance acoustique émis
par les sources de bruit à partir de la pression acoustique — Méthode
d'expertise dans des conditions approchant celles du champ libre sur plan
réfléchissant*



Reference number
ISO 3744:1994(E)



Documents
Document Sharing Hub

Contents

	Page
1 Scope	1
2 Normative references	2
3 Definitions	3
4 Acoustic environment	4
5 Instrumentation	5
6 Installation and operation of source under test.....	5
7 Measurement of sound pressure levels	7
8 Calculation of surface sound pressure level and sound power level.....	10
9 Information to be recorded.....	12
10 Information to be reported	13

Annexes

A Qualification procedures for the acoustic environment.....	14
B Microphone array on the hemispherical measurement surface	18
C Microphone array on the parallelepiped measurement surface	23
D Guidelines for the detection of impulsive noise	29
E Guidelines for the determination of the directivity index.....	30
F Bibliography	31
ZA Normative references to international publications with their relevant European publications	32

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 3744 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Sub-Committee SC 1, *Noise*.

This second edition cancels and replaces the first edition (ISO 3744:1981), which has been technically revised.

Annexes A, B and C form an integral part of this International Standard. Annexes D, E and F are for information only.

Introduction

0.1 This International Standard is one of the ISO 3740 series, which specifies various methods for determining the sound power levels of machines, equipment and their sub-assemblies. When selecting one of the methods of the ISO 3740 series, it is necessary to select the most appropriate for the conditions and purposes of the noise test. General guidelines to assist in the selection are provided in ISO 3740. The ISO 3740 series gives only general principles regarding the operating and mounting conditions of the machine or equipment under test. Reference should be made to the noise test code for a specific type of machine or equipment, if available, for specifications on mounting and operating conditions.

0.2 This International Standard specifies a method for measuring the sound pressure levels on a measurement surface enveloping the source, and for calculating the sound power level produced by the source. The enveloping surface method can be used for any of three grades of accuracy (see table 0.1), and is used in this International Standard for grade 2 accuracy.

The use of this International Standard requires certain qualification criteria to be fulfilled, as described in table 0.1. If the relevant qualification criteria cannot be met, other basic standards with different environmental requirements are suggested (table 0.1; see also ISO 3740 and ISO 9614).

Noise test codes for specific families of machines or equipment should be based without any contradiction on the requirements of one or more of the ISO 3740 series or ISO 9614.

Free-field conditions are usually not encountered in typical machine rooms where sources are normally installed. If measurements are made in such installations, corrections may be required to account for background noise or undesired reflections.

The methods specified in this International Standard permit the determination of sound power level both as an A-weighted value and in frequency bands.

The A-weighted value calculated from frequency band data may differ from that determined from measured A-weighted sound pressure levels.

0.3 In this International Standard, the computation of sound power level from sound pressure level measurements is based on the premise that the sound power output of the source is directly proportional to the mean-square sound pressure averaged over time and space.

Table 0.1 — Overview of International Standards for determination of sound power levels of noise sources using enveloping surface methods over a reflecting plane and giving different grades of accuracy

Parameter	ISO 3745 Precision method Grade 1	ISO 3744 Engineering method Grade 2	ISO 3746 Survey method Grade 3
Test environment	Hemi-anechoic room	Outdoors or indoors	Outdoors or indoors
Criterion for suitability of test environment ¹⁾	$K_2 \leq 0,5$ dB	$K_2 \leq 2$ dB	$K_2 \leq 7$ dB
Volume of sound source	Preferably less than 0,5 % of test room volume	No restriction; limited only by available test environment	No restriction; limited only by available test environment
Character of noise	Any (broad-band, narrow-band, discrete-frequency, steady, non-steady, impulsive)		
Limitation for background noise ¹⁾	$\Delta L \geq 10$ dB (if possible, exceeding 15 dB) $K_1 \leq 0,4$ dB	$\Delta L \geq 6$ dB (if possible, exceeding 15 dB) $K_1 \leq 1,3$ dB	$\Delta L \geq 3$ dB $K_1 \leq 3$ dB
Number of measurement points	≥ 10	≥ 9 ²⁾	≥ 4 ²⁾
Instrumentation: — Sound level meter at least complying with — Integrating sound level meter at least complying with — Frequency band filter set at least complying with	a) type 1 as specified in IEC 651 b) type 1 as specified in IEC 804 c) class 1 as specified in IEC 225	a) type 1 as specified in IEC 651 b) type 1 as specified in IEC 804 c) class 1 as specified in IEC 225	a) type 2 as specified in IEC 651 b) type 2 as specified in IEC 804 —
Precision of method for determining L_{WA} expressed as standard deviation of reproducibility	$\sigma_R \leq 1$ dB	$\sigma_R \leq 1,5$ dB	$\sigma_R \leq 3$ dB (if $K_2 < 5$ dB) $\sigma_R \leq 4$ dB (if $5 \text{ dB} \leq K_2 \leq 7$ dB) If discrete tones are predominant, the value of σ_R is 1 dB greater.
1) The values of K_1 and K_2 given shall be met in each frequency band within the frequency range of interest for determining the sound power spectrum. For determining A-weighted sound power levels, the same criteria apply to K_{1A} and K_{2A}. 2) Under given circumstances (see 7.2 to 7.4), it is permissible to use a reduced number of microphone positions.			

Acoustics — Determination of sound power levels of noise sources using sound pressure — Engineering method in an essentially free field over a reflecting plane

1 Scope

1.1 General

This International Standard specifies a method for measuring the sound pressure levels on a measurement surface enveloping a noise source, under essentially free-field conditions near one or more reflecting planes, in order to calculate the sound power level produced by the noise source. It gives requirements for the test environment and instrumentation, as well as techniques for obtaining the surface sound pressure level from which the sound power level of the source is calculated, leading to results which have a grade 2 accuracy.

It is important that specific noise test codes for various types of equipment be established and used in accordance with this International Standard. For each type of equipment, such noise test codes will give detailed requirements on mounting, loading and operating conditions for the equipment under test as well as a selection of the measurement surface and the microphone array as specified in this International Standard.

NOTE 1 The noise test code for a particular type of equipment should give detailed information on the particular surface that is selected, as the use of differently shaped measurement surfaces may yield differing estimates of the sound power level of a source.

1.2 Types of noise and noise sources

The method specified in this International Standard is suitable for measurements of all types of noise.

NOTE 2 A classification of different types of noise (steady, non-steady, quasi-steady, impulsive, etc.) is given in ISO 2204.

This International Standard is applicable to noise sources of any type and size (e.g. device, machine, component, sub-assembly).

NOTE 3 Measurements according to this International Standard may be impracticable for very tall or very long sources such as chimneys, ducts, conveyors and multi-source industrial plants.

1.3 Test environment

The test environment that is applicable for measurements made in accordance with this International Standard is an essentially free field near one or more reflecting planes (indoors or outdoors).

1.4 Measurement uncertainty

Determinations made in accordance with this International Standard result, with few exceptions, in standard deviations of reproducibility of the A-weighted sound power level equal to or less than 1,5 dB (see table 1).

A single value of the sound power level of a noise source determined according to the procedures given in this International Standard is likely to differ from the true value by an amount within the range of the measurement uncertainty. The uncertainty in determinations of the sound power level arises from several factors which affect the results, some associated with environmental conditions in the measurement laboratory and others with experimental techniques.

If a particular noise source were to be transported to each of a number of different laboratories, and if, at each laboratory, the sound power level of that source were to be determined in accordance with this International Standard, the results would show a scatter. The standard deviation of the measured levels could be calculated (see examples in ISO 7574-4:1985, an-

nex B) and would vary with frequency. With few exceptions, these standard deviations would not exceed those listed in table 1. The values given in table 1 are standard deviations of reproducibility, σ_R , as defined in ISO 7574-1. The values of table 1 take into account the cumulative effects of measurement uncertainty in applying the procedures of this International Standard, but exclude variations in the sound power output caused by changes in operating conditions (e.g. rotational speed, line voltage) or mounting conditions.

The measurement uncertainty depends on the standard deviation of reproducibility tabulated in table 1 and on the degree of confidence that is desired. As examples, for a normal distribution of sound power levels, there is 90 % confidence that the true value of the sound power level of a source lies within the range $\pm 1,645 \sigma_R$ of the measured value and a 95 % confidence that it lies within the range $\pm 1,96 \sigma_R$ of the measured value. For further examples, reference should be made to the ISO 7574 series and ISO 9296.

Table 1 — Estimated values of the standard deviations of reproducibility of sound power levels determined in accordance with this International Standard

Octave-band centre frequencies	One-third-octave band centre frequencies	Standard deviation of reproducibility σ_R
Hz	Hz	dB
63	50 to 80	5 ¹⁾
125	100 to 160	3
250	200 to 315	2
500 to 4 000	400 to 5 000	1,5
8 000	6 300 to 10 000	2,5
A-weighted		1,5 ²⁾
1) Normally for outdoor measurements; many rooms are not qualified for this frequency band.		
2) Applicable to a source which emits noise with a relatively "flat" spectrum in the frequency range 100 Hz to 10 000 Hz.		

NOTES

4 The standard deviations listed in table 1 are associated with the test conditions and procedures defined in this International Standard and not with the noise source itself. They arise in part from variations between measurement laboratories, changes in atmospheric conditions if outdoors, the geometry of the test room or outdoor environment, the acoustical properties of the reflecting plane, absorption at the test room boundaries if indoors, background noise, and the type and calibration of instrumentation. They are also due to variations in experimental techniques, including the size and shape of the measurement surface, number and

location of microphone positions, sound source location, integration times, and determination of environmental corrections, if any. The standard deviations are also affected by errors associated with measurements taken in the near field of the source; such errors depend upon the nature of the sound source, but generally increase for smaller measurement distances and lower frequencies (below 250 Hz).

5 If several laboratories use similar facilities and instrumentation, the results of sound power determinations on a given source in those laboratories may be in better agreement than would be implied by the standard deviations of table 1.

6 For a particular family of sound sources, of similar size with similar sound power spectra and similar operating conditions, the standard deviations of reproducibility may be smaller than the values given in table 1. Hence, a noise test code for a particular type of machinery or equipment making reference to this International Standard may state standard deviations smaller than those listed in table 1, if substantiation is available from the results of suitable inter-laboratory tests.

7 The standard deviations of reproducibility, as tabulated in table 1, include the uncertainty associated with repeated measurements on the same noise source under the same conditions (for standard deviation of repeatability, see ISO 7574-1). This uncertainty is usually much smaller than the uncertainty associated with interlaboratory variability. However, if it is difficult to maintain stable operating or mounting conditions for a particular source, the standard deviation of repeatability may not be small compared with the values given in table 1. In such cases, the fact that it was difficult to obtain repeatable sound power level data on the source should be recorded and stated in the test report.

8 The procedures of this International Standard and the standard deviations given in table 1 are applicable to measurements on an individual machine. Characterization of the sound power levels of batches of machines of the same family or type involves the use of random sampling techniques in which confidence intervals are specified, and the results are expressed in terms of statistical upper limits. In applying these techniques, the total standard deviation must be known or estimated, including the standard deviation of production, as defined in ISO 7574-1, which is a measure of the variation in sound power output between individual machines within the batch. Statistical methods for the characterization of batches of machines are described in ISO 7574-4.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 354:1985, *Acoustics — Measurement of sound absorption in a reverberation room*.

ISO 2204:1979, *Acoustics — Guide to International Standards on the measurement of airborne acoustical noise and evaluation of its effects on human beings*.

ISO 3745:1977, *Acoustics — Determination of sound power levels of noise sources — Precision methods for anechoic and semi-anechoic rooms*.

ISO 3747:1987, *Acoustics — Determination of sound power levels of noise sources — Survey method using a reference sound source*.

ISO 4871:1984, *Acoustics — Noise labelling of machinery and equipment*.

ISO 6926:1990, *Acoustics — Determination of sound power levels of noise sources — Requirements for the performance and calibration of reference sound sources*.

ISO 7574-1:1985, *Acoustics — Statistical methods for determining and verifying stated noise emission values of machinery and equipment — Part 1: General considerations and definitions*.

ISO 7574-4:1985, *Acoustics — Statistical methods for determining and verifying stated noise emission values of machinery and equipment — Part 4: Methods for stated values for batches of machines*.

IEC 225:1966, *Octave, half-octave and third-octave band filters intended for the analysis of sounds and vibrations*.

IEC 651:1979, *Sound level meters*.

IEC 804:1985, *Integrating-averaging sound level meters*.

IEC 942:1988, *Sound calibrators*.

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1 sound pressure, p : A fluctuating pressure superimposed on the static pressure by the presence of sound. It is expressed in pascals.

NOTE 9 The magnitude of the sound pressure can be expressed in several ways, such as instantaneous sound pressure, maximum sound pressure, or as the square root of the mean-square sound pressure over designated time and space (i.e. over the measurement surface).

3.2 sound pressure level, L_p : Ten times the logarithm to the base 10 of the ratio of the square of the sound pressure to the square of the reference sound pressure. Sound pressure levels are expressed in decibels.

The frequency weighting or the width of the frequency band used, and the time weighting (S, F or I, see IEC 651) shall be indicated. The reference sound pressure is 20 μPa (2×10^{-5} Pa).

NOTE 10 For example, the A-weighted sound pressure level with time weighting S is L_{pAS} .

3.2.1 time-averaged sound pressure level, $L_{peq,T}$: Sound pressure level of a continuous steady sound that, within a measurement time interval T , has the same mean-square sound pressure as a sound under consideration which varies with time:

$$\begin{aligned} L_{peq,T} &= 10 \lg \left[\frac{1}{T} \int_0^T 10^{0.1 L_p(t)} dt \right] \text{ dB} \\ &= 10 \lg \left[\frac{1}{T} \int_0^T \frac{p^2(t)}{p_0^2} dt \right] \text{ dB} \quad \dots (1) \end{aligned}$$

Time-averaged sound pressure levels are expressed in decibels and shall be measured with an instrument which complies with the requirements of IEC 804.

NOTES

11 Time-averaged sound pressure levels are usually A-weighted and denoted by $L_{pAeq,T}$ which is usually abbreviated to L_{pA} .

12 In general, the subscripts "eq" and "T" are omitted since time-averaged sound pressure levels are necessarily determined over a certain measurement time interval.

3.2.2 single-event sound pressure level, $L_{p,1s}$: Time-integrated sound pressure level of an isolated single sound event of specified duration T (or specified measurement time T) normalized to $T_0 = 1$ s. It is expressed in decibels and is given by the following formula:

$$\begin{aligned} L_{p,1s} &= 10 \lg \left[\frac{1}{T_0} \int_0^T \frac{p^2(t)}{p_0^2} dt \right] \text{ dB} \\ &= L_{p,eq,T} + 10 \lg \left(\frac{T}{T_0} \right) \text{ dB} \quad \dots (2) \end{aligned}$$

3.2.3 measurement time interval: A portion or a multiple of an operational period or operational cycle for which the time-averaged sound pressure level is determined.

3.3 measurement surface: A hypothetical surface of area S , enveloping the source, on which the measurement points are located. The measurement surface terminates on one or more reflecting planes.

3.4 surface sound pressure level, $\overline{L}_{pf}$: The energy-average of the time-averaged sound pressure levels at all the microphone positions on the measurement surface, with the background noise correction K_1 (3.15) and the environmental correction K_2 (3.16) applied. It is expressed in decibels.

3.5 sound power, W : The rate per unit time at which airborne sound energy is radiated by a source. It is expressed in watts.

3.6 sound power level, L_W : Ten times the logarithm to the base 10 of the ratio of the sound power radiated by the sound source under test to the reference sound power. It is expressed in decibels.

The frequency weighting or the width of the frequency band used shall be indicated. The reference sound power is 1 pW (10^{-12} W).

NOTE 13 For example, the A-weighted sound power level is L_{WA} .

3.7 free field: A sound field in a homogeneous, isotropic medium free of boundaries. In practice, it is a field in which reflections at the boundaries are negligible over the frequency range of interest.

3.8 free field over a reflecting plane: A sound field in a homogeneous, isotropic medium in the half-space above an infinite, rigid plane surface on which the source is located.

3.9 frequency range of interest: For general purposes, the frequency range of interest includes the octave bands with centre frequencies from 125 Hz to 8 000 Hz.

NOTE 14 For special purposes, it is permissible to extend or reduce the frequency range of interest at either end, provided the test environment and instrument accuracy are satisfactory for use over the extended or reduced frequency range. For sources which radiate predominantly high (or low) frequency sound, it is permissible to extend or reduce the frequency range of interest, in order to optimize the test facility and procedures.

3.10 reference box: A hypothetical surface which is the smallest rectangular parallelepiped that just encloses the source and terminates on the reflecting plane or planes.

3.11 characteristic source dimension, d_0 : Half the length of the diagonal of the box consisting of the reference box and its images in adjoining reflecting planes.

3.12 measurement distance, d : The distance from the reference box to a box-shaped measurement surface.

3.13 measurement radius, r : The radius of a hemispherical measurement surface.

3.14 background noise: The noise from all sources other than the source under test.

NOTE 15 Background noise may include contributions from airborne sound, structure-borne vibration, and electrical noise in instrumentation.

3.15 background noise correction, K_1 : A correction term to account for the influence of background noise on the surface sound pressure level; K_1 is frequency dependent and is expressed in decibels. The correction in the case of A-weighting is denoted K_{1A} .

3.16 environmental correction, K_2 : A correction term to account for the influence of reflected or absorbed sound on the surface sound pressure level; K_2 is frequency dependent and is expressed in decibels. The correction in the case of A-weighting is denoted K_{2A} .

3.17 impulsive noise index (impulsiveness): A quantity by means of which the noise emitted by a source can be characterized as "impulsive". (See annex D.) It is expressed in decibels.

3.18 directivity index, DI : A measure of the extent to which a source radiates sound predominantly in one direction. (See annex E.) It is expressed in decibels.

4 Acoustic environment

4.1 General

The test environments that are applicable for measurements according to this International Standard are:

- a laboratory room which provides a free field over a reflecting plane;
- a flat outdoor area that meets the requirements of 4.2 and annex A;
- a room in which the contributions of the reverberant field to the sound pressures on the measurement surface are small compared with those of the direct field of the source.

NOTE 16 Conditions described under c) above are usually met in very large rooms as well as in smaller rooms with sufficient sound-absorptive materials on their walls and ceilings.

4.2 Criterion for adequacy of the test environment

As far as is practicable, the test environment shall be free from reflecting objects other than a reflecting plane so that the source radiates into a free field over a reflecting plane.