



BSI Standards Publication

Additive manufacturing — Design

Part 3: PBF-EB of metallic materials

National foreword

This British Standard is the UK implementation of EN ISO/ASTM 52911-3:2023. It is identical to ISO/ASTM 52911-3:2023.

The UK participation in its preparation was entrusted to Technical Committee AMT/8, Additive manufacturing.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 539 20735 4

ICS 25.030

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2023.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

Additive Manufacturing - Design - Part 3: PBF-EB of metallic materials (ISO/ASTM 52911-3:2023)

Fabrication additive - Conception - Partie 3: BF-EB de
matériaux métalliques (ISO/ASTM 52911-3:2023)

Additive Fertigung - Konstruktion - Teil 3:
Pulverbettbasiertes Schmelzen von Metallen mittels
Elektronenstrahl (ISO/ASTM 52911-3:2023)

This European Standard was approved by CEN on 17 February 2023.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

This document (EN ISO/ASTM 52911-3:2023) has been prepared by Technical Committee ISO/TC 261 "Additive manufacturing" in collaboration with Technical Committee CEN/TC 438 "Additive Manufacturing" the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2023, and conflicting national standards shall be withdrawn at the latest by September 2023.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national standards body/national committee. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

Endorsement notice

The text of ISO/ASTM 52911-3:2023 has been approved by CEN as EN ISO/ASTM 52911-3:2023 without any modification.

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
4.1 Symbols	2
4.2 Abbreviated terms	3
5 Characteristics of powder bed fusion (PBF) processes	3
5.1 General	3
5.2 Part size and cost considerations	4
5.3 Benefits to be considered in regard to the PBF process	4
5.4 Limitations to be considered in regard to the PBF process	4
5.5 Build layout, part orientation, and cost considerations	5
5.6 Feature constraints (islands, overhang, stair-step effect)	6
5.6.1 General	6
5.6.2 Islands	6
5.6.3 Overhang	6
5.6.4 Stair-step effect	6
5.7 Dimensional, form and positional accuracy	7
5.8 Data quality, resolution, representation	7
6 Design guidelines for electron beam powder bed fusion of metals (PBF-EB/M)	8
6.1 General	8
6.1.1 Selecting PBF-EB/M	8
6.1.2 Design and test cycles	8
6.2 Material and structural characteristics	8
6.3 Build orientation, positioning and arrangement	9
6.3.1 General	9
6.3.2 Powder spreading	9
6.3.3 Support structures design	10
6.3.4 Part nesting	12
6.3.5 Build plate part design considerations	13
6.3.6 Curl effect	13
6.3.7 Melt parameters	14
6.4 Anisotropy/heterogeneity of the material and part characteristics	15
6.4.1 General	15
6.4.2 Grain morphology	15
6.4.3 Porosity	16
6.4.4 Intermetallic diffusion layer	16
6.4.5 Chemistry heterogeneity	16
6.4.6 Thermal history	16
6.5 Surfaces	17
6.6 Post-processing	17
6.6.1 General	17
6.6.2 Surface finishing	17
6.6.3 Removal of powder residue	17
6.6.4 Removal of support structures	18
6.6.5 Geometric tolerances	18
6.6.6 Heat treatment	18
6.7 Design considerations	18
6.7.1 General	18
6.7.2 Cavities	19

6.7.3	Gaps.....	19
6.7.4	Wall thicknesses.....	19
6.7.5	Holes and channels.....	19
6.7.6	Integrated markings.....	20
6.8	Example applications.....	20
6.8.1	Topology optimized bracket printed using stacking build layout (provided by GE Arcam).....	20
6.8.2	Acetabular cup stacking design (provided by LimaCorporate Spa).....	21
6.8.3	Optimized elbow implant design (provided by LimaCorporate Spa).....	22
6.8.4	Lightweight pipe design (provided by JEOL).....	23
Bibliography.....		25

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 261, *Additive manufacturing*, in cooperation with ASTM Committee F42, *Additive Manufacturing Technologies*, on the basis of a partnership agreement between ISO and ASTM International with the aim to create a common set of ISO/ASTM standards on additive manufacturing, and in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 438, *Additive manufacturing*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

A list of all parts in the ISO 52911 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Powder bed fusion of metals (PBF/M) is an additive manufacturing (AM) process that offers additional manufacturing options alongside other established AM processes. PBF/M has the potential to reduce manufacturing time and costs, and increase part functionality. Practitioners are aware of the strengths and weaknesses of conventional, long-established manufacturing processes, such as cutting, joining and shaping processes (e.g. by machining, welding or injection moulding), and of giving them appropriate consideration at the design stage and when selecting the manufacturing process. In the case of PBF/M and AM in general, design and manufacturing engineers only have a limited pool of experience. Without the limitations associated with conventional processes, the use of PBF/M offers designers and manufacturers a high degree of freedom and this requires an understanding about the possibilities and limitations of the process.

The ISO 52911 series provides guidance for different powder bed fusion (PBF) technologies. In addition to this document on PBF-EB/M, the series is made up of ISO 52911-1 on laser-based powder bed fusion of metals (PBF-LB/M) and ISO 52911-2 on laser-based powder bed fusion of polymers (PBF-LB/P). Each document in the series shares [Clauses 1](#) to [5](#), where general information including terminology and the PBF process is provided. The subsequent clauses focus on the specific technology.

This document provides support to technology users, such as design and production engineers, when designing parts that need to be manufactured by means of PBF-EB/M. It will help practitioners to explore the benefits of PBF-EB/M and to recognize the process-related limitations when designing parts. It also builds on ISO/ASTM 52910 to extend the requirements, guidelines and recommendations for AM design to include the PBF-EB/M process.

Additive manufacturing — Design —

Part 3: PBF-EB of metallic materials

1 Scope

This document specifies the features of electron beam powder bed fusion of metals (PBF-EB/M) and provides detailed design recommendations.

Some of the fundamental principles are also applicable to other additive manufacturing (AM) processes, provided that due consideration is given to process-specific features.

This document also provides a state of the art review of design guidelines associated with the use of powder bed fusion (PBF) by bringing together relevant knowledge about this process and by extending the scope of ISO/ASTM 52910.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/ASTM 52900, *Additive manufacturing — General principles — Fundamentals and vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/ASTM 52900 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

curl effect

<aspect of heat-induced warping> dimensional distortion as the melted material cools and solidifies after being built or by poorly evacuated heat input

3.2

downskin area

D

(sub-)area where the normal vector $\vec{n}$ projection on the Z-axis is negative

Note 1 to entry: See [Figure 1](#).

3.3
downskin angle
 δ

angle between the plane of the build platform and the *downskin area* (3.2) where the value lies between 0° (parallel to the build platform) and 90° (perpendicular to the build platform)

Note 1 to entry: See [Figure 1](#).

3.4
upskin area
 U


(sub-)area where the normal vector $\vec{n}$ in relation to Z-axis is positive

Note 1 to entry: See [Figure 1](#).

3.5
upskin angle
 υ

angle between the plane of the build platform and the *upskin area* (3.4) where the value lies between 0° (parallel to the build platform) and 90° (perpendicular to the build platform)

Note 1 to entry: See [Figure 1](#).



Key	
δ	downskin angles
$\vec{n}$	normal vector
D	downskin (left) areas
U	upskin (right) areas
υ	upskin angles
Z	build direction

NOTE Source: VDI 3405-3:2015[3].

Figure 1 — Orientation of the part surfaces relating to the build platform

4 Symbols and abbreviated terms

4.1 Symbols

The symbols given in [Table 1](#) are used in this document.

Table 1 — Symbols

Symbol	Designation	Unit
a	overhang	mm

Table 1 (continued)

Symbol	Designation	Unit
D	downskin area	mm ²
I	island	mm ²
$\vec{n}$	normal vector	—
U	upskin area	mm ²
δ	downskin angle	°
ν	upskin angle	°

4.2 Abbreviated terms

The following abbreviated terms are used in this document.

CT	computed tomography
DICOM	digital imaging and communications in medicine
PBF-EB/M	electron beam powder bed fusion of metals
HIP	hot isostatic pressing
PBF-LB	laser-based powder bed fusion
PBF-LB/M	laser-based powder bed fusion of metals (also known as, for example, laser beam melting, selective laser melting)
PBF-LB/P	laser-based powder bed fusion of polymers (also known as, for example, laser beam melting, selective laser melting)
MRI	magnetic resonance imaging

5 Characteristics of powder bed fusion (PBF) processes

5.1 General

Consideration should be given to the specific characteristics of the manufacturing process used in order to optimize the design of a part. Examples of the features of AM processes which need to be taken into consideration during the design and process planning stages are listed in [5.2](#) to [5.8](#). With regards to metal processing, a distinction can be made between, for example, laser-based PBF (applied for metals and polymers) and electron beam-based PBF (applied for metals only).

Polymers PBF uses, in almost every case, low power lasers to sinter polymer powders together. Electron beam powder bed fusion for polymers is not usually considered because the negative charge from the electron beam will accumulate in non-conductive polymer powder and cause repulsive events that will ruin powder layer continuity and make any controlled sintering or melting impossible. As with polymer powders PBF, metals PBF includes varying processing techniques. Like polymers, metals PBF often requires the addition of support structures (see [6.3.3](#)). Metals PBF processes may use low-power lasers to bind powder particles by only melting the surface of the powder particles or high-power (approximately 200 W to 1 kW) energy beams to fully melt and fuse the powder particles together.

PBF-EB/M and PBF-LB/M have similar capabilities, although differences between these processes leads, in general, to PBF-EB/M supporting faster build rates at lower feature resolution compared to PBF-LB/M. The beam energy from the electron beam is of a higher intensity (due to a high energy source 3 kW to 6 kW), and the mechanism to raster the beam (i.e. electromagnetics for PBF-EB/M, optics for PBF-LB/M) differs between the two types of PBF processes. PBF-EB/M also tends to utilize a larger beam spot size, larger powder size distribution, and larger layer thickness. In general, PBF-EB/M