

Semiconductor devices — Discrete devices —

Part 7-5: Bipolar transistors for power switching applications

ICS 31.080.30

National foreword

This British Standard reproduces verbatim IEC 60747-7-5:2005 and implements it as the UK national standard.

The UK participation in its preparation was entrusted to Technical Committee EPL/47, Semiconductors, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the IEC title page, pages 2 to 24, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 19 January 2006

© BSI 19 January 2006

INTERNATIONAL STANDARD

IEC
60747-7-5

First edition
2005-08

**Semiconductor devices –
Discrete devices –**

**Part 7-5:
Bipolar transistors for power
switching applications**



Reference number
IEC 60747-7-5:2005(E)

CONTENTS

1	Scope.....	3
2	Normative references	3
3	Terms and definitions	3
4	Letter symbols – Energies	4
5	Essential ratings and characteristics.....	4
5.1	Ratings (limiting values)	4
5.2	Characteristics	5
6	Measuring methods	7
6.1	Verification of ratings (limiting values)	7
6.2	Methods of measurement	17
7	Acceptance and reliability.....	20
7.1	Endurance and reliability tests, and test methods	20
7.2	Type tests and routine tests	23
	Figure 1 – Test circuit for collector current.....	8
	Figure 2 – Test circuit for peak collector current	9
	Figure 3 – Test circuit for base current	10
	Figure 4 – Test circuit for peak base current.....	10
	Figure 5 – Circuit for testing the collector-base voltage V_{CBS} , V_{CBR} , V_{CBX}	11
	Figure 6 – Circuit for testing the collector-emitter voltage V_{CES} , V_{CER} , V_{CEX}	12
	Figure 7 – Circuit for testing the emitter-base voltages V_{EB}	13
	Figure 8 – Test circuit of reverse bias safe operating area (RBSOA).....	14
	Figure 9a – Waveforms of base current I_B and collector current I_C during turn-off	14
	Figure 9b – RBSOA curves during turn-off	15
	Figure 10 – Circuit for testing safe operating pulse duration at load short circuit. (SCSOA).....	16
	Figure 11 – Waveforms of base current I_B , collector current I_C and voltage V_{CE} during load short circuit condition SCSOA.....	16
	Figure 12 – Circuit diagram for measuring turn-on intervals and energy.....	17
	Figure 13 – Waveforms during turn-on intervals	18
	Figure 14 – Waveforms during turn-off intervals	19
	Figure 15a – Circuit for high temperature blocking(Method 1)	21
	Figure 15b – Circuit for high temperature blocking(Method 2)	21
	Figure 15 – Test circuit for high temperature blocking	21
	Figure 16 – Circuit for Intermittent operating life	22
	Figure 17 – Expected number of cycles versus temperature rise ΔT_{vj}	23
	Table 1 – Failure defining characteristics and failure criteria.....	7
	Table 2 – Failure-defining characteristics for endurance and reliability tests	20
	Table 3 – Minimum items of type and routine tests for transistors when applicable	24

SEMICONDUCTOR DEVICES – DISCRETE DEVICES –

Part 7-5: Bipolar transistors for power switching applications

1 Scope

This part of IEC 60747 gives requirements for bipolar switching transistors used for power switching application above 1 A.

NOTE Requirements concerning bipolar transistors in general can be found in IEC 60747-7.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60747-7, *Semiconductor devices – Part 7: Bipolar transistors*

IEC 60747-1:1983, *Semiconductor devices – Discrete devices and integrated circuits – Part 1: General*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

switching times

$t_{d(on)}$, t_r , t_s and t_f

as described in IEC 60747-1, but here the input waveform is the base current and the output waveform is the collector current

3.2

collector-emitter sustaining voltage

$V_{CE(SUS)}$

the collector-emitter breakdown voltage at higher values of collector current where the breakdown voltage is relatively constant over decreasing collector current for a specified termination between base and emitter terminals

3.3

turn-on energy (per pulse)

E_{on}

energy dissipated in transistor during turn-on

3.4

turn-off energy (per pulse)

E_{off}

energy dissipated in transistor during turn-off

4 Letter symbols – Energies

See IEC 60747-7.

Name and designation	Letter symbol	Remarks
Turn-on energy	E_{on}	Energy is always per pulse
Turn-off energy	E_{off}	

5 Essential ratings and characteristics

5.1 Ratings (limiting values)

Ratings shall be valid for the whole range of operating conditions as stated for the particular device, with reference to a curve where appropriate.

5.1.1 Temperatures

5.1.1.1 Minimum and maximum of operating temperatures, ambient or case or virtual junction (T_a or T_c or T_{vj})

5.1.1.2 Minimum and maximum of storage temperatures (T_{stg})

5.1.2 Currents

The ratings must cover the operation of the device over the range of operating temperatures. Where such ratings are temperature dependent, this dependence should be indicated.

5.1.2.1 Maximum continuous collector current (I_C)

5.1.2.2 Where appropriate, maximum peak repetitive collector current, under specified conditions (I_{CRM}).

5.1.2.3 Maximum continuous base current (I_B)

5.1.2.4 Where appropriate, maximum peak repetitive base current, under specified conditions (I_{BRM}).

5.1.2.5 Where appropriate, maximum emitter current, continuous and/or peak repetitive, under specified conditions (I_E , I_{ERM}).

5.1.3 Voltages

5.1.3.1 Maximum collector-base voltage with zero emitter current (V_{CBO})

5.1.3.2 Maximum collector-emitter voltage, either with zero base current or with a specified emitter-base reverse voltage (V_{CEO} or V_{CEX}).

5.1.3.3 Maximum emitter-base voltage with zero collector current (V_{EBO}).

5.1.3.4 Collector-emitter sustaining voltage (V_{CEXsus}).

Maximum rated value at specified collector current and specified base-emitter (reverse) voltage

5.1.4 Power dissipation

5.1.4.1 Maximum total power dissipation (without additional cooling for ambient-rated devices) up to ambient or case temperature of 25 °C (P_{tot}).

5.1.4.2 Derating factor above 25 °C or, for case-rated devices, derating curve

5.1.5 Safe operating areas

5.1.5.1 Forward biased safe operating area (FBSOA)

Diagram showing the area of collector currents (I_C) and collector-emitter voltages (V_{CE}) which the transistor will sustain simultaneously without being damaged by thermal overload or by the first or second breakdown, for d.c. and pulse operation.

Conditions to be specified:

- case temperature (T_C);
- pulse time (t_P);
- duty cycle (δ).

5.1.5.2 Reverse biased safe operating area (RBSOA)

Diagram showing the area of collector currents (I_C) and collector-emitter voltages (V_{CE}) which the transistor will sustain simultaneously for a short period of time during turn-off without being damaged

Conditions to be specified:

- case temperature (T_C);
- reverse base current (I_{B2});
- conditions in the drive circuit.

5.1.5.3 Short-circuit safe operating area (SCSOA)

The SCSOA is given by a pair of values of short-circuit duration ($t_{p(sc)}$) and collector-emitter voltage (V_{CE}) that may not be exceeded under the load short circuit conditions. The device may be turned on and turned off again for shorting a voltage source without failure.

5.2 Characteristics

5.2.1 Cut-off currents

NOTE One or more of these currents should be stated.

5.2.1.1 Collector-base current (I_{CBO})

- Maximum value at 25 °C, preferably at the maximum rated value of the collector-base voltage and with the emitter open-circuited.
- Maximum value at a high operating temperature, at a voltage preferably between 65 % and 85 % of the maximum rated collector-base voltage, and with the emitter open-circuited.

5.2.1.2 Collector-emitter current (I_{CEX})

- Maximum value at 25 °C, preferably at the maximum rated value of collector-emitter voltage and under specified base-emitter bias conditions.
- Maximum value at a high operating temperature, at a voltage preferably between 65 % and 85 % of the maximum rated collector-emitter voltage and under specified base-emitter bias conditions.

5.2.1.3 Collector-emitter current (I_{CES})

- Maximum value at 25 °C, preferably at the maximum rated value of the collector-emitter voltage and with the base short-circuited to the emitter.
- Maximum value at a high operating temperature, at a voltage preferably between 65 % and 85 % of the maximum rated collector-emitter voltage and with the base short-circuited to the emitter.

5.2.1.4 Collector-emitter current (I_{CER})

- Maximum value at 25 °C, preferably at the maximum rated collector-emitter voltage and with a specified base-emitter resistance.
- Maximum value at a high operating temperature, at a voltage preferably between 65 % and 85 % of the maximum rated collector-emitter voltage and with a specified base-emitter resistance.

5.2.1.5 Emitter-base current (I_{EBO})

- Maximum value at 25 °C at a specified high value of the emitter-base voltage and with the collector open-circuited.
- Maximum value at a high operating temperature and at a specified emitter-base voltage, and with the collector open-circuited.

5.2.2 Static value of common-emitter forward current transfer ratio (h_{FE})

Minimum value at 25 °C, at specified collector current and collector-emitter voltage.

5.2.3 Collector-emitter saturation voltage (V_{CEsat})

Maximum value at 25 °C, for at least one specified collector current and specified base current

5.2.4 Base-emitter saturation voltage (V_{BEsat})

Maximum value at 25 °C, at specified collector and base currents.

5.2.5 Turn-on energy (E_{on})

Maximum value per pulse with inductive load under specified conditions of T_a or T_c or T_{vj} , high V_{CE} , high I_C and I_B .

5.2.6 Turn-off energy (E_{off})

Maximum value per pulse with inductive load under specified conditions of T_a or T_c or T_{vj} , high V_{CE} , high I_C and I_B .

5.2.7 Switching times**5.2.7.1 Turn-on delay time ($t_{d(on)}$)**

Maximum value for resistive load under specified conditions.

5.2.7.2 Rise time (t_r)

Maximum value, at nominal values of collector current (I_C) and base forward current (I_{B1}).

5.2.7.3 Turn-on time (t_{on})

Maximum value, at nominal values of collector current (I_C), base forward current (I_{B1}) and base-emitter voltage (V_{BE}) prior to turn-on pulse.

5.2.7.4 Storage time (t_s)

Maximum value, at nominal values of collector current (I_C) and base forward and reverse currents (I_{B1} and I_{B2}).

5.2.7.5 Fall time (t_f)

Maximum value for resistive load under specified conditions.

5.2.7.6 Turn-off time (t_{off})

Maximum value, at nominal values of collector current (I_C) and base forward and reverse currents (I_{B1} and I_{B2}).

5.2.8 Thermal resistance junction to case ($R_{th(j-c)}$)

Maximum value for case-rated transistors.

5.2.9 Thermal resistance junction to ambient ($R_{th(j-a)}$)

Maximum value for ambient-rated transistors.

5.2.10 Transient thermal impedance junction to case ($Z_{th(j-c)}$)

For case-rated transistors, diagram showing the maximum value against the time which has elapsed after a step change in power dissipation.

5.2.11 Transient thermal impedance junction to ambient ($Z_{th(j-a)}$)

For ambient-rated transistors, diagram showing the maximum value against the time which has elapsed after a step change in power dissipation.

6 Measuring methods

6.1 Verification of ratings (limiting values)

Table 1 – Failure defining characteristics and failure criteria

Failure-defining Characteristics	Failure criteria	Measurement conditions
I_{CES}	$I_{CES} > USL$	Specified V_{CE}
V_{CEsat}	$V_{CEsat} > USL$	I_C specified for V_{CEsat}
USL: upper specified limit.		

6.1.1 Voltages and currents

6.1.1.1 Collector current (I_C)

6.1.1.1.1 Purpose

To verify that the collector current capability of a transistor is not less than the maximum rated value I_C under specified conditions.