BS IEC 61966-12-1:2020

BSI Standards Publication

Multimedia systems and equipment — Colour measurement and management

Part 12-1: Metadata for identification of colour gamut (Gamut ID)

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

National foreword

This British Standard is the UK implementation of IEC 61966-12-1:2020. It supersedes BS EN 61966-12-1:2011, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee EPL/100, Audio-visual equipment.

A list of organizations represented on this committee can be obtained on request to its committee manager.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020
Published by BSI Standards Limited 2020

ISBN 978 0 580 96680 4

ICS 17.180.20; 33.160.60; 33.160.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2020.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

IEC 61966-12-1

Edition 2.0 2020-09

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Multimedia systems and equipment – Colour measurement and management – Part 12-1: Metadata for identification of colour gamut (Gamut ID)

Systèmes et appareils multimédias – Mesure et gestion de la couleur – Partie 12-1: Métadonnées d'identification des gammes de couleurs (Gamut ID)

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 17.180.20; 33.160.40

ISBN 978-2-8322-8762-0

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

AVA Documents
Document Sharing Hub

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

Full document details: BS IEC 61966-12-1:2020

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Abbreviated terms 8
4 Overview 8
5 Header of Gamut ID metadata 9
6 Description of gamut geometry (full profile) 12
6.1 General 12
6.2 Gamut geometry 12
6.3 Header of description of gamut geometry 14
6.4 Gamut Instances 15
6.5 Gamut Hulls 17
6.6 Gamut Component 18
6.6.1 General 18
6.6.2 Packing of face indices 19
6.7 Faces 20
6.7.1 General 20
6.7.2 Packing of vertex indices 21
6.8 Vertices 21
6.8.1 General 21
6.8.2 Packing of colour space coordinates for vertices 22
7 Description of gamut geometry (medium and simple profiles) 23
7.1 General 23
7.2 Medium profile 23
7.3 Simple profile 23
8 Description of colour reproduction 24
Annex A (informative) Size of Gamut ID metadata 27
Annex B (informative) Motivation and requirements 28
B.1 History 28
B.2 Motivation 28
B.3 Scope of Gamut ID metadata 29
B.4 Requirements 29
B.5 Structure 30
B.6 Specific features 32
Annex C (informative) Use of profiles 34
C.1 Gamut ID profiles 34
C.2 Medium profile 34
C.3 Simple profile 35
Annex D (informative) Example of Gamut ID metadata in simple profile 36
Bibliography 40

Documents
Document Sharing Hub
Full document details: BS IEC 61966-12-1:2020

Figure 1 – Logical structure of the description of gamut geometry (full profile) 13
Figure B.1 – Scope of Gamut ID – Generation and use of metadata are not specified 29
Figure B.2 – Example of a description of gamut geometry in CIEXYZ colour space consisting of a set of triangular faces 30
Figure B.3 – Example of a gamut with identified ridge due to colorant channels 33
Figure B.4 – Example of a non-convex gamut with two convex Gamut Hulls 33

Table 1 – Format of Gamut ID metadata 9
Table 2 – Header of Gamut ID metadata 10
Table 3 – Bit depth for encoding of a colour space coordinate 12
Table 4 – Description of gamut geometry 14
Table 5 – Header of description of gamut geometry 14
Table 6 – Gamut Instances 15
Table 7 – ith Gamut Instance 16
Table 8 – Gamut Hulls 17
Table 9 – hth Gamut Hull 18
Table 10 – Definition of Gamut Components 19
Table 11 – cth Gamut Component 19
Table 12 – Example for packing of Gamut Components 20
Table 13 – Definition of faces 20
Table 14 – Example for packing of faces 21
Table 15 – Vertices 22
Table 16 – Packing of 10-bit colour space coordinates 22
Table 17 – Packing of 12-bit colour space coordinates 23
Table 18 – Description of gamut geometry (simple profile) 24
Table 19 – Header of description of gamut geometry (simple profile) 24
Table 20 – Definition of vertices (simple profile) 24
Table 21 – Header of description of colour reproduction 25
Table B.1 – Requirements and Gamut ID features 32
Table C.1 – Profiles for the description of gamut geometry 34
Table D.1 – Colour gamut for digital cinema 36
Table D.2 – Example for the header 36
Table D.3 – Example for the header of description of gamut geometry 37
Table D.4 – Example of definition of vertices 37
Table D.5 – Encoded colour space coordinates for vertices 37

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MULTIMEDIA SYSTEMS AND EQUIPMENT – COLOUR MEASUREMENT AND MANAGEMENT –

Part 12-1: Metadata for identification of colour gamut (Gamut ID)

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61966-12-1 has been prepared by technical area 2: Colour measurement and management, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition cancels and replaces the first edition published in 2011. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) ITU-R BT.2020 colour spaces added in Clause 6;
b) ITU-R BT.2100 colour spaces added in Clause 6.

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/3126/CDV	100/3375/RVC

Documents
Document Sharing Hub

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61966 series, published under the general title *Multimedia systems and equipment – colour measurement and management*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

INTRODUCTION

New technologies in capturing and displaying wide-gamut colour images enable a new market of wide-gamut video colour content and high dynamic range video content creation. Recent video standards for wide gamut colour space encoding such as ITU-R BT.2020 (UHDTV) and IEC 61966-2-4 (xvYCC) were established in order to be able to distribute content with a colour gamut that is extended with respect to classical colour gamuts such as defined by colorimetry standards ITU-R BT.601 (standard-definition television) and ITU-R BT.709 (high-definition television). Recent video standards for high dynamic range (HDR) colour space encoding, such as ITU-R BT.2100, were established in order to be able to distribute content with a colour gamut and a dynamic range that are both extended with respect to classical colour encoding, such as that defined by ITU-R BT.709. With the increasing popularity of wide gamut and high dynamic range content and displays, the variety of colour gamuts of displays is expected to increase. This issue can be an obstacle for adopting wide-gamut video colour content in professional content creation since the compatibility of the content to the employed displays as well as the compatibility among different displays is not ensured. The term display includes here any video colour reproduction equipment, such as direct view displays and projectors. Thanks to improvements of technology, the variety of colour gamut and colour reproduction capacities of displays increases, while the colour gamut and the colour encoding rules of existing colour space encoding standards are fixed.

To address this issue, this document specifies a colour gamut metadata scheme for video systems including information for colour reproduction. This metadata can amend a video content or a display. More specifically, improvements can be achieved if the wide-gamut colour content is created with the knowledge of the display colour gamut as well as if the colour reproduction in the display is done with the knowledge of the colour gamut of the pictorial content.

This document permits video systems to define their own colour gamut. This document defines necessary metadata that allows managing inhomogeneous video systems with different colour gamuts. This document generalizes existing colour space encoding standards having a fixed colour gamut.

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

MULTIMEDIA SYSTEMS AND EQUIPMENT – COLOUR MEASUREMENT AND MANAGEMENT –

Part 12-1: Metadata for identification of colour gamut (Gamut ID)

1 Scope

This part of IEC 61966 defines the colour gamut metadata scheme for video systems and similar applications.

The metadata can be associated with wide-gamut video colour content or to a piece of equipment to display the content.

When associated with content, the colour gamut metadata defines the gamut for which the content was created. It can be used by the display for controlled colour reproduction even if the display's colour gamut is different from that of the content.

When associated with a display, the colour gamut metadata defines the display colour gamut. It can be used during content creation to enable improved colour reproduction.

The colour gamut metadata can cover associated colour encoding information, which includes all information required for a controlled colour reproduction, when such information is not provided by the colour encoding specification.

The colour gamut metadata scheme provides scalable solutions. For example, more flexible solutions will be used for the professional use, while much simpler solutions will be used for consumer use with easier product implementation.

This part of IEC 61966 only defines the colour gamut metadata scheme. Vendor-specific solutions for creation and end-use of this metadata are allowed.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-845, *International electrochnical vocabulary – Chapter 845: Lighting*

IEC 61966-2-4:2006, *Multimedia systems and equipment – Colour measurement and management – Part 2-4: Colour management – Extended-gamut YCC colour space for video applications – xvYCC*

ISO 15076-1:2010, *Image technology colour management – Architecture, profile format and data structure – Part 1: Based on ICC.1:2010*

ITU-R BT.709, *Parameter values for the HDTV standards for production and international programme exchange*

CIE 15:2004, *Colorimetry*

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

SMPTE 274M:2005, *SMPTE Standard for Television - 1920 x 1080 Image Sample Structure, Digital Representation and Digital Timing Reference Sequences for Multiple Picture Rates*

ITU-R BT.2020, *Parameter values for ultra-high definition television systems for production and international programme exchange*

ITU-R BT.2100, *Image parameter values for high dynamic range television for use in production and international programme exchange*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-845 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1.1
content
video content in production, post-production or consumption

3.1.2
gamut
solid in a colour space

Note 1 to entry: A solid in a colour space, such as specified by ITU-R BT.2100, can contain colours with high luminance.

3.1.3
gamut boundary description
description of the boundary of a colour gamut

3.1.4
radiometrically-linear colour space coordinates
colour space coordinates that are linear with respect to image radiance

3.2 Abbreviated terms

GBD gamut boundary description

LSB least significant bit

MSB most significant bit

GI gamut instance

GH gamut hull

GC gamut component

4 Overview

This document specifies metadata called "Gamut ID metadata" providing information on an actual colour gamut.

The Gamut ID metadata contains four parts and its format is summarized in Table 1.

AVA Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

Table 1 – Format of Gamut ID metadata

Byte # hex	**Metadata content**
0h0000	Header of Gamut ID metadata
ID_G	Description of gamut geometry
ID_E	Description of colour reproduction

Clause 5 specifies the header of Gamut ID metadata.

Clauses 6 and 7 specify the description of gamut geometry that corresponds to one of three profiles as listed below:

- full profile;
- medium profile;
- simple profile.

Clause 6 specifies the full profile of the description of gamut geometry. The medium and simple profiles are specified in Clause 7.

Clause 8 specifies the description of colour reproduction.

Annex A discusses the size of Gamut ID metadata.

Annex B gives background information.

Annex C discusses the use of simple, medium and full profiles.

5 Header of Gamut ID metadata

The Gamut ID metadata starts with the header shown in Table 2.

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

Table 2 – Header of Gamut ID metadata

Byte # hex	Size Bytes	Symbols	Description								Values
			7	6	5	4	3	2	1	0	
00	1	N, P	R	ID_PROFILE		ID_PRECISION		ID_GBD_SPACE			R = reserved = 0b0 (1bit) ID_PROFILE (2 bits): 0b00: Full profile 0b01: Medium profile 0b10: Simple profile 0b11: Reserved ID_PRECISION (2 bits): 0b00: 8 bits 0b01: 10 bits 0b10: 12 bits 0b11: Reserved ID_GBD_SPACE (3bits): 0b000: ITU-R BT.709 RGB 0b001: xvYCC-601 (IEC 61966-2-4 -SD) YCC 0b010: xvYCC-709 (IEC 61966-2-4 -HD) YCC 0b011: XYZ (see below) 0b100: ITU-R BT.2020 R'G'B' 0b101: ITU-R BT.2020 $Y'C'_BC'_R$ 0b110: ITU-R BT.2020 $Y_C'C'_{BC}C'_{RC}$ 0b111: ID_GBD_SPACE_EXT
01	2	ID_G	Byte # of start of the description of gamut geometry								[0h0009;0hFFFF]
03	2	ID_E	Byte # of start of the description of colour reproduction								[0;0hFFFF]
05	1		ID_GBD_SPACE_EXT								0h00: ITU-R BT.2100 R'G'B' PQ narrow 0h01: ITU-R BT.2100 R'G'B' PQ full 0h02: ITU-R BT.2100 R'G'B' HLG narrow 0h03: ITU-R BT.2100 R'G'B' HLG full 0h04: ITU-R BT.2100 $Y'C'_BC'_R$ PQ narrow 0h05: ITU-R BT.2100 $Y'C'_BC'_R$ PQ full 0h06: ITU-R BT.2100 $Y'C'_BC'_R$ HLG narrow 0h07: ITU-R BT.2100 $Y'C'_BC'_R$ HLG full 0h08: ITU-R BT.2100 IC_TC_P PQ narrow 0h09: ITU-R BT.2100 IC_TC_P PQ full 0h0A: ITU-R BT.2100 IC_TC_P HLG narrow 0h0B: ITU-R BT.2100 IC_TC_P HLG full 0h0C – 0hFF: reserved
06	3		Reserved. Shall be zero.								0h000000

AVA Documents
Document Sharing Hub

ID_PROFILE indicates the profile of the Gamut ID metadata and shall be one of

- 0b00: Full profile,
- 0b01: Medium profile,
- 0b11: Simple profile.

ID_GBD_SPACE indicates the colour space and the colour space encoding for colour vertices in the description of gamut geometry and shall be one of:

- 0b000: ITU-R BT.709, RGB space, encoding in accordance with SMPTE 274M,
- 0b001: xvYCC-601, YCbCr space, encoding in accordance with IEC 61966-2-4 – SD,
- 0b010: xvYCC-709, YCbCr space, encoding in accordance with IEC 61966-2-4 – HD,
- 0b011: XYZ; encoding shall use the XYZNumber format of ICC profiles specified in ISO 15076-1:2010 taking 12 bytes for one XYZ triple.
- 0b100: ITU-R BT.2020, RGB space, encoding in accordance with ITU-R BT.2020 R', G', B',
- 0b101: ITU-R BT.2020, YCbCr space', encoding in accordance with ITU-R BT.2020 Y', C'_B, C'_R,
- 0b110: ITU-R BT.2020, YCbCr space, encoding in accordance with ITU-R BT.2020 Y_C', C'_{BC}, C'_{RC},
- 0b111: colour space and colour space encoding are indicated by ID_GBD_SPACE_EXT.

If ID_GBD_SPACE equals 0b111, ID_GBD_SPACE_EXT indicates the colour space and the colour space encoding for colour vertices in the description of gamut geometry and shall be one of:

- 0h00: ITU-R BT.2100 R'G'B', PQ format, narrow range,
- 0h01: ITU-R BT.2100 R'G'B', PQ format, full range,
- 0h02: ITU-R BT.2100 R'G'B', HLG format, narrow range,
- 0h03: ITU-R BT.2100 R'G'B', HLG format, full range,
- 0h04: ITU-R BT.2100 $Y'C'_BC'_R$, PQ format, narrow range,
- 0h05: ITU-R BT.2100 $Y'C'_BC'_R$, PQ format, full range,
- 0h06: ITU-R BT.2100 $Y'C'_BC'_R$, HLG format, narrow range,
- 0h07: ITU-R BT.2100 $Y'C'_BC'_R$, HLG format, full range,
- 0h08: ITU-R BT.2100 IC_TC_P, PQ format, narrow range,
- 0h09: ITU-R BT.2100 IC_TC_P, PQ format, full range,
- 0h0A: ITU-R BT.2100 IC_TC_P, HLG format, narrow range,
- 0h0B: ITU-R BT.2100 IC_TC_P, HLG format, full range.

ID_PRECISION, ID_GBD_SPACE and ID_GBD_SPACE_EXT specify, in accordance with Table 3, the number N of bits that are used per colour channel in order to define the coordinates of a colour in a colour space.

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020

Table 3 – Bit depth for encoding of a colour space coordinate

ID_GBD_SPACE	ID_PRECISION	Bit depth N
0b011	Any	32 bits
else	0b00	8 bits
	0b01	10 bits
	0b10	12 bits
	0b11	Reserved

If ID_GBD_SPACE equals 0b011 for XYZ encoding, bit depth N shall be 32 independent of ID_PRECISION.

BT.2020 and BT.2100 encodings are defined by the ITU-R for bit depths of 10 or 12, only.

ID_G indicates the offset in bytes from the beginning of Gamut ID metadata to the beginning of the description of gamut geometry.

If ID_E is different from 0h0000, the Gamut ID metadata contains a description of colour reproduction and ID_E indicates the offset in bytes from the beginning of Gamut ID metadata to the beginning of the description of colour reproduction. If ID_E has the value 0h0000, the Gamut ID metadata does not contain a description of colour reproduction.

6 Description of gamut geometry (full profile)

6.1 General

In the header of Gamut ID metadata, if ID_PROFILE equals 0b00, the description of gamut geometry shall correspond to the full profile.

6.2 Gamut geometry

The description of gamut geometry of the Gamut ID metadata describes the boundary of the actual colour gamut. The description of gamut geometry starts at byte number ID_G.

The description of gamut geometry contains five sets of different elements:

- gamut instances,
- gamut hulls,
- gamut components,
- faces, and
- vertices.

The logical structure of the Gamut ID description of colour gamut is shown in Figure 1.

Documents
Document Sharing Hub

Full document details: BS IEC 61966-12-1:2020