BS IEC 62106-6:2018

BSI Standards Publication

# Radio data system (RDS) — VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018

# National foreword

This British Standard is the UK implementation of IEC 62106-6:2018.

The UK participation in its preparation was entrusted to Technical Committee EPL/100, Audio, video and multimedia systems and equipment.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 99143 1

ICS 33.160.40

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2018.

**Amendments/corrigenda issued since publication**

| Date | Text affected |
|---|---|

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018

# IEC 62106-6

Edition 1.0 2018-09

# INTERNATIONAL STANDARD

## Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz – Part 6: Compilation of technical specifications for Open Data Applications in the public domain

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.40

ISBN 978-2-8322-6071-5

**Warning! Make sure that you obtained this publication from an authorized distributor.**

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018

CONTENTS

FOREWORD ..... 4
INTRODUCTION ..... 6
1 Scope ..... 7
2 Normative references ..... 7
3 Terms, definitions, abbreviated terms and conventions ..... 7
3.1 Terms and definitions ..... 7
3.2 Abbreviated terms ..... 7
3.3 Notation and conventions ..... 8
4 ODAs in the public domain ..... 8
4.1 ODAs in the 37-bit ODA application group structure ..... 8
4.1.1 Traffic Message Channel (TMC) ..... 8
4.1.2 Other public ODAs ..... 8
4.2 ODAs in the group type C structure for the upper data-streams 1, 2 and 3 ..... 8
Annex A (normative) Coding of RadioText Plus (RT+) tagging information for RadioText in group type 2A/B ..... 9
A.1 General ..... 9
A.2 Terms used ..... 9
A.3 RT+ tag ..... 10
A.4 RT+ information elements and data model ..... 11
A.4.1 General ..... 11
A.4.2 List of RT content types ..... 11
A.4.3 Structures of RT+ messages ..... 12
A.4.4 Receiver data model ..... 13
A.5 RT+ coding for RT ..... 15
A.5.1 General ..... 15
A.5.2 RT+ identification (group type 3A) ..... 15
A.5.3 Coding of the RT+ tag ..... 16
A.5.4 Clearing of RT+ messages ..... 17
A.6 Broadcasting conventions ..... 20
A.7 Receiving conventions ..... 20
A.8 Marking ..... 20
Annex B (normative) Coding of RadioText Plus(RT+) tagging information for RadioText in the eRT ODA of Annex C ..... 21
Annex C (normative) Coding of enhanced RadioText (eRT) ..... 22
C.1 General ..... 22
C.2 Coding eRT in ODA groups ..... 22
C.2.1 General ..... 22
C.2.2 eRT identification (Group type 3A) and coding of the text string ..... 22
C.2.3 Coding of the eRT text string ..... 23
C.2.4 UTF-8 decoding problems when used with RT+ ..... 24
C.3 Broadcasting conventions ..... 25
C.4 Receiving conventions ..... 25
C.5 Marking ..... 25
Annex D (normative) Coding of AF lists in the frequency range 64,1 MHz to 107,9 MHz: ODA-AF ..... 26
D.1 Objective to be achieved ..... 26
D.2 Description of the coding process ..... 26

AVA Documents
Document Sharing Hub

D.2.1 ODA-AF identification (group type 3A) ..... 26
D.2.2 AF coding in the application group ..... 27
D.2.3 AF method A ..... 29
D.2.4 AF method B ..... 29
D.2.5 Convention for identification of the AF method used ..... 30

Figure A.1 – Example 1: RT+ information of the category 'Item' (see Table A.2) will be attached to the programme elements Item 1 and Item 2 ..... 14
Figure A.2 – Example 2: RT+ information of the category 'Item' will be attached to the programme elements Item 1 and Item 2, but not to the programme element News ..... 14
Figure A.3 – Example 3: RT+ information of the category 'Item' will be attached only to the programme element Item 1, but not to the programme element Talk ..... 14
Figure A.4 – Bit allocation for group 3A (message bits and AID) ..... 15
Figure A.5 – Coding of the message bits of the application group ..... 16
Figure C.1 – Bit allocation for group 3A (message bits and AID) ..... 23
Figure C.2 – Coding of the message bits of the application group type A ..... 24
Figure D.1 – New ODA-AF – group type 3A ..... 26
Figure D.2 – New ODA-AF application group – group type A ..... 27

Table A.1 – RT+ information elements for RT ..... 9
Table A.2 – Code list and 'RT+ class' description of RT content types (1 of 3) ..... 18
Table B.1 – RT+ information elements for eRT ..... 21
Table C.1 – eRT information elements ..... 22
Table D.1 – 9-bit AF code table for VHF Band I (64,0 MHz to 88,0 MHz) ..... 27
Table D.2 – 9-bit AF code table for VHF Band II (87,5 MHz to 108 MHz) ..... 27
Table D.3 – 9-bit special meanings code table ..... 28
Table D.4 – LF/MF code table – ITU regions 1 and 3 (9 kHz spacing) ..... 28
Table D.5 – MF code table – ITU region 2 (10 kHz spacing) ..... 28

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018

INTERNATIONAL ELECTROTECHNICAL COMMISSION

# RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

## Part 6: Compilation of technical specifications for Open Data Applications in the public domain

## FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62106-6 has been prepared by technical area 1: Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition, together with IEC 62106-1, IEC 62106-2, IEC 62106-3, IEC 62106-4 and IEC 62106-5, cancels and replaces IEC 62106:2015, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62106:2015:

- Provision has been made to carry RDS on multiple data-streams (RDS2);
- New are AF coding below 87,5 MHz (down to 64,0 MHz) using ODA-AID 0x6365;

AVA Documents
Document Sharing Hub

- RT+ can now be used simultaneously for RT and eRT, each having its own RT+ ODA;
- Data-streams 1, 2 and 3 are exclusively UTF-8 coded. For backwards compatibility, UCS-2 encoded eRT on data-stream 0 is retained.

The text of this International Standard is based on the following documents:

| CDV | Report on voting |
|---|---|
| 100/2912/CDV | 100/3060/RVC |

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62106 series, published under the general title *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018

# INTRODUCTION

Since the mid-1980s a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, specifically for smartphone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA.

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved, and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard IEC 62106 for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, IEC 62106 has been restructured as follows:

Part 1: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Usage and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

The following future parts are planned:

Part 7: RBDS

Part 8: Universal Encoder Communication Protocol UECP

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

Obsolete or unused functions from the original RDS standard IEC 62106:2015 have been deleted.

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018

# RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

## Part 6: Compilation of technical specifications for Open Data Applications in the public domain

## 1 Scope

This part of IEC 62106 contains the technical specifications for Open Data Applications in the public domain. This document is maintained by the RDS Forum Office. The RDS Forum Office applies an easy procedure for registering new Open Data Applications, to ensure that they can be used without the need to change the RDS standard. The ODA feature permits defining new applications that can be decoded on a receiver. The receiver needs to the adequate software handler for the specific AID, which identifies the application. Receivers that have not implemented the software handler needed for decoding are not affected by ODA data received for any of the applications already defined and specified.

The procedure for registering a new ODA is described in IEC 62106-3.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106 (all parts), *Radio Data System (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*

ISO/IEC 10646, *Information technology – Universal Coded Character Set (UCS)*

ISO 14819 (all parts), *Intelligent transport systems – Traffic and travel information messages via traffic message coding*

## 3 Terms, definitions, abbreviated terms and conventions

### 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62106-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

### 3.2 Abbreviated terms

For the purposes of this document, the abbreviated terms given in IEC 62106-1 and IEC 62106-2 apply.

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018

### 3.3 Notation and conventions

The notation and conventions given in IEC 62106-1 apply.

## 4 ODAs in the public domain

### 4.1 ODAs in the 37-bit ODA application group structure

#### 4.1.1 Traffic Message Channel (TMC)

This ODA has been standardized in ISO 14819 (all parts).

#### 4.1.2 Other public ODAs

There exist four other public ODAs:

- Annex A: Coding of RadioText Plus (RT+) tagging information for RadioText in group type 2A/B.
- Annex B: Coding of RadioText Plus (RT+) tagging information for enhanced RadioText (eRT).
- Annex C: Coding of enhanced RadioText (eRT) using UTF-8 coding as standardized in ISO/IEC 10646.
- Annex D: Coding of AF lists in the frequency range 64,1 MHz to 107,9 MHz.

### 4.2 ODAs in the group type C structure for the upper data-streams 1, 2 and 3

Such applications are still under development.

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018

# Annex A
(normative)

# Coding of RadioText Plus (RT+) tagging information for RadioText in group type 2A/B

## A.1 General

RT+ is designed to let the listener (or user) take additional benefit from the RadioText (RT) service by enabling receivers to offer direct access to specific elements of RadioText messages (e.g. to the title of the broadcast song transmitted at the same time, to news, to telephone numbers such as those used for voting, to web addresses for browsing web content offered by the radio programme provider, etc.).

These RT+ messages carried in the RadioText messages are identified by their location within the message and by the class code of their RT content type (see Table A.2). Thus, a receiver is able to store the different RT+ messages, and the listener may then select and request a specific content type from the storage at any instant in time that fits the user's needs. The advantage of this method is that a user is no longer forced to watch a lot of information passing by. The listener rather gets the opportunity to select specifically any favourite information to be shown on a static display.

Moreover, RT+ gives the possibility to present selected RT message elements to car drivers on a quasi static display without any major risk of distracting the attention of the driver. Furthermore, RT+ is well suited for mobile phones with built-in RDS FM receivers: telephone numbers may be routed directly from the RadioText to the dialer.

RT+ is based on RT messages and is completely backwards compatible. All additional information necessary for implementing the RT+ service is carried as an Open Data Application in group type 3A and in an associated ODA application group (see Table A.1).

The Application Identification (AID) assigned to RT+ for RT in group type 2A/B is 0x4BD7.

**Table A.1 – RT+ information elements for RT**

| RT+ information elements | | |
|---|---|---|
| **RT message** | **RT+ identification** | **RT+ tags** |
| Group type 2A/B (see IEC 62106-2) | AID in group type 3A | ODA application group type A |

## A.2 Terms used

**Category:** The 'RT content types' listed in Table A.2 are grouped in categories: Item (information on programme element), Info (general information services), Programme (information on the programme), Interactivity (related information), Descriptors (places and addresses, date, time, etc.) and Private classes (to be defined by individual broadcasters) and reserved codes for future amendments.

**Descriptor:** a category of 'RT content types used for describing places and addresses, date and time, specific identifiers, etc.

**Length marker:** part of the RT+ information element which describes the additional length of the tagged RadioText message. Counted are characters (64 maximum), not bytes. The addresses of the RadioText characters range from 0 to 63.

Documents
Document Sharing Hub

Full document details: BS IEC 62106-6:2018