

Implementation of
ISO 10163-1:1993

Information and documentation — Open Systems Interconnection — Search and Retrieve Application Protocol Specification —

Part 1: Protocol specification

UDC 025.32:681.3:621.39

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW



Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Information and Documentation Standards Policy Committee (DOT/-) to Technical Committee DOT/7, upon which the following bodies were represented:

- Aslib
- Bodleian Library
- British Library
- British Photographic Association
- Council of Polytechnic Librarians
- Engineering Equipment and Materials Users' Association
- INSPEC
- Information Systems Committee of the Universities Funding Council
- Institute of Information Scientists
- Library Association
- London and South Eastern Library Region (laser)
- Royal Institute of British Architects
- Science Museum Library
- Standing Conference of National and University Libraries
- University of Newcastle-upon-Tyne

The following bodies were also represented in the drafting of the standard, through sub-committees and panels:

- British Computer Society
- Joint Network Team
- Royal Society of Chemistry
- The Janet User Group for Libraries

This British Standard, having been prepared under the direction of the Information and Documentation Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 15 May 1993

© BSI 12-1999

The following BSI references relate to the work on this standard:
Committee reference DOT/7
Draft for comment 90/96234 DC

ISBN 0 580 21775 2

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
Foreword	iii
Text of ISO 10163-1	1

National foreword

This British Standard reproduces verbatim ISO 10163-1:1993 and implements it as the UK national standard.

This British Standard is published under the direction of the Information and Documentation Standards Policy Committee whose Technical Committee DOT/7 has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international committee any enquiries on interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

NOTE International and European Standards, as well as overseas standards, are available from BSI Sales Department, BSI, Linford Wood, Milton Keynes, MK14 6LE.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the ISO title page, pages ii to iv, pages 1 to 37 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

INTERNATIONAL STANDARD

ISO
10163-1

First edition
1993-02-15

Information and documentation — Open Systems Interconnection — Search and Retrieve Application Protocol Specification —

Part 1: Protocol specification

*Information et documentation — Interconnexion de systèmes ouverts
(OSI) — Spécification du protocole d'application pour la recherche
documentaire —*

Partie 1: Spécification du protocole



Reference number
ISO 10163-1:1993(E)

AVA Documents
Document Sharing Hub

Contents

	Page
Foreword	iii
Introduction	1
1 Scope	1
2 Normative references	2
3 Definitions	2
4 Abbreviations	3
5 Overview of the Search and Retrieve Protocol	4
6 SR Protocol Data Units	4
7 Elements of Procedure	5
7.1 Initialize and Initialize Response APDUs	5
7.2 Search and Search Response APDUs	6
7.3 Present and Present Response APDUs	10
7.4 Delete-Result-Set and Delete-Result-Set Response APDUs	11
7.5 Reference-Id	12
7.6 Termination	12
7.7 Message Size Limitations	12
7.8 Protocol Errors	13
7.9 Rules for Extensibility	13
8 Abstract Syntax	13
8.1 ASN.1 Specification of SR APDUs	13
8.2 ASN.1 Module ISO 10163-SR-1	14
8.3 Cross reference of types defined/referenced in module ISO10163-SR-1	22
9 Conformance	25
9.1 Static Conformance	25
9.2 Dynamic Requirements	25
9.3 Protocol Implementation Conformance Statement	25
Annex A (normative) State Transitions	26
Annex B (normative) Object Identifiers and Registration Requirements	31
Annex C (normative) Objects for Registration	31
Annex D (normative) Attribute Set Bib-1	32
Annex E (normative) Diagnostic Set Bib-1	35
Annex F (informative) Registration Procedures	36
Annex G (informative) Abstract Syntax Definition	37

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 10163-1 was prepared by Technical Committee ISO/TC 46, *Information and documentation*.

Annex A to Annex E form an integral part of this International Standard. Annex F and Annex G are for information only.

ISO 10163 consists of the following parts, under the general title *Information and documentation — Open Systems Interconnection — Search and Retrieve Application Protocol Specification*:

— *Part 1: Protocol specification.*

Introduction

This International Standard is one of a set of International Standards produced to facilitate the interconnection of computer systems. It is related to other International Standards in the set as defined by the Reference Model for Open Systems Interconnection (ISO 7498). The Reference Model subdivides the area of standardization for interconnection into a series of layers of specification, each of manageable size. The aim of Open Systems Interconnection is to allow, with a minimum of technical agreement outside the interconnection standards, the interconnection of information processing systems:

- from different manufacturers;
- under different managements;
- of different levels of complexity; and
- of different technologies.

This International Standard provides a complete protocol specification for Search and Retrieve (SR) communication. The SR protocol operates in the Application Layer and allows the parties involved in an SR activity to progress through the activity in an orderly and defined way.

The SR protocol has been designed to support the SR services defined in ISO 10162, the SR Service Definition.

This International Standard is one of a number of related International Standards supporting the interconnection of library systems. These International Standards can be used by themselves or in a cooperative manner to support library applications requiring a mixture of communications services. For example, ISO 10160 and ISO 10161 which support interlibrary loan may be used in conjunction with the SR protocol to obtain the loan of items. The control and management of interactions among such bibliographic applications are local matters that are outside the scope of this International Standard. The architecture for the combined use of several application service elements is defined in Application Layer Structure ISO 9545.

A number of additional protocol functions have been identified for future study and standardization; see Annex A of ISO 10162.

The specification technique used in this International Standard is consistent with techniques used in defining other OSI protocols. Within most of this document, the technique is self-explanatory. The Abstract Syntax of the SR Application Protocol Data Units (APDU) is defined by means of the ASN.1 specification technique specified in ISO 8824.

1 Scope

This International Standard defines the protocol procedures for an SR application-service-element (ASE). It specifies the behaviour which must be exhibited by a system in order to take part in the provision of the ISO search and retrieve service as defined in ISO 10162.

It provides a formal statement of the rules of behaviour of each of the two entities participating in SR communication. It states:

- a) the actions to be taken on receiving request service primitives issued by an SR service-user;
- b) the actions to be taken on receiving application-protocol-data-units (APDUs);
- c) the actions to be taken as a result of events within the local system.

It provides a definition (in clause 8) of the abstract syntax required to convey the SR protocol APDUs.

It states the conformance requirements to be met by implementors of this protocol (in clause 9).

The scope of the SR protocol is restricted to the interconnection of systems; it does not specify or restrict the possible implementation of interfaces within a computer system. Computer systems may range from stand-alone work-stations to mainframes.

This International Standard is primarily intended for use by systems supporting information retrieval services for organizations such as libraries, information utilities, and union catalogue centers.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 2709:1981, *Documentation — Format for bibliographic information interchange on magnetic tape*.

ISO 7498:1984, *Information processing systems — Open Systems Interconnection — Basic Reference Model*.

ISO/TR 8509:1987, *Information processing systems — Open Systems Interconnection — Service conventions*.

ISO 8649:1989, *Information processing systems — Open Systems Interconnection — Service definition for the Association Control Service Element*.

ISO 8650:1988, *Information processing systems — Open Systems Interconnection — Protocol specification for the Association Control Service Element*.

ISO 8777:—, *Documentation — Commands for interactive text searching*¹⁾.

ISO 8822:1988, *Information processing systems — Open Systems Interconnection — Connection oriented presentation service definition*.

ISO/IEC 8824:1988, *Information processing systems — Open Systems Interconnection — Specification of Abstract Syntax Notation One (ASN.1)*.

ISO/IEC 8825:1988, *Information processing systems — Open Systems Interconnection — Specifications of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1)*.

ISO/IEC 9545:1989, *Information processing systems — Open Systems Interconnection — Application Layer Structure*.

ISO/IEC 9834-1:—, *Information processing systems — Open Systems Interconnection — Registration Authorities*¹⁾.

ISO 10162:—, *Information and documentation — Open Systems Interconnection — Search and Retrieve Service Definition*¹⁾.

3 Definitions

3.1 Reference Model Definitions

This International Standard makes use of the following terms defined in ISO 7498.

application-entity

the aspects of an application-process pertinent to OSI

application-protocol-data-unit

a unit of data specified in an application-protocol and consisting of application-protocol-information and possibly application-user-data

presentation service

a capability of the Presentation Layer and the layers beneath it, which is provided to application-entities at the boundary between the Presentation and the Application Layer

application-process

an element within a real open system which performs the information processing for a particular application

N-layer

a subdivision of the OSI architecture, constituted by subsystems of the same rank (N)

transfer syntax

the concrete syntax used in the transfer of data between open systems

¹⁾ To be published.

3.2 Application Layer Structure Definitions

This International Standard makes use of the following terms defined in ISO/IEC 9545.

application-association, association

a cooperative relationship between two application-entity-invocations for the purpose of communication of information and coordination of their joint operation. This relationship is formed by the exchange of application-protocol-control-information using the Presentation-Service

application-context

a set of rules shared in common by two application-entity-invocations in order to enable their cooperative operation

application-context-definition

the description of an application-context

application-service-element

a set of application-functions that provides a capability for the interworking of application-entity-invocations for a specific purpose

3.3 Abstract Syntax Notation One Definitions

This International Standard makes use of the following terms defined in ISO 8824.

type

a name set of values

simple type

a type defined by directly specifying the set of its values

structured type

a type defined by reference to one or more other types

component type

one of the types referenced when defining a structured type

value

a distinguished member of a set of values

3.4 Presentation Service Definitions

This International Standard makes use of the following terms defined in ISO 8822.

abstract syntax

the specification of Application Layer data or application-protocol-control-information by using notation rules which are independent of the encoding technique used to represent them

4 Abbreviations

ACSE	Association Control Service Element
APDU	Application-protocol-data-unit
ASE	Application-service-element
ASN.1	Abstract Syntax Notation One
OSI	Open Systems Interconnection
SR	Search and Retrieve
SRPM	Search and Retrieve protocol machine
PCI	Protocol control information

5 Overview of the Search and Retrieve Protocol

5.1 Services Supported by the SR Protocol

This International Standard specifies the protocol which supports the Search and Retrieve Service defined in ISO 10162.

5.2 Services Assumed by SR Protocol

The protocol assumes the services of the Association Control Service Element ISO 8649. The services required are:

- a) A-Release: orderly association release, where both sides agree to the release and there is no loss of data in transit. The SR-release service is directly mapped to this service without any SR protocol information.
- b) A-Abort: association abort, which allows either origin or target, at any time, to explicitly terminate the association, immediately and unconditionally. Data in transit may be lost. The SR-abort service is directly mapped to this service without any SR protocol control information.

It is assumed that the SR user will handle the Association Control Services required to establish an association (A-Associate) with an application context encompassing the SR service.

The communication service that supports this SR protocol is a connection-oriented service using the P-DATA service, defined in ISO 8822 in an established application-association, in combination with the ACSE, ISO 8649.

An SR system establishes application-associations as necessary with the remote SR systems with whom it is engaged in SR activity. The SR application-service-element (ASE) may then use the P-DATA service defined in ISO 8822 directly to transmit SR APDUs. This provides a connection-oriented interaction between SR systems. A single application-association can be used to send a series of SR APDUs relating to multiple searches. A single system can be engaged in multiple application-associations with multiple remote systems simultaneously.

This International Standard defines a basic application context for Search and Retrieve in combination with ACSE, registered in C.2.1.

5.3 SR Protocol Model

In the abstract, the operation of the SR protocol is modelled by the interaction of two SR protocol machines (SRPMs). The two SRPMs communicate by exchanging SR APDUs through use of the services available at their lower boundary. At their upper boundary the SRPMs provide services to their service users.

6 SR Protocol Data Units

The SR Protocol Data Units are complex data types defined by an abstract syntax definition (see clause 8). This definition includes named parameters corresponding to those parameters in the SR Service carried directly by SR-PCI and any other parameters necessary for the operation of the protocol.

A transfer syntax of these data types is obtained by applying the Basic Encoding Rules for Abstract Syntax Notation One (ASN.1) ISO 8825.

This clause lists the APDUs used in the SR application and describes the use and meaning of the APDUs.

INITIALIZE — used by the origin to initialize communication with a target for subsequent SR activity.

INITIALIZE RESPONSE — used by the target to reply to the origin regarding proposals made in the Initialize APDU.

SEARCH — used by the origin to request a search by the target for records that meet certain criteria.

SEARCH RESPONSE — used by the target to inform the origin of the result of the search request.

PRESENT — used by the origin to request records from a result set on the target.

PRESENT RESPONSE — used by the target to send requested result set records to the origin.

DELETE-RESULT-SET — used by the origin to request deletion of a result set on the target.

DELETE-RESULT-SET RESPONSE — used by the target to tell the origin the outcome of the delete-result-set request.

7 Elements of Procedure

Each of the Initialize, Search, Present, and Delete-result-set request service primitives results in the preparation and transmission of the APDU of the corresponding name. The receipt of an Initialize, Search, Present, or Delete-result-set APDU results in a corresponding indication service primitive.

7.1 Initialize and Initialize Response APDUs

On the Initialize APDU, the origin proposes values for the parameters, and the target may propose alternative values in the Initialize Response APDU for some of the parameters. If so, the origin must either accept the alternative values proposed by the target or else terminate communication (see 7.6).

7.1.1 Protocol Version

The protocol version consists of a string of Boolean values, each value representing a version. The first value set to “on” indicates version 1 is available, the second value set to “on” indicates version 2 is available, and so on. Values higher than the highest known version should be ignored. Both the Initialize and Initialize Response APDUs include a value string corresponding to the supported versions. The highest common version is selected for use. If there are no versions in common, the Initialize Response APDU should indicate a value of “reject” for the parameter Initialization-status.

7.1.2 Options

On the Initialize APDU, the parameter Options specifies either “will use” or “will not use” for the services listed below. On the Initialize Response APDU the target specifies “will support” or “will not support” for each of these services:

- search
- present
- delete-result-set

If the target specifies “will support” for a particular service, then the origin may assume that the service will be available and may use the service during the association, even if the origin had specified “will not use” for that service.

7.1.3 Preferred-message size and Maximum-message-size

Both the Initialize APDU and the Initialize Response APDU contain Preferred-message-size and Maximum-message-size, specified in bytes. Maximum-message-size must be greater than or equal to Preferred-message-size. Note that the purpose of this distinction between Preferred-message-size and Maximum-message-size is to allow the transfer of normal length records to proceed in a routine fashion, with convenient buffer sizes, but to also provide for the transfer of an occasional exceptionally large database record without requiring the origin to continually allocate and hold local buffer space for worst-case records. The target may propose values different from those proposed by the origin in which case the values in the Initialize Response APDU override those in the Initialize APDU, and the origin may abort the connection if those values are not acceptable. Usage of these parameters is specified in 7.7.

7.1.4 Initialization-status

The target indicates whether or not it accepts the association by specifying a value of “accept” or “reject” respectively in the parameter Initialization-status of the Initialize Response APDU. If “reject” is indicated, the origin is expected to terminate communication with an SR-release or SR-abort (see 7.6).

7.1.5 User information-field

The parameter User-information-field may optionally be included on either the Initialization or Initialization Response APDU. It contains information supplied by the user; the definition of such information is outside the scope of this International Standard.

7.1.6 Implementation Parameters

Any of the following implementation-related parameters may optionally be included in either the Initialize or Initialize Response APDUs:

- Implementation-id: a unique identifier for the origin (or target) implementation.
- Implementation-name: a descriptive name for the origin (or target) implementation.
- Implementation-version: a descriptive name for the origin (or target) implementation version.

7.1.7 Authentication

The origin may provide information for use by the target in authenticating the origin. The need for such information and its form and content are a matter of prior, private agreement between the origin and the target. If the target requires authentication information and the origin either does not supply the information or supplies invalid information, the target may either reject the initialization request by returning an Initialization-status value of “reject”, or the target may abort the entire association through use of the Association Control A-Abort service.

7.2 Search and Search Response APDUs

7.2.1 Database-id

The target designates, by agreement outside the scope of this International Standard, what databases may be specified on a Search APDU, and also in what combinations they may be specified. For example, a target might specify that databases **A**, **B**, and **C** may be searched individually, and that **A** and **B** may be searched in combination (but not **A** and **C**, nor **B** and **C**).

The parameter Database-id in the Search APDU is a set of one or more database names. If the specified combination of databases is not supported by the target, the Search Response APDU will include a diagnostic, such as “combination of specified databases not supported”, and the value of the parameter Search-Status will be “failure”.

7.2.2 Proposed-result-set-id and Replace-indicator

The parameter Proposed-result-set-id specifies a name to be given to the result set which will be created by the query, so that it may be subsequently referenced within the same association. If a result set with the same name already exists at the target, then the action taken depends on the value of the parameter Replace-indicator, as follows:

- If the value of Replace-indicator is “on”, then prior to processing the query, the existing result set whose name is specified by the parameter Proposed-result-set-id will be deleted, and a new result set by that name created. The initial content of the result set is null. If no records are found by the query, the result set remains null.
- If the value of Replace-indicator is “off”, the search is not processed, an error diagnostic is included in the Search Response APDU, the value of the parameter Search-Status is “failure”, and the existing result set whose name is specified by the parameter Proposed-result-set-id is left unchanged.

If a result set does not exist with the name specified by the parameter Proposed-result-set-id, then a result set by that name is created by the target, and the parameter Replace-indicator is ignored. The initial content of the result set is null.

A target system need not support, in general, the naming of result sets by the origin (see, however, conformance statement requirements in **9.3**). However, a target system must support at least the result set whose name is “default”. If the origin specifies “default” as Proposed-result-set-id, then Replace-indicator must be “on”.

A result set which is created by a Search APDU (that is, specified by the parameter Proposed-result-set-id) may be referenced in a subsequent Present APDU or as an operand in a subsequent Search APDU (for example, in an RPN query). If a result set is created with the name “default”, that result set remains available for reference from the time it is created until the end of the association during which it is created, or until:

- another “default” result set is created, because the name “default” is specified as Proposed-result-set-id in a subsequent Search APDU, or
- it is unilaterally erased or deleted by the target.

If a result set is created with any name other than “default”, that result set remains available for reference from the time it is created until it is deleted in one of the following ways:

- by a Delete-result-set APDU
- implicitly, because a result set was specified by the same name in a Search APDU, during the current association, and the value of the parameter Replace-indicator was “on”
- unilaterally by the target (at any time)
- by termination of the association.