

Cranes — Tolerances for wheels and travel and traversing tracks —

Part 1: General

ICS 53.020.20

National foreword

This British Standard reproduces verbatim ISO 12488-1:2005 and implements it as the UK national standard.

The UK participation in its preparation was entrusted by Technical Committee MHE/3, Cranes and derricks, to Subcommittee MHE/3/3, Bridge, Gantry and slewing jib cranes, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the ISO page, pages ii to v, a blank page, pages 1 to 21 and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 19 May 2005

© BSI 19 May 2005

ISBN 0 580 46024 X

INTERNATIONAL STANDARD

ISO
12488-1

First edition
2005-04-15

Cranes — Tolerances for wheels and travel and traversing tracks —

Part 1: General

*Appareils de levage à charge suspendue — Tolérances des roues et
des voies de roulement et de déplacement —*

Partie 1: Généralités



Contents		Page
Foreword.....		iv
Introduction		v
1	Scope.....	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	2
5	Classification of tolerances	3
6	Tolerances	4
Bibliography		21

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12488-1 was prepared by Technical Committee ISO/TC 96, *Cranes*, Subcommittee SC 8, *Jib cranes*.

This first edition cancels and replaces ISO 8306:1985, of which it constitutes a technical revision.

ISO 12488 consists of the following parts, under the general title *Cranes — Tolerances for wheels and travel and traversing tracks*:

- *Part 1: General*
- *Part 4: Jib cranes*

Introduction

This part of ISO 12488 establishes requirements and gives guidance and design rules that reflect the present state of art in the field of crane machine design. The rules given represent good design practice that ensures fulfilment of essential safety requirements and adequate service life of components. Deviation from these rules normally leads to increased risks or reduction of service life, but it is acknowledged that new technical innovations, materials etc. may enable new solutions that result in equal or improved safety and durability.

Cranes — Tolerances for wheels and travel and traversing tracks —

Part 1: General

1 Scope

This part of ISO 12488 specifies tolerances for construction assemblies and operational conditions of cranes and associated crane tracks as defined in ISO 4306-1. The purpose of the requirements in this part of ISO 12488 is to promote safe operation and achievement of the expected life of components by the elimination of excessive load effects due to deviations or misalignments from the normal dimensions of the structure.

Tolerances given are extreme values. The elastic deformations due to load effects are outside the scope of this part of ISO 12488. These will need to be taken into account at the design stage using other criteria to achieve the intended operation and performance.

Specific values for particular crane types are given in other parts of ISO 12488.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 286-2:1988, *ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts*

ISO 1101, *Geometrical Product Specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out*

ISO 4306-1, *Cranes — Vocabulary — Part 1: General*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

construction tolerance

amount by which a specific dimension is permitted to vary, resulting from the assembly of the complete crane and its tracks, in new, modified, rebuilt or repaired buildings, before operational use

NOTE 1 This applies to new build or repaired or modified cranes and tracks.

NOTE 2 The amount is given either by the absolute value of the difference between the limits of size, or by the allowable geometric variation.