BS ISO 14223-2:2010

BSI Standards Publication

Radiofrequency identification of animals — Advanced transponders

Part 2: Code and command structure

bsi.

...making excellence a habit.™

Document Sharing Hub

Full document details: BS ISO 14223-2:2010

National foreword

This British Standard is the UK implementation of ISO 14223-2:2010.

The UK participation in its preparation was entrusted to Technical Committee AGE/6/1, Radio Frequency ID for Animals.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© BSI 2010

ISBN 978 0 580 57468 9

ICS 35.240.99; 65.020.30

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2010.

Amendments issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO 14223-2:2010

INTERNATIONAL STANDARD

ISO 14223-2

First edition
2010-08-15

Radiofrequency identification of animals — Advanced transponders —

Part 2: Code and command structure

Identification des animaux par radiofréquence — Transpondeurs évolués —

Partie 2: Code et structure de commande

Reference number
ISO 14223-2:2010(E)

Documents
Document Sharing Hub
© ISO 2010

Full document details: BS ISO 14223-2:2010

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

© ISO 2010 – All rights reserved

Documents
Document Sharing Hub

Full document details: BS ISO 14223-2:2010

Contents

Page

Foreword v
Introduction vi
1 Scope 1
2 Normative references 1
3 Conformance 1
3.1 Transponder 1
3.2 Transceiver 1
4 Terms and definitions 2
5 Abbreviated terms 2
6 Transmission protocol 3
6.1 Basic elements 3
6.2 Unique identifier 3
6.3 Request format 4
6.4 Response format 5
6.5 Request flags 5
6.5.1 General 5
6.5.2 NOS flag 6
6.5.3 SEL flag and ADR flag 7
6.5.4 CRCT flag 7
6.6 Response flag and error code 7
6.7 Error handling 8
6.8 Block security status (BSS) 8
6.9 Start of frame pattern (SOF) 9
6.9.1 Transceiver request 9
6.9.2 Transponder response 9
6.10 Cyclic redundancy check (CRC) 9
6.11 Data storage format identifier (DSFID) 9
7 Memory organization 10
7.1 General 10
7.2 User data memory — Page 0 10
7.3 User data memory — Extended memory (⩾ page 1) 10
8 Transponder states 11
8.1 General 11
8.2 RF-off state 11
8.3 ISO 11785 state 11
8.4 Wait state 11
8.5 Ready state 11
8.6 Quiet state 11
8.7 Selected state 11
8.8 State diagram 12
9 Anticollision 13
9.1 General 13
9.2 Request parameters 13
9.3 Request processing by the transponder 14
9.4 Explanation of anticollision sequences 16
9.4.1 General 16
9.4.2 Anticollision sequence with one slot 16

Documents
Document Sharing Hub

© ISO 2010 – All rights reserved

Full document details: BS ISO 14223-2:2010

9.4.3 Anticollision sequence with 16 slots 16
9.4.4 Mixed population with transponders of type FDX-ADV and HDX-ADV 17
9.4.5 Advanced anticollision mode 17

10 Commands 19
10.1 Command classification 19
10.2 Command list 20
10.3 Mandatory commands 21
10.3.1 INVENTORY 21
10.3.2 READ UID 22
10.3.3 READ MULTIPLE BLOCKS 22
10.3.4 STAY QUIET 23
10.3.5 WRITE SINGLE BLOCK 23
10.3.6 LOCK BLOCK 23
10.4 Optional commands 24
10.4.1 READ SINGLE BLOCK 24
10.4.2 READ SINGLE BLOCK WITH SECURITY STATUS 24
10.4.3 READ MULTIPLE BLOCKS WITH SECURITY STATUS 25
10.4.4 WRITE MULTIPLE BLOCKS 25
10.4.5 GET SYSTEM INFORMATION 26
10.4.6 SELECT 27
10.4.7 RESET TO READY 28
10.4.8 WRITE SYSTEM DATA 28
10.4.9 LOCK SYSTEM DATA 29
10.4.10 READ EXTENDED MULTIPLE BLOCKS 29
10.4.11 WRITE EXTENDED MULTIPLE BLOCKS 30
10.4.12 LOCK EXTENDED BLOCK 31
10.4.13 Optional command execution in inventory mode 31
10.5 Custom commands 32
10.6 Proprietary commands 32

Annex A (informative) **Description of a typical anticollision sequence with FDX and HDX transponders** 33

Bibliography 34

© ISO 2010 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

ISO 14223-2 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 19, *Agricultural electronics*.

ISO 14223 consists of the following parts, under the general title *Radiofrequency identification of animals — Advanced transponders*:

— *Part 1: Air Interface*

— *Part 2: Code and command structure*

The following part is under preparation:

— *Part 3: Applications*

© ISO 2010 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010

Introduction

This part of 14223 specifies the communication interface of the radio frequency (RF) system for advanced transponders for animals. The technical concept of advanced transponders for animal identification described is based upon the principle of radio frequency identification (RFID) and is an extension of the standards ISO 11784 and ISO 11785. Apart from transmission of the (unique) identification code of animals, the application of advanced technologies facilitates the storage and retrieval of additional information (integrated database), the implementation of authentication methods and the reading of data from integrated sensors, etc.

The International Organization for Standardization (ISO) draws attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning the methods of transmission referred to throughout the document.

ISO takes no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured ISO that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with ISO. Information may be obtained from:

N.V. Nederlandsche Apparatenfabriek “Nedap”
Parallelweg 2
NL-7141 DC Groenlo
The Netherlands

Texas Instruments Deutschland GmbH
Haggerstrasse 1
D-85356 Freising
Germany

NXP Semiconductors
Mikron-Weg 1
A-8101 Gratkorn
Austria

EM Microelectronic-Marin SA
Sors 3
CH-2074 Marin
Switzerland

Atmel Germany GmbH
P.O. Box 3535
74025 Heilbronn
Germany

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO shall not be held responsible for identifying any or all such patent rights.

© ISO 2010 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010

INTERNATIONAL STANDARD ISO 14223-2:2010(E)

Radiofrequency identification of animals — Advanced transponders —

Part 2: Code and command structure

1 Scope

This part of ISO 14223 specifies the code and command structure between the transceiver and the advanced transponder used in the radiofrequency identification of animals, this specification being fully backwards-compatible with those of ISO 11784 and ISO 11785. As a direct extension of ISO 11785, it is intended to be used in conjunction with that International Standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11784, *Radio frequency identification of animals — Code structure*

ISO 11785, *Radio frequency identification of animals — Technical concept*

ISO/IEC 7816-6, *Identification cards — Integrated circuit cards — Part 6: Interindustry data elements for interchange*

ISO 24631-1, *Radiofrequency identification of animals — Part 1: Evaluation of conformance of RFID transponders with ISO 11784 and ISO 11785 (including granting and use of a manufacturer code)*

3 Conformance

3.1 Transponder

For conformance with this part of ISO 14223 to be claimed, a transponder shall be FDX-ADV or HDX-ADV.

NOTE Nothing in this International Standard prevents a transponder being of more than one type, although for technical reasons, it is unlikely that such transponders are ever marketed.

3.2 Transceiver

For conformance with this part of ISO 14223 to be claimed, a transceiver shall support both FDX-ADV and HDX-ADV. When in the inventory mode, the transceiver shall alternate between FDX-ADV and HDX-ADV interrogation. The transceiver shall move back to ISO 11785 mode after completion of the advanced operation.

© ISO 2010 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1
advanced transponder
transponder conforming to ISO 14223, downward compatible according to ISO 11784 and ISO 11785, with facilities for storage and retrieval of additional data, integrated sensors, etc.

4.2
advanced mode
operating method of the advanced transponder after reception of a valid command

4.3
anticollision sequence
algorithm used to prepare for and handle a dialogue between transceiver and one or more transponders out of several in its energizing field

4.4
byte
eight bits of data designated b1 to b8, from the most significant bit (MSB, b8) to the least significant bit (LSB, b1)

5 Abbreviated terms

BSS block security status

CRC cyclic redundancy check

CRCT response cyclic redundancy check flag

DSFID data storage format identifier

EOF end of frame

FDX full duplex

IC integrated circuit

ICR integrated circuit reference number

HDX half duplex

LSB least significant bit

MFC integrated circuit manufacturer code

MSB most significant bit

MSN manufacturer serial number

NOB number of blocks per page

NOP number of pages

NOS number of slots

NRZ non-return to zero

© ISO 2010 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010

NSS number of sensors

RF radio frequency

RTF reader talk first

RFU reserved for future use

SOF start of frame

UID unique identifier (includes MFC and MSN)

6 Transmission protocol

6.1 Basic elements

The advanced transmission protocol defines the mechanism for exchanging instructions and data between the transceiver and the transponders, in both directions.

It is based on the following concepts.

— The transponders are by default conformant with ISO 11784 and ISO 11785. This shall be evaluated conformant with ISO 24631-1. For advanced instructions the transceiver has the ability to communicate with a transponder in the advanced mode. In this mode the transponder is communicating in RTF mode and does not start to respond unless it has received and decoded a valid request from the transceiver.

— The transponders are uniquely identified by 48 bit UID, programmed at the manufacture of the integrated circuit. The UID coding is defined in 6.2.

— An identification code of 64 bits according to ISO 11784 is stored in page 0 (the four blocks given in Table 11 can be used to store the full ISO 11785 protocol) of the user memory area (blocks 0 to 3). This identification code shall be programmed and locked by the transponder issuer in order to avoid manipulations.

The advanced mode protocol is based on

— a request from the transceiver to the transponder, and

— a response from the transponder to the transceiver.

The protocol is bit-oriented. The number of bits transmitted after a SOF depends on the respective request and response.

Flags are used for the control of request and response format. The setting of the flags indicates either request and response variants (e.g. number of slots) or the presence of optional fields. In the case of optional fields, when the flag is set to one (1), the field is present. When the flag is reset to zero (0), the field is absent.

RFU flags shall be set to zero (0).

6.2 Unique identifier

The UID is used for addressing each transponder uniquely and individually.

The length of the UID is 48 bits, the format of the UID is presented in Table 1. The IC manufacturer is responsible for setting the UID as defined by this part of ISO 14223 and for ensuring the uniqueness of the MSN.

© ISO 2010 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010

Table 1 — UID format

MSB	LSB
48 41	40 1
IC manufacturer code (MFC)	IC manufacturer serial number (MSN)

The UID shall comprise

— the 8 bit MFC, according to ISO/IEC 7816-6, and

— the 40 bit MSN, a unique serial number assigned by the IC manufacturer.

6.3 Request format

A request consists of the following elements:

— SOF;

— flags;

— command;

— parameters (depending on the command);

— data (depending on the command);

— CRC (optional);

— EOF.

The general request format is presented in Table 2.

Table 2 — General request format

SOF	flags	command	parameters	data	CRC	EOF

Each request starts with a SOF. The fields are transmitted successively from the first field (flags) to the last field (e.g. CRC). All fields are transmitted LSB first. At the end of a request, an EOF is appended.

The allocation of the LSB and MSB for each field of the request format is shown in Table 3.

Table 3 — Allocation of LSB and MSB to the request fields

	LSB MSB	LSB MSB	LSB MSB	LSB MSB	LSB MSB	
SOF	Field 1 (5 bits) (Flags 1 … 5)	Field 2 (6 bits) (Command)	Field 3 (Parameters)	Field 4 (Data)	Field 5 (16 bits) (CRC)	EOF

© ISO 2010 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010

6.4 Response format

A response consists of the following elements:

— SOF pattern;

— error flag;

— error code;

— data (depending on the command);

— CRC (is optional depending on command and flag settings);

— EOF pattern.

The format of the general response if there is no error is presented in Table 4 and that of the general response if there is an error in Table 5.

Table 4 — General response format if no error

SOF	Error flag 0	Data	CRC	EOF

Table 5 — General response format if error

SOF	Error flag 1	Error code	CRC	EOF

Each response begins with a SOF. The subsequent fields are transmitted successively from the first field (Flag) to the last field (e.g. CRC). All fields are transmitted LSB first. At the end of a response, an EOF is appended.

The allocation of the LSB and MSB for each field of the response format is shown in Table 6.

Table 6 — Allocation of LSB and MSB to response fields

	LSB MSB	LSB MSB	LSB MSB	
SOF	Field 1 (1 bit) (Error flag)	Field 2 (⩾3 bits) (Error code or data)	Field 3 (16 bits) (CRC)	EOF

6.5 Request flags

6.5.1 General

In each request, five flags are used, with flag b1 to be transmitted first. The specific meaning of the request flags depends on the context. The meaning of request flags b1 to b3 is explained in Table 7, that of b4 and b5 where the inventory flag is *not* set in Table 8 and that where the inventory flag *is* set in Table 9.

© ISO 2010 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010

Table 7 — Meaning of request flags b1 to b3

Bit	Flag name	Value	Description
b1	PEXT (protocol extension) flag	0	No protocol format extension
		1	RFU
b2	INV (inventory) flag	0	The meaning of flags b4 to b5 is according to Table 8
		1	The meaning of flags b4 to b5 is according to Table 9
b3	CRCT	0	CRC shall *not* be appended to the transponder response
		1	CRC shall be appended to the transponder response

Table 8 — Request flags b4 to b5 definition when inventory flag is *not* set

Bit	Flag name	Value	Description
b4	SEL (select) flag	0	Request shall be executed by any transponder according to the setting of the address flag.
		1	Request shall be executed only by transponder in selected state. The address flag shall be set to 0 and the UID field shall not be included in the request.
b5	ADR (address) flag	0	Request is not addressed. UID field is not included. It shall be executed by any transponder.
		1	Request is addressed. UID field is included. It shall be executed only by that transponder whose UID matches the UID specified in the request. The SEL flag shall be set to 0.

Table 9 — Request flags b4 to b5 definition when the inventory flag is set

Bit	Flag name	Value	Description
b4	RFU	0	—
b5	NOS flag	0	16 slots
		1	1 slot

A further description of these flags is given in 6.5.2 to 6.5.4.

6.5.2 NOS flag

The NOS flag (see Table 10) is used by the INVENTORY command to select the number of slots during execution of the anticollision sequence.

Table 10 — Meaning of NOS flag

NOS flag	Meaning only for INVENTORY command
0	16 slots
1	1 slot

© ISO 2010 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 14223-2:2010