

Mineral and sapphire watch-glasses —

Part 2: Assembly to the case by adhesive or using a gasket

ICS 39.040.10

National foreword

This British Standard reproduces verbatim ISO 14368-2:2003 and implements it as the UK national standard.

The UK participation in its preparation was entrusted to Technical Committee STI/53, Specifications and test methods for jewellery, horology, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the ISO title page, pages ii and iii, a blank page, pages 1 to 5 and a back cover.

The BSI copyright date displayed in this document indicates when the document was last issued.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 20 February 2003

Amendments issued since publication

Amd. No.	Date	Comments

© BSI 20 February 2003

INTERNATIONAL STANDARD

ISO
14368-2

First edition
2003-02-01

Mineral and sapphire watch-glasses — **Part 2:** **Assembly to the case by adhesive or** **using a gasket**

Verres de montres minéraux et en saphir —

Partie 2: Fixation à la boîte par collage ou à l'aide d'un joint



