BS ISO 14404-1:2013

BSI Standards Publication

Calculation method of carbon dioxide emission intensity from iron and steel production

Part 1: Steel plant with blast furnace

bsi.

...making excellence a habit.™

Document Sharing Hub

Full document details: BS ISO 14404-1:2013

National foreword

This British Standard is the UK implementation of ISO 14404-1:2013.

The UK participation in its preparation was entrusted to Technical Committee ISE/1, Iron and steel standards co-ordinating committee.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013.
Published by BSI Standards Limited 2013.

ISBN 978 0 580 73786 2

ICS 77.080.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2013.

Amendments issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO 14404-1:2013

INTERNATIONAL STANDARD

ISO 14404-1

First edition
2013-03-15

Calculation method of carbon dioxide emission intensity from iron and steel production —

Part 1:
Steel plant with blast furnace

Méthode de calcul de l'intensité de l'émission de dioxyde de carbone de la production de la fonte et de l'acier —

Partie 1: Usine sidérurgique avec fourneau

Reference number
ISO 14404-1:2013(E)

Documents
Document Sharing Hub

© ISO 2013

Full document details: BS ISO 14404-1:2013

COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

© ISO 2013 – All rights reserved

Documents
Document Sharing Hub

Full document details: BS ISO 14404-1:2013

Contents

Page

Foreword ..... **iv**

Introduction ..... **v**

1 Scope **1**

2 Terms and definitions **1**
2.1 Emissions 1
2.2 Gas fuel 2
2.3 Liquid fuel 2
2.4 Solid fuel 2
2.5 Auxiliary material 3
2.6 Energy carriers 4
2.7 Ferrous containing materials 4
2.8 Alloys 4
2.9 Product and by-product 4
2.10 Others 5

3 Symbols **6**

4 Principles **7**
4.1 General 7
4.2 Relevance 7
4.3 Completeness 7
4.4 Consistency 7
4.5 Accuracy 7
4.6 Transparency 7

5 Definition of boundary **7**
5.1 General 7
5.2 Category 1 8
5.3 Category 2 8
5.4 Category 3 9
5.5 Category 4 9

6 Calculation **9**
6.1 General 9
6.2 Calculation procedure 9

Annex A (informative) **Calculation of energy consumption and intensity** **15**

Annex B (informative) **An example of template for using different emission factors or emission sources from Table 4** **16**

Annex C (informative) **An example of CO_2 emission and intensity calculations for a steel plant** **18**

Annex D (informative) **Explanation of emission factors for by-product gases in Table 4** **21**

Bibliography **24**

© ISO 2013 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 14404-1:2013

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14404-1 was prepared by Technical Committee ISO/TC 17, *Steel*.

ISO 14404 consists of the following parts, under the general title of *Calculation method of carbon dioxide emission intensity from iron and steel production:*

Part 1: Steel plant with blast furnace

Part 2: Steel plant with electric arc furnace (EAF)

© ISO 2013 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 14404-1:2013

Introduction

The steel industry recognizes the urgent need to take actions concerning climate change. Slowing and halting global warming requires reductions in GHG emissions on a global scale. To play a part in achieving these reductions, it is necessary for steel plants to identify the amount of CO_2 emitted during the production of steel products, in order to identify next opportunities for reduction of CO_2.

The production process of steel involves complex chemical reactions, various heating cycles, and the recycling of various by-products. This variety of imports, including raw materials, reactive agents, fuel and heat sources are transformed into wide range of steel products, by-products, waste materials and waste heat.

Steel plants manufacture various products including: sheet products, plate products, long products, pipe and tubes and many other types of products. In addition, steel plants produce unique speciality grade steel products with high-performance, which are achieved by various sub-processes including micro-alloying and applying surface treatments like galvanizing and coating that require additional heat treatments. Therefore, none of the steel plants in the world is exactly identical.

Climate regulations in each country require steel companies to devise methods to lower CO_2 emissions from steel plants while continuing to produce steel products by these diverse and complex steelmaking processes. To accomplish this, it is desirable to have universally common indicators for determining steel plant CO_2 emissions.

There are many methods for calculating CO_2 emission intensity for steel plants and specific processes. Each method was created to match the objectives of a particular country or region. In some cases, a single country can have several calculation methods in order to fulfill different objectives. Every one of these methods reflects the unique local characteristics of a particular country or region. As a result, these methods cannot be used for comparisons of CO_2 emission intensity of steel plants in different countries and regions.

The World Steel Association (worldsteel), which consists of more than 130 major steel companies in 55 countries and regions of the world, has been working on the development of a calculation method for CO_2 emission intensity of steel plants to facilitate steel plant CO_2 emissions improvement by the objective comparison of the intensity among the member companies' steel plants located in various places in the world. An agreement was reached among members, and worldsteel has issued the method as a guideline called "CO_2 Emissions Data Collection User Guide." Actual data collection among worldsteel members based upon the guide started in 2007. Furthermore, worldsteel is encouraging even non-member steel companies to begin using the guide to calculate CO_2 emission intensity of their steel plants.

This calculation method establishes clear boundaries for collection of CO_2 emissions data. The net CO_2 emissions and production from a steel plant are calculated using all parameters within the boundaries. The CO_2 emission intensity of the steel plant is calculated by the net CO_2 emission from the plant using the boundaries divided by the amount of crude steel production of the plant. With this methodology, the CO_2 emission intensity of steel plants is calculated irrespective of the variance in the type of process used, products manufactured and geographic characteristics.

This calculation method only uses basic imports and exports that are commonly measured and recorded by the plants; thus, the method requires neither the measurement of the specific efficiency of individual equipments or processes nor dedicated measurements of the complex flow and recycling of materials and waste heat. In this way, the calculation method ensures its simplicity and universal applicability without requiring steel plants to install additional dedicated measuring devices or to collect additional dedicated data other than commonly used data in the management of plants. However, because different regions have different energy sources and raw materials available to them, the resulting calculations cannot be used to determine a benchmark or best in class across regions.

With this method, a steel company can calculate a single figure for the CO_2 emissions intensity of a plant as a whole. As was explained earlier, most steel plants manufacture vast range of products with various shapes and specifications. This calculation method ensures the simplicity and universal applicability by not accommodating the differences in the production processes of such diverse products, and treats

AVA Documents
Document Sharing Hub

© ISO 2013 – All rights reserved

Full document details: BS ISO 14404-1:2013

a whole steel plant as one unit with one CO_2 emission intensity. Therefore, this calculation method is not applicable for calculating and determining the carbon footprint of any specific steel product. Also, and for this reason, this method can be used neither for establishing caps or benchmarks for emissions under emissions trading scheme in any specific local or regional economic system, nor for the generation of CO_2 data that would allow a comparison of CO_2 intensities of production processes that are operated inside the site.

© ISO 2013 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 14404-1:2013

INTERNATIONAL STANDARD ISO 14404-1:2013(E)

Calculation method of carbon dioxide emission intensity from iron and steel production —

Part 1: Steel plant with blast furnace

1 Scope

This part of ISO 14404 specifies calculation methods for the carbon dioxide (CO_2) intensity of plant where steel is produced through a blast furnace.

NOTE The steel plant is generally called "the integrated steel works".

It includes boundary definition, material and energy flow definition and emission factor of CO_2. Besides direct source import to the boundary, upstream and credit concept is applied to exhibit the plant CO_2 intensity.

This part of ISO 14404 supports the steel producer to establish CO_2 emissions attributable to a site. This part of ISO 14404 cannot be used to calculate benchmarks or to compare CO_2 intensities of production processes that are operated inside the site.

Conversion to energy consumption and to consumption efficiency can be obtained using Annex A.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1 Emissions

2.1.1
emission source
process emitting CO_2 during production of steel products

Note 1 to entry: There are three categories of CO_2 emission sources: direct, upstream and credit. Examples of emission sources that are subject to this part of ISO 14404 are given in 2.1.2, 2.1.3 and 2.1.4.

2.1.2
direct CO_2 emission
CO_2 emissions from steel production activity inside the boundary

Note 1 to entry: Direct CO_2 emission is categorized as "direct GHG emissions" in ISO 14064-1.

2.1.3
upstream CO_2 emission
CO_2 emissions from imported material related to outsourced steel production activities outside the boundary and from imported electricity and steam into the boundary

Note 1 to entry: Possible outsourced activities are, for example, production of coke, burnt lime, burnt dolomite, pellet, sintered ore, hot metal, cold iron, direct reduced iron, oxygen, nitrogen and argon.

Note 2 to entry: CO_2 emissions from imported material in this term is categorized as "other indirect GHG emissions" in ISO 14064-1.

Note 3 to entry: CO_2 emissions from imported electricity and steam in this term are categorized as "energy indirect GHG emissions" in ISO 14064-1.

© ISO 2013 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 14404-1:2013

2.1.4
credit CO_2 emission
CO_2 emission that corresponds to exported material and electricity or steam

Note 1 to entry: Credit CO_2 emission is categorized as "direct GHG emissions" in ISO 14064-1.

2.2 Gas fuel

2.2.1
natural gas
mixture of gaseous hydrocarbons, primarily methane, occurring naturally in the earth and used principally as a fuel

2.2.2
coke oven gas
COG
gas recovered from coke oven

2.2.3
blast furnace gas
BFG
gas recovered from blast furnace

2.2.4
BOF gas
LDG
gas recovered from basic oxygen furnace (Linze Donawitz converter)

Note 1 to entry: BOF: basic oxygen furnace

2.3 Liquid fuel

2.3.1
heavy oil
No. 4- No. 6 fuel oil defined by ASTM

Note 1 to entry: ASTM: American Society for Testing and Materials

2.3.2
light oil
No. 2- No. 3 fuel oil defined by ASTM

2.3.3
kerosene
paraffin (oil)

2.3.4
LPG
liquefied petroleum gas

2.4 Solid fuel

2.4.1
coking coal
coal for making coke, including anthracite

© ISO 2013 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 14404-1:2013

2.4.2
BF injection coal
pulverized coal injection (PCI) coal, including anthracite

Note 1 to entry: BF: blast furnace

2.4.3
sinter coal
BOF coal
coal for sinter/BOF, including anthracite

2.4.4
steam coal
boiler coal for producing electricity and steam, including anthracite

2.4.5
coke
solid carbonaceous material

2.4.6
charcoal
devolatilized or coked carbon neutral materials

EXAMPLE Trees, plants.

2.5 Auxiliary material

2.5.1
limestone
calcium carbonate, $CaCO_3$

2.5.2
burnt lime
CaO

2.5.3
crude dolomite
calcium magnesium carbonate, $CaMg(CO_3)_2$

2.5.4
burnt dolomite
$CaMgO_2$

2.5.5
nitrogen
N_2
inert gas separated from air at oxygen plant, imported from outside the boundary or exported to outside the boundary

2.5.6
argon
Ar
inert gas separated from air at oxygen plant, imported from outside the boundary or exported to outside the boundary

2.5.7
oxygen
O_2
gas separated from air at oxygen plant, imported from outside the boundary or exported to outside the boundary

© ISO 2013 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 14404-1:2013