

Acceptance sampling procedures by attributes — Specified quality levels in nonconforming items per million

ICS 03.120.30

National foreword

This British Standard reproduces verbatim ISO 14560:2004 and implements it as the UK national standard.

The UK participation in its preparation was entrusted to Technical Committee SS/5, Acceptance sampling schemes, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the ISO title page, pages ii to v, a blank page, pages 1 to 19 and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 25 August 2004

© BSI 22 December 2004

ISBN 0 580 44348 5

INTERNATIONAL STANDARD

BS ISO 14560:2004

ISO
14560

First edition
2004-08-15

Corrected version
2004-11-01

Acceptance sampling procedures by attributes — Specified quality levels in nonconforming items per million

*Règles d'échantillonnage par attributs en vue d'acceptation — Niveaux
spécifiés de qualité en termes d'individus non conformes pour un million
d'individus*



Reference number
ISO 14560:2004(E)

AVA **Documents**
Document Sharing Hub

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references.....	1
3 Terms, definitions, symbols and abbreviated terms	1
4 General principles	2
4.1 Objective	2
4.2 Quality assessment of product.....	2
4.3 Acceptance sampling of a lot.....	2
5 Estimation of quality levels in nonconforming items per million items	3
5.1 Prerequisites.....	3
5.2 Data sources	3
5.3 Estimation of p_M , the process quality level	3
5.4 Sampling requirements and guidelines	4
5.5 Examples of estimation of the quality level.....	4
5.6 Reporting results.....	5
6 Lot acceptance sampling requirements and procedures	6
6.1 Overview.....	6
6.2 Requirements and guidelines	6
6.3 Lot acceptance procedure.....	7
6.4 Illustrated use of Table 1	7
7 Single sampling plans indexed by LQL in nonconforming items per million items	8
Annex A (normative) Data exclusion	12
Annex B (informative) Underlying theory for generating point estimates of quality level in fraction nonconforming	15
Annex C (informative) Statistical theory and calculation of Table 1	17
Bibliography.....	19

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14560 was prepared by Technical Committee ISO/TC 69, *Applications of statistical methods*, Subcommittee SC 5, *Acceptance sampling*.

This corrected version of ISO 14560:2004 incorporates the following correction: in Annex C the maximum consumer's risk has been corrected to 21 %.

Introduction

For processes that produce nonconforming items relatively rarely, it is advantageous to replace traditional methods of estimating and reporting quality levels by more suitable methods. For example, an estimated outgoing quality level reported as 10 nonconforming items per million items carries a more immediately comprehensible message than either 0,00001 nonconforming items per item or 0,001 nonconforming items per 100 items. This International Standard provides alternative methods that use nonconforming items per million items terminology in estimating and reporting quality levels.

This International Standard provides a means by which quality requirements, stated to be no worse than a given number of nonconforming items per million items, can be verified on a lot-by-lot basis. Procedures are also provided for estimation of the process quality level based on evidence from previous audit and/or lot acceptance samples. Additionally, guidance is given for presuming a process quality level so that the verification procedure can be used when prior sample data is inadequate or not available.

A key feature of this International Standard is that it provides incentives for suppliers to improve their quality. The lot acceptance portion of this specification requires larger sample sizes when quality declines, smaller sample sizes when quality improves. If a customer specifies the same quality requirements to multiple suppliers of a product, those suppliers with superior quality will require, on average, smaller samples for acceptance sampling.

This document is based upon the US Electronic Industries Alliance standards EIA-554 and EIA-555, which it consolidates and reorients to indicate that the procedures are generic and can therefore also be used in industrial or service applications not generally serviced by EIA.

Acceptance sampling procedures by attributes — Specified quality levels in nonconforming items per million

1 Scope

This International Standard specifies, for quality levels expressed as nonconforming items per million items, procedures for estimating the quality level of a single entity (e.g. a lot) and, when the production process is in statistical control, for estimating the process quality level based on evidence from several samples. Procedures are also specified for using this information when selecting a suitable sampling plan so as to verify that the quality level of a given lot does not exceed a stated limiting quality level (LQL). For the case where no prior sample data is available, guidance is given for presuming a process quality level in selecting a plan.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2859-1, *Sampling procedures for inspection by attributes — Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*

ISO 3534-1, *Statistics — Vocabulary and symbols — Part 1: Probability and general statistical terms*

ISO 3534-2, *Statistics — Vocabulary and symbols — Part 2: Statistical quality control*

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in ISO 2859-1, ISO 3534-1 and ISO 3534-2, and the following symbols and abbreviated terms apply.

- Ac acceptance number, representing the largest number of nonconforming items found in the sample that permits the acceptance of the lot, as given in the sampling plan
- d number of nonconforming items observed
- d_i number of nonconforming items found in the sample from the i th lot
- LQL limiting quality level, in nonconforming items per million items (i.e. the actual quality level of a lot that corresponds to a probability of 21 % or less of lot acceptance for the sampling plan used)
- L_P lower limit to the assessed process quality level for a given LQL and Ac, used for selecting a plan from Table 1

NOTE 1 L_P is the lowest actual quality level of a lot for which the probability of lot acceptance is 90 % or more for a sampling plan with the given acceptance number, but which is less than 90% for a sampling plan with the next smaller acceptance number for the same LQL.