



BSI Standards Publication

Hydraulic fluid power — Determination of the fluid-borne noise characteristics of components and systems

Part 3: Measurement of hydraulic impedance

National foreword

This British Standard is the UK implementation of [ISO 15086-3:2022](#).

The UK participation in its preparation was entrusted to Technical Committee MCE/18/-/8, Product testing.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2022
Published by BSI Standards Limited 2022

ISBN 978 0 539 14470 3

ICS 17.140.20; 23.100.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 August 2022.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL STANDARD

ISO
15086-3

Second edition
2022-07-20

Hydraulic fluid power — Determination of the fluid-borne noise characteristics of components and systems —

Part 3: Measurement of hydraulic impedance

*Transmissions hydrauliques — Évaluation des caractéristiques du
bruit liquidien des composants et systèmes —*

Partie 3: Mesurage de l'impédance hydraulique



Reference number
ISO 15086-3:2022(E)
Documents
Document Sharing Hub
© ISO 2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	2
5 Test conditions and accuracy of instrumentation	3
5.1 Test conditions (permissible variations)	3
5.1.1 General	3
5.1.2 Fluid temperature	4
5.1.3 Fluid density and viscosity	4
5.1.4 Mean fluid pressure	4
5.1.5 Mean flow measurement	4
5.2 Instrumentation precision	4
5.2.1 Steady-state accuracy class	4
5.2.2 Dynamic-state accuracy class	4
6 Measurement of the impedance of a single-port passive component	4
6.1 Local impedance — Measurement principle	4
6.2 Hydraulic impedance	5
6.2.1 Measurement principle	5
6.2.2 Simplified algorithm for determining the component of the local hydraulic impedance	5
6.3 Factors influencing the accuracy of the impedance measurement	6
6.3.1 General	6
6.3.2 Pulse generator	6
6.3.3 Pressure transfer function measured by the PTx/PT3 pressure transducers and the calibration correction	7
6.3.4 Numerical value of terms <i>A</i> and <i>B</i> of the pipe section admittance matrix used for the indirect determination of the pulsed flows	7
6.4 Measurement of local impedance	9
6.4.1 Test circuit	9
6.4.2 Test procedure	10
7 Measurement of the admittance matrix and impedance matrix of a two-port passive hydraulic component	14
7.1 Definitions and principles of measurement of the admittance matrix and impedance matrix of a two-port passive hydraulic component	14
7.1.1 General	14
7.1.2 Principle of the method of measuring the admittance matrix	14
7.1.3 Algorithm for determining the admittance matrix of a two-port, passive component for identical dimensions of upstream and downstream pipes	17
7.1.4 Measurement result presentation	20
8 Test report	22
8.1 General	22
8.2 General information	22
8.3 Test data	22
9 Identification statement (reference to this document)	23
Bibliography	24

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 8, *Product testing*.

This second edition cancels and replaces the first edition (ISO 15086-3:2008), which has been technically revised.

The main changes are as follows:

- the symbols P_y , y , $Q_{3 \rightarrow x}$ and $Q_{3 \rightarrow 0}$ have been added to [Table 1](#);
- [Formula \(7\)](#) has been added;
- [Formulae \(3\), \(8\), \(13\), \(14\), \(16\) and \(17\)](#) have been corrected;
- [Figures 1, 2, 3, 5, 6, 7 and 8](#) have been corrected;
- various additional editorial modifications have been made.

A list of all parts in the ISO 15086 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within a closed circuit. During the process of converting mechanical power into fluid power, fluid-borne noise (flow ripple and pressure ripple) is generated. This in turn leads to structure-borne noise and airborne noise. The transmission of fluid-borne noise is influenced by the impedance of the components installed in the hydraulic circuit.

This document adopts the concepts of [ISO 15086-1](#) which describe the basis for the methods of measurement that make it possible to determine the characteristics of fluid-borne noise emitted or transmitted by hydraulic transmission systems.

[Clause 6](#) of this document describes the method for measuring the hydraulic impedance of a single-port component (local hydraulic impedance) and [Clause 7](#) describes the method for measuring the hydraulic impedance matrix of a two-port hydraulic component.

This page deliberately left blank

Hydraulic fluid power — Determination of the fluid-borne noise characteristics of components and systems —

Part 3: Measurement of hydraulic impedance

1 Scope

This document describes the procedure for determining the impedance characteristics of hydraulic components by means of measurements from pressure transducers mounted in a pipe.

This document is applicable to passive components, irrespective of size, operating under steady-state conditions, over a frequency range from 10 Hz to 3 kHz.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 80000-1](#), *Quantities and units — Part 1: General*

[ISO 1219-1](#), *Fluid power systems and components — Graphical symbols and circuit diagrams — Part 1: Graphical symbols for conventional use and data-processing applications*

[ISO 5598](#), *Fluid power systems and components — Vocabulary*

[ISO 15086-1:2001](#), *Hydraulic fluid power — Determination of the fluid-borne noise characteristics of components and systems — Part 1: Introduction*

[ISO 15086-2:2000](#), *Hydraulic fluid power — Determination of the fluid-borne noise characteristics of components and systems — Part 2: Measurement of the speed of sound in a fluid in a pipe*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in [ISO 5598](#) and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

flow ripple

fluctuation of flow rate in the hydraulic fluid

3.2

pressure ripple

fluctuating component of pressure in the hydraulic fluid, caused by interaction of the source *flow ripple* ([3.1](#)) with the system

3.3 pulse generator

hydraulic component generating a periodic *flow ripple* (3.1) and consequently *pressure ripple* (3.2) in a circuit, or a hydraulic component generating a pressure ripple and, consequently, a flow ripple in a circuit

3.4 fundamental frequency

lowest frequency of the *pressure ripple* (3.2) [or *flow ripple* (3.1)] considered in a theoretical analysis or measured by an instrument

EXAMPLE A hydraulic pump or motor with a shaft frequency of N revolutions per second can be taken to have a fundamental frequency of N Hz. Alternatively, for a pump or motor with k displacement elements, the fundamental frequency can be taken to be Nk Hz, provided that the measured behaviour does not deviate significantly from cycle to cycle.

3.5 harmonic

sinusoidal component of a signal that occurs at an integer multiple of the *fundamental frequency* (3.4)

Note 1 to entry: A harmonic can be represented by its amplitude and phase, or by its real and imaginary parts.

3.6 impedance

ratio of the *pressure ripple* (3.2) to the *flow ripple* (3.1) occurring at a given point in a hydraulic system and at a given frequency

3.7 admittance

reciprocal of *impedance* (3.6)

3.8 hydro-acoustic energy

fluctuating part of the energy in a liquid

4 Symbols

Table 1 — Symbols

Symbol	Description	Unit
A_e	complex coefficient (term of admittance matrix between transducer PT3 and component 0)	$\text{m}^3 \cdot \text{s}^{-1} \cdot \text{Pa}^{-1}$
A_x	complex coefficient (term of admittance matrix between transducers PTx and PT3)	$\text{m}^3 \cdot \text{s}^{-1} \cdot \text{Pa}^{-1}$
A_{xy}	terms of admittance matrix (for x and y equal to 1 or 2)	$\text{m}^3 \cdot \text{s}^{-1} \cdot \text{Pa}^{-1}$
B_e	complex coefficient (term of admittance matrix between transducer PT3 and component 0)	$\text{m}^3 \cdot \text{s}^{-1} \cdot \text{Pa}^{-1}$
B_x	complex coefficient (term of admittance matrix between transducers PTx and PT3)	$\text{m}^3 \cdot \text{s}^{-1} \cdot \text{Pa}^{-1}$
c	speed of sound in the fluid	$\text{m} \cdot \text{s}^{-1}$
$f_{\min}$	minimum frequency	Hz
$f_{\max}$	maximum frequency	Hz
H_{x3}	transfer function between pressure ripples P_x and P_3	—
L	distance between transducers	m
p_m	mean test pressure	MPa
P_e	Fourier transform of pressure ripple at upstream port of component	Pa

Symbol	Description	Unit
P_s	Fourier transform of pressure ripple at downstream port of component	Pa
P_x	Fourier transform of pressure ripple at location x , where x is the number of the pressure transducer, equal to 1, 2 or 3, corresponding to PT1, PT2 or PT3, respectively	Pa
P_y	Fourier transform of pressure ripple at location y , where y is the number of the pressure transducer, equal to 4, 5 or 6, corresponding to PT4, PT5 or PT6, respectively	Pa
P_1, P_2 and P_3	Fourier transform of pressure ripple at the location of pressure transducer 1 (PT1), pressure transducer 2 (PT2) and pressure transducer 3 (PT3), respectively	Pa
q_m	mean flow rate	$\text{l}\cdot\text{s}^{-1}$
$Q_{e\rightarrow 0}$	Fourier transform of flow ripple into upstream port of component (0)	$\text{m}^3\cdot\text{s}^{-1}$
$Q_{s\rightarrow 0}$	Fourier transform of flow ripple into downstream port of component (0)	$\text{m}^3\cdot\text{s}^{-1}$
$Q_{3\rightarrow x}$	Fourier transform of flow ripple at the location of pressure transducer 3 (PT3), defined as positive when towards location of pressure transducer x	$\text{m}^3\cdot\text{s}^{-1}$
$Q_{3\rightarrow 0}$	Fourier transform of flow ripple at the location of pressure transducer 3 (PT3), defined as positive when towards location of pressure transducer (0)	$\text{m}^3\cdot\text{s}^{-1}$
T_m	fluid mean temperature	$^{\circ}\text{C}$
x	number of the pressure transducer, equal to 1, 2 or 3, corresponding to PT1, PT2 or PT3, respectively	—
y	number of the pressure transducer, equal to 4, 5 or 6, corresponding to PT4, PT5 or PT6, respectively	—
Z_e	hydraulic impedance	$\text{Pa}\cdot\text{s}\cdot\text{m}^{-3}$
$Z_{e\rightarrow 0}$	hydraulic impedance of component (0)	$\text{Pa}\cdot\text{s}\cdot\text{m}^{-3}$
ν	kinematic viscosity	$\text{mm}^2\cdot\text{s}^{-1}$ (cSt)
θ	phase of harmonic component (pressure or flow ripple, as appropriate)	degree ($^{\circ}$)
$d\theta$	phase precision of the Fourier analyser	degree ($^{\circ}$)

Units used in this document shall be in accordance with [ISO 80000-1](#).

Graphical symbols used in this document shall be in accordance with [ISO 1219-1](#) unless otherwise stated.

5 Test conditions and accuracy of instrumentation

5.1 Test conditions (permissible variations)

5.1.1 General

The required operating conditions shall be maintained throughout each test within the limits specified in [Table 2](#).

Table 2 — Permissible variations in test conditions

Test parameter	Permissible variation
Mean flow	$\pm 2\%$
Mean pressure	$\pm 2\%$
Temperature	$\pm 2\text{ }^{\circ}\text{C}$